

```

#include <iostream>
using namespace std;

class Human
{
private:
    string name;
    int age;
    string gender;

public:

    // Method to set all details
    void set_detail(string n, int a, string g)
    {
        name = n;
        age = a;
        gender = g;
    }

    // Method to display details
    void display_detail()
    {
        cout << "Name : " << name << endl;
        cout << "Age : " << age << endl;
        cout << "Gender : " << gender << endl;
    }

    // Method to check voting eligibility
    void can_vote()
    {
        if (age >= 18)
        {
            cout << "Yes, you can vote." << endl;
        }
        else
        {
            cout << "You cannot vote." << endl;
        }
    }
};

int main()
{
    Human h1;

    h1.set_detail("samar", 25, "Male");

```

```

    h1.display_detail();

    h1.can_vote();

    return 0;
}

```

```

#include <iostream>
using namespace std;
//The lesser the identifiers you use, the lesser mistakes you would make.
//As a result it is advisable to use exact local variables with exact identifiers as system and
instance variables.
//One can use 'this' pointer to differentiate between Instance member and local member
//this->XXXXX is instance member of current object
class Human
{
private:
    string name;
    int age;
    string gender;

public:

    // Method to set all details
    void set_detail(string name, int age, string gender)
    {
        this->name = name;
        this->age = age;
        this->gender = gender;
    }

    // Method to display details
    void display_detail()
    {
        cout << "Name   : " << name << endl;
        cout << "Age    : " << age << endl;
        cout << "Gender : " << gender << endl;
    }

    // Method to check voting eligibility
    void can_vote()
    {
        if (age >= 18)
        {
            cout << "Yes, you can vote." << endl;
        }
        else

```

```
        {  
            cout << "You cannot vote." << endl;  
        }  
    }  
};
```

```
int main()  
{  
    Human h1;  
  
    h1.set_detail("samar", 25, "Male");  
  
    h1.display_detail();  
  
    h1.can_vote();  
  
    return 0;  
}
```

Create a C++ program using **two classes: INR and Dollar**.

The user has some money in both Indian Rupees and US Dollars.

- Class `INR` should store the amount in Indian Rupees.
- Class `Dollar` should store the amount in US Dollars.
- Keep the data members **private**.
- Create a **friend function** called `total_evaluation()` that can access the private data of both classes.
- The friend function should calculate and display:
 1. **Total amount in INR**
 2. **Total amount in USD**

For currency conversion, assume:

1 USD = ₹90

The Dollar amount should be converted into INR, and the INR amount should be converted into USD.

Sample Input

Enter amount in INR: 18000

Enter amount in USD: 200

Sample Output

Total Amount in INR: ₹36000

Total Amount in USD: \$400

Explanation

Given:

INR = ₹18000

USD = \$200

Conversion Rate = ₹90 per USD

Convert USD to INR:

$\$200 \times 90 = ₹18000$

Therefore:

Total INR = ₹18000 + ₹18000
= ₹36000

Convert INR to USD:

$₹18000 \div 90 = \$200$

Therefore: Total USD = \$200 + \$200
= \$400

```
#include <iostream>

using namespace std;

class Dollar; // Forward declaration

class INR
{
private:
    float amount;

public:
    void set_amount(float a)
    {
        amount = a;
    }

    friend void total_evaluation(INR i, Dollar d);
};

class Dollar
{
    float amount;

public:
    void set_amount(float a)
    {
        amount = a;
    }

    friend void total_evaluation(INR i, Dollar d);
```

```

};

void total_evaluation(INR i, Dollar d)
{
    float totalINR, totalUSD;

    // Convert Dollar to INR
    totalINR = i.amount + (d.amount * 90);

    // Convert INR to Dollar
    totalUSD = d.amount + (i.amount / 90);

    cout << "Total Amount in INR: " << totalINR << endl;
    cout << "Total Amount in USD: " << totalUSD << endl;
}

int main()
{
    INR i;
    Dollar d;

    float inr, dollar;

    cout << "Enter amount in INR: ";
    cin >> inr;//10000

    cout << "Enter amount in USD: ";
    cin >> dollar;//100

    i.set_amount(inr);

```

```
d.set_amount(dollar);

total_evaluation(i, d);

return 0;
}
```