SKYSHIELD TECHNOLOGY

Ravin

VTOL tailsitter UAV — technical specification



AIRFRAME

Configuration	**VTOL tailsitter**
Max takeoff weight	**6 kg**
Wingspan	**1.5 m**
Flight endurance	**Up to 2 hours**
Field deployment	**Under 3 minutes**
Portability	**Single backpack**
Crew	**1 operator**
Recovery	**Vertical landing, no net**

aman@skyshieldtech.in

Structure	**Composite unibody**
Payload bay	**Modular, centre-body**

AIRFRAME FEATURES

Unibody composite shell. Wing, body and tail formed as one structure — fewer joints and fasteners, less to fail in the field and less to inspect between sorties.

Twin motor pods per wing. The same units provide vertical lift on takeoff and cruise thrust once the aircraft is wing-borne.

Modular sensor bay. A defined volume in the centre body with its own access panel and mounting interface — the payload can be swapped without touching flight structure.

Wingtip navigation lights and skid fairings. Lit for orientation in low light, and doubling as the aircraft's landing contact point.

CONCEPT OF OPERATIONS

The aircraft is carried in a single backpack and launched vertically from any clear ground — no runway, catapult or launch rail. It transitions to horizontal flight for the mission, trading rotor lift for wing efficiency, and returns to the vertical to settle onto its wingtip skids. One operator handles the whole cycle.

Specification is indicative and subject to change. Issued 2026.

aman@skyshieldtech.in