

# Database Design & Applications

## The Database Language - SQL Aggregation

# Aggregating Data Using Group Functions

## Objectives

- After completing this lesson, you should be able to do the following:
  - Identify the available group functions
  - Describe the use of group functions
  - Group data using the GROUP BY clause
  - Include or exclude grouped rows by using the
  - HAVING clause

# What Are Group Functions?

- Group functions operate on sets of rows to give one result per group.

## EMPLOYEES

DEPARTMENT_ID	SALARY
90	24000
90	17000
90	17000
60	9000
60	6000
60	4200
50	5800
50	3500
50	3100
50	2600
50	2500
80	10500
80	11000
80	8600
	7000
10	4400

20 rows selected.

The maximum salary in the **EMPLOYEES** table.

MAX(SALARY)
24000

## Types of Group Functions

- AVG
- COUNT
- MAX
- MIN
- STDDEV
- SUM
- VARIANCE



## Group Functions Syntax

```
SELECT      [column,] group_function(column), ...  
FROM        table  
[WHERE      condition]  
[GROUP BY   column]  
[ORDER BY   column];
```



## AVG and SUM Functions

- You can use AVG and SUM for numeric data.

```
SELECT AVG(salary), MAX(salary),  
       MIN(salary), SUM(salary)  
FROM employees  
WHERE job_id LIKE '%REP%';
```

AVG(SALARY)	MAX(SALARY)	MIN(SALARY)	SUM(SALARY)
8150	11000	6000	32600

## MIN and MAX Functions

- You can use MIN and MAX for any data type.

```
SELECT MIN(hire_date) , MAX(hire_date)
FROM   employees;
```

MIN(HIRE_	MAX(HIRE_
17-JUN-87	29-JAN-00

## COUNT Function

COUNT(\*) returns the number of rows in a table.

```
SELECT COUNT (*)  
FROM employees  
WHERE department_id = 50;
```

COUNT(*)
5



## COUNT Function

- COUNT(*expr*) returns the number of rows with non-null values for the *expr*.
- Display the number of department values in the EMPLOYEES table, excluding the null values.

```
SELECT COUNT(commission_pct)
FROM employees
WHERE department_id = 80;
```

COUNT(COMMISSION_PCT)
3

## DISTINCT Keyword

- COUNT(DISTINCT expr) returns the number of distinct non-null values of the *expr*.
- Display the number of distinct department values in the EMPLOYEES table.

```
SELECT COUNT(DISTINCT department_id)  
FROM employees;
```

COUNT(DISTINCTDEPARTMENT_ID)
7



## Group Functions and Null Values

- Group functions ignore null values in the column.

```
SELECT AVG(commission_pct)
FROM employees;
```

AVG(COMMISSION_PCT)	
	.2125

## Handling NULLs with Group Functions

- The ISNULL function forces group functions to include null values.

```
SELECT AVG (ISNULL (commission_pct,  
0)) FROM employees;
```

AVG(NVL(COMMISSION_PCT,0))
.0425

# Creating Groups of Data

For each department average salary in EMPLOYEE table

## EMPLOYEES

DEPARTMENT_ID	SALARY
10	4400
20	13000
20	6000
50	5800
50	3500
50	3100
50	2500
50	2600
60	9000
60	6000
60	4200
80	10500
80	8600
80	11000
90	24000
90	17000

4400

9500

3500

6400

DEPARTMENT_ID	AVG(SALARY)
10	4400
20	9500
50	3500
60	6400
80	10033.3333
90	19333.3333
110	10150
	7000

...

20 rows selected.



## GROUP BY Clause

```
SELECT      column,  
FROM        group_function(column) table  
[WHERE      condition]  
[GROUP BY group_by_expression]  
[ORDER BY column];
```

Divide rows in a table into smaller groups by using the GROUP BY clause.

## GROUP BY Clause

All columns in the SELECT list that are not in group functions must be in the GROUP BY clause.

```
SELECT department_id, AVG(salary)
FROM employees
GROUP BY department_id ;
```

DEPARTMENT_ID	AVG(SALARY)
10	4400
20	9500
50	3500
60	6400
80	10033.3333
90	19333.3333
110	10150
	7000

8 rows selected.

## GROUP BY Clause

The GROUP BY column does not have to be in the SELECT list.

```
SELECT AVG(salary)
FROM employees
GROUP BY department_id ;
```

AVG(SALARY)	
	4400
	9500
	3500
	6400
	10033.3333
	19333.3333
	10150
	7000

# Grouping by More Than One Column

## EMPLOYEES

DEPARTMENT_ID	JOB_ID	SALARY
90	AD_PRES	24000
90	AD_VP	17000
90	AD_VP	17000
60	IT_PROG	9000
60	IT_PROG	6000
60	IT_PROG	4200
50	ST_MAN	5800
50	ST_CLERK	3500
50	ST_CLERK	3100
50	ST_CLERK	2600
50	ST_CLERK	2500
80	SA_MAN	10500
80	SA_REP	11000
80	SA_REP	8600

...

20	MK_REP	6000
110	AC_MGR	12000
110	AC_ACCOUNT	8300

20 rows selected.

Add up the salaries in the **EMPLOYEES** table for each job, grouped by department.

DEPARTMENT_ID	JOB_ID	SUM(SALARY)
10	AD_ASST	4400
20	MK_MAN	13000
20	MK_REP	6000
50	ST_CLERK	11700
50	ST_MAN	5800
60	IT_PROG	19200
80	SA_MAN	10500
80	SA_REP	19600
90	AD_PRES	24000
90	AD_VP	34000
110	AC_ACCOUNT	8300
110	AC_MGR	12000
	SA_REP	7000

13 rows selected.



## Grouping by More Than One Column

```
SELECT    department_id dept_id, job_id, SUM(salary)
FROM      employees
GROUP BY  department_id, job_id ;
```

DEPT_ID	JOB_ID	SUM(SALARY)
10	AD_ASST	4400
20	MK_MAN	13000
20	MK_REP	6000
50	ST_CLERK	11700
50	ST_MAN	5800
60	IT_PROG	19200
80	SA_MAN	10500
80	SA_REP	19600
90	AD PRES	24000
90	AD_VP	34000
110	AC_ACCOUNT	8300
110	AC_MGR	12000
	SA_REP	7000

13 rows selected.



## Illegal Queries Using Group Functions

Any column or expression in the SELECT list that is not an aggregate function must be in the GROUP BY clause.

```
SELECT department_id,  
COUNT(last_name) FROM employees;
```

ERROR:

Column 'EMPLOYEES.department\_id' is invalid in the select list because it is not contained in either an aggregate function or the GROUP BY clause.

## Illegal Queries Using Group Functions

- You cannot use the WHERE clause to restrict groups.
- You use the HAVING clause to restrict groups.
- You cannot use group functions in the WHERE clause.

```
SELECT    department_id,  
FROM      AVG(salary) employees  
WHERE     AVG(salary) > 8000  
GROUP BY  department_id;
```

```
WHERE AVG(salary) > 8000  
ERROR at line 3:
```

**Cannot use the WHERE clause to restrict groups**

# Excluding Group Results

## EMPLOYEES

DEPARTMENT_ID	SALARY
90	24000
90	17000
90	17000
60	9000
60	6000
60	4200
50	5800
50	3500
50	3100
50	2600
50	2500
80	10500
80	11000
80	8600
...	...
20	6000
110	12000
110	8300

20 rows selected.

The maximum salary per department when it is greater than \$10,000

DEPARTMENT_ID	MAX(SALARY)
20	13000
80	11000
90	24000
110	12000

## Using HAVING Clause

Use the HAVING clause to restrict groups:

- Rows are grouped.
- The group function is applied.
- Groups matching the HAVING clause are displayed.

```
SELECT      column,  
FROM        group_function table  
[WHERE      condition]  
[GROUP BY   group_by_expression  
[HAVING     group_condition]  
[ORDER BY   column];
```

## Using HAVING Clause

```
SELECT    department_id,  
MAX(salary) FROM employees  
GROUP BY department_id  
HAVING MAX(salary) > 10000 ;
```

DEPARTMENT_ID	MAX(SALARY)
20	13000
80	11000
90	24000
110	12000



## Using HAVING Clause

```
SELECT    job_id, SUM(salary)
FROM      PAYROLL employees
WHERE     job_id NOT LIKE '%REP%'
GROUP BY  job_id
HAVING SUM(salary) > 13000
ORDER BY  SUM(salary);
```

JOB_ID	PAYROLL
IT_PROG	19200
AD PRES	24000
AD_VP	34000

THANK YOU!

