

CLamb

Lexical Specifications

1. Token set / Specifications

Category	Class Part	Value Part	Expected Output Format
Data Types	data_type	int, float, char, bool, string, void, auto	<data_type, float> <data_type, int>
Keyword	keyword	if, else, for, while, return, lamb, null, print, malloc, free	<keyword, lamb> <keyword, return>
Identifiers	identifier	User-defined string	<identifier, total> <identifier, 2sum>
Integer Literals	integer_literal	Numeric String	<integer_literal, 7>
Float Literals	float_literal	Decimal String	<float_literal, 3.14>
Char Literals	char_literal	Single Character	<char_literal, a>
String Literals	string_literal	Text enclosed in “	<string_literal, “hi”>
Boolean Literals	boolean_literal	true, false	<boolean_literal, “true”>
Additive Operators	add_op	+, -	<add_op, +>
Multiplicative Operators	mul_op	/, %	<mul_op, %>
Asterisk	asterisk	*	<asterisk, *>
Logical Operators	logical_op	AND, OR, NOT	<logical_op, AND>
Relational Operators	relational_op	<, >, <=, >=, ==, !=	<relational_op, ==>
Assignment	assignment_op	=	<assignment_op, ==>

Address Operator	address_op	&	<address_op, &>
Left Parenthesis	l_paren	(	<l_paren, (>
Right Parenthesis	r_paren	)	<r_paren,)>
Left Brace	l_brace	{	<l_brace, {>
Right Brace	r_brace	}	<r_brace, }>
Left Bracket	l_bracket	[	<l_bracket, [>
Right Bracket	r_bracket	]	<r_bracket,]>
Semicolon	semicolon	;	<semicolon, ;>
Comma	comma	,	<comma, ,>
Comment	comment	//	<comment, //>

2. DFA Transition Table

Character Classes

- Letters (l) = a-z, A-Z
- Underscore = _
- Digits (d) = 0-9
- Whitespace (WS) = (space, tabs, newline)
- Other = Any character not explicitly matched in the current state.

Reserved Keywords Table:

Lexeme Set	Emitted Token
if, else, for, while, return, lamb, null, print, malloc, free	<keyword, value>
int, float, char, bool, string, void, auto	<data_type, value>
true, false	<boolean_literal, value>
AND, OR, NOT	<logical_op, value>
anything else	<identifier, value>

Current State	Input Character Class	Next State	Accepting State?
S0(Start)	Letter	S1	No
S0	Digit	S2	No
S0	_	S1	No
S0	"	S5	No
S0	'	S6	No
S0	=	S8	No
S0	<	S9	No
S0	>	S10	No
S0	!	S11	No
S0	/	S12	No
S0	+, -	S_AddOp	Yes (<add_op, value>)
S0	*	S_Asterisk	Yes (<asterisk, *>)
S0	%	S_MulOp	Yes (<mul_op, %>)
S0	&	S_Ampersand	Yes (<address_op, &>)
S0	(	S_LParen	Yes (<l_paren, (>)
S0	)	S_RParen	Yes (<r_paren,)>)
S0	{	S_LBrace	Yes (<l_brace, {>)
S0	}	S_RBrace	Yes (<r_brace, }>)
S0	[	S_LBracket	Yes (<l_bracket, [>)
S0	]	S_RBracket	Yes (<r_bracket,]>)
S0	;	S_Semicolon	Yes (<semicolon, ;>)
S0	,	S_Comma	Yes (<comma, ,>)
S0	WS	S0	No

S0	Other	S_Error	Error State
S1(Identifier)	Letter, Digit, _	S1	No
S1	Other	S1(Accept)	Yes → reserved-word lookup: <code><keyword,·></code> / <code><boolean_literal,·></code> / <code><logical_op,·></code> / <code><data_type, value></code> / else <code><identifier, value></code> , not consumed, pushback
S2(Digit-Initial)	Digit	S2	No
S2	_	S1	No
S2	. (fullstop)	S3	No
S2	Letter	S1	No
S2	Other	S2(Accept)	Yes (<code><integer_literal, value></code>), not consumed, pushback
S3 (Float dot)	Digit	S4	No
S3	Other	S_Error	Error State
S4(Float)	Digit	S4	No
S4	Letter	S_Error	Error State
S4	Other	S4(Accept)	Yes (<code><float_literal, value></code>), not consumed, pushback
S5(String)	“	S5(Accept)	Yes (<code><string_literal, value></code>)
S5	Other (including WS)	S5	No
S6(Char Start)	Any char (except ‘)	S7	No
S6	‘ (Immediately)	S_Error	Error State
S7(Char End)	‘	S7(Accept)	Yes (<code><char_literal, value></code>)
S7	Other	S_Error	Error State
S8(=)	=	S8_Eq(Accept)	Yes (<code><relational_op,</code>

			<code>== ></code> , token consumed
S8	Other	S8_Assign(Accept)	Yes (<code><assignment_op, = ></code>), not consumed, pushback
S9(<)	=	S9_Eq(Accept)	Yes (<code><relational_op, <= ></code>) , token consumed
S9	Other	S9_Lt(Accept)	Yes (<code><relational_op, <\></code>) not consumed, pushback
S10(>)	=	S10_Eq(Accept)	Yes (<code><relational_op, >= ></code>) , token consumed
S10	Other	S10_Gt(Accept)	Yes (<code><relational_op, > ></code>) not consumed, pushback
S11(!)	=	S11_Eq(Accept)	Yes (<code><relational_op, !=></code>) token consumed
S11	Other	S_Error	Error State, token not consumed, pushback
S12(/)	/	S13	No (Comment Starts)
S12	Other	S12(Accept)	Yes (<code><mul_op, /></code>), not consumed, pushback
S13(Comment)	\n (Newline)	S0	No
S13	Other	S13	No
S_Error	Any	S_Error	Consume and discard character; emit error diagnostic once on entry
S_Error	WS	S0	Resume normal tokenizing
S_Error	Recognizable start char (Letter, Digit, " , ' , operator chars)	S0	Resume normal tokenizing without consuming this

			character (re-lex it as a fresh token)
--	--	--	--

3. Lexical Analyser

4. Test Input

5. Generated Token Stream