

```
// R_FatNumForName ( SKY3 )
// IF NO WOULD LEVELS, NO TEXT EXIT
// If (gamemode == commercial)
// 66 (W_CheckNumForName("map31")<0)
// secrettext = false;
// secrettext = true;
// gamemode == go_completed;
// skip the description field
// memtest (check, 0, sizeof(check));
// sprint (check, "version %d", VERSION);
// if (strcmp (base, v, check))
// return;
// bad version
// save_p += VERSIONSIZE;

// This was quite messy with SPECIAL and commented parts,
// supposedly backs to make the latest edition work,
// it might not work properly,
// if (episode < 1)
// episode = 1;

// if (gamemode == retail )
// {
// episode = 4;
// }
// else if (gamemode == shareware )
// {
// if (episode > 3)
// episode = 1; // only start episode 1 on shareware
// }
// else
// {
// if (episode > 3)
// episode = 3;
// }

// if (map < 1)
// map = 1;

// if (map > 90)
// {
// 65 (gamemode != commercial )
// map = 9;
// }

// M_ClearRandom (0);

// (skill == sk_nightmare || respawnparm )
// {
// respawnmonsters = true;
// }
// else
// {
// respawnmonsters = false;
// }

// (lastparm || skill == sk_nightmare && gameskill != sk_nightmare)
// {
// for (i=S_SARG_RUN1; i<=S_SARG_RUN2; i++)
// statesh.tics >>= 1;
// mobinfo[MT_BRUISERSHOT].speed = 20*FRACUNIT;
// mobinfo[MT_TROOPSHOT].speed = 20*FRACUNIT;
// }
// else if (skill != sk_nightmare && gameskill == sk_nightmare)
// {
// for (i=S_SARG_RUN1; i<=S_SARG_RUN2; i++)
// statesh.tics <<= 1;
// mobinfo[MT_BRUISERSHOT].speed = 15*FRACUNIT;
// mobinfo[MT_TROOPSHOT].speed = 10*FRACUNIT;
// }

// force players to be initialized upon first level load
// for (i=0; i<MAXPLAYERS; i++)
// players[i].playerstate = PST_REBORN;

// usergame = true; // will be set, false if a demo
// paused = false;
// demoplayback = false;
// automapactive = false;
// viewactive = true;
// gamemode = episode;
// gamemap = map;
// gameskill = skill;
// viewactive = true;
```

# JSON and the REST ASP.NET Core

Rasmus Lystrøm  
External Associate Professor  
ITU  
[rnie@itu.dk](mailto:rnie@itu.dk)

# Agenda

Interlude: Solution best practices  
and exercises for this week

XML (History lesson)

JSON

REST

ASP.NET Core

Web API with ASP.NET Core

# Solution Best Practices

<company>.<product>.Entities

<company>.<product>.Entities.Tests

<company>.<product>.Models

<company>.<product>.Models.Tests

<company>.<product>.Web

<company>.<product>.Web.Tests

<company>.<product>.App

<company>.<product>.App.Tests

This weeks exercises

# What is XML?

eXtensible Markup Language

Markup language like HTML

Designed to carry data, not to display data

Tags are not predefined – You must define your own tags

Designed to be self-descriptive

# XML Does Not Do Anything

XML was created to structure, store, and transport information

```
<?xml version="1.0" encoding="UTF-8"?>
<note id="1">
  <to>Tom</to>
  <from>Kathleen</from>
  <heading>Reminder</heading>
  <body>Don't forget small change!</body>
</note>
```

# How Can XML be Used?

Separates data from HTML

Simplifies data sharing

Simplifies data transport

Simplifies platform changes

Used to create new (Internet) languages

- XHTML
- WSDL for describing web services
- RSS and ATOM for news feeds
- XAML
- JSONx [https://www.ibm.com/support/knowledgecenter/en/SS9H2Y\\_7.2.0/com.ibm.dp.doc/json\\_jsonxconversionexample.html](https://www.ibm.com/support/knowledgecenter/en/SS9H2Y_7.2.0/com.ibm.dp.doc/json_jsonxconversionexample.html)

# What is JSON?

JavaScript Object Notation

Lightweight text-data interchange format

Language independent (uses JavaScript syntax)

“Self-describing” and easy to understand



# JSON Syntax

(subset of the JavaScript object notation syntax)

Data is in name/value pairs

Data is separated by commas

Curly braces hold objects

Square brackets hold arrays

# JSON Name/Value Pairs

A name/value pair consists of a field name (in double quotes), followed by a colon, followed by a value:

```
"firstName" : "John"
```

This is simple to understand, and equals to the JavaScript statement:

```
firstName = "John"
```

# JSON Data Types

Number (integer or floating point)

String (in double quotes)

Boolean (true or false)

Array (in square brackets)

Object (in curly brackets)

null

# Examples

## Objects

```
{ "firstName":"John" , "lastName":"Doe" }
```

## Array

```
{  
  "employees": [  
    { "firstName":"John" , "lastName":"Doe" },  
    { "firstName":"Jane" , "lastName":"Doe" },  
    { "firstName":"John" , "lastName":"Smith" }  
  ]  
}
```

# REST

## REpresentational State Transfer

# REST

Maps your CRUD actions to HTTP verbs

Action	Verb
Create	POST
Read (Retrieve)	GET
Update (Replace)	PUT
Update (Modify)	PATCH
Delete	DELETE

# HTTP status codes

Code	Meaning
200	OK
201	Created
202	Accepted
204	No content
301	Moved permanently
302	Moved temporarily
400	Bad request
401	Unauthorized
403	Forbidden
404	Not found
409	Conflict
500	Internal server error
501	Not implemented
503	Service unavailable

# HTTP headers

Header Field	Description	Example
Accept	Content-Types that are acceptable for the response	text/plain, application/json, application/xml
Content-Type	The MIME type of the body of the request (POST and PUT)	application/x-www-form-urlencoded application/json
Authorization	Authentication credentials for HTTP authentication	OAuth realm="http://sp.example.test/", oauth_consumer_key="0685bd9184jfhq22", oauth_token="ad180jld733klru7", oauth_signature_method="HMAC-SHA1", oauth_signature="wOJlO9A2W5mFwDgiDvZb..."
WWW-Authenticate	Authentication scheme	WWW-Authenticate: OAuth realm="http://sp.example.test/"



# Why REST?

Simple, both conceptually and programmatically

Simpler and cleaner than SOAP

REST is the new black

# ASP.NET Core

<http://www.asp.net>

# Demo