

Push Pads

DATASHEET

Sensor Partners BV

James Wattlaan 15
5151 DP Drunen
The Netherlands

+31 (0)416 - 37 82 39
info@sensorpartners.com
sensorpartners.com

Sensor Partners BVBA

Z.1 Researchpark 310
B-1731, Zellik
Belgium

+32 (0)2 - 464 96 90
info@sensorpartners.com
sensorpartners.com



Push Pads

Activation

Durable & Attractive Stainless Steel Push Pads

Elegant, vandal-resistant wireless and hardwired push pads designed to facilitate disabled pedestrian access to all public buildings

- **Tamper Resistant**
Manufactured from high grade stainless steel and assembled without visible fixings ensuring a tamper resistant push pad
- **Wireless for Ease of Installation**
Can be radio-controlled with the addition of an optional miniature remote control transmitter and receiver
- **Durable**
Tested to in excess of 10 million activation cycles our range of switches offer low maintenance combined with elegance
- **Available in a Range of Sizes**
 - 6" (152mm) Square
 - 4.5" (115mm) Square
 - 4.5" x 1.5" (115 x 38mm) Jamb Style

Push Pads

Activation



Technical Specification

Accessories



4UFK
Recess mounting kit for
4S1UO and 4S1U4

Model	Stainless Steel Wireless + Hardwired Push Pads	
Material	18-gauge stainless steel with a brushed finish	
Power	12 VDC or 24 VDC/VAC	
Operating Temperature	-40°C to 60°C (-40°F to 140°F)	
Operating Options	Hardwired and Radio Control versions operating at 433 MHz	
Transmitter	Receiver	
Frequency	433.92 MHz	433.92 MHz
Dimensions	31x22x6mm (1.25"x0.875"x0.25")	57x32x19mm (2.25"x 1.25"x 0.75")
Security Code Method	Code Hopping	Code Hopping
Battery Life	60,000 cycles	Can learn up to 12 different transmitters
Operating Temperature Range	-20°C to +55°C (-4°F to +122°F)	-20°C to +55°C (-4°F to +122°F)
Electrical Rating	-	100,000 cycles at 2 Amps at either
	-	24 VDC or 120 VAC
Input Power	24 VAC, 24VDC or 12 VDC	24 VAC, 24VDC or 12 VDC
Relay Output	-	1 NO 1 NC
Signal Range	150ft (45m)	-

Range Available



J01J0
Hardwired Jamb Box Push
Plate 4.5" x 1.5" (115 x 38mm)



4S1U0
Hardwired Push Pad
4.5"(115mm) square



6S1U0
Hardwired Push Pad
6"(152mm) square



J01J4
J01J0 + 433 MHz
transmitter 4.5" x 1.5" (115 x
38mm)



4S1U4
4S1U0 + 433 MHz
transmitter 4.5"(115mm)
square



6S1U4
6S1U0 + 433 MHz
transmitter 6"(152mm)
square



433MHz-RX
Ultra-small 433MHz
receiver



433MHz-TX
Ultra-small 433MHz
replacement
transmitter