


# FMM6/CN-3H

DATASHEET



#### **Sensor Partners BV**

- O James Wattlaan 15 5151 DP Drunen The Netherlands
- +31 (0)416 37 82 39
- sensorpartners.com

#### Sensor Partners BVBA

- OZ.1 Researchpark 310 B-1731, Zellik Belgium
- **>** +32 (0)2 464 96 90
- sensorpartners.com

## FMM6/CN-3H

## cylindrical full metal inductive





Indicative image





### **Detection properties**

Nominal sensing distance	3mm
--------------------------	-----

Operanting distance 0...2,43mm

Standard target 12x12mm FE360

**Correction Factor** Kupfer: 0 / Aluminium: 0 / Messing: 0,1 / rostfreier Edelstahl: 0,53

Thermal drift of Sr < 10%

5% (UB 24V Ta=23°C ±5°C) **Repeat Accuracy** 

Hysteresis 1 ... 20%

#### **Outputs**

Output type NPN

**Output Function** NC

Switching frequency 200Hz

#### **Electrical data**

Operating Voltage	1030Vdc
No-Load supply current	≤ 10mA
Load current	≤ 200mA
Leakage current	≤ 10µA
Output voltage drop	≤ 1,5V @200mA
Max ripple content	≤10%
LED indicators	Yellow LED output state
Time delay before availability	≤ 50ms
Short-circuit protection	Yes (auto-reset)
Reverse Polarity Protection	Yes
Protection against inductive loads	Yes

#### Mechanical data

Mounting	Shielded
Dimensions	M12 x 1 / L = 52mm
Weight	20g
Housing Material	stainless steel AISI316L
Connections	M12 Plug
Active Head Material	stainless steel AISI316L
Tightening torque	10Nm
Operating temperature	-25°C+70°C
0,25mm	0,50mm
Diameter/Dimension	M12

## Test/Approvals


Approvals	CE cULus	
EMC compatibility	IEC 60947-5-2	
Shocks and vibrations	Vibration IEC 60068-2-6 / Shock IEC 60068-2-27	
Degree of protection	IP68, IP69K	
IK05	IK05	
80bar	80bar	


#### Accessories

Supplied Accessories	2 nuts M12x1

# Electrical diagrams of the connections

## Connector





# Response Curves

