




Rasterization - Theory



2D Canvas



2D Canvas



Implicit Geometry Representation

- Define a curve as zero set of 2D implicit function

- $F(x,y) = 0 \rightarrow$ on curve

- $F(x,y) < 0 \rightarrow$ inside curve

- $F(x,y) > 0 \rightarrow$ outside curve

- Example: Circle with center (c_x, c_y) and radius r

$$F(x, y) = (x - c_x)^2 + (y - c_y)^2 - r^2$$




Implicit Geometry Representation

- Define a curve as zero set of 2D implicit function

- $F(x,y) = 0 \rightarrow$ on curve

- $F(x,y) < 0 \rightarrow$ inside curve

- $F(x,y) > 0 \rightarrow$ outside curve




Implicit Rasterization

for all pixels (i,j)

$(x,y) = \text{map_to_canvas}(i,j)$


if $F(x,y) < 0$

set_pixel (i,j, color)




Barycentric Interpolation

- Barycentric coordinates:
- $\mathbf{p} = \alpha\mathbf{a} + \beta\mathbf{b} + \gamma\mathbf{c}$ with $\alpha + \beta + \gamma = 1$



Barycentric Interpolation

- Barycentric coordinates:
- $\mathbf{p} = \alpha \mathbf{a} + \beta \mathbf{b} + \gamma \mathbf{c}$ with $\alpha + \beta + \gamma = 1$
- Unique for non-collinear $\mathbf{a}, \mathbf{b}, \mathbf{c}$



$$\begin{bmatrix} \mathbf{a}_x & \mathbf{b}_x & \mathbf{c}_x \\ \mathbf{a}_y & \mathbf{b}_y & \mathbf{c}_y \\ 1 & 1 & 1 \end{bmatrix} \cdot \begin{bmatrix} \alpha \\ \beta \\ \gamma \end{bmatrix} = \begin{bmatrix} \mathbf{p}_x \\ \mathbf{p}_y \\ 1 \end{bmatrix}$$


Barycentric Interpolation

- Barycentric coordinates:
 - $\mathbf{p} = \alpha\mathbf{a} + \beta\mathbf{b} + \gamma\mathbf{c}$ with $\alpha + \beta + \gamma = 1$
 - Unique for non-collinear $\mathbf{a}, \mathbf{b}, \mathbf{c}$
 - Ratio of triangle areas

$$\alpha(\mathbf{p}) = \frac{\text{area}(\mathbf{p}, \mathbf{b}, \mathbf{c})}{\text{area}(\mathbf{a}, \mathbf{b}, \mathbf{c})}$$




$$\beta(\mathbf{p}) = \frac{\text{area}(\mathbf{p}, \mathbf{c}, \mathbf{a})}{\text{area}(\mathbf{a}, \mathbf{b}, \mathbf{c})}$$

$$\gamma(\mathbf{p}) = \frac{\text{area}(\mathbf{p}, \mathbf{a}, \mathbf{b})}{\text{area}(\mathbf{a}, \mathbf{b}, \mathbf{c})}$$




Barycentric Interpolation

- Barycentric coordinates:
 - $\mathbf{p} = \alpha\mathbf{a} + \beta\mathbf{b} + \gamma\mathbf{c}$ with $\alpha + \beta + \gamma = 1$
 - Unique for non-collinear $\mathbf{a}, \mathbf{b}, \mathbf{c}$
 - Ratio of triangle areas
 - $\alpha(\mathbf{p})$, $\beta(\mathbf{p})$, $\gamma(\mathbf{p})$ are linear functions




Barycentric Interpolation

- Barycentric coordinates:
 - $\mathbf{p} = \alpha\mathbf{a} + \beta\mathbf{b} + \gamma\mathbf{c}$ with $\alpha + \beta + \gamma = 1$
 - Unique for non-collinear $\mathbf{a}, \mathbf{b}, \mathbf{c}$
 - Ratio of triangle areas
 - $\alpha(\mathbf{p}), \beta(\mathbf{p}), \gamma(\mathbf{p})$ are linear functions
 - Gives inside/outside information




Barycentric Interpolation


- Barycentric coordinates:
 - $\mathbf{p} = \alpha\mathbf{a} + \beta\mathbf{b} + \gamma\mathbf{c}$ with $\alpha + \beta + \gamma = 1$
 - Unique for non-collinear $\mathbf{a}, \mathbf{b}, \mathbf{c}$
 - Ratio of triangle areas
 - $\alpha(\mathbf{p})$, $\beta(\mathbf{p})$, $\gamma(\mathbf{p})$ are linear functions
 - Gives inside/outside information
 - Use barycentric coordinates to interpolate vertex normals (or other data, e.g. colors)
$$\mathbf{n}(\mathbf{P}) = \alpha \cdot \mathbf{n}(\mathbf{A}) + \beta \cdot \mathbf{n}(\mathbf{B}) + \gamma \cdot \mathbf{n}(\mathbf{C})$$



Color Interpolation




Per-vertex



Evaluate color on vertices,
then interpolates it

Per-pixel



Interpolates positions and normals,
then evaluate color on each pixel


Triangle Rasterization

- Each triangle is represented as three 2D points (x_0, y_0) , (x_1, y_1) , (x_2, y_2)
- Rasterization using barycentric coordinates

$$x = a \cdot x_0 + \beta \cdot x_1 + \gamma \cdot x_2$$

$$y = a \cdot y_0 + \beta \cdot y_1 + \gamma \cdot y_2$$


$$a + \beta + \gamma = 1$$





Triangle Rasterization

- Each triangle is represented as three 2D points
 $(x_0, y_0), (x_1, y_1), (x_2, y_2)$
- Rasterization using barycentric coordinates

```
for all y do
  for all x do
    compute  $(\alpha, \beta, \gamma)$  for  $(x, y)$ 
    if  $(\alpha \in [0, 1] \text{ and } \beta \in [0, 1] \text{ and } \gamma \in [0, 1])$ 
      set_pixel  $(x, y)$ 
```





Clipping




- Ok if you do it brute force
- Care is required if you are explicitly tracing the boundaries

Objects Depth Sorting


- To handle occlusion, you can sort all the objects in a scene by depth
- This is not always possible!



z-buffering



Image





Depth (z)

- You render the image both in the Image and in the depth buffer, where you store only the depth
- When a new fragment comes in, you draw it in the image only if it is closer
- This always work and it is cheap to evaluate! It is the default in all graphics hardware
- You still have to sort for transparency...

z-buffer quantization and “z-fighting”

- The z-buffer is quantized (the number of bits is heavily dependent on the hardware platform)
- Two close objects might be quantized differently, leading to strange artifacts, usually called “z-fighting”



Super Sampling Anti-Aliasing



Non-antialiased type




Antialiased type



Enlarged portion of type


- Render $n \times n$ pixels instead of one
- Assign the average to the pixel




$$\frac{c_1 + c_2 + c_3 + c_4}{4}$$

Many different names and variants

- SSAA (FSAA)
- MSAA
- CSAA
- EQAA
- FXAA
- TX AA



MSAA



References

Fundamentals of Computer Graphics, Fourth Edition
4th Edition **by Steve Marschner, Peter Shirley**

Chapter 8