CABLE TERMINATION

BLIT Bimetallic Cable Lugs

Bimetallic cable lugs engineered for reliable copper-to-aluminium connections, secure crimping, and stable electrical conductivity.



KEY PRODUCT FEATURES

- **Copper & Aluminium Construction**
- **Bimetallic Connection Design**
- **Secure Crimp Termination**
- **Multiple Size Options**

Manufactured to strict British Standards, ensuring high durability, verified ratings, and dependable operation.

PRODUCT OVERVIEW & ENGINEERING DESIGN

BLIT Bimetallic Cable Lugs are designed for joining aluminium stranded cables to copper electrical busbars. The solid friction-welded joint eliminates galvanic electrolysis and contact resistance. Barrels are pre-filled with neutral antioxidant contact paste.

TECHNICAL SPECIFICATIONS

TECHNICAL PARAMETER	SPECIFICATION & RATING VALUE
Joint Construction	Friction-Welded Molecular Bond between Aluminium & Copper
Palm Material	Electrolytic Copper (99.9% Cu)
Barrel Material	High-Conductivity Aluminium (99.5% Al)
Internal Compound	Factory Pre-Filled with Neutral Antioxidant Contact Paste & Capped
Galvanic Protection	Prevents Electrolytic Corrosion between Dissimilar Metals
Conductor Range	16 mm² to 500 mm² Aluminium Conductors
Standards Compliance	IEC 61238-1 Class A Electrical & Mechanical Standards
Recommended Applications	Low & Medium Voltage Feeder Lines, Solar Inverter Substations, Main Panels