

BLIT ELECTRIC | V RANGE LUXURY CATALOGUE

Complete Specification Catalogue for Luxury Brushed Metal & Anthracite Wiring Accessories

BLIT V RANGE LUXURY COLLECTION

BLIT V Range represents an architectural benchmark in luxury wiring accessories. Crafted with premium brushed metal plates in anthracite and champagne finishes, combined with smooth tactile toggle switches and smart USB charging solutions, V Range is specified for luxury residential villas, boutique hotels, and executive workspaces.

1. PLATE SWITCHES

Model Code	Item Description & Specification	Dimensions	Standard Compliance
BTV301	1 gang 1 way switch	86 x 86 mm	BS EN 60669-1
BTV302	1 gang 2 way switch	86 x 86 mm	BS EN 60669-1
BTV313	1 gang 2 way intermediate switch	86 x 86 mm	BS EN 60669-1
BTV303	2 gang 1 way switch	86 x 86 mm	BS EN 60669-1
BTV304	2 gang 2 way switch	86 x 86 mm	BS EN 60669-1
BTV305	3 gang 1 way switch	86 x 86 mm	BS EN 60669-1
BTV306	3 gang 2 way switch	86 x 86 mm	BS EN 60669-1
BTV307	4 gang 1 way switch (wide plate)	146 x 86 mm	BS EN 60669-1
BTV307X	4 gang 2 way switch (square profile)	86 x 86 mm	BS EN 60669-1
BTV309	6 gang 1 way switch (wide plate)	146 x 86 mm	BS EN 60669-1

2. BELL & SPECIAL SWITCHES

Model Code	Item Description & Specification	Dimensions	Standard Compliance
BTV317	1 gang retractive bell push switch	86 x 86 mm	BS EN 60669-1

3. 20A & 45A SWITCHES

Model Code	Item Description & Specification	Dimensions	Standard Compliance
BTV324	20A 1 gang switch, DP + neon	86 x 86 mm	BS EN 60669-2-1
BTV327	45A 1 gang switch, DP + neon	86 x 86 mm	BS EN 60669-2-1
BTV329	45A 1 gang switch, DP + neon (large plate)	86 x 86 mm	BS EN 60669-2-1
BTV331	45A 1 gang switch + neon + 13A switched socket + neon (Cooker Control)	146 x 86 mm	BS 4177

4. DIMMERS & FAN CONTROLS

Model Code	Item Description & Specification	Dimensions	Standard Compliance
BTV350-2	1 gang 400W/500W rotary dimmer switch	86 x 86 mm	BS EN 60669-2-1
BTV351	1 gang 400W fan speed control switch	86 x 86 mm	IEC 60669
BTV353-2	2 gang 400W rotary dimmer switch	86 x 86 mm	BS EN 60669-2-1
BTV355	1 gang 500W dimmer switch	86 x 86 mm	BS EN 60669-2-1
BTV359	1 gang 600W/1000W dimmer switch	86 x 86 mm	BS EN 60669-2-1

5. SOCKET OUTLETS

Model Code	Item Description & Specification	Dimensions	Standard Compliance
BTV4010B	1 gang 13A single switched socket outlet	86 x 86 mm	BS 1363-2
BTV4030B	2 gang 13A twin switched socket outlet	146 x 86 mm	BS 1363-2
BTV4113-3.1A	1 gang 13A switched socket + 3.1A dual USB charger	86 x 86 mm	BS 1363-2 / IEC 62368
BTV4121-3.1A	2 gang 13A switched socket + 3.1A dual USB charger	146 x 86 mm	BS 1363-2 / IEC 62368

BLIT ELECTRIC | V RANGE LUXURY CATALOGUE

Complete Specification Catalogue for Luxury Brushed Metal & Anthracite Wiring Accessories

6. MULTI-FUNCTION & SPECIAL SOCKETS

Model Code	Item Description & Specification	Dimensions	Standard Compliance
BTV4243-3.1A	13A switched universal multi-socket + 3.1A USB	86 x 86 mm	IEC 60884
BTV4250	2 gang universal multi-socket outlet	146 x 86 mm	IEC 60884
BTV4253-3.1A	2 gang universal multi-socket + 3.1A USB	146 x 86 mm	IEC 60884 / IEC 62368
BTV429	15A 1 gang switched round-pin socket	86 x 86 mm	BS 546
BTV480	10A/13A 1 gang universal multi-socket	86 x 86 mm	IEC 60884
BTV482	13A 1 gang switched universal multi-socket + neon	86 x 86 mm	BS 1363 / IEC 60884
BTV484	13A 2 gang switched universal multi-socket	146 x 86 mm	BS 1363 / IEC 60884

7. FUSED CONNECTION UNITS & PLATES

Model Code	Item Description & Specification	Dimensions	Standard Compliance
BTV416	13A fused connection unit (FCU)	86 x 86 mm	BS 1363-4
BTV422	13A switched fused connection unit + neon	86 x 86 mm	BS 1363-4
BTV401	1 gang blank plate	86 x 86 mm	BS 5733
BTV402	2 gang blank plate	146 x 86 mm	BS 5733
BTV820	20A heavy-duty connection plate	86 x 86 mm	BS 5733
BTV821	45A heavy-duty connection plate	86 x 86 mm	BS 5733

8. DATA, TV & TELECOM OUTLETS

Model Code	Item Description & Specification	Dimensions	Standard Compliance
BTV442	1 gang RJ45 Cat6 data socket outlet (8 terminal)	86 x 86 mm	TIA/EIA-568
BTV443	2 gang RJ45 Cat6 data socket outlet (8 terminal)	86 x 86 mm	TIA/EIA-568