

IP55 SPLASHPROOF WIRING ACCESSORIES

Built for Everyday Exterior Safety, Balconies, Garages & Semi-Sheltered Utility Zones

1. IP55 Splashproof Switches (10AX / 20A Heavy Duty)

IMAGE	MODEL CODE	DESCRIPTION	DIMENSION	STANDARD / IP
	BTSP302	1 Gang 1 Way Splashproof Switch Plate (10AX)	86 x 86 mm	BS EN 60669-1 / IP55
	BTSP304	1 Gang 2 Way Splashproof Switch Plate (10AX)	86 x 86 mm	BS EN 60669-1 / IP55
	BTSP306	2 Gang 2 Way Splashproof Switch Plate (10AX)	86 x 86 mm	BS EN 60669-1 / IP55
	BTSP317	1 Gang Splashproof Bell Push Switch (10A)	86 x 86 mm	BS EN 60669-1 / IP55
	BTSP324	20A Double Pole Heavy-Duty Splashproof Switch + Neon	86 x 86 mm	BS EN 60669-2-1 / IP55

2. IP55 Switched Socket Outlets (13A BS 1363 / 15A BS 546)

IMAGE	MODEL CODE	DESCRIPTION	DIMENSION	STANDARD / IP
	BTSP405	13A 1 Gang Single Switched Socket with IP55 Spring Lid	86 x 86 mm	BS 1363-2 / IP55
	BTSP406	13A 2 Gang Twin Switched Socket with Dual IP55 Spring Lids	146 x 86 mm	BS 1363-2 / IP55

IMAGE	MODEL CODE	DESCRIPTION	DIMENSION	STANDARD / IP
	BTSP429	15A 1 Gang Round Pin Switched Socket with IP55 Spring Lid	86 x 86 mm	BS 546 / IP55