

IP55 SPLASHPROOF WIRING ACCESSORIES

Semi-Sheltered Outdoor & High Humidity Wiring Accessories with Transparent Spring Lids

1. IP55 Splashproof Switches (10AX / 20A Heavy Duty)



BTSP304

**1 Gang 2 Way Splashproof
Switch Plate (10AX)**

Dimensions: 86 x 86 mm

Standard: BS EN 60669-1 / IP55



BTSP306

**2 Gang 2 Way Splashproof
Switch Plate (10AX)**

Dimensions: 86 x 86 mm

Standard: BS EN 60669-1 / IP55



BTSP317

**1 Gang Splashproof Bell Push
Switch (10A)**

Dimensions: 86 x 86 mm

Standard: BS EN 60669-1 / IP55



BTSP324

**20A Double Pole Splashproof
Switch + Neon**

Dimensions: 86 x 86 mm

Standard: BS EN 60669-2-1 / IP55

2. IP55 Weatherproof Switched Socket Outlets with Transparent Cover



BTSP405

13A 1 Gang Switched Socket + IP55 Cover

Dimensions: 86 x 86 mm

Standard: BS 1363-2 / IP55



BTSP406

13A 2 Gang Twin Switched Socket + Dual IP55 Covers

Dimensions: 146 x 86 mm

Standard: BS 1363-2 / IP55



BTSP429

15A 1 Gang Round Pin Socket + IP55 Cover

Dimensions: 86 x 86 mm

Standard: BS 546 / IP55