

IP66 WEATHERPROOF WIRING ACCESSORIES

Dust-Tight & High Pressure Water Jet Protected Outdoor Switches & Protective Enclosures

1. IP66 Weatherproof Switches (20AX High Inrush Capacity)

IMAGE	MODEL CODE	DESCRIPTION	DIMENSION	STANDARD / IP
	BTAG3012WHI	1 Gang 2 Way Weatherproof Switch (20AX)	86 x 86 mm	BS EN 60669-1 / IP66
	BTAG3022WHI	2 Gang 2 Way Weatherproof Switch (20AX)	86 x 86 mm	BS EN 60669-1 / IP66
	BTAG3013WHI	1 Gang Intermediate Weatherproof Switch (20AX)	86 x 86 mm	BS EN 60669-1 / IP66
	BTAG3016WHI-BEL	1 Gang Retractive Bell Push Switch (10A)	86 x 86 mm	BS EN 60669-1 / IP66
	BTAG3214WHI	20A Double Pole Isolator Switch + Neon	86 x 86 mm	BS EN 60669-2-1 / IP66

2. IP66 Protective Socket Enclosures

IMAGE	MODEL CODE	DESCRIPTION	DIMENSION	STANDARD / IP
	BTAG-SKT	IP66 Double Socket Enclosure with Spring Lock	160 x 140 mm	BS 1363 / IP66