CABLE MANAGEMENT

BLIT Heavy-Duty GI Flexible Conduits

Heavy-duty galvanised flexible conduits designed for flexible cable routing, mechanical protection, and demanding installations.



KEY PRODUCT FEATURES

- **Heavy-Duty Galvanised Metal Construction**
- **Flexible Cable Routing**
- **Mechanical Cable Protection**
- **Multiple Size Options**

Manufactured to strict British Standards, ensuring high durability, verified ratings, and dependable operation.

PRODUCT OVERVIEW & ENGINEERING DESIGN

BLIT Heavy-Duty GI Flexible Conduits are manufactured from helically-wound interlocked galvanised steel strips, offering dynamic flexibility and superior crush protection. Designed for routing cables to motors, vibrating equipment, and intricate architectural bends.

TECHNICAL SPECIFICATIONS

TECHNICAL PARAMETER	SPECIFICATION & RATING VALUE
Core Material	Helically-Wound Hot-Dip Galvanised Mild Steel Strip (Interlocked Core)
Outer Coating	Available in Bare Galvanised Metal or Smooth Black PVC Over-Sheath
Mechanical Performance	Exceptional Crush Resistance, Tensile Strength, and Impact Toughness
Flexibility Rating	High Dynamic Bending Flexibility for Tight-Radius Routing
Temperature Range	-20°C to +105°C Service Temperature
Conduit Sizes (ID)	16mm, 20mm, 25mm, 32mm, 40mm, 50mm Internal Diameters
Ingress Protection	Up to IP66 with Matched Brass Compression Glands
Recommended Applications	Electric Motor Terminations, Industrial Machinery, HVAC, Vibrating Feeds