COMPUTER NETWORKS (CN)

LAB 2 ASSIGNMENT

AMARNATH C

RA2211026050037

CSE AIML A

3rd Year

Objective

- To configure static and default routing on routers to enable communication between different network segments.
- To use Cisco Packet Tracer to create a network with multiple routers and PCs and configure routing to ensure proper data transfer between devices.

Steps taken to set up the network

STEP 1:

Set up the network by dragging required end devices (PC0 and PC1), and network devices (Router PT, 2 Switch 2960-24TT's) and connect them using straight through copper cables.

STEP 2:

Using the config table given, just label the devices with a text box with ip address and subnet mask to ease it up



STEP 3:

Tap on Router-PT and navigate to the physical tab, add PT-ROUTER-NM-1CGE Module to the router after turning the power off, and turn on the power after adding at least two of those modules.





STEP 4:

Now connect the Switches via Straight through the cable to the router PT on GigabitEthernet 6/0 and 7/0 respectively.

STEP 5:

Open the Router PT and open the CLI tab;

On CLI tab follow up with these commands below;

```
Press RETURN to get started!



Router>
Router>enable
Router#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#int GigabitEthernet 6/0
Router(config-if)#ip address 192.168.0.65 255.255.255.224
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet6/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet6/0, changed state to up

Router(config-if)#exit
Router(config)#int GigabitEthernet 7/0
Router(config-if)#ip address 192.168.0.1 255.255.255.192
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet7/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet7/0, changed state to up

Router(config-if)#exit
Router(config)#
```

STEP 6:

Open switches and open the CLI and use the commands as shown

```
Switch>enable
Switch#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#int vlan 1
Switch(config-if)#ip address 192.168.0.64 255.255.255.192
Bad mask /26 for address 192.168.0.64
Switch(config-if)#
Switch(config-if)#
Switch(config-if)#
Switch(config-if)#
%LINK-3-UPDOWN: Interface FastEthernet0/1, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to down

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

Switch(config-if)#
Switch(config-if)#
Switch(config-if)#
```

STEP 7:

Open the PC0 and PC1 and configure IP addresses




PC1
Physical
Config
Desktop
Programming
Attributes
IP Configuration
X
Interface
FastEthernet0
IP Configuration
DHCP
Static
IPv4 Address
192.168.0.66
Subnet Mask
255.255.255.224
Default Gateway
192.168.0.65
DNS Server
0.0.0.0
IPv6 Configuration
Automatic
Static
IPv6 Address
/
Link Local Address
FE80::2E0:A3FF:FED7:19A2
Default Gateway
DNS Server
802.1X
Use 802.1X Security
Authentication
MD5
Username
Password
Top

STEP 8:

Ping PC1 from PC0



Simulation ping PC1 from PC0:
ARP REQUEST:






192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66

ARP REPLY:


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66


192.168.0.1 --
255.255.255.192
192.168.0.65
255.255.255.224
Router-PT
R0
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66

ARP REQUEST:


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66

ARP REPLY:





ICMP ECHO REQUEST:


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66



ICMP ECHO REPLY:




192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66


192.168.0.1 --
255.255.255.192
Router-PT
R0
192.168.0.65
255.255.255.224
2960-24TT
A
192.168.0.64
2960-24TT
B
192.168.0.254
PC-PT
PC0
192.168.0.2
PC-PT
PC1
192.168.0.66