

DOM

JS HTML

Method

`getElementById()`

`getElementsByTagName()`

`getElementsByClassName()`

`querySelector()`

`querySelectorAll()`

`createElement()`

`removeChild()`

Purpose

Select element by id

Select elements by tag

Select elements by class

Select first matching element

Select all matching elements

Create new element

Remove element

```
<!DOCTYPE html>
<html>
<head>
<title>Example</title>
</head>

<body>
<h1 id="title">Hello World</h1>
<button onclick="changeText()">Click Me</button>

<script>
function changeText() {
    document.getElementById("title").innerHTML = "Hello JavaScript!";
}
</script>

</body>
</html>
```

```
<!DOCTYPE html>
<html>
<body>

<p>Paragraph 1</p>
<p>Paragraph 2</p>

<script>
var x = document.getElementsByTagName("p");
x[0].style.color = "red";
</script>

</body>
</html>
```

```
<!DOCTYPE html>
<html>
<body>

<p class="demo">Paragraph 1</p>
<p class="demo">Paragraph 2</p>

<script>
document.querySelector(".demo").style.color = "green";
</script>

</body>
</html>
```

```
<!DOCTYPE html>
<html>
<body>

<p class="test">First paragraph</p>
<p class="test">Second paragraph</p>

<script>
var x = document.getElementsByClassName("test");
x[1].style.color = "blue";
</script>

</body>
</html>
```

```
<!DOCTYPE html>
<html>
<body>

<p class="demo">Paragraph 1</p>
<p class="demo">Paragraph 2</p>

<script>
var x = document.querySelectorAll(".demo");
x[0].style.color = "red";
x[1].style.color = "blue";
</script>

</body>
</html>
```

```
<!DOCTYPE html>
<html>
<body>

<div id="container"></div>

<script>
var p = document.createElement("p");
p.innerHTML = "New Paragraph";

document.getElementById("container").appendChild(p);
</script>

</body>
</html>
```

```
<!DOCTYPE html>
<html>
<body>

<ul id="list">
<li>Item 1</li>
<li id="remove">Item 2</li>
</ul>

<script>
var parent = document.getElementById("list");
var child = document.getElementById("remove");

parent.removeChild(child);
</script>

</body>
</html>
```