

GTM Tracking Important Notes

Project: Blinkit Clone

GTM Container: GTM-K9DRNHRR

1. Short Summary

Website me Google Tag Manager installed hai. Code ecommerce actions ko window.dataLayer me push karta hai. GTM me marketer Google Ads / GA4 tags ko in events par fire kara sakta hai.

2. GTM Script Kahan Add Hai

GTM script Layout.jsx me nahi hai. GTM script root index.html file me add hai. Layout.jsx sirf Header, Outlet, Footer render karta hai.

```
// index.html
(function (w, d, s, l, i) {
  w[l] = w[l] || [];
  w[l].push({
    "gtm.start": new Date().getTime(),
    event: "gtm.js"
  });
  var f = d.getElementsByTagName(s)[0],
      j = d.createElement(s),
      dl = l != "dataLayer" ? "&l=" + l : "";
  j.async = true;
  j.src = "https://www.googletagmanager.com/gtm.js?id=" + i + dl;
  f.parentNode.insertBefore(j, f);
})(window, document, "script", "dataLayer", "GTM-K9DRNHRR");
```

3. Live Tracking Ka Matlab

Tag Assistant ka Connect button sirf preview/debug mode ke liye hota hai. Real users ko connect karne ki zarurat nahi hoti.

Live tracking tab kaam karegi jab GTM container published ho, Google Ads/GA4 tags configured hon, aur triggers correct events par lage hon.

4. dataLayer Helper Function

```
// src/lib/gtm.ts
export const pushToDataLayer = (data: object) => {
  window.dataLayer = window.dataLayer || [];
  window.dataLayer.push(data);
};
```

Ye function event object ko GTM dataLayer me bhejta hai.

5. Ecommerce Events Used

- add_to_cart: user ADD button click karta hai.
- view_cart: user cart drawer open karta hai.
- begin_checkout: user Proceed Item click karta hai.
- purchase: user Fake Pay Now click karta hai.

6. add_to_cart Code

```
pushToDataLayer({
  event: "add_to_cart",
```

```

ecommerce: {
  currency: "INR",
  value: Number(item.price),
  items: [
    {
      item_id: item.id,
      item_name: item.name || item.FirstP,
      price: Number(item.price),
      quantity: 1
    }
  ]
}
});

```

7. view_cart Code

```

pushToDataLayer({
  event: "view_cart",
  ecommerce: {
    currency: "INR",
    value: cart.totalPrice,
    items: cart.items.map((item) => ({
      item_id: item.id,
      item_name: getItemName(item),
      price: Number(item.price),
      quantity: item.quantity
    })))
  }
});

```

8. begin_checkout Code

```

pushToDataLayer({
  event: "begin_checkout",
  ecommerce: {
    currency: "INR",
    value: cart.totalPrice,
    items: cart.items.map((item) => ({
      item_id: item.id,
      item_name: getItemName(item),
      price: item.price,
      quantity: item.quantity
    })))
  }
});

```

```

navigate("/checkout");

```

9. purchase Code

```

const handlePayment = () => {
  pushToDataLayer({

```

```

event: "purchase",
ecommerce: {
  transaction_id: "ORDER_" + Date.now(),
  currency: "INR",
  value: cart.totalPrice,
  items: cart.items.map((item) => ({
    item_id: item.id,
    item_name: item.name || item.FirstP || "Unknown Product",
    price: item.price,
    quantity: item.quantity
  })))
}
});

console.log("purchase fired");
navigate("/success");
};

```

10. Ecommerce Object Meaning

- event: GTM trigger ke liye event name.
- currency: currency code, yahan INR.
- value: product/cart total amount.
- transaction_id: purchase order id.
- items: product list array.
- item_id: product id.
- item_name: product name.
- price: product price.
- quantity: product quantity.

11. item_name Undefined Fix

Pehle kuch products ka naam FirstP me tha aur selected product pages ka naam name me tha. Isliye item_name undefined aa sakta tha.

```

const itemName = newItem.name || newItem.FirstP;

name: itemName,
FirstP: itemName

```

Events me fallback use hua:

```

item.name || item.FirstP || "Unknown Product"

```

Note: Agar browser localStorage me old cart item undefined ke saath saved hai, to cart clear karke item dobara add karna hoga.

12. GTM Preview Undefined Fields

allowlist, blocklist, whitelist, blacklist, tagTypeBlacklist undefined GTM ke internal debug fields hain. Ye hamare ecommerce data ka issue nahi hai.

Important check: ecommerce.items ke andar item_name, price, quantity sahi aa rahe hon.

13. UTM Add Kiya Hai Ya Nahi

Nahi. Is project me UTM reader/pusher code add nahi kiya gaya. Humne GTM + ecommerce dataLayer tracking add ki hai.

Example UTM URL:

?utm_source=google&utm_medium=cpc&utm_campaign=sale

Google Ads ke liye generally gclid auto-tagging + Conversion Linker use hota hai. UTM separate reporting need ho to later add kiya ja sakta hai.

14. GTM Setup For Marketer

- GTM container GTM-K9DRNHRR open karo.
- Conversion Linker tag add karo, trigger: All Pages.
- Google Ads Conversion tag add karo.
- Purchase trigger: Custom Event purchase.
- Value variable: ecommerce.value.
- Currency variable: ecommerce.currency.
- Transaction ID variable: ecommerce.transaction_id.
- Preview test karo, phir container publish karo.

15. GTM vs GA4 vs UTM Difference

GTM: Google Tag Manager. Tags manage/run karta hai. Example: GTM-K9DRNHRR.

GA4: Google Analytics 4. Analytics reports banata hai, users/events analyze karta hai.

Example: add_to_cart, purchase reports.

UTM: Campaign URL parameters. Source/medium/campaign identify karta hai. Example: utm_source=google.

16. Final Notes

Code side complete hai for ecommerce dataLayer events. Live reporting ke liye GTM side tags/triggers publish karne honge. UTM currently add nahi hai; ye future optional requirement hai.