Unfolded Hyperspectral and Multispectral Image Fusion with Exact Observation Operators

Anonymous CVPR submission

Abstract

Deep unfolding networks for hyperspectral and multispectral image fusion alternate data-consistency steps with learned priors. In most of them the blur, downsampling and spectral-response operators are learned or use zero padding, so they differ from the operators that produced the data, and each network is trained for a single sensor pair. We study what exact operators bring to such a network. With a separable blur and the true border rule, the data step has a closed form in a product eigenbasis, and the null space of fusion, the part of the image that no observation constrains, is explicit. An exact data step keeps the ground truth fixed, while an inexact one moves it by an amount that we bound, and both operators can be estimated from the two observations. Our network, PUFormer, combines exact data steps with a residual U-Net prior and is trained over a family of blurs, spectral responses and noise levels. We retrain five published fusion networks from their authors' code under one protocol and training budget. PUFormer is the most accurate on Chikusei and Pavia Centre, by 0.99 and 1.00 dB PSNR, and its error in the observed subspace is 5.8–8.6 times smaller. Most of the margin comes from the prior and its training; the exact data steps add a smaller gain and make the operator replaceable at test time. Trained over the operator family, PUFormer stays accurate when the blur, the spectral response or the noise change, but not under misregistration.

1. Introduction

Hyperspectral cameras record hundreds of narrow bands at a coarse spatial resolution, and multispectral cameras record a few broad bands at a fine one. Fusing the two images gives a high-resolution hyperspectral image (HR-HSI) [31, 41]. Most recent methods are deep networks trained on simulated pairs: convolutional networks [48], transformers [7, 16, 18], state-space models [21, 23] and diffusion models [3, 6].

Deep unfolding networks [9, 14, 36, 37] take a different route. They unroll an iterative solver of the inverse problem, and each stage applies a data step, which reduces the mismatch between the estimate and the two observations, followed by a learned prior. The data step needs the blur, the downsampling and the spectral response of the sensors. In most unfolding networks these operators are learned convolution layers, or fixed but zero-padded, whereas the benchmark data are simulated with a known blur and a different border rule. The network's operator then differs from the one that produced the data, and even the ground truth fails the network's own consistency check. Each network is also trained for one sensor pair and cannot use another operator at test time.

Evaluation is a second problem. Results on the same dataset vary widely between papers because splits, spectral responses, normalizations and metric code differ [31]. PSRT [7], for example, is reported at 44.60 dB PSNR on Chikusei $\times 4$ in [21] and at 50.67 dB in [6]. Numbers copied from different papers therefore say little about which method is better.

This paper asks what exact operators bring to an unfolded fusion network. We write fusion as maximum a posteriori (MAP) estimation with parametric operators, unroll half-quadratic splitting (HQS) [46], and study the resulting data step. Our contributions are:

- An analysis of the operators in unfolded fusion: with a separable blur and the true border rule, the data step has a closed form and the null space of fusion is explicit (it holds 88% of the unknowns on Chikusei); an exact data step keeps the ground truth fixed, while the displacement caused by an inexact one is bounded independently of the learned weights; and both operators are identifiable from the observation pair (Sec. 3).
- PUFormer, an unfolded network with exact and replaceable operators, a learned spectral data step that keeps these guarantees, and training over a family of observation models with the operators estimated at test time (Sec. 4).
- An equal-budget benchmark of five published networks, retrained from their authors' code, and a null-space split of the error that shows where each method fails (Sec. 5). It also shows where PUFormer's margin comes from: mostly from the prior and its training, while the exact operators matter most when the operator changes.

2. Related work

Deep fusion networks map the two observations directly to the HR-HSI with convolutions [48], transformers [7, 11, 16, 18, 38], general fusion backbones [22], state-space models [21, 23] or diffusion [3, 6], without using the observation model.

Unfolding and operator knowledge. Algorithm unrolling [13, 19] turns the iterations of a solver into network stages. MHF-Net [36], MoG-DCN [9] and DHIF-Net [14] unfold fusion solvers with learned or approximate operators, and later networks strengthen the learned prior [2, 33, 37] or the proximal update [42]. In single-image super-resolution, USRNet [46] gives the blur kernel to a closed-form data step under periodic borders and predicts its step sizes from the noise level, and blind methods train on randomized degradations [45, 47]. We carry this idea over to fusion, where two operators and the border rule must match the data, and analyze what it gives and costs.

Closed forms and separable operators. FUSE [35] solves the quadratic fusion problem through a Sylvester equation under periodic borders. Tensor methods [15, 17, 25] model the spatial degradation as separable matrices to prove recoverability of low-rank models. Our closed form holds for the reflect border of the simulation and is used as a differentiable layer whose operators change from image to image. Learned filters in a data step resemble deep Wiener deconvolution [8]; we bound ours so that the step stays non-expansive.

Range and null space. Splitting a reconstruction into a part determined by the measurements and a null-space part is the basis of null-space networks [28], decomposition learning [5] and diffusion-based restoration [34]. We use the explicit null space of fusion to analyze the errors of existing methods. That an image border or an adjoint that do not match the data bias an iterative reconstruction is known from deconvolution and tomography [20, 27, 44].

3. Exact operators in unfolded fusion

3.1. Observation model and unfolding

Let $\mathbf{X} \in \mathbb{R}^{B\times H\times W}$ be the HR-HSI. The two observations are

$$\mathbf{Y}_{\mathrm{H}} = \mathcal{D}_\theta \mathbf{X} + \mathbf{N}_{\mathrm{H}}, \qquad \mathbf{Y}_{\mathrm{M}} = \mathcal{R}_\phi \mathbf{X} + \mathbf{N}_{\mathrm{M}}, \tag{1}$$

where $\mathcal{D}_\theta$ applies to every band reflect padding, a Gaussian blur of width θ and decimation by s starting at index zero, so $\mathbf{Y}_{\mathrm{H}} \in \mathbb{R}^{B\times h\times w}$ with $h = H/s$, $w = W/s$; $\mathcal{R}_\phi$ applies to every pixel the M spectral responses of the multispectral sensor, shifted along wavelength by ϕ nm; and $\mathbf{N}_{\mathrm{H}}, \mathbf{N}_{\mathrm{M}}$ are white Gaussian noise with standard deviations $\varsigma_{\mathrm{H}}, \varsigma_{\mathrm{M}}$. The benchmarks use $s = 4$, a 7×7 blur with $\theta = \sigma_0 = 2$, $\phi = 0$ and no noise [6]. We implement $\mathcal{D}_\theta$ and its exact adjoint, in which the adjoint of reflect padding adds the padded margins back onto the pixels they were copied from (the supplementary material); the adjoint test $\langle \mathcal{D}\mathbf{X}, \mathbf{Y}\rangle = \langle \mathbf{X}, \mathcal{D}^\top \mathbf{Y}\rangle$ holds to 10^{-13} in double precision.

With a prior $p(\mathbf{X}) \propto \exp(-\lambda\Phi(\mathbf{X}))$, the MAP estimate minimizes $\frac{1}{2\varsigma_{\mathrm{H}}^2}\|\mathcal{D}_\theta\mathbf{X}-\mathbf{Y}_{\mathrm{H}}\|^2 + \frac{1}{2\varsigma_{\mathrm{M}}^2}\|\mathcal{R}_\phi\mathbf{X}-\mathbf{Y}_{\mathrm{M}}\|^2 + \lambda\Phi(\mathbf{X})$. HQS couples $\mathbf{X}$ to an auxiliary image $\mathbf{Z}$ with a penalty $\frac{\mu_k}{2}\|\mathbf{Z}-\mathbf{X}\|^2$ and alternates a data step and a prior step, $\mathbf{X}_k = \mathrm{prox}_{(\lambda/\mu_k)\Phi}(\mathbf{Z}_k)$. With $\alpha_k = 1/(\mu_k\varsigma_{\mathrm{H}}^2)$ and $\beta_k = 1/(\mu_k\varsigma_{\mathrm{M}}^2)$ the data step is the linear system

$$(\mathbf{I}+\alpha_k\mathcal{D}_\theta^\top\mathcal{D}_\theta+\beta_k\mathcal{R}_\phi^\top\mathcal{R}_\phi)\mathbf{Z}_k = \mathbf{X}_{k-1}+\alpha_k\mathcal{D}_\theta^\top\mathbf{Y}_{\mathrm{H}}+\beta_k\mathcal{R}_\phi^\top\mathbf{Y}_{\mathrm{M}}, \tag{2}$$

and one gradient step from $\mathbf{X}_{k-1}$ is its linearization,

$$\mathbf{Z}_k \approx \mathbf{X}_{k-1}-\alpha_k\mathcal{D}_\theta^\top(\mathcal{D}_\theta\mathbf{X}_{k-1}-\mathbf{Y}_{\mathrm{H}})-\beta_k\mathcal{R}_\phi^\top(\mathcal{R}_\phi\mathbf{X}_{k-1}-\mathbf{Y}_{\mathrm{M}}). \tag{3}$$

An unfolded network replaces the proximal map by a learned module. The derivation already says two things about such a network: the ratio $\beta_k/\alpha_k = \varsigma_{\mathrm{H}}^2/\varsigma_{\mathrm{M}}^2$ should follow the noise of the two observations, and the operators enter only through $\mathcal{D}_\theta$, $\mathcal{R}_\phi$ and their adjoints, so they can be replaced at test time without retraining.

3.2. Separable structure and the fusion null space

A Gaussian blur aligned with the image axes is separable, and padding and decimation act on rows and columns independently. The operators therefore factor exactly, border included:

$$\mathcal{D}_\theta\mathbf{X} = \mathbf{X}\times_2\mathbf{D}_{\mathrm{r}}\times_3\mathbf{D}_{\mathrm{c}}, \qquad \mathcal{R}_\phi\mathbf{X} = \mathbf{X}\times_1\mathbf{r}_\phi, \tag{4}$$

where $\times_n$ is the mode-n product, $\mathbf{D}_{\mathrm{r}} \in \mathbb{R}^{h\times H}$ and $\mathbf{D}_{\mathrm{c}} \in \mathbb{R}^{w\times W}$ pad, blur and decimate one axis, and $\mathbf{r}_\phi \in \mathbb{R}^{M\times B}$ holds the spectral responses.

Theorem 1 (Closed-form data step and null space)**.** *Let* $\mathbf{D}_{\mathrm{r}}^\top\mathbf{D}_{\mathrm{r}} = \mathbf{U}_{\mathrm{r}}\mathrm{diag}(\boldsymbol{\lambda}^{\mathrm{r}})\mathbf{U}_{\mathrm{r}}^\top$, $\mathbf{D}_{\mathrm{c}}^\top\mathbf{D}_{\mathrm{c}} = \mathbf{U}_{\mathrm{c}}\mathrm{diag}(\boldsymbol{\lambda}^{\mathrm{c}})\mathbf{U}_{\mathrm{c}}^\top$ *and* $\mathbf{r}_\phi^\top\mathbf{r}_\phi = \mathbf{V}\mathrm{diag}(\boldsymbol{\nu})\mathbf{V}^\top$*, and let* $\mathcal{Q}(\cdot) = (\cdot)\times_1\mathbf{V}\times_2\mathbf{U}_{\mathrm{r}}\times_3\mathbf{U}_{\mathrm{c}}$*. (a)* $\mathcal{D}_\theta^\top\mathcal{D}_\theta$ *and* $\mathcal{R}_\phi^\top\mathcal{R}_\phi$ *are diagonal in the orthonormal basis* $\mathcal{Q}$*, with eigenvalues* $\lambda_i^{\mathrm{r}}\lambda_j^{\mathrm{c}}$ *and* ν_b*. (b) The solution of* (2) *is*

$$\mathbf{Z}_k = \mathcal{Q}\Big(\mathcal{Q}^{-1}(\mathbf{C}_k) \oslash \big[1+\alpha_k\lambda_i^{\mathrm{r}}\lambda_j^{\mathrm{c}}+\beta_k\nu_b\big]_{bij}\Big), \tag{5}$$

with $\mathbf{C}_k$ *the right-hand side of* (2) *and* $\oslash$ *element-wise division. (c) The joint null space* $\mathcal{N}(\mathcal{D}_\theta)\cap\mathcal{N}(\mathcal{R}_\phi)$ *is spanned by the basis tensors with* $\nu_b = 0$ *and* $\lambda_i^{\mathrm{r}}\lambda_j^{\mathrm{c}} = 0$*. If* $\mathbf{r}_\phi$*,* $\mathbf{D}_{\mathrm{r}}$ *and* $\mathbf{D}_{\mathrm{c}}$ *have full row rank, its dimension is* $(B-M)(HW-hw)$*, a fraction* $(1-M/B)(1-1/s^2)$ *of the unknowns.*

The proof (the supplementary material) uses the mixed-product rule of the Kronecker product: every factor of $\mathcal{Q}$

diagonalizes one mode. The step (5) costs three mode products in each direction, $O(BHW(B+H+W))$ operations, and needs no iteration. FUSE [35] solves the same system with Fourier transforms, which assumes periodic borders; (5) holds for the border rule of the simulation, at the cost of eigendecompositions of an $H \times H$, a $W \times W$ and a $B \times B$ matrix per operator. Part (c) states what any fusion method must infer from a prior: the high spatial frequencies of the spectral directions that the multispectral sensor does not see. This is 88% of the unknowns on Chikusei and 90% on Pavia Centre at $\times 4$. Every other component is fixed by the observations, which lets us split the error of any method into a part that contradicts the observations and a part in the null space (Sec. 5.3).

3.3. The cost of an inexact operator

Stack the data terms as $\mathbf{A} = [\mathcal{D}_\theta; \mathcal{R}_\phi]$, $\mathbf{Y} = [\mathbf{Y}_\mathrm{H}; \mathbf{Y}_\mathrm{M}]$ and $\mathbf{W}_k = \mathrm{diag}(\alpha_k \mathbf{I}, \beta_k \mathbf{I})$, and let $\tilde{\mathbf{A}}$ be the operator a network actually uses: one with a zero border, a learned one, or one with wrong parameters. Write $T(\mathbf{V}) = (\mathbf{I} + \tilde{\mathbf{A}}^\top \mathbf{W}_k \tilde{\mathbf{A}})^{-1}(\mathbf{V} + \tilde{\mathbf{A}}^\top \mathbf{W}_k \mathbf{Y})$ for the exact data step and $G(\mathbf{V}) = \mathbf{V} - \tilde{\mathbf{A}}^\top \mathbf{W}_k(\tilde{\mathbf{A}}\mathbf{V} - \mathbf{Y})$ for its linearization.

Theorem 2 (Fixed point and operator mismatch)**.** *Let* $\mathbf{Y} = \mathbf{A}\mathbf{X}^*$. *(a) If* $\tilde{\mathbf{A}} = \mathbf{A}$, *then* $T(\mathbf{X}^*) = G(\mathbf{X}^*) = \mathbf{X}^*$ *for all* $\alpha_k, \beta_k > 0$. *(b) For any* $\tilde{\mathbf{A}}$, *with* $\mathbf{e} = \mathbf{W}_k^{1/2}(\mathbf{A} - \tilde{\mathbf{A}})\mathbf{X}^*$,

$$\|T(\mathbf{X}^*) - \mathbf{X}^*\| \le \tfrac{1}{2}\|\mathbf{e}\|, \qquad \|G(\mathbf{X}^*) - \mathbf{X}^*\| \le \|\mathbf{W}_k^{1/2}\tilde{\mathbf{A}}\|\,\|\mathbf{e}\|. \tag{6}$$

(c) If stage k *computes* $\mathbf{X}_k = (\mathcal{I} + \mathcal{P}_k)(T_k(\mathbf{X}_{k-1}))$ *with a residual prior that satisfies* $\mathcal{P}_k(\mathbf{X}^*) = \mathbf{0}$ *and makes* $\mathcal{I} + \mathcal{P}_k$ L_k*-Lipschitz, then a* K*-stage network started at* $\mathbf{X}^*$ *returns* $\|\mathbf{X}_K - \mathbf{X}^*\| \le \frac{1}{2}\sum_{k=1}^{K}\big(\prod_{j=k}^{K} L_j\big)\|\mathbf{e}_k\|$, *where* $\mathbf{e}_k$ *is* $\mathbf{e}$ *for the weights* $\mathbf{W}_k$ *of stage* k.

The bounds follow from the singular values of $(\mathbf{I} + \mathbf{B}^\top\mathbf{B})^{-1}\mathbf{B}^\top$ with $\mathbf{B} = \mathbf{W}_k^{1/2}\tilde{\mathbf{A}}$, which are $b_i/(1+b_i^2) \le \frac{1}{2}$, and from the nonexpansiveness of T_k (the supplementary material). With the exact operator the ground truth is a fixed point of every data step, and the priors only have to remove reconstruction error. With an inexact one every data step moves the ground truth, and the priors must undo this displacement as well; since it depends on the image, no fixed correction removes it. The exact proximal step bounds the displacement whatever the learned weights are, whereas the gradient step does not, because training can make $\|\mathbf{W}_k^{1/2}\tilde{\mathbf{A}}\|$ large. The theorem also explains why an exact operator can be swapped: for data generated by $\mathbf{A}'$, giving the network $\tilde{\mathbf{A}} = \mathbf{A}'$ restores (a), which a learned operator cannot do.

Corollary 1 (Border rule)**.** *If* $\tilde{\mathbf{A}}$ *differs from* $\mathbf{A}$ *only in the border rule of* $\mathcal{D}_\theta$, *then* $(\mathbf{A} - \tilde{\mathbf{A}})\mathbf{X}^*$ *is nonzero only on the low-resolution pixels whose kernel support reaches the padding, i.e., within* $\lceil p/s \rceil$ *pixels of the border for a* $(2p+1) \times (2p+1)$ *kernel.*

For our benchmarks only the first low-resolution row and column are affected: 3% of a 64×64 test image, but 12% of the 16×16 patches on which networks are trained.

3.4. Estimating the operators

Theorem 3 (Identifiability)**.** *Let* $\mathcal{D}_\theta$ *act identically on every band and* $\mathcal{R}_\phi$ *identically on every pixel. (a)* $\mathcal{D}_\theta\mathcal{R}_{\phi'} = \mathcal{R}_{\phi'}\mathcal{D}_\theta$, *so for noise-free data generated with* (θ^*, ϕ^*) *the criterion*

$$J(\theta, \phi) = \|\mathcal{D}_\theta \mathbf{Y}_\mathrm{M} - \mathcal{R}_\phi \mathbf{Y}_\mathrm{H}\|^2 \tag{7}$$

vanishes at (θ^*, ϕ^*). *(b) On a finite set* $\mathcal{G}$ *of candidate parameters on which* $\theta \mapsto \mathcal{D}_\theta$ *and* $\phi \mapsto \mathbf{r}_\phi$ *are injective, and if no column of* $\mathbf{r}_\phi$ *vanishes,* (θ^*, ϕ^*) *is the unique zero of* J *on* $\mathcal{G}$ *for almost every* $\mathbf{X}$.

Part (a) is the relation HySure [29] uses to estimate the responses of a model-based method; part (b) shows that a grid search on J cannot be fooled by a wrong pair except for a set of images of measure zero (the supplementary material). We minimize J on a grid with steps of $0.025\,\sigma_0$ and 1 nm. Noise biases the blur estimate upward by an amount that vanishes as the SNR grows, and the theorem needs the family to contain the true operator; Sec. 5.5 tests what happens when it does not.

4. PUFormer

Stages. PUFormer (Fig. 1) unrolls HQS for $K = 3$ stages from the bicubic upsampling $\mathbf{X}_0$ of $\mathbf{Y}_\mathrm{H}$. Stage k first takes a data step with the exact operators, either the linearized step

$$\begin{aligned}\mathbf{Z}_k = \mathbf{X}_{k-1} &- s^2\alpha_k \mathcal{D}_\theta^\top(\mathcal{D}_\theta \mathbf{X}_{k-1} - \mathbf{Y}_\mathrm{H}) \\ &- \beta_k \mathcal{R}_\phi^\top(\mathcal{R}_\phi \mathbf{X}_{k-1} - \mathbf{Y}_\mathrm{M})\end{aligned} \tag{8}$$

or the closed form (5). The step sizes $\alpha_k = \mathrm{softplus}(a_k)$ and $\beta_k = \mathrm{softplus}(b_k)$ are learned per stage, and the factor s^2 compensates the $1/s^2$ gain of $\mathcal{D}^\top\mathcal{D}$ on smooth images. The prior step is a learned residual, $\mathbf{X}_k = \mathbf{Z}_k + \Delta_k$ with $(\Delta_k, \mathbf{F}_k) = \mathcal{P}_k([\mathbf{Z}_k, \mathbf{Y}_\mathrm{M}, s^2\mathcal{D}^\top(\mathcal{D}\mathbf{Z}_k - \mathbf{Y}_\mathrm{H})], \mathbf{F}_{k-1})$: the third input tells the prior where the estimate still disagrees with $\mathbf{Y}_\mathrm{H}$, and $\mathbf{F}_{k-1}$ are the decoder features of the previous stage (cross-stage memory [30]). The last layer of every prior starts at zero, so training starts from plain HQS, for which the condition $\mathcal{P}_k(\mathbf{X}^*) = \mathbf{0}$ of Theorem 2(c) holds. All operator applications run in 32-bit precision.

Learned spectral data step. In the basis of Theorem 1 the exact step multiplies each component of the data residual by $1/(1 + \alpha_k \lambda_i^\mathrm{r} \lambda_j^\mathrm{c} + \beta_k \nu_b)$, the filter of a white Gaussian prior. Images are not white and noise does not affect all components equally, so we let two small networks modulate these




Figure 1. PUFormer, the HQS iteration of Section 3.1 unrolled for three stages. Top: the observation model is set up once per image: the operator parameters are given or estimated from the observation pair (Theorem 3), the exact operators and their eigenbasis are built (Theorem 1), and the noise levels form the observation code $\mathbf{c}$. Middle: every stage refines the estimate and passes its decoder features to the next (memory). Bottom: inside a stage, a data step makes the estimate agree with both observations, and a learned prior adds the detail that the observations cannot provide.




Figure 2. The data step of stage k, the exact solution of (2). Two physics branches compare the estimate with the observations: the spatial branch blurs and downsamples it and compares it with the LR-HSI, the spectral branch applies the multispectral responses and compares it with the HR-MSI; both mismatches are spread back to the full cube by the exact adjoints. The closed-form solve rotates this correction into the eigenbasis of the separable operators, removes in each component a share $\Gamma_{bij}(\alpha_k \lambda_i^\mathrm{r} \lambda_j^\mathrm{c} + \beta_k \nu_b)$ of the mismatch that grows with how strongly the observations see that component (blue: the exact step (5); orange: the range allowed to the learned gains of Proposition 1), and rotates back. Components that neither observation sees (the null space) are left to the prior.

gains:

$$\mathbf{Z}_k = \mathbf{X}_{k-1} + \mathcal{Q}\big(\mathcal{Q}^{-1}(\mathbf{G}_k) \odot \mathbf{\Gamma}_k\big),$$
$$\Gamma_{k,bij} = \frac{\exp\big(\ln 2 \tanh(u_k(\lambda^{\mathrm{r}}_i \lambda^{\mathrm{c}}_j) + v_k(\nu_b))\big)}{1 + \alpha_k \lambda^{\mathrm{r}}_i \lambda^{\mathrm{c}}_j + \beta_k \nu_b}, \quad (9)$$

where $\mathbf{G}_k = \alpha_k \mathcal{D}_\theta^\top(\mathbf{Y}_{\mathrm{H}} - \mathcal{D}_\theta \mathbf{X}_{k-1}) + \beta_k \mathcal{R}_\phi^\top(\mathbf{Y}_{\mathrm{M}} - \mathcal{R}_\phi \mathbf{X}_{k-1})$ and u_k, v_k are two-layer perceptrons of the log-eigenvalues (and of the observation code below), initialized to zero so that training starts from (5). The gain factors over space and spectrum, so the perceptrons run $HW + B$ times per stage, not BHW times.

Proposition 1. *For any u_k, v_k: (a) with exact operators and noise-free data, $\mathbf{X}^*$ is a fixed point of (9); (b) the step is nonexpansive; (c) with an inexact operator it moves $\mathbf{X}^*$ by at most $\|\mathbf{e}\|$, twice the bound (6) of the exact step.*

The gain lies in $(\frac{1}{2}, 2)$ times the exact one, which keeps every factor of the step in $(-1, 1]$ (the supplementary material). The learned step can thus change how much the network trusts each observed component, but it cannot move a correct estimate or amplify errors.

Prior. Each prior is a three-level U-Net [26] (widths 48, 96, 192) of Restormer blocks [43], whose transposed attention forms a channel-by-channel attention map with a cost linear in the number of pixels. The three priors hold 3.4 M parameters each, 10.1 M in total for Chikusei. Their design is not our contribution, and Sec. 5.4 shows that a convolutional mixer works about as well.

Training over a family of observation models. A network trained with one operator pair on noise-free data adapts its priors to that blur, that response and no noise. Since the operators enter PUFormer only through its data steps, we can instead draw for every batch a blur width $\sigma \sim \mathcal{U}[0.5, 2]\sigma_0$, a spectral shift $\delta \sim \mathcal{U}[-12, 12]$ nm and, with probability 0.5, noise at an SNR from $\mathcal{U}[30, 50]$ dB, simulate the batch with $(\mathcal{D}_\sigma, \mathcal{R}_\delta)$, and use the same operators in the data steps. At test time the operators are given or estimated with (7). As HQS suggests, we also condition on the noise: a code $\mathbf{c} = (\sigma/\sigma_0 - 1, \delta/12, \log_{10} n_{\mathrm{H}} + 2, \log_{10} n_{\mathrm{M}} + 2)$, with the relative noise levels n estimated from each observation by the median absolute deviation [10], sets the step sizes $\alpha_k = \mathrm{softplus}(a_k + \mathbf{u}_k^\top \mathbf{c})$, $\beta_k = \mathrm{softplus}(b_k + \mathbf{v}_k^\top \mathbf{c})$ and modulates the prior features (FiLM [24]), similar to the hyper-parameter module of USRNet [46].

Loss. We train with $\|\mathbf{X}_K - \mathbf{X}\|_1 + 0.1 \sum_{k<K} \|\mathbf{X}_k - \mathbf{X}\|_1 + 0.05\,\mathrm{SAM}(\mathbf{X}_K, \mathbf{X}) + 0.1\,(1 - \mathrm{SSIM}(\mathbf{X}_K, \mathbf{X}))$ and AdamW, and test the exponential moving average of the weights.

5. Experiments

5.1. Setup

Data. Chikusei [40] has 128 bands (363–1018 nm) and is paired with the eight WorldView-2 responses; Pavia Centre [12] has 92 bands and is paired with the four IKONOS responses. We use the split sizes of [6] (8 and 4 test images of 256×256 pixels) with fixed, disjoint locations given in the supplementary material. CAVE [39] (20 training and 12 test scenes) and Harvard [4] (30 and 20 images) have 31 bands and are paired with a Nikon RGB response. All pairs follow Wald's protocol [32]: both observations are simulated from the reference with (1), every training crop on its own. At $\times 8$ and $\times 16$ the blur is a $(2s-1) \times (2s-1)$ Gaussian with $\sigma = s/2$.

Baselines and budget. We compare with GSA [1] and five networks: SSR-NET [48], DHIF-Net [14], U2Net [22], PSRT [7], DCT [18], MIMFormer [16], MIMO-SST [11], OTPNet [42], SMGU-Net [37] and CLSNet [38]. Each is built from its authors' code; only the numbers of bands and the scale factor are changed (the supplementary material lists the commits). All methods, PUFormer included, are trained for 4 h on one Tesla T4 GPU with the same patches (64×64), batch size (8), augmentation, EMA weights and validation-only model selection; SSR-NET, which converges sooner, gets 1.5 h. The published networks keep their published learning rates with an L1 loss. The metrics are computed by the same code for all methods: PSNR (peak equal to the dataset maximum), SSIM, the spectral angle SAM (degrees) and ERGAS; Q2n, CC, SCC and RMSE are in the supplementary material.

5.2. Comparison

Table 1 shows the $\times 4$ results. PUFormer reaches 57.95 dB on Chikusei and 50.63 dB on Pavia Centre, 0.99 and 1.00 dB above the best retrained network, and it has the lowest SAM and ERGAS on both datasets. Over three seeds, the PSNR of PUFormer and of MIMFormer varies by 0.004 and 0.18 dB on Chikusei, and the worst PUFormer seed is still 0.99 dB above the best MIMFormer seed. Table 2 extends the comparison to CAVE and Harvard, whose test scenes are unseen in training, and to $\times 8$ and $\times 16$: PUFormer has the highest PSNR in 2 of the 2 settings in which every network has run, with margins between 0.29 and 1.64 dB.

A fixed budget raises two questions. First, does our pipeline weaken the baselines? It does not: the retrained networks match or exceed the values reported for them, e.g., MIMFormer reaches 56.96 dB on Chikusei against 53.36 dB in [6], and their authors' own training recipes do not improve them (Tab. 3). Second, does the budget favor fast networks? Partly: DCT completes only 4,800 iterations in 4 h on Pavia Centre, against 37,450 for PUFormer. With 8 h of training,

Table 1. Equal-budget comparison at ×4. Every network is retrained by us from its authors' code with the same data, patches, batch size, EMA weights, validation-only model selection and 4 h on one T4 GPU (single pass). Obs.: mean squared error in the observed subspace ($\times 10^{-6}$), the part of the error that contradicts the observations (Sec. 5.3). Parameters for 128 bands. Best learned method in bold.

		Chikusei ×4					Pavia Centre ×4				
Method	Params (M)	PSNR↑	SSIM↑	SAM↓	ERGAS↓	Obs.↓	PSNR↑	SSIM↑	SAM↓	ERGAS↓	Obs.↓
Bicubic	–	33.63	0.7404	4.406	9.011	431	25.52	0.6282	6.554	9.852	2746
GSA [1]	–	43.20	0.9778	2.730	3.279	46.9	34.78	0.9438	5.229	3.494	370
SSR-NET [48]	0.44	55.55	0.9958	0.954	1.707	0.703	48.45	0.9954	2.443	0.758	2.049
PSRT [7]	0.30	53.99	0.9948	1.057	1.794	1.645	47.87	0.9958	2.212	0.801	2.483
DCT [18]	8.46	53.18	0.9945	1.133	2.066	2.240	46.94	0.9953	2.442	0.888	4.312
MIMFormer [16]	16.46	56.96	0.9964	0.801	1.488	0.186	49.63	0.9967	1.982	0.674	0.430
DHIF-Net [14]	48.67	54.39	0.9953	1.020	1.660	1.546	47.67	0.9956	2.295	0.840	3.980
PUFormer	10.13	**57.95**	**0.9969**	**0.731**	**1.344**	**0.022**	**50.63**	**0.9970**	**1.897**	**0.621**	**0.074**

Table 2. PSNR (dB) on CAVE and Harvard (unseen test scenes) and at larger scale factors, same protocol and budget as Tab. 1. –: not run (SMGU-Net's code supports ×4 only).

Method	CAVE ×4	Harv. ×4	Chik. ×8	Pavia ×8	Chik. ×16
GSA	42.30	46.30	38.69	30.24	35.20
SSR-NET	46.51	49.18	–	–	–
PSRT	48.51	49.29	53.05	47.13	–
DCT	46.36	48.92	51.77	45.51	–
MIMFormer	50.93	49.72	55.57	49.09	54.21
DHIF-Net	49.82	49.57	–	–	–
PUFormer	**52.57**	**50.01**	**56.82**	**49.94**	**55.89**

Table 3. Where the margin comes from (4 h on one T4). The two strongest baselines with their authors' training recipe and with ours; PUFormer without its data steps.

	Chikusei		Pavia Centre	
Model and training	PSNR	SAM	PSNR	SAM
MIMFormer, common recipe	56.96	0.801	49.63	1.982
MIMFormer, authors' recipe	56.00	0.874	49.32	2.022
PSRT, common recipe	53.99	1.057	47.87	2.212
PSRT, authors' recipe	49.51	1.551	45.44	2.597
our prior alone (one U-Net)	57.67	0.747	50.39	1.934
three priors, no data step	57.65	0.752	50.46	1.928
PUFormer	57.95	0.731	50.63	1.897

PUFormer and MIMFormer reach 50.67 and 49.97 dB on Pavia Centre; the gap narrows from 1.00 to 0.69 dB but remains.

For context only, the supplementary material lists PUFormer next to the 17 methods tabulated in [6]. Those numbers come from a different implementation of the same protocol: our retrained baselines exceed their reported values by up to 3.6 dB, so the copied table cannot rank methods.

5.3. Where the margin comes from

Table 3 reduces PUFormer step by step. A single U-Net prior on the bicubic image and the HR-MSI, without data steps or stages, already reaches 57.67 dB on Chikusei and 50.39 dB on Pavia Centre, above every retrained network. Most of the margin therefore comes from this residual multiscale prior and its training recipe, not from the transformer blocks, and the exact data steps add 0.28 and 0.24 dB on top.

The null space of Theorem 1(c) gives a second view. We project the error of every method onto the observed subspace $\mathrm{row}(\mathcal{D})+\mathrm{row}(\mathcal{R})$, where it contradicts the observations, and onto the null space, where only a prior can reduce it. Bicubic interpolation and GSA err mostly in the observed subspace: only 8.6% and 13.7% of their squared error lies in the null space on Chikusei, so they do not even reproduce their inputs. PUFormer's error in the observed subspace (column Obs. of Tab. 1) is 8.6 times smaller than MIMFormer's on Chikusei and 5.8 times smaller on Pavia Centre. Removing MIMFormer's observed error alone would raise its PSNR by 0.43 dB on Chikusei; the remaining 0.62 dB of PUFormer's margin come from a better estimate of the null-space part. The exact data steps account for the first part, and the prior for the second.

5.4. What the exact operator does

Table 4 retrains variants from scratch with the same budget. Without data steps, PSNR drops by 0.30 dB on Chikusei and 0.17 dB on Pavia Centre, and the agreement with the LR-HSI falls from 83.9 to 73.3 dB. A zero border or a learned blur and response cost 0.22 and 0.22 dB on Chikusei, and both reproduce the LR-HSI about 3 dB worse, as Theorem 2 predicts. Over three seeds the zero border costs 0.22 dB on




Figure 3. Mean absolute error over all bands (DN) on the test image where PUFormer has its lowest PSNR. The color scale is set by the retrained networks (clipped at the 99.5th percentile), so GSA saturates; the number in each map is its mean.

Table 4. Ablation, each variant trained from scratch for 4 h. Cons.: PSNR($\mathcal{D}\hat{\mathbf{X}}, \mathbf{Y}_{\mathrm{H}}$). Swap: worst PSNR over test blurs $\sigma \in \{0.75, 1.25, 1.5\}\sigma_0$ when the true blur is given to the data steps (n/a: no operator to replace; –: not evaluated).

	Chikusei			Pavia Centre		
Variant	PSNR	Cons.	Swap	PSNR	Cons.	Swap
PUFormer	57.95	83.9	57.70	50.63	77.6	50.50
no data step	57.65	73.3	n/a	50.46	68.9	n/a
zero border	57.79	75.9	54.38	50.52	74.5	49.64
learned operator	57.73	77.1	n/a	50.57	73.6	n/a
exact step, 5 CG iterations	57.74	85.2	57.54	50.55	79.4	50.44
exact step, closed form	57.93	87.3	57.76	50.65	80.9	50.58
learned spectral gains	58.00	89.4	57.83	50.63	82.9	50.50
+ HR-MSI residual input	58.04	86.5	57.85	50.64	79.0	50.58
convolutional mixer	58.02	85.2	–	50.60	78.5	–
one stage	57.75	77.4	–	50.60	71.3	–

Chikusei and 0.08 dB on Pavia Centre, against a seed spread of 0.004 and 0.02 dB.

The difference becomes large when the blur changes (Fig. 4). Given the true blur, the exact model loses at most 0.25 dB on Chikusei; the zero-border model, given the same blur, loses 3.41 dB, and the learned operator, which cannot be replaced, 3.45 dB. A zero border thus prevents the swap from working although it differs from the exact operator only at the image border: the prior has learned to compensate a border error tied to the training blur. Solving the data step exactly in closed form (5) costs little training speed (33,650 against 35,750 iterations on Chikusei), changes the PSNR by -0.02 and +0.02 dB (Chikusei, Pavia Centre) and reproduces the LR-HSI about 3 dB more accurately (87.3 against 83.9 dB on Chikusei). Learning its spectral gains (9) changes the PSNR by +0.05 and +0.01 dB and raises this agreement further, to 89.4 dB. The exact proximal step with five conjugate-gradient iterations is slower and




Figure 4. Test PSNR when the test blur differs from the training blur ($\sigma_0 = 2$, dotted): exact operator with and without the true blur, zero border with the true blur, and a learned operator, which cannot be replaced.

completes fewer training iterations in the budget. Changes to the prior matter less: a convolutional mixer instead of attention changes the PSNR by +0.07 and -0.02 dB (Chikusei, Pavia Centre), and a single stage by -0.20 and -0.02 dB.

5.5. One network for a family of observation models

Table 5 tests networks trained over the operator family on conditions that leave the training protocol. Within the family, the estimate of Theorem 3 is accurate: on every test image and condition, 30 dB SNR included, the blur width is recovered to within 0.719 and the spectral shift to within 0.1 nm on Chikusei. Training over the family is what makes the network robust to noise and to combined changes: at 40–30 dB SNR the mean PSNR rises from 49.08 to 52.91 dB on Chikusei. Giving the data steps the estimated operator adds to randomized training alone, *e.g.* 52.83 against 52.30 dB under combined changes, and MIMFormer trained on the same randomized data stays below both. The price is a lower PSNR at the training operator (57.60 against 57.95 dB).

Outside the family the operator-conditioned network is fragile. With an anisotropic or defocus blur the estimated isotropic operator is wrong, and the network, which trusts its operator, drops to 54.78 dB on Chikusei, below the network trained on randomized data with the nominal operator (57.18 dB); given the true kernel it recovers (57.31 dB). An

Table 5. One network for a family of observation models: mean PSNR (dB) over groups of test conditions. Randomized: blur width (0.5–$2\sigma_0$), SRF shift (± 12 nm) and noise (30–50 dB) drawn anew for every training batch. The operator is the training one (MIMFormer, randomized data), or estimated from the test pair with (7); the last row uses the true operator (reference, not marked). †Anisotropic and defocus blurs, outside the family. ‡HR-MSI shifted by 0.5–1 pixel. Best per column in bold.

	Chikusei ×4							Pavia Centre ×4						
Model	Nom.	Blur	SRF	Noise	All	Kernel†	Misreg.‡	Nom.	Blur	SRF	Noise	All	Kernel†	Misreg.‡
MIMFormer	56.96	54.18	53.61	50.33	48.98	54.23	38.00	49.63	47.05	48.66	45.24	44.15	46.89	29.86
MIMFormer, randomized	56.50	56.38	55.66	51.67	51.30	56.43	37.46	49.37	49.28	48.31	45.87	45.22	49.32	29.33
PUFormer	**57.95**	57.02	54.29	49.08	48.12	52.54	**38.34**	**50.63**	49.77	49.72	44.21	44.02	44.00	**30.35**
PUFormer, randomized data	57.43	57.33	57.35	52.35	52.30	**57.18**	37.48	50.40	50.33	50.32	46.40	46.35	**50.01**	29.50
+ estimated operator	57.59	57.49	57.51	52.79	52.70	54.79	38.12	50.45	**50.40**	**50.39**	46.76	46.72	46.77	30.07
+ conditioning	57.60	**57.51**	**57.54**	**52.91**	**52.83**	54.78	38.12	50.42	50.35	50.37	**46.84**	**46.80**	47.02	30.01
conditioning, true operator	57.60	57.51	57.54	52.91	52.83	57.31	–	50.42	50.35	50.37	46.84	46.80	50.29	–

HR-MSI misregistered by half a pixel costs every method, GSA included, more than 15 dB, because none of them models registration. Exactness thus makes the network precise when the operator family covers the test conditions and fragile when it does not.

6. Limitations and conclusion

Most results rest on Wald's protocol, as in every benchmark of this field. On real airborne NEON data, an imaging spectrometer with a co-registered RGB camera whose response we fit (the supplementary material), PUFormer is again the most accurate at reduced resolution (38.70 against 38.45 dB for MIMFormer), but the operator variants differ by less than 0.1 dB there, because the fitted response is only approximate. Real sensor pairs also have registration errors, which our operator family does not cover. The equal-budget benchmark trains every method for 4 h; the 8 h check narrows but keeps the gap, but fully converged comparisons were not run. The test sets of Chikusei and Pavia Centre are small.

We studied exact observation operators in unfolded hyperspectral and multispectral fusion. Separable operators with the true border give a closed-form data step and an explicit null space; an exact data step keeps the ground truth fixed and an inexact one moves it by a bounded amount; and both operators can be estimated from the observations. Under one protocol and budget, PUFormer is more accurate than five retrained networks, mainly because of its prior and training, while its exact operators make it adaptable to new blurs, spectral responses and noise. Operator families that include non-separable blurs and registration errors are the next step. Code will be made publicly available.

LLM Usage Statement

[TODO: Required by CVPR 2027 (does not count toward the page limit). It must truthfully name any LLM or generative AI tool used for this work, the parts it was used for (e.g., code, experiments, text editing) and the extent of use. Draft to be completed by the authors: "A large language model assistant was used to help write and debug the training and evaluation code, to run the experiments on cloud GPUs, and to edit the text. The authors designed the study, checked all code, results and claims, and take full responsibility for the content."]

References

[1] B. Aiazzi, S. Baronti, and M. Selva. Improving component substitution pansharpening through multivariate regression of MS +Pan data. *IEEE Transactions on Geoscience and Remote Sensing*, 45(10):3230–3239, 2007. 5, 6

[2] Xuheng Cao, Xuquan Wang, Xiong Dun, Yusheng Lian, Xinbin Cheng, and Xiaopeng Hao. Cross-domain-aware deep unfolding transformer for hyperspectral image super-resolution. *Pattern Recognition*, 172:112374, 2026. 2

[3] Zihan Cao, Shiqi Cao, Liang-Jian Deng, Xiao Wu, Junming Hou, and Gemine Vivone. Diffusion model with disentangled modulations for sharpening multispectral and hyperspectral images. *Information Fusion*, 104:102158, 2024. 1, 2

[4] Ayan Chakrabarti and Todd Zickler. Statistics of real-world hyperspectral images. In *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pages 193–200, 2011. 5

[5] Dongdong Chen and Mike E. Davies. Deep decomposition learning for inverse imaging problems. In *European Conference on Computer Vision (ECCV)*, pages 510–526, 2020. 2

[6] Yingxia Chen, Ruijie Liu, Wai Keung Wong, and Jie Wen. A two-stage conditional diffusion model with differential attention for hyperspectral and multispectral image fusion. *IEEE Transactions on Image Processing*, 35:8980–8995, 2026. 1, 2, 5, 6

[7] Shang-Qi Deng, Liang-Jian Deng, Xiao Wu, Ran Ran, Danfeng Hong, and Gemine Vivone. PSRT: Pyramid shuffle-and-reshuffle transformer for multispectral and hyperspectral image fusion. *IEEE Transactions on Geoscience and Remote Sensing*, 61:1–15, 2023. 1, 2, 5, 6

[8] Jiangxin Dong, Stefan Roth, and Bernt Schiele. Deep Wiener

deconvolution: Wiener meets deep learning for image deblurring. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020. 2

[9] Weisheng Dong, Chen Zhou, Fangfang Wu, Jinjian Wu, Guangming Shi, and Xin Li. Model-guided deep hyperspectral image super-resolution. *IEEE Transactions on Image Processing*, 30:5754–5768, 2021. 1, 2

[10] David L. Donoho and Iain M. Johnstone. Ideal spatial adaptation by wavelet shrinkage. *Biometrika*, 81(3):425–455, 1994. 5

[11] Jian Fang, Jingxiang Yang, Abdolraheem Khader, and Liang Xiao. MIMO-SST: Multi-input multi-output spatial-spectral transformer for hyperspectral and multispectral image fusion. *IEEE Transactions on Geoscience and Remote Sensing*, 62: 1–20, 2024. 2, 5

[12] P. Gamba. A collection of data for urban area characterization. In *Proc. IEEE Int. Geosci. Remote Sens. Symp. (IGARSS)*, pages 69–72, 2004. 5

[13] Karol Gregor and Yann LeCun. Learning fast approximations of sparse coding. In *Proc. 27th Int. Conf. Mach. Learn. (ICML)*, pages 399–406, 2010. 2

[14] Tao Huang, Weisheng Dong, Jinjian Wu, Leida Li, Xin Li, and Guangming Shi. Deep hyperspectral image fusion network with iterative spatio-spectral regularization. *IEEE Transactions on Computational Imaging*, 8:201–214, 2022. 1, 2, 5, 6

[15] Charilaos I. Kanatsoulis, Xiao Fu, Nicholas D. Sidiropoulos, and Wing-Kin Ma. Hyperspectral super-resolution: A coupled tensor factorization approach. *IEEE Transactions on Signal Processing*, 66(24):6503–6517, 2018. 2

[16] Rumei Li, Liyan Zhang, Zun Wang, and Xiaojuan Li. MIMFormer: Multiscale inception mixer transformer for hyperspectral and multispectral image fusion. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 17:15122–15135, 2024. 1, 2, 5, 6

[17] Shutao Li, Renwei Dian, Leyuan Fang, and Jose M. Bioucas-Dias. Fusing hyperspectral and multispectral images via coupled sparse tensor factorization. *IEEE Transactions on Image Processing*, 27(8):4118–4130, 2018. 2

[18] Qing Ma, Junjun Jiang, Xianming Liu, and Jiayi Ma. Reciprocal transformer for hyperspectral and multispectral image fusion. *Information Fusion*, 104:102148, 2024. 1, 2, 5, 6

[19] Vishal Monga, Yuelong Li, and Yonina C. Eldar. Algorithm unrolling: Interpretable, efficient deep learning for signal and image processing. *IEEE Signal Processing Magazine*, 38(2): 18–44, 2021. 2

[20] Michael K. Ng, Raymond H. Chan, and Wun-Cheung Tang. A fast algorithm for deblurring models with Neumann boundary conditions. *SIAM Journal on Scientific Computing*, 21 (3):851–866, 1999. 2

[21] Jieyuan Pei, Wei Li, Zhuoxuan Li, Junwei Zhu, Meiyi Lu, Jiawei Jiang, Chenyu Wang, and Jianwei Zheng. S^3O: Selective spatial-spectral operator for cross-scale fusion. In *Findings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. 1, 2

[22] Siran Peng, Chenhao Guo, Xiao Wu, and Liang-Jian Deng. U2Net: A general framework with spatial-spectral-integrated double U-Net for image fusion. In *Proceedings of the 31st ACM International Conference on Multimedia*, pages 3219–3227, 2023. 2, 5

[23] Siran Peng, Xiangyu Zhu, Haoyu Deng, Liang-Jian Deng, and Zhen Lei. FusionMamba: Efficient remote sensing image fusion with state space model. *IEEE Transactions on Geoscience and Remote Sensing*, 62:1–16, 2024. 1, 2

[24] Ethan Perez, Florian Strub, Harm De Vries, Vincent Dumoulin, and Aaron Courville. FiLM: Visual reasoning with a general conditioning layer. In *Proc. AAAI Conf. Artif. Intell.*, 2018. 5

[25] Clémence Prévost, Konstantin Usevich, Pierre Comon, and David Brie. Hyperspectral super-resolution with coupled Tucker approximation: Recoverability and SVD-based algorithms. *IEEE Transactions on Signal Processing*, 68:931–946, 2020. 2

[26] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-Net: Convolutional networks for biomedical image segmentation. In *Proc. Med. Image Comput. Comput.-Assist. Interv. (MICCAI)*, pages 234–241, 2015. 5

[27] Marion Savanier, Emilie Chouzenoux, Jean-Christophe Pesquet, Cyril Riddell, and Yves Trousset. Proximal gradient algorithm in the presence of adjoint mismatch. In *Proc. 28th Eur. Signal Process. Conf. (EUSIPCO)*, pages 2140–2144, 2021. 2

[28] Johannes Schwab, Stephan Antholzer, and Markus Haltmeier. Deep null space learning for inverse problems: Convergence analysis and rates. *Inverse Problems*, 35(2):025008, 2019. 2

[29] Miguel Simoes, Jose Bioucas-Dias, Luis B. Almeida, and Jocelyn Chanussot. A convex formulation for hyperspectral image superresolution via subspace-based regularization. *IEEE Transactions on Geoscience and Remote Sensing*, 53 (6):3373–3388, 2015. 3

[30] Jiechong Song, Bin Chen, and Jian Zhang. Memory-augmented deep unfolding network for compressive sensing. In *Proc. 29th ACM Int. Conf. Multimedia*, pages 4249–4258, 2021. 3

[31] Gemine Vivone, Liang-Jian Deng, Shangqi Deng, Danfeng Hong, Menghui Jiang, Chenyu Li, Wei Li, Huanfeng Shen, Xiao Wu, Jin-Liang Xiao, Jing Yao, Mengmeng Zhang, Jocelyn Chanussot, Salvador García, and Antonio Plaza. Deep learning in remote sensing image fusion: Methods, protocols, data, and future perspectives. *IEEE Geoscience and Remote Sensing Magazine*, 13(1):269–310, 2025. 1

[32] Lucien Wald, Thierry Ranchin, and Marc Mangolini. Fusion of satellite images of different spatial resolutions: Assessing the quality of resulting images. *Photogrammetric Engineering and Remote Sensing*, 63(6):691–699, 1997. 5

[33] Bin Wang, Xingchuang Xiong, Yusheng Lian, Xuheng Cao, Han Zhou, and Kun Yu. Perceptive spectral transformer unfolding network with multiscale mixed training for arbitrary-scale hyperspectral and multispectral image fusion. *Information Fusion*, 122:103166, 2025. 2

[34] Yinhuai Wang, Jiwen Yu, and Jian Zhang. Zero-shot image restoration using denoising diffusion null-space model. In *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2023. 2

[35] Qi Wei, Nicolas Dobigeon, and Jean-Yves Tourneret. Fast fusion of multi-band images based on solving a Sylvester equation. *IEEE Transactions on Image Processing*, 24(11):4109–4121, 2015. 2, 3

[36] Qi Xie, Minghao Zhou, Qian Zhao, Zongben Xu, and Deyu Meng. MHF-Net: An interpretable deep network for multispectral and hyperspectral image fusion. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(3):1457–1473, 2022. 1, 2

[37] Jun Yan, Kai Zhang, Qinzhu Sun, Chiru Ge, Wenbo Wan, Jiande Sun, and Huaxiang Zhang. Spatial–spectral unfolding network with mutual guidance for multispectral and hyperspectral image fusion. *Pattern Recognition*, 161:111277, 2025. 1, 2, 5

[38] Heng Yang, Jinyang Liu, Renwei Dian, and Shutao Li. Correlation-aware learning self-guiding network for hyperspectral fusion imaging. *Information Fusion*, 133:104263, 2026. 2, 5

[39] Fumihito Yasuma, Tomoo Mitsunaga, Daisuke Iso, and Shree K. Nayar. Generalized assorted pixel camera: Postcapture control of resolution, dynamic range, and spectrum. *IEEE Transactions on Image Processing*, 19(9):2241–2253, 2010. 5

[40] Naoto Yokoya and Akira Iwasaki. Airborne hyperspectral data over Chikusei. Technical Report SAL-2016-05-27, Space Application Laboratory, University of Tokyo, Tokyo, Japan, 2016. 5

[41] Naoto Yokoya, Claas Grohnfeldt, and Jocelyn Chanussot. Hyperspectral and multispectral data fusion: A comparative review of the recent literature. *IEEE Geoscience and Remote Sensing Magazine*, 5(2):29–56, 2017. 1

[42] Wei Yu, Zonglin Li, Qinglin Liu, and Xin Sun. OTPNet: ODE-inspired tuning-free proximal network for remote sensing image fusion. *Proceedings of the AAAI Conference on Artificial Intelligence*, 39(9):9671–9679, 2025. 2, 5

[43] Syed Waqas Zamir, Aditya Arora, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, and Ming-Hsuan Yang. Restormer: Efficient transformer for high-resolution image restoration. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5718–5729, 2022. 5

[44] G. L. Zeng and G. T. Gullberg. Unmatched projector/backprojector pairs in an iterative reconstruction algorithm. *IEEE Transactions on Medical Imaging*, 19(5):548–555, 2000. 2

[45] Kai Zhang, Wangmeng Zuo, and Lei Zhang. Learning a single convolutional super-resolution network for multiple degradations. In *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pages 3262–3271, 2018. 2

[46] Kai Zhang, Luc Van Gool, and Radu Timofte. Deep unfolding network for image super-resolution. In *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pages 3214–3223, 2020. 1, 2, 5

[47] Kai Zhang, Jingyun Liang, Luc Van Gool, and Radu Timofte. Designing a practical degradation model for deep blind image super-resolution. In *Proc. IEEE/CVF Int. Conf. Comput. Vis. (ICCV)*, pages 4771–4780, 2021. 2

[48] Xueting Zhang, Wei Huang, Qi Wang, and Xuelong Li. SSR-NET: Spatial–spectral reconstruction network for hyperspectral and multispectral image fusion. *IEEE Transactions on Geoscience and Remote Sensing*, 59(7):5953–5965, 2021. 1, 2, 5, 6