6000 42 10210
Amartya Mishra
COMPS C31

ML: Experiment 1

Aim: To implement linear Regression

Theory:
LR is one of easiest & most popular ML Algos
It is Statistical Method used for predictive analysis. It makes prediction for continous / real / numeric Variables such as sales, salary, age etc. It shows linear relationship between dependent (Y) & one or more undependent Variable (X)
It finds how value of x causes a change in the output variable Y
This Model provides sloped line representing relationship between variable



Mathematically it is represented as

$$y = w_0 + w_1 x$$

y = undependent Variable
w_0 = Y intercept
w_1 = Slope of line
x = Independent Variable.

Linear Regression

- Simple - Single Independent Variable is used
- Multiple - More than one independent Variable used

- Conclusion

Hence we have implemented linear regression using both statistical method & machine learning.

Ml- Lab 1 Linear regression

[2]:
```
import numpy as np
import matplotlib.pyplot as plt
```

[3]:
```
def estimate_coeff(x, y):
    n = np.size(x)
    mean_x = np.mean(x)
    mean_y = np.mean(y)
    SS_xy = np.sum(y * x) - n * mean_y * mean_x
    SS_xx = np.sum(x * x) - n * mean_x * mean_x
    SS_yx2 = mean_y * np.sum(x * x) - mean_x * np.sum(x * y)
    SS_x = np.sum(x * x) - n * mean_x * mean_x
    w_1 = SS_xy / SS_xx
    w_0 = SS_yx2 / SS_x
    return (w_0, w_1)
```

[4]:
```
def plot_regression_line(x, y, w):
    plt.scatter(x, y, color = "m", marker = "o", s = 30)
    y_pred = w[0] + w[1] * x
    plt.plot(x, y_pred, color = "g")
    plt.xlabel('x')
    plt.ylabel('y')
    plt.show()
```

[6]:
```
x = np.array([1, 2, 3, 4])
y = np.array([6, 5, 3, 3])
w = estimate_coeff(x, y)
print("Estimated coefficients - \nw_0 = {}\nw_1 = {}".format(w[0], w[1]))
print("The equation is : y = {} + {}x\n".format(w[0], w[1]))
```

```
Estimated coefficients w_0 =
7.0 w_1 = -1.1 The equation
is : y = 7.0 + -1.1x
```



[8]:
```
import pandas as pd
```

[73]:
```
X = np.array([2,3,4,5,6,7,8,9,10])
y = np.array([1,3,6,9,11,13,15,17,20])
```

[78]:
```
w_0 = 0.1
w_1 = 0.2
alpha = 0.01
epochs = 100
```

[79]:
```
for epoch in range(epochs):
    y_pred = w_0 + w_1 * X  # predicted values
    error = y_pred - y  # difference between predicted and actual values

    # Update weights using gradient descent
    w_0 -= alpha * np.mean(error)  # update intercept
    w_1 -= alpha * np.mean(error * X)  # update slope
```

[81]:
```
print("Intercept (w_0):", w_0)
print("Slope (w_1):", w_1)

# Plot the original data points
plt.scatter(X, y, color='blue', label='Original data')

# Plot the linear regression line
plt.plot(X, w_0 + w_1 * X, color='red', label='Manual linear regression')

plt.xlabel('X')
plt.ylabel('Y')
plt.title('Manual Linear Regression')
plt.legend()
plt.show()
```

```
Intercept (w_0): -0.2099873738061369
Slope (w_1):
1.8768486428539883
```