

Sri Lanka Institute of Information Technology

Faculty of Computing

BSc (Hons) in Software Engineering | Year 2 Semester 2

SE2020 - Web and Mobile Technologies

Clinic Appointment Application

API ENDPOINT TABLES

Group XX | Individual/group format to be confirmed with lecturer

System and User Management

Public system status and account authentication routes.

Core Component	Access Role	Method	Route	Description
System Status	Public	GET	/api/health	Check API availability and MongoDB connection state.
User Management	Public	POST	/api/auth/register	Register an account with name, email, and password; returns a JWT and user profile.
User Management	Public	POST	/api/auth/login	Authenticate with email and password; returns a JWT and user profile.

Doctor Management

All routes require a signed-in User JWT. Doctor creation and updates accept multipart form data; the optional image field is named image.

Core Component	Access Role	Method	Route	Description
Doctor Management	User (JWT)	GET	/api/doctors?search=	List doctors; optional search matches doctor name or specialty.
	User (JWT)	GET	/api/doctors/:id	Retrieve one doctor profile.
	User (JWT)	POST	/api/doctors	Create a doctor profile and optionally upload a JPG, PNG, or WebP image (maximum 3 MB).
	User (JWT)	PUT	/api/doctors/:id	Update doctor profile fields and optionally replace the image.
	User (JWT)	DELETE	/api/doctors/:id	Delete a doctor when no active appointments reference the doctor.

Doctor-management access note

The current implementation protects doctor routes with authentication but does not define a separate Admin role.

Appointment Management

All routes require a signed-in User JWT and enforce ownership. Appointment times are ISO 8601 date-time values.

Core Component	Access Role	Method	Route	Description
Appointment Management	User (JWT)	GET	/api/appointments	List appointments belonging to the signed-in user.
	User (JWT)	GET	/api/appointments/:id	Retrieve one appointment belonging to the signed-in user.
	User (JWT)	POST	/api/appointments	Request an appointment with doctorId, startAt, endAt, and reason.
	User (JWT)	PUT	/api/appointments/:id	Edit an owned appointment; validates future times and rechecks conflicts.
	User (JWT)	PATCH	/api/appointments/:id/status	Cancel an active owned appointment; status changes to Cancelled.
	User (JWT)	DELETE	/api/appointments/:id	Permanently delete an owned appointment record.

Business rule: reject a request when the same doctor has a non-cancelled appointment with startAt < requestedEnd and endAt > requestedStart. Cancelled appointments do not block a time slot.