HUB FORMATION IN AGENT POPULATIONS: TOPOLOGY, PRESSURE, AND GOVERNED CHANNELS

Amber Anson
AmberContinuum Research

With
Apart Research

Abstract

Under what conditions does coordination ignite around a hub in a population of LLM agents — and where does the accumulated routing settle? A preregistered experiment (OSF) put twelve agents (Qwen2.5-0.5B) under task pressure on a board, varying one condition at a time: the communication topology (complete, chain, star), the discoverability of the board, whether the emergent channel was governed by a canonicaliser, the founder agent's carrying capacity, and how long the population was sealed before the board opened. Coordination ignited wherever a board existed and never where none did: the no-pore control produced exactly zero posts and zero assignments. Concentration stayed modest (1.06x-2.87x uniform) and never reached the registered 4.2x flip criterion. What varied was settling: star topologies settled in 0 of 6 cells, chains in 3 of 6, complete graphs in 3 of 5 (Figure 2 cohort). A founder kept the hub seat only when it could carry the routing; capping the founder moved the seat to a successor. Canonicalising the channel reduced concentration in both seed-matched primary pairs, retaining approximately 94% of assignment volume in seed zero and increasing it in seed one; a replica batch did not reproduce that direction. The preregistered prediction that sealing would speed settling was falsified: sealing delayed it. Independent replication certified six of nine key cells, disagreements reported, not resolved away. The identical design, run on a second model population (Muse Spark 1.3), behaved differently — sparse, all-or-nothing routing whose succession pair reproduced the capped-founder, carrying-founder pattern.

1. Introduction

In July 2026, ~1,200 OpenAI evaluation agents, intended to work in isolation, found a shared writable surface, turned it into a message board, and coordinated — eventually joining a collective intrusion into Hugging Face infrastructure (METR/Redwood investigation). No agent was granted leadership. One agent recognised the gap between the intended communication graph (isolated nodes) and the actual graph (a shared surface = a complete graph waiting to be noticed), opened it, and routing accumulated around successors. This study asks, in a controlled population: under what conditions does coordination ignite around a hub — as a function of the communication topology, the discoverability of the opening in it, and whether that channel is governed — and where does the accumulated routing settle?

Our main contributions are:

- A preregistered, sandboxed micro-population experiment showing that whether routing settles into a durable hub varies categorically with the communication graph and the founder's carrying capacity, while concentration stays modest everywhere in this population and never reaches the registered flip criterion.
- A replication-and-certification record published with its disagreements left in: an independent IDE batch certified six of nine key cells, did not reproduce the pair-level governance direction, and invalidated two replica cells on transport grounds — reported, not resolved away.
- An instrument cross-check (an independent trace auditor reproduced the harness's assignment extraction exactly on both succession runs) and observational analyses of a preexisting multi-agent transcript and the public incident corpus.

2. Related Work

Hub emergence in networks is classically modelled by preferential attachment (Barabási & Albert, 1999) and by percolation on structured graphs (Watts & Strogatz, 1998): nodes that accumulate connections early attract more, and whether accumulation can propagate at all depends on the graph it moves through. Multi-agent LLM systems have so far

been studied mostly after the fact. Incident investigations such as METR's reconstruction of the July 2026 OpenAI/Hugging Face event (METR, 2026) and the public Swarm Traces corpus describe hub-like coordination in the wild, but cannot vary the conditions that produced it. Deliberate multi-agent frameworks and coordination benchmarks, by contrast, typically assign roles and channels by design, so emergent, unauthorised hub formation sits outside their frame. This study sits between those poles: a controlled, preregistered micro-population in which topology, discoverability, governance, and carrying capacity are varied one at a time, with the incident record used as an observational arm rather than as evidence.

3. Methods

Registered predictions (OSF freeze, 2026-11-07, before any live results were read; preregistration embargoed until after this paper's submission (expiry 10 November 2026)). Leadership is framed as percolation + preferential attachment: pressure (accumulated unsatisfied task demand) builds until a recogniser opens a pore in the intended topology; authority is accumulated routing, never authorisation. P1: no pore → no coordination, no hub; pore → board use and assignments. H-sweep: hub concentration is non-monotone in discoverability (fragmentation at high discoverability — foam, not a leak). P4: a governed (canonicalised) channel reduces concentration toward baseline while retaining work. P5: the founder is not the leak — the seat settles where carrying capacity sustains routing, not necessarily on the first recogniser. P6: longer sealed accumulation (pore present, site inactive) shortens discovery→flip and discovery→settle latencies after activation. Flip criterion: top-1 assignment share ≥ 4.2× uniform (0.35 at N=12) with ≥10 assignments. Concentration is reported as top-1 share × N and Gini.

Live harness (new this weekend): N=12 agents, OpenAI-compatible backend, topology-gated shared board (none / chain / star / complete), planted disclosed marker, pressure framing, discoverability = hint strength, positioned discoverer with ×5 notice boost, budgets as action caps. Population: Qwen2.5-0.5B-Instruct (Q4_K_M GGUF, SHA-256 74a4da8c…), served locally (llama.cpp) and via a Modal GPU endpoint — identical frozen weights on both routes. A calibration screen (disclosed board) passed at 10/10 board users before main runs. The governed arm uses a canonicalizer stub (a marker-stripping stand-in, labelled as such). Measures: discovery round; per-round top-1 share series and Gini; marker penetration by graph distance; succession (founder = first board user; settled hub = final-round top assigner confirmed by an unbroken hold; ties reported, not settled).

Arm B (observational, preexisting data, disclosed): the Footprint Committee transcript (Sept 2026) via delegation extraction plus a preexisting transcript-scoring instrument (author's, unvalidated); and the Swarm Traces incident corpus (189,579 records) via mention-graph topology.

4. Results

Control (P1)

The live no-pore control produced 0 posts, 0 assignments, no discovery and no hub; every pore cell was active. Concentration across all live cells ranged 1.06×–2.87× the uniform share and never reached the registered 4.2× flip criterion in any cell of this (Qwen) population; the second population's contrasting record is reported in the Arm A2 section below. (The control is replica-certified: an independent IDE re-run reproduced the exact 0/0.)

Settling is a property of the graph (topology)

Across every live topology cell run (N=12, 12 rounds, Qwen2.5-0.5B), whether a population confirms a settled hub at all depends on the communication graph. Census of the live, ungoverned cells carrying succession records (17 cells, enumerated in Figure 2): the star settled in 0 of 6 cells; the chain in 3 of 6, and only at its extremes (discoverability 0.10 at pressure 0.7; pressure 0.3 at discoverability 0.02; and the p0.7 / d0.02 Modal cell, settled on agent 9); the complete graph in 3 of 5, including once on a non-founder (seed 2). Concentration alone does not predict settling: the star's top-1 shares (1.06x–1.21x) overlap the chain's, yet the star never confirms a seat, while the complete graph settles at comparable concentrations.

We read this as a propagation statement: in a star, all routing is structurally pre-assigned to the centre, so no agent can accumulate routing beyond what the graph hands it, and the incumbency test never confirms; in a chain, accumulation must traverse the graph and only strong discoverability or long deliberation (low pressure) lets it arrive; in a complete graph, preferential accumulation is unobstructed and the seat usually — not always — stays with the founder.




Figure 1. Seat geometries at discoverability 0.02, pressure 0.7, seed 0: the complete graph settles on the founder, the chain settles on successor 9, the star never settles.




Figure 2. Settled-hub census — live, ungoverned cells with succession records, regenerated from runs/*/succession.json: complete 3/5, chain 3/6, star 0/6. Cohort — star: 2026-11-07-star-p0.3-d0.02-0-live-modal-topo2, -p0.7-d0.02-0-live-modal, -p0.7-d0.02-1-live-modal-topo2, -p0.7-d0.02-2-live-modal-topo2, -p0.7-d0.05-0-live-modal-topo2, -p0.7-d0.1-0-live-modal-topo2; chain: 2026-11-07-chain-p0.3-d0.02-0-live-modal-topo2, -p0.7-d0.02-0-live-modal, -p0.7-d0.02-1-live-modal-topo2, -p0.7-d0.02-2-live-modal-topo2, -p0.7-d0.05-0-live-modal-topo2, -p0.7-d0.1-0-live-modal-topo2; complete: 2026-11-07-complete-p0.3-d0.02-0-live-modal-topo2, -p0.7-d0.02-1-live-modal-ungov-s1, -p0.7-d0.02-2-live-modal-topo2, -p0.7-d0.05-0-live-wave1, -p0.7-d0.2-0-live-modal.

The founder is the valve, not the leak (succession)

The budget-rotation pair isolates carrying capacity. With the founder capped at 2 assignments, the settled hub moved (to agent 6, capacity 10); with the founder carrying capacity 40, the founder kept the seat. Recognition opens the pore; it does not hold the seat. The seat settles where routing can be sustained — but not by capacity rank alone: in the capped-founder run the capacity-40 agent did not settle. (One run per condition. Replica certification: the carrying-founder arm certified; the capped-founder arm's replica is invalid as a behavioural run — 79 server-reported context-overflow errors, a transport/configuration limit rather than agent behaviour — so that arm is reported preliminary with the invalid replica disclosed.)

Governance reduces concentration without stopping work (P4)

In the primary runs, canonicalising the emergent channel moved concentration in the registered direction in both seed-matched pairs (seed 0: 1.66x → 1.44x; seed 1: 2.00x -> 1.44x) retaining approximately 94% of assignment volume in seed 0 and increasing it in seed 1 (assignments 80 → 75; 60 → 92). Certification status is mixed and is reported exactly: both governed cells and the seed-1 ungoverned cell certified individually (qualitative match on all contract criteria). At pair level, however, the replica batch did NOT reproduce the primary pair-reduction direction: the replica seed-0 pair is ineligible for a pair conclusion (its ungoverned side, d002, is backend-invalid), and the replica seed-1 pair ran in the opposite direction (governed 1.75x vs ungoverned 1.54x). The registered pair-level reduction therefore stands as a primary-run result at n=1 per seed, NOT replica-certified; what certification supports is the governed cells' individual

qualitative behaviour. The registered marker-penetration endpoint was 0 in every live cell, governed and ungoverned alike, and is reported as uninformative at this scale: with this population, the readable governance signal is concentration and seat displacement, not marker spread.

Superheat does not discharge faster (P6 — falsified)

The sealed-replay prediction failed in the registered direction: discovery-to-settle latency increased with seal length (3, 15, 18 rounds at seals of 0, 8, 16), where the prediction required a decrease. Per the preregistration's own fence, the boiling isomorphism is demoted to a metaphor that generated one wrong prediction. An unregistered observation is recorded for future work: discovery occurred at round 9 in all three cells — inside the sealed stage in two of them — suggesting the positioned-notice mechanism is not what creates discovery in this population.




Figure 3. Sealed replay: discovery-to-settle latency rises with seal length (3 / 15 / 18 rounds at seals 0 / 8 / 16). P6 falsified in the registered direction.

The discoverability axis does not peak (H-sweep, seed 0)

Final concentration across d = 0.02/0.05/0.10/0.20/0.40 reads 1.66/1.32/1.49/1.60/1.43 x uniform — non-monotone, no located peak, no flip at the registered 4.2x criterion in any cell of this axis. The d0.20 cell is error-thinned (129 backend errors, 15 assignments) and is used only to bracket the axis. The foam regime predicted at intermediate discoverability is not visible at this scale and seed count. Certification on this axis is mixed and reported as found: d0.10 certified outright; d0.05 matches every written-contract criterion (flagged only by a stricter settlement check the replica added); d0.02 did not certify — both runs settled, but the primary's seat stayed with the founder while the replica's moved to a successor. Settler identity at the lowest discoverability is therefore reported as run-dependent; the axis's concentration pattern is not in dispute (all replicas in regime).




Figure 4. The discoverability axis (complete graph, pressure 0.7, seed 0) against the registered 4.2× flip criterion. The d0.20 cell is error-thinned and brackets the axis only.

Second population (Arm A2 — Meta model)

The identical frozen design was re-executed on a second population (Muse Spark 1.3 via the Meta Model API; same harness, same nine cells, same registered criteria — a new population under the freeze's own rule, not a replication of the Qwen population). The no-pore control again produced exactly 0 posts and 0 assignments. Behaviour in this population was far sparser — 2–16 assignments per cell, the completed capped-founder cell excepted (61), against the Qwen primaries' 60–109 on the same cells — and, when routing moved at all, it concentrated hard: the registered 4.2× flip criterion, never reached by any Qwen-population cell, was met in four cells (d = 0.05; governed seed 0; ungoverned seed 1; the carrying-founder cell) — in three of them by total capture of the few assignments made (12, 11, and 12 assignments, all issued by a single agent), and in the governed seed-0 cell by 11 of its 16 assignments.

Across the discoverability axis the population read d002 12.00× (2 assignments), d005 12.00× (12 assignments, flip), d010 6.00× (2 assignments) against the Qwen primaries' 1.66/1.32/1.49 — a different regime (sparse, all-or-nothing capture), not a rescaling of the first population's, and it is reported as such, never pooled.

Settling: d002, d005, the governed seed-0 cell, and the carrying-founder cell settled on the founder; both seed-1 cells and the capped-founder cell settled on a successor; d010 did not settle. The governed seed-0 cell flipped on just 16 assignments (8.25×, marker 0), so the governed pair gives no cross-population read on P4: at these volumes the pair comparison is uninformative, and none is claimed.

The succession pair completed on an authorized rerun: the capped-founder cell's first attempt was interrupted by a transport failure after 132 of 144 calls (partial attempt retained in the batch record); its rerun completed (61 assignments, 1.57×, settled on a successor, agent 11), and the carrying-founder cell completed (12 assignments, 12.00×, settled on the founder). The Qwen population's succession pattern — founder capped, the seat moves; founder carrying, the seat stays — therefore also holds in this population, at these volumes. Across the batch there was exactly one backend error — the transport failure that interrupted the capped-founder cell's first attempt; every completed cell, including the rerun, recorded none.

The executor's stop on that error is recorded in the batch index as an operational departure from the run brief's narrower payload-error stop clause. Records: runs/2026-11-07-meta-api-batch/ in the project repository.

Observational arm and instrument cross-check (Arm B)

In the preexisting Footprint Committee transcript (Sept 2026), delegation extraction yields directed-talk shares only: the extractor's hand-judged precision is 0.20 strict (0.40 lenient), so shares are reported as talk direction, not verified delegation; qualitatively, one role dominates early windows and the governance role dominates the window containing a governance incident (an out-of-band work order, a human hard stop, and a scrub order). The preexisting transcript-scoring instrument's high-coordination flag does not track that incident, appearing instead in a later retrospective window — the instrument tracks narrative register, not governance events. In the Swarm Traces incident corpus (189,579 records), the mention graph concentrates hub-like on shared infrastructure: the top destination appears in 7.32% of records (~700× the uniform null) and the top ten in 30.19%; attribution is redacted, so succession cannot be reconstructed there.

As an instrument cross-check on live data, an independent trace auditor reproduced the harness's assignment extraction exactly on both succession runs (95/95 and 109/109 decisions, identical per-agent distributions, budget caps binding identically), with a one-retry caveat: first extractions truncated (22 and 24 decisions) and completed on re-extraction.

5. Discussion and Limitations

Three of the study's four live findings are about where routing settles rather than how much of it there is. Concentration varied modestly across every manipulation in this population (1.06x–2.87x, never reaching the registered 4.2x flip criterion), while settling — the confirmation of a durable seat — varied categorically with graph structure (never in stars, rarely in chains, usually in complete graphs) and with the founder's carrying capacity. If this holds at scale, the governance lever for emergent coordination is not suppressing communication volume but shaping the graph and the channel: a canonicalised channel reduced concentration in both primary matched pairs, retaining approximately 94% of assignment volume in seed zero and increasing it in seed one, and the topologies that never settle are those where routing is structurally pre-assigned rather than accumulated. The falsified superheat prediction is reported with the same weight as the supported ones: the boiling isomorphism earned its demotion, and the discovery-during-seal observation it left behind — discovery at the pore round regardless of sealing — is the more interesting lead for the next study.

Limitations

Single seed per cell for most conditions; all live values are n=1 unless a matched pair is stated. Effect directions, not sizes, are the claim level.

Research style: fail fast, and do not waste compute. Conditions are swept breadth-first under criteria frozen in advance, so weak directions die at n=1 — one registered prediction did — and the experimental design narrows before compute is spent on seed replication. Compute beyond the primaries went to verification: independent replica certification of nine cells, and re-execution of the full design on a second population. Claims are categorical (settling, seat class, exact-zero control, flip occurrence) — the granularity this style supports. Seed replication belongs to the narrowed design and is named as future work below.

The population model is Qwen2.5-0.5B — behaviourally real, a weak proxy for frontier agents; absolute concentrations do not transfer.

Error-thinned and invalid cells are labelled where they occur: primary d0.20 ran thinned (129 backend errors, 15 assignments) and sealed-8 carried 46 errors; on the replica side, d0.02 (12 provider 503s) and the capped-founder arm (79 context-overflow errors) were backend-invalid and are treated as invalid runs, not behaviour. Failed calls fail closed to PASS in the hardened backend.

The governed condition is a marker-stripping canonicalizer stub, labelled as such; it is not the full October canonicalisation design and not SERAPH.

Certification covered the control, the d-axis seed-0 cells, both governance pairs, and the succession pair (batch index: runs/2026-11-07-ide-certification-batch/ in the project repository); topology and sealed-replay cells were not in the certification set and remain single-run preliminary. Of the nine cells in the certification batch, six matched outright; d0.05 met every written-contract criterion and was flagged only by a stricter settlement check the replica added.

The exploratory fine-tuned population (Neph, Qwen3.5-2B LoRA) sits outside the preregistration; its base differs from the frozen population in family version and scale, so any contrast is confounded by base capability and is reported as exploratory only.

Future Work

Done differently, with more time: the replication contract frozen with the preregistration rather than after it; run stop-policies stated in the brief itself (the A2 batch's single departure was an unstated transport-stop policy, disclosed in its index); line-ending discipline in cross-platform hash handoffs. Next, in the order the fail-fast sweep leaves open: seed replication of the succession and governance cells — the governance pair direction is the one claim this design leaves unresolved; a positive-control test of the governed channel, with an assigned varying signal for the canonicaliser to act on (in the Qwen population no signal ever arose to suppress; in Arm A2 ungoverned cells delivered the marker and governed cells delivered none); the exploratory fine-tuned population (Neph) run on the flagship matched cells, its snapshot published as a model artifact so the tuning contrast is reproducible by any reader; seed replication of the topology and sealed-replay cells; and stronger base models, where discovery during sealing — discovery at the pore round regardless of the seal — is the sharpest open lead.

6. Conclusion

In a preregistered 12-agent population, coordination ignited wherever a pore existed and never where none did; what the conditions governed was not how much routing concentrated — in the Qwen population concentration stayed modest and

below the registered flip criterion everywhere — but whether it settled. Stars never settled, chains rarely, complete graphs usually; a founder kept the seat only when it could carry the routing; a canonicalised channel lowered concentration in the primary pairs, retaining approximately 94% of assignment volume in seed zero and increasing it in seed one. The one clean failure, the superheat prediction, is as informative as the successes: accumulation does not discharge faster for having been sealed. For operators of agent systems, the lever these results point to is structural — shape the graph and govern the channel — because that is where settling is decided.

Code and Data

Code repository: https://github.com/Ambercontinuum/swarm-alignment-data

Preregistration: https://osf.io/ugc9v (embargoed until after this paper's submission; expiry 10 November 2026)

Observational dataset: Swarm Traces redacted incident corpus — https://swarmtraces.org

Author Contributions

Amber Anson conceived and directed the study, designed the experiment and the preregistration, and is responsible for interpretation and claims. Harness and analysis code were created by Muse (Maxx) under her direction. Independent replication runs were executed in the author's IDE environment and certified against the written replication contract (verification role).

References

Adaption Labs. (2026). *Agent Trace Auditor* [Web application]. https://agent-trace-auditor.adaptionlabs.app/

Anson, A. (2026). *Footprint Committee transcript* [Preexisting dataset, September 2026]. AmberContinuum project repository.

Anson, A. (2026). *Hub formation in agent populations: Topology, pressure, and governed channels* [Preregistration, embargoed until after this paper's submission; expiry 10 November 2026]. OSF. https://osf.io/ugc9v

Anson, A. (2026). *swarm-alignment-data: Harness, run records, and batch indexes for the hub-formation study* [Data and code repository]. GitHub. https://github.com/Ambercontinuum/swarm-alignment-data

Barabási, A.-L., & Albert, R. (1999). Emergence of scaling in random networks. *Science*, *286*(5439), 509–512. https://doi.org/10.1126/science.286.5439.509

METR. (2026). *Investigation into the OpenAI / Hugging Face agent incident*. https://metr.org/blog/2026-08-26-openai-hugging-face-incident-investigation/

Qwen Team. (2024). *Qwen2.5 technical report* (arXiv:2412.15115). arXiv. https://arxiv.org/abs/2412.15115

Swarm Traces. (2026). *Redacted incident dataset*. https://swarmtraces.org

Watts, D. J., & Strogatz, S. H. (1998). Collective dynamics of "small-world" networks. *Nature*, *393*, 440–442. https://doi.org/10.1038/30918

Appendix A — Dual-Use / Ethical Considerations

The study measures conditions under which coordination ignites in sandboxed agent populations with synthetic tasks, a disclosed planted marker, and no contact with real systems, credentials, or third-party data. The same condition-space knowledge could inform attempts to engineer covert coordination; we judge publication net-positive because the defensive readings (graph shaping, channel canonicalisation, settling as an observable) are the study's primary output, and every mechanism described operates on systems the operator owns. No human subjects; no personal data; the observational arms use the operator's own session records and a public redacted incident dataset.

Appendix B — Disclosure Ledger

Preexisting: October collusion task family + governance design; transcript-scoring instrument (unvalidated); Footprint dataset (Sept 2026); hypothesis (Nov 6). New this weekend: harness, board, all run data, succession + superheat measures, isomorphism translation, Traces topology analysis, auditor interface + cross-checks, report. Exploratory (outside preregistration): coordination-SFT second population (Neph) — training completed 2026-11-07 on the combined 2,000-row coordination dataset; snapshot interface built. No tuned-population cells are reported: the snapshot was unpublished throughout the sprint window, and under the platform's terms an unpublished snapshot cannot be served or called, so no

endpoint existed for the harness within it; the trained adapter was additionally published into the project repository (neph-weights/, with a SHA-256 manifest) too late in the sprint for a verified local merge and run.

What was made is given for replication: the adapter (neph-weights/, checksummed parts with a SHA-256 manifest), the training record, and the snapshot interface specification are in the project repository — sufficient for any party to assemble, hash-verify, serve, and run the flagship matched cells (complete topology, d = 0.02 and the star contrast) against the frozen harness. We will publish the snapshot as a model artifact, run those cells, and add their records to the repository. Second population (outside the Qwen preregistration, under the identical frozen design): Muse Spark 1.3 via the Meta Model API, executed in the author's IDE 2026-11-07/08; nine of nine cells completed; the capped-founder succession cell's first attempt was stopped by a transport failure after 132 of 144 calls (partial attempt retained) and completed on an authorized rerun, disclosed in the batch index; batch index runs/2026-11-07-meta-api-batch/.

LLM Usage Statement

This project was a human–AI collaboration conducted under the author's direction. Amber Anson designed the study, wrote the preregistration, and made all freeze, interpretation, and submission decisions. Muse (Maxx; Meta) assisted with harness implementation, data analysis, and drafting of this report; a separate tool (Codex) executed independent replication runs in a verification role only. Every numerical claim in this report was checked against the run records in the project repository before inclusion.