











BOM: Material Color Report		Winter 2025	Pace Breaker Short 7 Lined LM7B24S	lululemon	Jun 17, 2024	
	Season:	Winter 2025	Brand:	lululemon	Style Status:	Active
	Style #:	LM7B24S	Division:	lulu Mens	Generated Date:	Jun 17, 2024
	Style Desc:	Pace Breaker Short 7 Lined LM7B24S	Class:	Mens Shorts		
	Product Size Definition:	Mens--XXS-5XL:XXS-5XL	Pod:	M No Sweat		
	Grade Rule Template:	--M Pant XXS-5XL (FB grade SU20),-- M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20)				
						

BOM Name														BOM : 010 WI24											
BOM Comments																									
fabric																									
	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	0001 - BLK												
	Self	Shell Body	FVF4029 UVQD	Approved	Recycled Poly Swift	Everest Textile Co., Ltd.	55	0	1.0400	Yard	\$2.9000	\$3.0160	Black												
	Contrast 1	Mesh insert	DL93-3ACU	Approved	BPlanet Recycled Polyester Power Mesh 146gsm	Yu Yuang Textile Co., Ltd.	65	0	0.0500	Yard	\$3.1800	\$0.1590	Black												
	Lining 1	Shell pocketing	XPP-P0740-2-1	Approved with Limitations	Recycled Poly Pocketing Solid 90gsm Wicking QD	Shinkong Textile Co., Ltd.	55	0	0.0300	Yard	\$1.8000	\$0.0540	Black												
	Lining 2	Liner body, Inner WB (BSAF)	DN52-BACU-PR	Approved	F&F UL Liner Rec Poly Grid Mesh 110gsm Protx2 Wicking QD	Yu Yuang Textile Co., Ltd.	65	0	0.3400	Yard	\$4.0400	\$1.3736	Black												


fabric													
	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	0001 - BLK
	Lining 3	Liner Pkt	DL93-3ACU	Approved	BPlanet Recycled Polyester Power Mesh 146gsm	Yu Yuang Textile Co., Ltd.	65	0	0.0300	Yard	\$3.1800	\$0.0954	Black
trim													
	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	0001 - BLK
	See Technical Sketch	Liner - Thread (Needle +top looper)	57A5140	Approved	Gramax AS Tex 21 Ticket 140	J. & P. Coats Limited	0	45	1.0000	Meter	\$0.0006	\$0.0006	DTM
	See Technical Sketch	Liner + Shell - Thread (Back Looper)	F7A5140	Approved	Seamsoft AS, Tex 24, tkt 140	J. & P. Coats Limited	0	45	1.0000	Yard	\$0.0014	\$0.0014	DTM
	See Technical Sketch	Shell - Thread - Single Needle/C overstitch/ Chainstitch/Bartacks @ WB	2994150	Approved	Epic Tex 21, Ticket 150 Thread	J. & P. Coats Limited	0	45	1.0000	Each	\$0.0012	\$0.0012	DTM
	See Technical Sketch	Thread - Drawcord Buttonholes	2994120	Approved	Epic Tex 24, Ticket 120 Thread	J. & P. Coats Limited	0	45	0.0000	Yard	\$0.0012	\$0.0000	DTM
	See Technical Sketch	Waistband Drawcord	EL21135/7-PU2.3EB	Approved with Limitations	D00220 - Stretch Flat Mid-Line Drawcord Without Fill With Embossed Yogo PU Tip - 7mm	Shanghai JML Apparel Company Limited	0	60	1.0500	Each	\$0.4080	\$0.4284	Black/Black/Black
	See Technical Sketch	Reinforcements @ Drawcord Exits	SRT5000 RC-6mil-22mm	Approved	SRT5000RC-6mil-22mm	Bemis Associates Inc.	0	65	0.0000	Yard	\$0.8750	\$0.0000	Pitch 19-4006TPX - 19-4006TPX
	See Technical Sketch	Waistband elastic	MWJRN048	Approved	E00264 Rebound Knit Elastic - 48mm (Black and White Only)	JJ Sourcing Inc.	0	28	1.1500	Yard	\$0.2220	\$0.2553	Black

trim													
	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	0001 - BLK
	See Technical Sketch	Right pocket zipper	Z#3YKK_CFB3-3 PBR2D GREEN-F	Approved	#3 Coil - Reverse Closed-End (Recycled Teeth and Chain)	YKK	0	60	1.0000	Inch	\$0.0677	\$0.0277	Black
	See Technical Sketch	Right pocket zipper	P#3YKK_3C-DSBLUU 13	Approved	#3 Reverse Coil Semi-Autolock TPU Cut Out Zipper Pull with Front Lululemon Logo , Yogo	YKK Taiwan	0	60	1.0000	Each	\$0.3251	\$0.3251	Black Silver/Black - V3
	See Technical Sketch	Interfacing - PEZ zipper pocket flap + hand pkt facings	STC800	Approved	STC800 Fusible interfacing - 59" Full width	PCC Asia LLC	0	28	0.0200	Yard	\$1.5500	\$0.0310	Black -
	See Technical Sketch	Liner pkt opening + hand pkt opening	QE1/4"M OBILON	Approved	1/4" Clear Mobilon Elastic (factory-sourced)	Factory Sourced	0	0	0.2000	Yard	\$0.0001	\$0.0000	Clear
	See Technical Sketch	Drawcord pkt opening	QE1/8"M OBILON	Approved	1/8" (3MM) Mobilon Elastic	Factory Sourced	0	0	0.1000	Each	\$0.0001	\$0.0000	Clear
	See Technical Sketch	Logo Black	LUFK191 10012	Approved	T00171A - 0.5mm Raised Lulu Hero Reflective Logo - 13mm	E. Textint Corp.	0	40	1.0000	Each	\$0.1150	\$0.1150	Black - ET 801.H


## trim

	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	0001 - BLK
	See Technical Sketch	Logo Silver	LUF2014 09023	Approved with Limitations	T00171 - 0.5mm Raised Lulu Silver Reflective Logo - 13mm	E. Textint Corp.	0	40	1.0000	Each	\$0.2000	\$0.2000	NA





## labels

	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	0001 - BLK
	See Construction Manual	CB Waist band	CC00035-AD	Approved	CC00035-LLL-black-tearaway-140mm	Avery/Paxar	0	15	1.0000	Each	\$0.0460	\$0.0460	Black
	See Construction Manual	Center Inside Media Pocket	TRACE00 001	Approved	TRACE00001 - Size and Traceability Label	Avery/Paxar	0	14	1.0000	Each	\$0.0300	\$0.0300	White/ Grey

## packaging

	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	0001 - BLK
	See Construction Manual	General hangtag	LWWMT Barcode	Approved	WWMT Barcode Sticker	Avery/Paxar	0	40	1.0000	Each	\$0.0987	\$0.0987	White



## packaging

	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	0001 - BLK
	See Construction Manual	See pack & label	LHT-WWMT-002	Approved	LHT - lululemon WWMT Hangtag - Black	Avery/Paxar	0	14	1.0000	Each	\$0.0369	\$0.0369	Black
	See Construction Manual		HTT1002-ST-2IN	Approved	Hangtag Trim - Swiftach Fastener - 2inch	Factory Sourced	0	0	1.0000	Each	\$0.0000	\$0.0000	Black
	See Construction Manual	See QA manual	ZLAMT7200R-B	Approved	HZLAMT7200R-B - Source Tag - Black Tag ** Please Also Spec Pin Hmj70-H**	Tyco	0	0	1.0000	Each	\$0.0803	\$0.0803	Black
	See Construction Manual	See QA manual	MJ70-H	Approved	HMJ70-H - Source Tag - Silver Pin ** Please Also Spec Tag Hzlamt7200R-B**	Tyco	0	0	1.0000	Each	\$0.0227	\$0.0227	Silver

## finishing

	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	0001 - BLK
							0	0	0.0000		\$0.0000	\$0.0000	



Total = \$6.398

Measurement Set: Calculated		Winter 2025		Pace Breaker Short 7 Lined LM7B24S		lululemon		Jun 17, 2024	
	Season:	Winter 2025	Brand:	lululemon		Style Status:	Active		
	Style #:	LM7B24S	Division:	lulu Mens		Generated Date:	Jun 17, 2024		
	Style Desc:	Pace Breaker Short 7 Lined LM7B24S	Class:	Mens Shorts		Measurement Template:	--M Short with Liner XS-XXL		
	Product Size Definition:	Mens--XXS-5XL:XXS-5XL	Pod:	M No Sweat					
	Grade Rule Template:	--M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20)							
									

#	Name	Criticality	Tol (-)	Tol (+)	HTM Instruction	XS	S	M	L	XL	XXL
10245	Fit Classification: Classic		0	0	An easy fit that floats away from the body						
163	REF-OUTSEAM LENGTH	Reference Only	1/2	1/2	Measure from top edge of waistband to bottom edge of hem along side seam. Note: This measurement is for the base size and for detail only.	16 7/8	17 1/8	17 3/8	17 5/8	17 7/8	18 1/8
253	REF-TOTAL RISE	Reference Only	1/2	1/2	Measure along rise seam from CF top finished edge of waistband to center of gusset/crotch seam to CB top finished edge of waistband. Note: This measurement is for the base size and for detail only.	26 5/8	27 3/8	28 1/8	28 7/8	29 5/8	30 3/8
254	REF-TOTAL LINER RISE	Reference Only	1/2	1/2	Measure at liner along rise seam from CF top finished edge of waistband to center of gusset/crotch seam to CB top finished edge of waistband. Note: This measurement is for the base size and for detail only.	22 1/2	23 1/4	24	24 3/4	25 1/2	26 1/4
310	REF - HIP CIRC 5" down fr TOP of WST	Reference Only	1/2	1/2	Measure from fold edge of garment to CF crotch seam to fold edge of garment at a point 5" below top of waistband, multiply by 2. NOTE: Place garment flat in its natural state and ensure CF drop is correct.	37 1/4	39 1/4	41 1/4	43 1/4	46 1/4	49 1/4
289	WAIST CIRC RELAXED	Critical	1/2	1/2	Measure along finished edge of waistband from fold edge of garment to fold edge of garment with waistband top edge aligned in a relaxed state, multiply by 2.	25 1/2	27 1/2	29 1/2	31 1/2	34 1/2	37 1/2
290	WAIST CIRC EXTENDED	Critical	1/2	1/2	Measure along finished edge of waistband from fold edge of garment to fold edge of garment with waistband top edge aligned in a fully extended state, multiply by 2.	35	37	39	41	44	47
30	WAISTBAND HEIGHT		1/8	1/8	Measure from top of waistband edge straight down to waistband seam.	1 5/8	1 5/8	1 5/8	1 5/8	1 5/8	1 5/8
32	REF-CF DROP at WAISTBAND		0	0	Measure from top finished edge of CB waistband straight down to top finished edge of CF waistband when laying garment flat in its natural state. This is a guideline for getting the garment in correct position to measure hip.	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8
183	Yoke Height at CB: Waist Seam to CB Yoke Seam		1/8	1/8	Measure from waist seam to yoke seam at Center Back.	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4

Measurement Set: Calculated			Winter 2025		Pace Breaker Short 7 Lined LM7B24S		Iululemon		Jun 17, 2024		
#	Name	Criticality	Tol (-)	Tol (+)	HTM Instruction	XS	S	M	L	XL	XXL
13001	Low Hip Position : from Top Waist Edge		0	0	Lay garment flat with waist laying in it's natural position. Measure from top edge to specified Low Hip Positions at sides and CF, measure the Low Hip from side edge to CF to side edge. Top edge of tape to be placed at Low Hip Position	6 1/4	6 1/2	6 3/4	7	7 1/4	7 1/2
12983	Low Hip Circumference: 3 Point Measure	Critical	1/2	1/2	Lay garment flat with waist laying in its natural position. At specified Low Hip Positions, measure from side edge to CF to side edge, if style has pleats, open them to measure Low Hip. Top edge of tape to be placed at Low Hip Position, double the measurement	38 1/4	40 1/4	42 1/4	44 1/4	47 1/4	50 1/4
373	Thigh Circumference: 1" below Rise Seam	Critical	3/8	3/8	At 1" below rise seam, measure straight across from inside leg fold edge to outer leg fold edge parallel to leg opening, double the measurement	25 1/4	26 1/2	27 3/4	29	30 3/4	32 1/2
9	HEM SWEEP CIRC	Critical	1/2	1/2	Measure from left fold edge to right fold edge straight across bottom edge of finished hem, multiply by 2.	21 3/4	23	24 1/4	25 1/2	27 1/4	29
12	HEM HEIGHT		1/8	1/8	Measure from top of hem stitching line straight down to finished hem edge.	3/4	3/4	3/4	3/4	3/4	3/4
31	INSEAM	Critical	1/2	1/2	Measure from center of gusset or crotch seam straight down to bottom edge of leg opening.	7	7	7	7	7	7
20	RISE FRONT fr TOP of WST down	Critical	1/4	1/4	Measure along front rise seam from CF top finished edge of waistband to crotch seam.	10 3/4	11	11 1/4	11 1/2	11 3/4	12
22	RISE BACK fr TOP of WST down	Critical	1/4	1/4	Measure along back rise seam from CB top finished edge of waistband to crotch seam.	13 5/8	13 7/8	14 1/8	14 3/8	14 5/8	14 7/8
298	GUSSET PANEL RISE		1/8	1/8	Measure length of gusset panel along rise seam direction, from center of stitching at front rise to center of stitching at back rise.	2 1/4	2 1/2	2 3/4	3	3 1/4	3 1/2
293	LINER-RISE at FRONT	Critical	1/4	1/4	Measure at liner along front rise seam/CF rise from top finished edge of waistband to center of gusset/crotch seam.	12 3/8	12 3/4	13 1/8	13 1/2	13 7/8	14 1/4
296	LINER-RISE at BACK	Critical	1/4	1/4	Measure at liner along back rise seam/center front of rise from top finished edge of waistband to center of gusset/crotch seam.	10 1/8	10 1/2	10 7/8	11 1/4	11 5/8	12
343	LINER-HIP CIRC 5" down fr TOP of WST	Reference Only	1/2	1/2	Measure from fold edge of garment to CF crotch seam to fold edge of garment, multiply by 2. NOTE: Place garment flat in its natural state and ensure CF drop is correct.	25 3/4	27 3/4	29 3/4	31 3/4	34 3/4	37 3/4
308	LINER-INSEAM	Critical	1/4	1/4	Measure at liner from center of gusset or crotch seam straight down to bottom edge of leg opening.	6	6	6	6	6	6
376	LINER-LEG OPENING	Critical	3/8	3/8	Measure along finished edge of leg opening.	12 1/4	13 1/2	14 3/4	16	17 3/4	19 1/2

#	Name	Criticality	Tol (-)	Tol (+)	HTM Instruction	XS	S	M	L	XL	XXL
12	Liner Hem Height		1/8	1/8	Measure from top of hem stitching line straight down to finished hem edge.	3/4	3/4	3/4	3/4	3/4	3/4
301	CROTCH SEAM WIDTH		1/8	1/8	Measure across crotch seam from finished edge to finished edge.	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2
375	CROTCH WIDTH AT NARROWEST		1/8	1/8	Measure across crotch from finished edge to finished edge at narrowest point.	1 3/8	1 3/8	1 3/8	1 3/8	1 3/8	1 3/8
122	PKT1 OPENING at FRONT		1/8	1/8	Measure from finished edge to finished edge along pocket opening.	6 1/2	6 3/4	7	7	7 1/4	7 1/4
121	PKT2 MEDIA OPENING		1/8	1/8	Measure from finished edge to finished edge along pocket opening.	5 1/2	5 1/2	5 1/2	5 1/2	5 1/2	5 1/2
135	FLY STITCHING LENGTH		1/8	1/8	Measure from top of fly seam straight down to bottom of fly placket stitching.	4 3/4	4 3/4	5	5	5 1/4	5 1/4
136	FLY STITCHING WIDTH		0	0	Measure from fly edge straight across to outer fly stitching line.	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2
53	DRAWCORD LENGTH		1/2	1/2	Measure from aligned drawcord tips or center fold of continuous drawcord to center fold edge of garment, multiply by 2.	44	46	48	50	53	56

	<b>Season:</b>	Winter 2025	<b>Brand:</b>	lululemon	<b>Style Status:</b>	Active	
	<b>Style #:</b>	LM7B24S	<b>Division:</b>	lulu Mens	<b>Generated Date:</b>	Jun 17, 2024	
	<b>Style Desc:</b>	Pace Breaker Short 7 Lined LM7B24S	<b>Class:</b>	Mens Shorts	<b>Measurement Template:</b>	--M Short with Liner XS-XXL	
	<b>Product Size Definition:</b>	Mens--XXS-5XL:XXS-5XL	<b>Pod:</b>	M No Sweat			
	<b>Grade Rule Template:</b>	--M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20),--M Pant XXS-5XL (FB grade SU20)					

#	Name	Criticality	Tol (-)	Tol (+)	HTM Instruction	3XL	4XL	5XL
10245	Fit Classification: Classic		0	0	An easy fit that floats away from the body			
163	REF-OUTSEAM LENGTH	Reference Only	1/2	1/2	Measure from top edge of waistband to bottom edge of hem along side seam. Note: This measurement is for the base size and for detail only.	18 1/2	18 3/4	19
310	REF - HIP CIRC 5 1/2" down fr TOP of WST	Reference Only	1/2	1/2	Measure from fold edge of garment to CF crotch seam to fold edge of garment at a point 5 1/2" below top of waistband, multiply by 2. NOTE: Place garment flat in its natural state and ensure CF drop is correct.	52 3/8	55 3/8	58 3/8
289	WAIST CIRC RELAXED	Critical	1/2	1/2	Measure along finished edge of waistband from fold edge of garment to fold edge of garment with waistband top edge aligned in a relaxed state, multiply by 2.	40 1/2	43 1/2	46 1/2
290	WAIST CIRC EXTENDED	Critical	1/2	1/2	Measure along finished edge of waistband from fold edge of garment to fold edge of garment with waistband top edge aligned in a fully extended state, multiply by 2.	49 3/4	52 3/4	55 3/4
30	WAISTBAND HEIGHT		1/8	1/8	Measure from top of waistband edge straight down to waistband seam.	1 5/8	1 5/8	1 5/8
32	REF-CF DROP at WAISTBAND		0	0	Measure from top finished edge of CB waistband straight down to top finished edge of CF waistband when laying garment flat in its natural state. This is a guideline for getting the garment in correct position to measure hip.	1 1/2	1 1/2	1 1/2
183	Yoke Height at CB: Waist Seam to CB Yoke Seam		1/8	1/8	Measure from waist seam to yoke seam at Center Back.	2 1/4	2 1/4	2 1/4
13001	Low Hip Position : from Top Waist Edge		0	0	Lay garment flat with waist laying in it's natural position. Measure from top edge to specified Low Hip Positions at sides and CF, measure the Low Hip from side edge to CF to side edge. Top edge of tape to be placed at Low Hip Position	7 3/4	8	8 1/4
12983	Low Hip Circumference : 3 Point Measure	Critical	1/2	1/2	Lay garment flat with waist laying in its natural position. At specified Low Hip Positions, measure from side edge to CF to side edge, if style has pleats, open them to measure Low Hip. Top edge of tape to be placed at Low Hip Position, double the measurement	52 3/4	55 3/4	58 3/4
373	Thigh Circumference: 1" below Rise Seam	Critical	3/8	3/8	At 1" below rise seam, measure straight across from inside leg fold edge to outer leg fold edge parallel to leg opening, double the measurement	33 1/4	35	36 3/4

Measurement Set: Calculated			Winter 2025		Pace Breaker Short 7 Lined LM7B24S	lululemon	Jun 17, 2024	
#	Name	Criticality	Tol (-)	Tol (+)	HTM Instruction	3XL	4XL	5XL
9	HEM SWEEP CIRC	Critical	1/2	1/2	Measure from left fold edge to right fold edge straight across bottom edge of finished hem, multiply by 2.	28 1/4	30	31 3/4
12	HEM HEIGHT		1/8	1/8	Measure from top of hem stitching line straight down to finished hem edge.	3/4	3/4	3/4
31	INSEAM	Critical	1/2	1/2	Measure from center of gusset or crotch seam straight down to bottom edge of leg opening.	7	7	7
20	RISE FRONT fr TOP of WST down	Critical	1/4	1/4	Measure along front rise seam from CF top finished edge of waistband to crotch seam.	12 1/4	12 1/2	12 3/4
22	RISE BACK fr TOP of WST down	Critical	1/4	1/4	Measure along back rise seam from CB top finished edge of waistband to crotch seam.	16 1/8	16 3/8	16 5/8
298	GUSSET PANEL RISE		1/8	1/8	Measure length of gusset panel along rise seam direction, from center of stitching at front rise to center of stitching at back rise.	3 3/4	4	4 1/4
293	LINER-RISE at FRONT	Critical	1/4	1/4	Measure at liner along front rise seam/CF rise from top finished edge of waistband to center of gusset/crotch seam.	13	13 1/2	14
296	LINER-RISE at BACK	Critical	1/4	1/4	Measure at liner along back rise seam/center front of rise from top finished edge of waistband to center of gusset/crotch seam.	13 7/8	14 1/8	14 3/8
343	LINER-HIP CIRC 5 1/2" down fr TOP of WST	Reference Only	1/2	1/2	Measure from fold edge of garment to CF crotch seam to fold edge of garment, multiply by 2. NOTE: Place garment flat in its natural state and ensure CF drop is correct.	34 3/4	37 3/4	40 3/4
308	LINER-INSEAM	Critical	1/4	1/4	Measure at liner from center of gusset or crotch seam straight down to bottom edge of leg opening.	6 1/2	6 1/2	6 1/2
376	LINER-LEG OPENING	Critical	3/8	3/8	Measure along finished edge of leg opening.	17 3/4	19 1/2	21 1/4
12	Liner Hem Height		1/8	1/8	Measure from top of hem stitching line straight down to finished hem edge.	3/4	3/4	3/4
301	CROTCH SEAM WIDTH		1/8	1/8	Measure across crotch seam from finished edge to finished edge.	3 1/2	3 1/2	3 1/2
375	CROTCH WIDTH AT NARROWEST		1/8	1/8	Measure across crotch from finished edge to finished edge at narrowest point.	1 3/8	1 3/8	1 3/8
122	PKT1 OPENING at FRONT		1/8	1/8	Measure from finished edge to finished edge along pocket opening.	7 1/2	7 1/2	7 3/4
121	PKT2 MEDIA OPENING		1/8	1/8	Measure from finished edge to finished edge along pocket opening.	5 1/2	5 1/2	5 1/2
135	FLY STITCHING LENGTH		1/8	1/8	Measure from top of fly seam straight down to bottom of fly placket stitching.	5 1/2	5 3/4	6
136	FLY STITCHING WIDTH		0	0	Measure from fly edge straight across to outer fly stitching line.	1 1/2	1 1/2	1 1/2
53	DRAWCORD LENGTH		1/2	1/2	Measure from aligned drawcord tips or center fold of continuous drawcord to center fold edge of garment, multiply by 2.	59	62	65