

Visualizations with statistical details: The 'ggstatsplot' approach

Indrajeet Patil¹

1 Center for Humans and Machines, Max Planck Institute for Human Development, Berlin, Germany

Summary

During exploratory data analysis, the graphical displays can reveal problems in a statistical model that might not be apparent from purely numerical summaries. Such visualizations can also be helpful for the reader to evaluate validity of a model if the said analysis is reported in a scholary publication/report. But given the onerous cost of preparing information-rich graphics and exploring several statistical approaches/tests available, researchers can avoid this practice. The ggstatsplot package in R programming language (R Core Team, 2021) provides a one-line syntax to create densely informative ggplot2-based visualizations with the results from statistical analysis embedded in the visualization itself. In doing so, the package helps researchers adopt a rigorous, reliable, and robust data exploratory and reporting workflow and holds the potential to alleviate a few of the crises affecting scientific research.

Statement of Need

Recent meta-research has revealed a number of problems plaguing the credibility of scientific research: findings are not replicable, codes are computationally irreproducible, the statistical reporting is inaccurate, the effects do not survive further robustness checks, etc. A few of these problems can be alleviated simply by adopting good practices while exploring (analyzing and visualizing) data and reporting results from statistical analysis. This is where ggstatsplot comes in.

In a typical data analysis workflow, data visualization and statistical modeling are two different phases: visualization informs modeling, and modeling in its turn can suggest a different visualization method, and so on and so forth (Wickham & Grolemund, 2016). The central idea of ggstatsplot is simple: combine these two phases into one in the form of an informative graphic with statistical details.

Before discussing benefits of this approach, we will see one example (Figure 1).

```
library(ggstatsplot)
library(palmerpenguins) # for 'penguins' dataset
ggbetweenstats(penguins, species, body_mass_g)
```

As can be seen, with a **single** line of code, the function produces details about descriptive statistics, inferential statistics, effect size estimate and its uncertainty, pairwise comparisons, Bayesian hypothesis testing, Bayesian posterior estimate and its uncertainty. Moreover, these details are juxtaposed with informative and well-labeled visualizations, designed to follow best practices in **both** data visualization (Cleveland, 1985; Grant, 2018; Healy, 2018; Tufte, 2001; Wilke, 2019) and (Frequentist/Bayesian) statistical reporting (Association & others, 1985; Doorn et al., 2020). Without ggstatsplot, getting these statistical details and customizing a plot would require significant amount of time and

DOI:

Software

- Review 12
- Repository ☐
- Archive ௴

Submitted: Published:

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License (CC-BY).






Figure 1: Example plot from the 'ggstatsplot' package illustrates its philosophy of juxtaposing informative visualizations with details from statistical analysis. To see all supported plots and statistical analyses, see the package website: https://indrajeetpatil.github.io/ggstatsplot/

work. In other words, this package takes away an excuse from researchers to thoroughly explore their data and instills good data sanitation/exploration habits.

Behind the scenes, data cleaning is carried out using tidyverse (Wickham et al., 2019), while statistical analysis is carried out via statsExpressions (Patil, 2021) and easystats (Ben-Shachar, Lüdecke, & Makowski, 2020; Lüdecke, Ben-Shachar, Patil, & Makowski, 2020; Lüdecke, Ben-Shachar, Patil, Waggoner, & Makowski, 2021; Lüdecke, Waggoner, & Makowski, 2019; Makowski, Ben-Shachar, & Lüdecke, 2019; Makowski, Ben-Shachar, Patil, & Lüdecke, 2020). All visualizations are constructed using ggplot2 (Wickham, 2016; Wilkinson, 2012).

This package is an ambitious, ongoing, long-term project, and it will continue to grow to support ever increasing collection of visualizations and statistical analyses.

Benefits

We can now succinctly summarize the benefits of ggstatsplot's approach. It-

- a. produces charts displaying both raw data, and numerical plus graphical summary indices,
- b. avoids errors in statistical reporting,
- c. highlights the importance of the effect by providing effect size measures by default,
- d. provides an easy way to evaluate absence of an effect using Bayesian framework,
- e. forces to evaluate statistical assumptions of a model in the context of the underlying data (Figure 2), and
- f. is easy and simple enough that somebody with little-to-no coding experience can use it without making an error.



Standard approach

Pearson's correlation test revealed that, across 142 participants, variable \mathbf{x} was negatively correlated with variable \mathbf{y} : t(140) = -0.76, p = .446. The effect size (r = -0.06, 95%CI[-.23, .10]) was small, as per Cohen's (1988) conventions. The Bayes Factor for the same analysis revealed that the data were 5.81 times more probable under the null hypothesis as compared to the alternative hypothesis. This can be considered moderate evidence (Jeffreys, 1961) in favor of the null hypothesis (absence of any correlation between \mathbf{x} and \mathbf{y}).




Figure 2: Comparing the standard approach of reporting statistical analysis in a scholarly publications with the 'ggstatsplot' with approach of reporting the same analysis next to an informative graphic.

Licensing and Availability

ggstatsplot is licensed under the GNU General Public License (v3.0), with all source code stored at GitHub, and with a corresponding issue tracker for bug reporting and feature enhancements. In the spirit of honest and open science, we encourage requests/tips for fixes, feature updates, as well as general questions and concerns via direct interaction with contributors and developers, by filing an issue. See the package's *Contribution Guidelines*.

Acknowledgements

I would like to acknowledge the support of Mina Cikara, Fiery Cushman, and Iyad Rahwan during the development of this project. <code>ggstatsplot</code> relies heavily on the <code>easystats</code> ecosystem, a collaborative project created to facilitate the usage of R for statistical analyses. Thus, I would like to thank the <code>members</code> of <code>easystats</code> as well as the users. I would additionally like to thank the contributors to <code>ggstatsplot</code> for reporting bugs, providing helpful feedback, or helping with enhancements.

References

Association, A. P., & others. (1985). Publication manual of the american psychological association. American psychological association.

Ben-Shachar, M. S., Lüdecke, D., & Makowski, D. (2020). effectsize: Estimation of effect size indices and standardized parameters. *Journal of Open Source Software*, 5(56), 2815. doi:10.21105/joss.02815

Cleveland, W. S. (1985). *The Elements of Graphing Data* (1st edition.). Monterey, Cal: Wadsworth, Inc.

Doorn, J. van, Bergh, D. van den, Böhm, U., Dablander, F., Derks, K., Draws, T., Etz, A., et al. (2020). The JASP guidelines for conducting and reporting a bayesian analysis. *Psychonomic Bulletin & Review*, 1–14. doi:10.3758/s13423-020-01798-5

Grant, R. (2018). Data Visualization: Charts, Maps, and Interactive Graphics. CRC Press.



- Healy, K. (2018). Data Visualization: A Practical Introduction. Princeton University Press.
- Lüdecke, D., Ben-Shachar, M. S., Patil, I., & Makowski, D. (2020). Parameters: Extracting, computing and exploring the parameters of statistical models using R. *Journal of Open Source Software*, 5(53), 2445. doi:10.21105/joss.02445
- Lüdecke, D., Ben-Shachar, M. S., Patil, I., Waggoner, P., & Makowski, D. (2021). Assessment, testing and comparison of statistical models using R. *Journal of Open Source Software*, 6(59), 3112. doi:10.31234/osf.io/vtq8f
- Lüdecke, D., Waggoner, P., & Makowski, D. (2019). Insight: A unified interface to access information from model objects in R. *Journal of Open Source Software*, 4(38), 1412. doi:10.21105/joss.01412
- Makowski, D., Ben-Shachar, M. S., & Lüdecke, D. (2019). bayestestR: Describing effects and their uncertainty, existence and significance within the bayesian framework. Journal of Open Source Software, 4(40), 1541. doi:10.21105/joss.01541
- Makowski, D., Ben-Shachar, M. S., Patil, I., & Lüdecke, D. (2020). Methods and algorithms for correlation analysis in R. *Journal of Open Source Software*, 5(51), 2306. doi:10.21105/joss.02306
- Patil, I. (2021). statsExpressions: R package for tidy dataframes and expressions with statistical details. *Journal of Open Source Software*, 6(59), 3111. doi:10.31234/osf.io/ntbvy
- R Core Team. (2021). R: A language and environment for statistical computing. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from https://www.R-project.org/
- Tufte, E. R. (2001). The Visual Display of Quantitative Information (2nd edition.). Cheshire, Conn. Graphics Press.
- Wickham, H. (2016). ggplot2: Elegant graphics for data analysis. Springer-Verlag New York. Retrieved from https://ggplot2.tidyverse.org
- Wickham, H., Averick, M., Bryan, J., Chang, W., McGowan, L. D., François, R., Grolemund, G., et al. (2019). Welcome to the tidyverse. *Journal of Open Source Software*, 4(43), 1686. doi:10.21105/joss.01686
- Wickham, H., & Grolemund, G. (2016). R for Data Science. O'Reilly Medias.
- Wilke, C. O. (2019). Fundamentals of Data Visualization. O'Reilly Media.
- Wilkinson, L. (2012). The grammar of graphics. *Handbook of computational statistics* (pp. 375–414). Springer.