

AI LAB

LAB 9

Convert a given first order logic statement into Conjunctive Normal Form (CNF)

Algorithm:

□ **Eliminate biconditionals and implications**

- Replace:
- $A \leftrightarrow B$ with $(A \rightarrow B) \wedge (B \rightarrow A)$

□ **Move NOT (\neg) inwards (Negation Normal Form)**

- Use De Morgan's laws:
 - $\neg(A \wedge B) \rightarrow (\neg A \vee \neg B)$
 - $\neg(A \vee B) \rightarrow (\neg A \wedge \neg B)$
- For quantifiers:
 - $\neg \forall x P(x) \rightarrow \exists x \neg P(x)$
 - $\neg \exists x P(x) \rightarrow \forall x \neg P(x)$

□ **Standardize variables**

- Rename bound variables so that each quantifier has a unique variable.

□ **Skolemization (remove existential quantifiers)**

- Replace $\exists x P(x)$ with $P(f(y_1, \dots, y_n))$ where $y_1 \dots y_n$ are universally quantified variables in scope.
- This introduces **Skolem functions**.

□ **Drop universal quantifiers**

- After Skolemization, all remaining quantifiers are universal — can be dropped implicitly.

□ **Distribute \vee over \wedge**

- Apply distributive laws to obtain a conjunction of disjunctions:
 - $(A \vee (B \wedge C))(A \vee (B \wedge C))(A \vee (B \wedge C)) \rightarrow (A \vee B) \wedge (A \vee C) \wedge (A \vee B) \wedge (A \vee C)$

□ **Simplify**

- Remove duplicate literals, tautologies, etc.

CODE:

```
from sympy import symbols
from sympy.logic.boolalg import to_cnf
from sympy.abc import x, y

# Define propositional variables (for simplicity)
P, Q, R = symbols('P Q R')

# Example: (P >> (Q | ~R))
expr = P >> (Q | ~R)

# Convert to CNF
cnf_expr = to_cnf(expr, simplify=True)

print("Original Expression:")
print(expr)
print("\nCNF Form:")
print(cnf_expr)
```

Output:

Original Expression:
 $\text{Implies}(P, Q \mid \sim R)$

CNF Form:
 $Q \mid \sim P \mid \sim R$