

Create a class hierarchy (e.g., animals with different sounds) and manage object lifetimes and relationships using smart pointers. Include error handling to gracefully handle situations where resources might not be available.

```
#include <iostream>

#include <memory>

#include <stdexcept>

class Animal {                                // Base class Animal
public:
    virtual ~Animal() = default;
    virtual void makeSound() const = 0;
};

class Dog : public Animal {                    // Derived class Dog
public:
    void makeSound() const override {
        std::cout << "Woof!" << std::endl;
    }
};

class Cat : public Animal {                    // Derived class Cat
public:
    void makeSound() const override {
        std::cout << "Meow!" << std::endl;
    }
};

class Cow : public Animal {                    // Derived class Cow
public:
```

```

void makeSound() const override {

    std::cout << "Moo!" << std::endl;

}

};

std::shared_ptr<Animal> createAnimal(const std::string& type) { // Function to create an animal
based on type

    if (type == "Dog") {

        return std::make_shared<Dog>();

    } else if (type == "Cat") {

        return std::make_shared<Cat>();

    } else if (type == "Cow") {

        return std::make_shared<Cow>();

    } else {

        throw std::invalid_argument("Unknown animal type");

    }

}

int main() { // Main function demonstrating
the usage

    try {

        std::shared_ptr<Animal> dog = createAnimal("Dog");

        std::shared_ptr<Animal> cat = createAnimal("Cat");

        std::shared_ptr<Animal> cow = createAnimal("Cow");

        dog->makeSound();

        cat->makeSound();

        cow->makeSound();

    } catch (const std::exception& e) {

```

```

        std::cerr << "Error: " << e.what() << std::endl;
    }

    std::weak_ptr<Animal> weakDog;

    {
        std::shared_ptr<Animal> dog = createAnimal("Dog");

        weakDog = dog;
    }

    if (auto sharedDog = weakDog.lock()) {
        sharedDog->makeSound();
    } else {
        std::cout << "Dog has been destroyed" << std::endl;
    }

    return 0;
}

```

Simulate rolling dice, flipping coins, or generating random temperatures within a range. Users can choose the type of distribution and potentially customize parameters.

```

#include <iostream>

#include <random>

#include <ctime>

int rollDie(int sides) { // Function to simulate rolling a fair n-sided die

    std::random_device rd;

    std::mt19937 gen(rd());

    std::uniform_int_distribution<> dis(1, sides);

    return dis(gen);
}

```

```

int flipCoin() {                                     // Function to simulate flipping a fair coin (1 for
heads, 0 for tails)

    std::random_device rd;

    std::mt19937 gen(rd());

    std::uniform_int_distribution<> dis(0, 1);

    return dis(gen);
}

double generateRandomTemperature(double minTemp, double maxTemp) {           // Function
to generate a random temperature within a specified range

    std::random_device rd;

    std::mt19937 gen(rd());

    std::uniform_real_distribution<> dis(minTemp, maxTemp);

    return dis(gen);
}

int main() {

    srand(time(0));                                // Seed for rand() function (optional)

    std::cout << "Simulating rolling a 6-sided die: " << rollDie(6) << std::endl;

    std::cout << "Simulating flipping a coin: " << (flipCoin() ? "Heads" : "Tails") << std::endl;

    double minTemp = 10.0, maxTemp = 15.0;

    std::cout << "Generating random temperature between " << minTemp << " and " << maxTemp << "
degrees Celsius: ";

    std::cout << generateRandomTemperature(minTemp, maxTemp) << " C" << std::endl;

    return 0;
}

```

Project 4: File I/O with Regular Expressions (Enhanced with Error Handling and Performance)

Concept: Employ C++11 file I/O streams (ifstream, ofstream) to read from and write to files.

Enhancements:

Error Handling: Implement robust error handling to gracefully deal with file opening failures, I/O errors, or invalid data formats. Consider using exceptions or custom error codes for better diagnostics.

Regular Expressions: Utilize the <regex> library to search for patterns within text files, allowing for more complex data extraction or manipulation.

Example: Create a program that reads a log file, searches for specific error messages using regular expressions, and writes the matching lines to a new file, providing informative error messages if issues arise during file access or processing.

```
#include <iostream>

#include <fstream>

#include <regex>

#include <string>

#include <stdexcept>

class FileIOException : public std::runtime_error {           // Custom exception for file I/O
    errors

public:

    explicit FileIOException(const std::string& message)

        : std::runtime_error(message) {}

};

// Function to read from a file, search for error messages, and write to another file

void processLogFile(const std::string& inputFilePath, const std::string& outputFilePath, const
std::string& pattern) {

    std::ifstream inputFile(inputFilePath);

    if (!inputFile) {

        throw FileIOException("Error opening input file: " + inputFilePath);

    }

    std::ofstream outputFile(outputFilePath);

    if (!outputFile) {
```

```

        throw FileIOException("Error opening output file: " + outputFilePath);
    }

    std::regex errorPattern(pattern);

    std::string line;

    while (std::getline(inputFile, line)) {

        if (std::regex_search(line, errorPattern)) {

            outputFile << line << std::endl;

        }

    }

    if (inputFile.bad()) {

        throw FileIOException("Error reading input file: " + inputFilePath);

    }

    if (outputFile.bad()) {

        throw FileIOException("Error writing to output file: " + outputFilePath);

    }

}

int main() {                                     // Main function to demonstrate the usage

    std::string inputFilePath;

    std::string outputFilePath;

    std::string pattern;

    std::cout << "Enter the input log file path: ";

    std::cin >> inputFilePath;

    std::cout << "Enter the output file path: ";

    std::cin >> outputFilePath;

    std::cout << "Enter the regex pattern to search for: ";

```

```

std::cin.ignore(); // Clear the newline character from the input buffer

std::getline(std::cin, pattern);

try {

    processLogFile(inputFilePath, outputFilePath, pattern);

    std::cout << "Log file processed successfully. Matching lines written to " << outputFilePath <<
std::endl;

} catch (const FileIOException& e) {

    std::cerr << "File I/O Error: " << e.what() << std::endl;

} catch (const std::regex_error& e) {

    std::cerr << "Regex Error: " << e.what() << std::endl;

} catch (const std::exception& e) {

    std::cerr << "Unexpected Error: " << e.what() << std::endl;

}

return 0;

}

```

Project 5: Modern C++ Design Patterns (Using Move Semantics and Lambdas)

Concept: Explore modern C++ design patterns like move semantics (rvalue references) and lambdas to write efficient and expressive code.

Enhancements:

Move Semantics: Optimize code by understanding how to efficiently move resources (like large objects) to avoid unnecessary copies.

Lambdas: Utilize lambda expressions to create concise and readable anonymous functions, particularly for short-lived logic or event handling.

Example: Create a container class that efficiently stores and moves large objects like images or scientific data. Implement custom iterators or member functions using lambdas to process elements in the container.

These enhanced projects will significantly improve your proficiency in C++11 by:

```
Image& operator=(Image&& other) noexcept { // Move assignment
operator
```



```

        if (this != &other) {

            delete[] data_;

            size_ = other.size_;

            data_ = other.data_;

            other.size_ = 0;

            other.data_ = nullptr;

            std::cout << "Image moved (assignment)." << std::endl;

        }

        return *this;

    }

    Image(const Image&) = delete; // Deleted copy constructor and copy
assignment operator

    Image& operator=(const Image&) = delete;

    size_t size() const { return size_; }

private:

    size_t size_;

    int* data_;

};

template<typename T> // Container class for large objects

class Container {

public:

    void add(T&& item) {

        items_.emplace_back(std::move(item));

    }

    template<typename Func>

    void forEach(Func func) {

```

```

        std::for_each(items_.begin(), items_.end(), func);
    }
private:
    std::vector<T> items_;
};

int main() {
    try {
        Container<Image> imageContainer;

        imageContainer.add(Image(1000));
        imageContainer.add(Image(2000));
        imageContainer.add(Image(3000));

        imageContainer.forEach([](const Image& img) {
            Process images with a lambda function //
            std::cout << "Processing image of size " << img.size() << std::endl;

        });
    } catch (const std::exception& e) {
        std::cerr << "Error: " << e.what() << std::endl;
    }

    return 0;
}

```

MAP QUIZ :-

```

#include <iostream>

#include<iterator>

#include<map>

using namespace std;

```

```

int main()
{
    //empty map container
    map<int, int>gquiz1;

    //insert elements in random order
    gquiz1.insert(pair<int, int>(1,40));
    gquiz1.insert(pair<int, int>(2,30));
    gquiz1.insert(pair<int, int>(3,60));
    gquiz1.insert(pair<int, int>(4,20));
    gquiz1.insert(pair<int, int>(5,50));
    gquiz1.insert(pair<int, int>(6,50));
    gquiz1.insert(pair<int, int>(7,10));

    //printing map gquiz1
    map<int, int>::iterator itr;

    cout<<"\n The map gquiz1 is:\n";
    cout<<"\tKEY\tELEMENT\n";

    for(itr = gquiz1.begin();itr != gquiz1.end(); ++itr){
        cout<<"\t" <<itr->first<<"\t"<<itr->second<<"\n";
    }

    cout<<endl;

    //assigning the elements from gquiz1 to gquiz2
    map<int, int>gquiz2(gquiz1.begin(),gquiz1.end());

    //print all elements of the map gquiz2
    cout<<"\nThe map gquiz2 after"<<"assign from gquiz1 is :\n";
    cout<<"\tKEY\tELEMENT\n";

```

```

for(itr = gquiz2.begin();itr != gquiz2.end(); ++itr){
    cout<<'t' <<itr->first<<'t'<<itr->second<<'n';
}

cout<<endl;

//remove all elements up to
// element with key=3 in gquiz2

cout<<"\n gquiz2 after removal of""elements less thsn key=3:\n";

cout<<"\tKEY\tELEMENT\n";

gquiz2.erase(gquiz2.begin(),gquiz2.find(3));

for(itr = gquiz2.begin();itr != gquiz2.end(); ++itr){
    cout<<'t' <<itr->first<<'t'<<itr->second<<'n';
}

//remove all elements with key=4

int num;

num=gquiz2.erase(4);

cout<<"\ngquiz2.erase(4).:";

cout<<num<<"removed\n";

cout<<"\tKEY\tELEMENT\n";

gquiz2.erase(gquiz2.begin(),gquiz2.find(3));

for(itr = gquiz2.begin();itr != gquiz2.end(); ++itr){
    cout<<'t' <<itr->first<<'t'<<itr->second<<'n';
}

cout<<endl;

//lower bound and upper bound for map gquiz1 key =5

cout<<"gquiz1.lower_bound(5):"<<"\tKEY=";

```

```

cout<<gquiz1.lower_bound(5)->first<<"\t";

cout<<"\tELEMENT="<<gquiz1.lower_bound(5)->second<<"\t";

cout<<"gquiz1.upper_bound(5):"<<"\tKEY=";

cout<<gquiz1.upper_bound(5)->first<<"\t";

cout<<"\tELEMENT="<<gquiz1.lower_bound(5)->second<<"\t";

return 0;

}

```

OUTPUT :-

```

1 #include <iostream>
2 #include <iterator>
3 #include <map>
4 using namespace std;
5 int main()
6 {
7     //empty map container
8     map<int, int> gquiz1;
9
10    The map gquiz1 is:
11    KEY    ELEMENT
12    1      40
13    2      30
14    3      60
15    4      20
16    5      50
17    6      30
18    7      10
19
20    The map gquiz2 after assign from gquiz1 is :
21    KEY    ELEMENT
22    1      40
23    2      30
24    3      60
25    4      20
26    5      50
27    6      30
28    7      10
29
30    gquiz2 after removal of elements less than key 3:
31    KEY    ELEMENT
32    3      60
33    4      20
34    5      50
35    6      30
36    7      10
37
38    gquiz2.erase(4):removed
39    KEY    ELEMENT
40    3      60
41    5      50
42    6      30
43    7      10
44
45    gquiz1.lower_bound(5): KEY=5    ELEMENT=50    gquiz1.upper_bound(5): KEY=6    ELEMENT=50
46    ...Program finished with exit code 0

```

Develop a C++ program that allows users to enter and store contact details (name, phone number, email) in a map. The program should provide options for adding new contacts, searching for existing contacts, and displaying all stored contacts.

```

#include <iostream>

#include <map>

#include <string>

struct Contact {                                // Structure to hold contact details

    std::string phone_number;

```

```

        std::string email;
    };

    void addContact(std::map<std::string, Contact>& contacts) {           // Function to add a new
        contact to the map

        std::string name, phone, email;

        std::cout << "Enter name: ";

        std::cin >> name;

        std::cout << "Enter phone number: ";

        std::cin >> phone;

        std::cout << "Enter email: ";

        std::cin >> email;

        Contact new_contact = {phone, email};

        contacts[name] = new_contact;

        std::cout << "Contact added successfully!\n";
    }

    void searchContact(const std::map<std::string, Contact>& contacts) {   // Function to
        search for a contact by name

        std::string name;

        std::cout << "Enter name to search: ";

        std::cin >> name;

        auto it = contacts.find(name);

        if (it != contacts.end()) {

            std::cout << "Name: " << it->first << std::endl;

            std::cout << "Phone number: " << it->second.phone_number << std::endl;

            std::cout << "Email: " << it->second.email << std::endl;

        } else {

            std::cout << "Contact not found.\n";

        }
    }

```

```

}

void displayContacts(const std::map<std::string, Contact>& contacts) { // Function
to display all contacts

    if (contacts.empty()) {

        std::cout << "No contacts to display.\n";

    } else {

        std::cout << "List of contacts:\n";

        for (const auto& pair : contacts) {

            std::cout << "Name: " << pair.first << std::endl;

            std::cout << "Phone number: " << pair.second.phone_number << std::endl;

            std::cout << "Email: " << pair.second.email << std::endl;

            std::cout << "-----\n";

        }

    }

}

int main() {

    std::map<std::string, Contact> contacts;

    int choice;

    while (true) {

        std::cout << "\n*** Contact Management System ***\n";
// Display menu

        std::cout << "1. Add New Contact\n";

        std::cout << "2. Search Contact\n";

        std::cout << "3. Display All Contacts\n";

        std::cout << "4. Exit\n";

        std::cout << "Enter your choice: ";

        std::cin >> choice;

        switch (choice) {

```

```
        case 1:
            addContact(contacts);

            break;

        case 2:
            searchContact(contacts);

            break;

        case 3:
            displayContacts(contacts);

            break;

        case 4:
            std::cout << "Exiting program...\n";

            return 0;

        default:
            std::cout << "Invalid choice. Please try again.\n";

    }

}

return 0;

}
```

OUTPUT :-


```
Meeting Link_C++ Programmin: x Meeting now | Microsoft To: x Online C Compiler - online edit: x Online C Compiler - online edit: x Ameesha614/wipro-c wipro c p: x + -
```

https://www.onlinegdb.com/online_c_compiler#

Language: C++

```
*** Contact Management System ***
1. Add New Contact
2. Search Contact
3. Display All Contacts
4. Exit
Enter your choice: 1
Enter name: Raju
Enter phone number: 1234567890
Enter email: xyz@gmail.com
Contact added successfully

*** Contact Management System ***
1. Add New Contact
2. Search Contact
3. Display All Contacts
4. Exit
Enter your choice: 2
Enter name to search: Raju
Name: Raju
Phone number: 1234567890
Email: xyz@gmail.com

*** Contact Management System ***
1. Add New Contact
2. Search Contact
3. Display All Contacts
4. Exit
Enter your choice: 1
Enter name: Kiran
Enter phone number: 9876543210
Enter email: abc@gmail.com
Contact added successfully

*** Contact Management System ***
1. Add New Contact
2. Search Contact
3. Display All Contacts
4. Exit
Enter your choice: 3
List of contacts:
Name: Kiran
Phone number: 9876543210
Email: abc@gmail.com
-----
Name: Raju
Phone number: 1234567890
Email: xyz@gmail.com
-----

*** Contact Management System ***
1. Add New Contact
```

Type here to search

26°C Cloudy 16:45 15-07-2024