```
-- ============================================================
-- NAVI Crewing Management System — Supabase Schema
-- Paste this whole file into Supabase Dashboard -> SQL Editor -> New query -> Ru
-- ============================================================

-- 1. STAFF PROFILES (extends Supabase's built-in auth.users with name + role)
create table if not exists profiles (
  id uuid primary key references auth.users(id) on delete cascade,
  full_name text not null,
  role text not null default 'staff' check (role in ('admin','staff')),
  created_at timestamptz not null default now()
);

-- 2. VESSELS
create table if not exists vessels (
  id uuid primary key default gen_random_uuid(),
  name text not null unique,
  vessel_type text,
  home_port text,
  marina_reg_no text,
  grt numeric,
  nrt numeric,
  loa numeric,
  breadth numeric,
  depth numeric,
  dwt numeric,
  engine_power_kw numeric,
  safe_manning_cert_no text,
  safe_manning_issue_date date,
  safe_manning_expiry_date date,
  updated_at timestamptz not null default now(),
  updated_by uuid references profiles(id)
);

-- 3. CREW (mirrors the existing app's data model)
create table if not exists crew (
  id uuid primary key default gen_random_uuid(),
  crew_control_no text unique,
  crew_name text not null,
  vessel_id uuid references vessels(id),
  position text,
  status text,
  contract_type text,
  dob date,
```

```
  nationality text,
  contact_no text,
  passport_no text,
  sirb_no text,
  sirb_expiry date,
  next_of_kin text,
  next_of_kin_contact text,
  address text,
  license_hold text,
  license_required text,
  embark_date date,
  embark_port text,
  coe_end date,
  ext_end date,
  actual_disembark_date date,
  disembark_port text,
  remarks text,
  reliever_name text,
  reliever_contact text,
  reliever_license text,
  reliever_status text,
  nfr boolean default false,
  nfr_reason text,
  illness boolean default false,
  illness_notes text,
  incident_count int default 0,
  accident_count int default 0,
  emergency_contact_name text,
  emergency_contact_relationship text,
  emergency_contact_no text,
  emergency_contact_address text,
  photo_path text,               -- points to a file in Supabase Storage bucket '
  created_at timestamptz not null default now(),
  updated_at timestamptz not null default now(),
  updated_by uuid references profiles(id)
);

-- 4. SEA SERVICE RECORDS (per crew member's history)
create table if not exists service_records (
  id uuid primary key default gen_random_uuid(),
  crew_id uuid references crew(id) on delete cascade,
  vessel_name text,
  vessel_type text,
  position text,
  embark_date date,
  disembark_date date,
  months_onboard numeric,
```

```
  grt numeric,
  engine_kw numeric,
  reason_for_disembarkation text,
  created_at timestamptz not null default now()
);

-- 5. DOCUMENTS (crew document uploads; actual files live in Supabase Storage buc
create table if not exists documents (
  id uuid primary key default gen_random_uuid(),
  crew_id uuid references crew(id) on delete cascade,
  title text,
  category text,
  file_path text,          -- path inside the 'crew-documents' storage bucket
  file_type text,
  uploaded_at timestamptz not null default now(),
  uploaded_by uuid references profiles(id)
);

-- 6. CRP-009 GENERATION LOG (record of who generated what, for accountability)
create table if not exists crp009_log (
  id uuid primary key default gen_random_uuid(),
  crew_id uuid references crew(id),
  employment_status text,
  from_value text,
  to_value text,
  generated_at timestamptz not null default now(),
  generated_by uuid references profiles(id)
);

-- ============================================================
-- ROW LEVEL SECURITY — only logged-in NAVI staff can read/write anything.
-- (Everyone with an account has equal read/write here, matching "one shared
-- team working together"; admin/staff role is tracked for future tightening.)
-- ============================================================
alter table profiles enable row level security;
alter table vessels enable row level security;
alter table crew enable row level security;
alter table service_records enable row level security;
alter table documents enable row level security;
alter table crp009_log enable row level security;

create policy "logged-in staff can read profiles" on profiles for select using (a
create policy "users manage their own profile" on profiles for update using (auth

create policy "logged-in staff full access to vessels" on vessels for all using (
create policy "logged-in staff full access to crew" on crew for all using (auth.u
create policy "logged-in staff full access to service_records" on service_records
```

```
create policy "logged-in staff full access to documents" on documents for all usi
create policy "logged-in staff full access to crp009_log" on crp009_log for all u

-- ============================================================
-- REALTIME — turn on live push updates for these tables
-- ============================================================
alter publication supabase_realtime add table crew;
alter publication supabase_realtime add table vessels;
alter publication supabase_realtime add table documents;
alter publication supabase_realtime add table service_records;

-- ============================================================
-- Auto-create a profile row whenever a new staff account signs up
-- ============================================================
create or replace function public.handle_new_user()
returns trigger as $$
begin
  insert into public.profiles (id, full_name, role)
  values (new.id, coalesce(new.raw_user_meta_data->>'full_name', new.email), 'sta
  return new;
end;
$$ language plpgsql security definer;

create trigger on_auth_user_created
  after insert on auth.users
  for each row execute procedure public.handle_new_user();
```