
Analyzing NAEP/TIMSS Data with Direct Estimation using the R packages EdSurvey and Dire

Presenters: Paul Bailey, Ting Zhang, Michael Lee, & Sinan Yavuz

April 2022

Workshop Goal


Provide participants with an overview of the methods used to analyze national and international large-scale assessment data using the R package **EdSurvey** and **Dire**.

Outline of EdSurvey Workshop

1. Introduction to R, EdSurvey, and Dire
2. Data Processing and Data Manipulation
3. Hands-on practice
4. Descriptive statistics
5. Hands-on practice
6. Direct estimation with EdSurvey and Dire
7. Hands-on practice

Course Materials

Available here: 2022 NCME Training Content



The screenshot shows a GitHub repository page for '2022-NCME-EdSurvey-Training'. At the top, there's a breadcrumb trail: 'main' (with a dropdown arrow) followed by '2022-NCME-EdSurvey-Training / 2022-NCME-EdSurvey-Training.zip'. To the right are buttons for 'Go to file' and a three-dot menu. Below this, a commit summary shows a user profile icon for 'mikeleeco' with the message 'add initial training content'. To the right of the message, it says 'Latest commit 0f23fae 37 seconds ago' and a 'History' button with a clock icon. Underneath the commit message, it says '1 contributor' with a person icon. A red arrow points to the 'Download' button. Below the commit information, the file size '3.86 MB' is shown on the left, and the 'Download' button (with a download icon) and a trash icon are on the right. At the bottom, there's a link 'View raw' and a message: '(Sorry about that, but we can't show files that are this big right now.)'

main ▾ 2022-NCME-EdSurvey-Training / 2022-NCME-EdSurvey-Training.zip Go to file ...

mikeleeco add initial training content Latest commit 0f23fae 37 seconds ago History

1 contributor

3.86 MB Download

[View raw](#)
(Sorry about that, but we can't show files that are this big right now.)

Introduction to R, EdSurvey, and Dire

Why R?

1. **Free:** users can legally use and edit R package code
2. **Extensible:** large variety of contributed packages that expand its functionality
3. **Reproducible:** automated data analysis
4. **Designed by and for researchers:** robust ecosystem to translate data into analyses, visualizations, and summary reports with one software

Why EdSurvey?

1. **One-stop shop** for data downloading, processing, manipulation and analysis of survey data.
2. **Automated**: Weights and complex sampling design calculations are automated following standard OECD methodology.
3. **Simple**: e.g., a regression with 80 replicate weights requires only a few lines of code.
4. **Flexible**: You can use functions that rely on EdSurvey methods or get the data and use traditional R.
5. **Minimizes memory footprint** by only reading in required data.

Why Dire?

1. **Wow:** Assessments with the matrix booklet design require special considerations in data analysis, e.g., IRT and multiple imputation for item responses. **Dire** provides direct estimation functions that handles analyses of these assessment data properly.
2. **Efficient:** Students' latent proficiency distribution, as well as reporting group difference parameters, are estimated on the fly.
3. **Plausible Values Generation:** No need to rely on testing companies. Plausible values can be generated from the user-defined MML model and used for further analysis.
4. **Expanding Research Scope:** Providing the opportunity for researchers to link administrative data, aggregate data about a community from official statistics, or data from multiple surveys to open up new research questions.

Basic R Infrastructure



CRAN stores packages

Basic R Infrastructure



CRAN stores packages

Accessed via

```
install.packages("ggplot2")
```

**and loaded into R
on your machine**

```
library("ggplot2")
```



Basic R Infrastructure



CRAN stores packages

Accessed via

```
install.packages("ggplot2")
```

and loaded into R
on your machine

```
library("ggplot2")
```

**These package libraries
consist of functions**

```
ggplot()  
geom_point()  
...
```



Basic R Infrastructure



CRAN stores packages

Accessed via

```
install.packages("ggplot2")
```

and loaded into R
on your machine

```
library("ggplot2")
```




**These package libraries
consist of functions**

```
ggplot()  
geom_point()  
...
```

That can be used to analyze data

```
ggplot(mpg, aes(displ, hwy, colour = class)) +  
  geom_point()
```



Get to Know the R Environment

Follow Along - R Scripts

The screenshot shows the RStudio environment with three callout boxes highlighting key components:

- Script:** The editor window on the left contains an R script named "PISA Data Script.R". The script includes comments and code for installing the 'intsvy' package, setting the working directory, and importing data from a file named "PISA 2012".
- Console:** The console window at the bottom left shows the R version (3.1.2) and the R Foundation's copyright notice. It also displays the error message: "Error in tools::startDynamicHelp() : unable to create socket".
- Help and Plots windows:** The right-hand pane displays the "Global Environment" window, which lists installed packages and their versions. A table of installed packages is shown below.

Name	Description	Version
bitops	Bitwise Operations	1.0-6
boot	Bootstrap Functions (originally by Angelo Canty for S)	1.3-13
class	Functions for Classification	7.3-11
cluster	Cluster Analysis Extended Rousseeuw et al.	1.15.3
codetools	Code Analysis Tools for R	0.2-9
colorspace	Color Space Manipulation	1.2-4
compiler	The R Compiler Package	3.1.2
datasets	The R Datasets Package	3.1.2
devtools		1.6.1
dichromat		2.0-0
digest		0.6.8
evaluate		0.5.5
foreign		0.8-61
ggplot2		1.0.0
graphics		3.1.2
grDevices		3.1.2
grid		3.1.2
gtable	Arrange grobs in tables.	0.1.2
httr	Tools for Working with URLs and HTTP	0.6.1
intsvy	International Assessment Data Manager	1.6
jsonlite	A Robust, High Performance JSON Parser and Generator for R	0.9.14
KernSmooth	Functions for kernel smoothing for Wand & Jones (1995)	2.23-13
labeling	Axis Labeling	0.3

Follow along in [edsurvey_part1_Script.R](#)

Notes About Using R

- Highlight , **ctrl** + **enter** executes code to console
- Comment character is a hash

```
# this line is not executed
```

- Variables are assigned with an equals or **<-**

```
x <- 12
```

```
x
```

```
## [1] 12
```

- In file names on Windows use a forward slash
 - **C:/**
- R is case sensitive!

```
j <- 12
```

```
J
```

```
## Error in eval(expr, envir, enclos): object 'J' not found
```


Notes About Using R (cont)

- Any command can be input with a question mark preceding it to open the help guide

```
?mean
```

- Use the up arrow on your keyboard to copy your previous lines of code
- Try tab completion, type, "data" then hit the tab key

```
> data|
```



Using R Functions

- `c()` function combines values, separated by a comma, into a vector

```
colors <- c("red", "green", "blue")  
colors
```

```
## [1] "red" "green" "blue"
```

```
numbers <- c(1, 2, 3)  
numbers
```

```
## [1] 1 2 3
```

- In the **EdSurvey** package we'll use vectors to combine the names of variables in our analyses

Using R Functions

- Arguments can be explicitly or implicitly named


```
mean(x = numbers)
```

```
## [1] 2
```

```
mean(numbers)
```

```
## [1] 2
```

- Arguments are separated by commas



Installing the EdSurvey Package

- After opening up RStudio, run the following scripts in the console to download and initialize the **EdSurvey** package:

```
# to install the package  
install.packages("EdSurvey")
```

```
# to load the package  
library(EdSurvey)
```

Learning EdSurvey

- Reading vignettes provided in training materials

```
vignette("introduction", package="EdSurvey")
```

- R help

```
help(package = "EdSurvey")
```

- EdSurvey eBook
- EdSurvey Website
- EdSurvey Github
- NAEP Data Training workshop

Self-Reflection - R Functions

Ask yourself: What are the arguments of the function `readNAEP()`?
What are some examples of acceptable values for each argument?

Self-Reflection - R Functions

`readNAEP()` arguments, from R documentation (*type ?readNAEP in the console*)

Usage

```
readNAEP(path, defaultWeight = "origwt", defaultPvs = "composite",  
  omittedLevels = c("Multiple", NA, "Omitted"), frPath = NULL)
```

Arguments


<code>path</code>	a character value indicating the full filepath location and name of the (.dat) data file
<code>defaultWeight</code>	a character value that indicates the default weight specified in the resulting <code>edsurvey.data.frame</code> . Default value is <code>origwt</code> if not specified.
<code>defaultPvs</code>	a character value that indicates the default plausible value specified in the resulting <code>edsurvey.data.frame</code> . Default value is <code>composite</code> if not specified.
<code>omittedLevels</code>	a character vector indicating which factor levels/labels should be excluded. When set to the default value of <code>c('Multiple', NA, 'Omitted')</code> , adds the vector to the <code>edsurvey.data.frame</code> .
<code>frPath</code>	a character value indicating the location of the <code>fr2</code> parameter layout file included with the data companion to parse the specified filepath data file

Data Processing

Data Processing

- First, read in the publicly available NAEP data from **NAEPprimer**

```
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEP
```



- How long did that take?

Data Processing


- Can also read in other restricted-use NAEP data by naming the file location

```
math17 <- readNAEP("//path_to_directory/Data/M48NT2AT.dat")
```

- The first character indicates the subject - **M** (Math)
- The second and third characters indicate the NAEP year - **48** (2017 - 1969 = 48)
- The fourth character indicates the component - **N** (National)
- The fifth character indicates the type of data - **T** (Student)
- The sixth character indicates the grade cohort - **2** (8th)
- The seventh and eighth characters indicate the sample - **AT** (Main NAEP)

Data Processing

NOTE: the dat file requires its intact data folder directory in order to be read in correctly; containing both the student and school level files to merge data



Name	Date modified	Type	Size
AM	8/15/2016 10:39 A...	File folder	
Catalog	8/15/2016 10:39 A...	File folder	
Codebook	8/15/2016 10:39 A...	File folder	
Companion	8/15/2016 10:39 A...	File folder	
Data	8/15/2016 10:39 A...	File folder	
Examples	8/15/2016 10:39 A...	File folder	
NAEPEX	8/15/2016 10:39 A...	File folder	
SAS	8/15/2016 10:39 A...	File folder	
Select	8/15/2016 10:39 A...	File folder	
SPSS	8/15/2016 10:39 A...	File folder	
Stata	8/15/2016 10:39 A...	File folder	
ID	6/16/2016 10:11 A...	Text Document	1 KB

Meet Your Data

Quick Terminology Notes

The `edsurvey.data.frame` class stores information about survey data via a data connection, which allows for:

- Correct calculation of relevant statistics.
- Limited working memory usage.

SDF


The Edsurvey package uses the acronym **SDF** in the names of several functions to signify their relationship to **S**urvey **D**ata **F**rames.

Quick Terminology Notes

The `edsurvey.data.frame.list` class stores a list of `edsurvey.data.frame` objects.

- The list can be passed to the analysis functions, and a result list will be returned.
- A list can store both `cov` (covariants) and `labels` arguments. For example, the 'year' and 'country' might vary across the `edsurvey.data.frame`s in the list.
- `edsurvey.data.frame.lists` can also be constructed manually. See the `?edsurvey.data.frame.list` documentation.

One-stop Shop for NCES Survey Analysis



One-stop Shop for NCES Survey Analysis



Initialize your machine

- Install R and EdSurvey
- Download and read-in data

Example functions:

- `readTIMSS`
- `downloadTIMSS`

One-stop Shop for NCES Survey Analysis

01


Understand the data

- *Explore*: explore the codebook, see the variables with plausible values, see weights
- *Search*: search variables
- *Expand*: see variable levels, tabulate response percentages, see assessment scores by response category, summarize continuous variables

Example functions:

- `showCodebook`, `showPlausibleValues`, `showWeights`
- `searchSDF`, `levelsSDF`
- `summary2`, `edsurveyTable`

One-stop Shop for NCES Survey Analysis



In *EdSurvey*: Clean and manipulate data with built-in subset and recode features.

In *R*: Extract and manipulate data as a data frame (for experienced users)

Example functions:

- `subset`
- `rename.sdf`, `recode.sdf`
- `getData`, `rebindAttributes`

One-stop Shop for NCES Survey Analysis

03


Run analyses

- *Run analyses*: such as regression analysis, logit analysis, mixed models, show gaps, calculate achievement levels, correlate variables, calculate percentiles.

Example functions:

- `achievementLevels`, `percentile`
- `cor.sdf`
- `gap`
- `lm.sdf`, `glm.sdf`
- `mvr1m.sdf`, `mixed.sdf`

One-stop Shop for NCES Survey Analysis



- Related Documentation - [EdSurvey.pdf](#), Chap 3, EdSurvey Book

Meet Your Data - print

print()

- Print returns detailed data file information:

```
print(sdf)
```

```
## edsurvey.data.frame for 2005 NAEP (Mathematics) in USA
## Dimensions: 17606 rows and 302 columns.
##
## There is 1 full sample weight in this edsurvey.data.frame:
##   'origwt' with 62 JK replicate weights (the default).
##
##
## There are 6 subject scale(s) or subscale(s) in this edsurvey.data.frame:
## 'num_oper' subject scale or subscale with 5 plausible values.
##
## 'measurement' subject scale or subscale with 5 plausible values.
##
## 'geometry' subject scale or subscale with 5 plausible values.
##
## 'data_anal_prob' subject scale or subscale with 5 plausible values.
##
```

Meet Your Data - dim

`dim()`

- Returns the dimensions of the student data set:

```
dim(sdf)
```

```
## [1] 17606 302
```

Meet Your Data - colnames

colnames()

- Prints the names of all variables in the student and school data sets:

colnames(sdf)

```
## [1] "year" "cohort" "scrpsu" "dsex" "iep" "lep" "ell3" "sdracem" "pared" "b003501" "b003601" "b013801"
## [13] "b017001" "b017101" "b018101" "b018201" "b017451" "m815401" "m815501" "m815601" "m815801" "m815701" "rptsamp" "repgrp1"
## [25] "repgrp2" "jkunit" "origwt" "srwt01" "srwt02" "srwt03" "srwt04" "srwt05" "srwt06" "srwt07" "srwt08" "srwt09"
## [37] "srwt10" "srwt11" "srwt12" "srwt13" "srwt14" "srwt15" "srwt16" "srwt17" "srwt18" "srwt19" "srwt20" "srwt21"
## [49] "srwt22" "srwt23" "srwt24" "srwt25" "srwt26" "srwt27" "srwt28" "srwt29" "srwt30" "srwt31" "srwt32" "srwt33"
## [61] "srwt34" "srwt35" "srwt36" "srwt37" "srwt38" "srwt39" "srwt40" "srwt41" "srwt42" "srwt43" "srwt44" "srwt45"
## [73] "srwt46" "srwt47" "srwt48" "srwt49" "srwt50" "srwt51" "srwt52" "srwt53" "srwt54" "srwt55" "srwt56" "srwt57"
## [85] "srwt58" "srwt59" "srwt60" "srwt61" "srwt62" "smsrswt" "mrps11" "mrps12" "mrps13" "mrps14" "mrps15" "mrps21"
## [97] "mrps22" "mrps23" "mrps24" "mrps25" "mrps31" "mrps32" "mrps33" "mrps34" "mrps35" "mrps41" "mrps42" "mrps43"
## [109] "mrps44" "mrps45" "mrps51" "mrps52" "mrps53" "mrps54" "mrps55" "mrpcm1" "mrpcm2" "mrpcm3" "mrpcm4" "mrpcm5"
## [121] "m075201" "m075401" "m075601" "m019901" "m066201" "m047301" "m046201" "m066401" "m020101" "m067401" "m086101" "m047701"
## [133] "m067301" "m048001" "m093701" "m086001" "m051901" "m076001" "m046001" "m046101" "m067701" "m046701" "m046901" "m047201"
## [145] "m046601" "m046801" "m067801" "m066601" "m067201" "m068003" "m068005" "m068008" "m068007" "m068006" "m093601" "m053001"
## [157] "m047801" "m086301" "m085701" "m085901" "m085601" "m085501" "m085801" "m019701" "m020001" "m046301" "m047001" "m046501"
## [169] "m066501" "m047101" "m066301" "m067901" "m019601" "m051501" "m047901" "m053101" "m143601" "m143701" "m143801" "m143901"
## [181] "m144001" "m144101" "m144201" "m144301" "m144401" "m144501" "m144601" "m144701" "m144801" "m144901" "m145001" "m145101"
```

Meet Your Data - searchSDF

searchSDF() - Search the survey data frame by character strings

```
searchSDF("education", sdf)
```

```
##  variableName                      Labels
##  1      pared Parental education level (from 2 questions)
##  2      b003501                      Mother's education level
##  3      b003601                      Father's education level
##  4      c044007                      Percent in special education
```

- Add argument **levels = TRUE** to return variable levels.

```
searchSDF("b003501", sdf, levels = TRUE)
```

```
## Variable: b003501
## Label: Mother's education level
## Levels (Lowest level first):
##      1. Did not finish H.S.
##      2. Graduated H.S.
##      3. Some ed after H.S.
##      5. I don't know
```

- What occurs with an empty string?

```
searchSDF("", sdf)
```

Meet Your Data - levelsSDF

levelsSDF()

- Show the levels of a variable

```
levelsSDF("b018201", sdf)
```

```
## Levels for Variable 'b018201' (Lowest level first):  
##      1. Never (n = 9524)  
##      2. Once in a while (n = 3328)  
##      3. Half the time (n = 1178)  
##      4. All or most of time (n = 2133)  
##      8. Omitted* (n = 741)  
##      0. Multiple* (n = 11)  
##      NOTE: * indicates an omitted level.
```


Meet Your Data - showCodebook

showCodebook()

- Show the levels of a variable

```
showCodebook(sdf)
```

##	variableName	Labels
## 1	year	Assessment year
## 2	cohort	All students
## 3	scrpsu	Scrambled PSU and school code
## 4	dsex	Gender
## 5	iep	Student classified as having a disability (504)
## 6	lep	Student classified as ELL (2 categories)
## 7	ell3	Student classified Eng lang learner (3 categ)
## 8	sdracem	Race/ethnicity (from school records)
## 9	pared	Parental education level (from 2 questions)
## 10	b003501	Mother's education level
## 11	b003601	Father's education level
## 12	b013801	Books in home
## 13	b017001	Newspaper in home
## 14	b017101	Computer at home

- **View()** shows a preview of a selected data set

```
View(showCodebook(sdf))
```

Meet Your Data - showPlausibleValues

showPlausibleValues() - Prints all plausible values

```
showPlausibleValues(sdf)
```

```
## There are 6 subject scale(s) or subscale(s) in this edsurvey.data.frame:  
## 'num_oper' subject scale or subscale with 5 plausible values.  
##  
## 'measurement' subject scale or subscale with 5 plausible values.  
##  
## 'geometry' subject scale or subscale with 5 plausible values.  
##  
## 'data_anal_prob' subject scale or subscale with 5 plausible values.  
##  
## 'algebra' subject scale or subscale with 5 plausible values.  
##
```

- add **verbose = TRUE**

```
showPlausibleValues(sdf, verbose = TRUE)
```

```
## There are 6 subject scale(s) or subscale(s) in this edsurvey.data.frame:  
## 'num_oper' subject scale or subscale with 5 plausible values.  
## The plausible value variables are 'mrps11', 'mrps12', 'mrps13', 'mrps14', and 'mrps15'  
##  
## 'measurement' subject scale or subscale with 5 plausible values.  
## The plausible value variables are 'mrps21', 'mrps22', 'mrps23', 'mrps24', and 'mrps25'  
##
```

Meet Your Data - showWeights

showWeights() - Prints all weights:

```
showWeights(sdf)
```

```
## There is 1 full sample weight in this edsurvey.data.frame:  
## 'origwt' with 62 JK replicate weights (the default).
```

- add **verbose = TRUE** to print the complete list of jackknife replicate weights associated with each full sample weight.

```
showWeights(sdf, verbose = TRUE)
```

```
## There is 1 full sample weight in this edsurvey.data.frame:  
## 'origwt' with 62 JK replicate weights (the default).  
## Jackknife replicate weight variables associated with the full sample weight 'origwt':  
## 'srwt01', 'srwt02', 'srwt03', 'srwt04', 'srwt05', 'srwt06', 'srwt07', 'srwt08', 'srwt09', 'srwt10', 'srwt11',  
## 'srwt12', 'srwt13', 'srwt14', 'srwt15', 'srwt16', 'srwt17', 'srwt18', 'srwt19', 'srwt20', 'srwt21', 'srwt22',  
## 'srwt23', 'srwt24', 'srwt25', 'srwt26', 'srwt27', 'srwt28', 'srwt29', 'srwt30', 'srwt31', 'srwt32', 'srwt33',  
## 'srwt34', 'srwt35', 'srwt36', 'srwt37', 'srwt38', 'srwt39', 'srwt40', 'srwt41', 'srwt42', 'srwt43', 'srwt44',  
## 'srwt45', 'srwt46', 'srwt47', 'srwt48', 'srwt49', 'srwt50', 'srwt51', 'srwt52', 'srwt53', 'srwt54', 'srwt55',  
## 'srwt56', 'srwt57', 'srwt58', 'srwt59', 'srwt60', 'srwt61', and 'srwt62'
```

Meet Your Data - Omitted Levels

- Levels of the variables that will be omitted by default from the `edsurvey.data.frame`

```
> sdf
```

```
edsurvey.data.frame with 17606 rows and 302 columns.
```

```
There are 1 full sample weight(s) in this edsurvey.data.frame
```

```
  'origwt' with 62 JK replicate weights (the default).
```

```
There are 6 subject scale(s) or subscale(s) in this edsurvey.data.frame
```

```
  'num_oper' subject scale or subscale with 5 plausible values.
```

```
  'measurement' subject scale or subscale with 5 plausible values.
```

```
  'geometry' subject scale or subscale with 5 plausible values.
```

```
  'data_anal_prob' subject scale or subscale with 5 plausible values.
```

```
  'algebra' subject scale or subscale with 5 plausible values.
```

```
  'composite' subject scale or subscale with 5 plausible values (the default).
```

```
Omitted Levels: 'Multiple', 'NA', 'Omitted'
```

```
Default Conditions:
```

```
  tolower(rptsamp) == "reporting sample"
```

```
Achievement Levels:
```

```
  Basic:      262
```

```
  Proficient: 299
```

```
  Advanced:   333
```

```
Survey: NAEP
```

Meet Your Data - Default Conditions

- Special considerations for a particular `edsurvey.data.frame`

```
> sdf
```

```
edsurvey.data.frame with 17606 rows and 302 columns.
```

```
There are 1 full sample weight(s) in this edsurvey.data.frame  
'origwt' with 62 JK replicate weights (the default).
```

```
There are 6 subject scale(s) or subscale(s) in this edsurvey.data.frame  
'num_oper' subject scale or subscale with 5 plausible values.  
'measurement' subject scale or subscale with 5 plausible values.  
'geometry' subject scale or subscale with 5 plausible values.  
'data_anal_prob' subject scale or subscale with 5 plausible values.  
'algebra' subject scale or subscale with 5 plausible values.  
'composite' subject scale or subscale with 5 plausible values (the default).
```

```
Omitted Levels: 'Multiple', 'NA', 'Omitted'
```

```
Default Conditions:
```

```
  tolower(rptsamp) == "reporting sample"
```

```
Achievement Levels:
```

```
  Basic:    262
```

```
  Proficient: 299
```


```
  Advanced:  333
```

```
Survey: NAEP
```

Data Manipulation

EdSurvey Calls Network Connection

Small Memory Footprint



Data Manipulation - getData

getData(): reads in selected variables and sampling weights from the EdSurvey database and returns a **light.EdSurvey.data.frame** (a data frame like object) into the Global environment.

Functionality

- Retrieve variables by call.
- Manipulate the resulting **light.EdSurvey.data.frame**:
 - Subset.
 - Recode.
 - Drop levels.
- Use **EdSurvey** package functions on **light.EdSurvey.data.frames**.
- Related Documentation - [getData.pdf](#), Chap 9, EdSurvey Book

Data Manipulation - getData

getData()

```
gddat <- getData(sdf, varnames = c('dsex', 'sdracem', 'b018201', 'b017451',  
                                   'composite', 'geometry', 'origwt'),  
                addAttributes = TRUE, omittedLevels = FALSE)
```

NAEP mathematics composite scale scores of 8th grade students

- A vector of variable names, including **dsex** (Gender), **sdracem** (Race/ethnicity), **b018201** (Language other than English spoken in home) and **b017451** (Frequency of talk about studies at home)
- Overall math performance across subscales (**composite**) and five others associated with **geometry**
- The sampling weight for this dataframe: **origwt**

Data Manipulation - getData

Output:

```
# Note: head returns the first 6 rows of a data frame
```

```
head(gddat)
```

```
##      dsex sdracem      b018201      b017451 mrpcm1 mrpcm2 mrpcm3 mrpcm4 mrpcm5 mrps31 mrps32 mrps33 mrps34 mrps35
## 1  Male   White      Never      Every day 318.01 303.68 296.61 328.97 315.70 294.79 286.84 264.39 311.77 304.62
## 2 Female   White      Never  About once a week 288.43 283.93 280.45 290.03 286.23 277.26 266.43 261.98 286.23 264.76
## 3 Female   White      Never      Every day 342.72 338.03 329.48 352.46 342.26 354.18 320.11 331.88 354.47 365.00
## 4  Male   White      Never      Every day 348.76 321.79 327.87 333.35 327.32 326.91 302.79 321.28 333.43 318.45
## 6 Female   White Once in a while Once every few weeks 278.44 245.08 263.00 277.50 285.04 263.22 232.62 260.05 280.10 278.96
## 7  Male   White Once in a while  2 or 3 times a week 327.95 338.59 328.07 334.07 320.02 309.38 317.19 328.37 331.75 309.70
##      srwt01 srwt02 srwt03 srwt04 srwt05 srwt06 srwt07 srwt08 srwt09 srwt10 srwt11 srwt12 srwt13 srwt14 srwt15 srwt16 srwt17 srwt18
## 1 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004
## 2 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004
## 3 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004
## 4 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004
## 6 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004
## 7 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004
##      srwt19 srwt20 srwt21 srwt22 srwt23 srwt24 srwt25 srwt26 srwt27 srwt28 srwt29 srwt30 srwt31 srwt32 srwt33 srwt34 srwt35 srwt36
## 1 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 2.2008 1.1004 1.1004 1.1004 1.1004
## 2 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 2.2008 1.1004 1.1004 1.1004 1.1004
## 3 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 2.2008 1.1004 1.1004 1.1004 1.1004
## 4 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 1.1004 2.2008 1.1004 1.1004 1.1004 1.1004
```

Data Manipulation - getData

getData()

```
gddat <- getData(sdf, varnames = c('dsex', 'sdracem', 'b018201', 'b017451',  
                                   'composite', 'geometry', 'origwt'),  
                addAttributes = TRUE, omittedLevels = FALSE)
```

- A few important things to note:
 - "**addAttributes = TRUE**" allows the data.frame to be passed to **EdSurvey** package functions
 - all of the jackknife replicates are automatically returned (**srwt01** to **srwt62**)
 - "**omittedLevels = FALSE**" returns variables with special values (such as multiple entries or NA's) and manipulated by the user

Data Manipulation - subset

subset(): Returns only the data matching elements from a variable

- Subset the connection to the data for all analyses:

```
subsetSDF <- subset(sdf, dsex %in% c("Male"))
```

- As expected the **subsetSDF** contains about half of the rows as the original:

```
dim(sdf)
```

```
## [1] 17606 302
```

```
dim(subsetSDF)
```

```
## [1] 8905 302
```

Data Manipulation - recode.sdf

recode.sdf() is used to recode the levels of a variable

- collapse or rename values

```
sdf2 <- recode.sdf(sdf, recode =  
  list(b017451 = list(from = c("Never or hardly ever",  
    to = c("Infrequently")),  
    b017451 = list(from = c("Every day",  
    to = c("Frequently"))))  
)  
searchSDF("b017451", sdf2, levels = TRUE)
```

```
## Variable: b017451  
## Label: Talk about studies at home  
## Levels (Lowest level first):  
##      3. About once a week  
##      4. 2 or 3 times a week  
##      8. Omitted  
##      0. Multiple  
##      9. Infrequently  
##     10. Frequently
```

Data Manipulation - rename.sdf

rename.sdf() is used to rename variables

```
sdf2 <- rename.sdf(sdf2, oldnames = "b017451",  
                   newnames = "studytalkfrequency")  
searchSDF("studytalkfrequency", sdf2, levels = TRUE)
```

```
## Variable: studytalkfrequency  
## Label: Talk about studies at home  
## Levels (Lowest level first):  
##      3. About once a week  
##      4. 2 or 3 times a week  
##      8. Omitted  
##      0. Multiple  
##      9. Infrequently  
##     10. Frequently
```