HopeFOAM

(High Order Parallel Extensible CFD Software)

用户指南

版本 0.1

The Exercise Group

Innovation Institute for Defence Science and Technology, the Academy of Military Science (AMS), China. 2017年09月

Copyright © 2017-2017 The Exercise Group, Innovation Institute for Defence Science and Technology, the Academy of Military Science (AMS), China.

This work is licensed under a Creative Commons Attribution - NonCommercial NoDerivs 3.0 Unported License.

目录

Lic	ense	1
关	于 Ho	ppeFOAM7
1	可压炸	商涡流9
	1.1	网格生成9
	1.2	初始条件和边界条件10
	1.3	物理特性参数12
	1.4	离散方法和矩阵求解器设置12
	1.5	计算时间和控制13
	1.6	运行算例14
	1.7	后处理14
	1.8	收敛阶计算15
	1.9	并行计算15
2 3	双马赤	赤反射16
	2.1	网格生成
	2.2	初始条件和边界条件17
	2.3	运行算例
	2.4	后处理
3	不可足	医涡流21
	3.1	网格生成21
	3.2	初始条件和边界条件23
	3.3	物理特性参数23
	3.4	离散方法和矩阵求解器设置24
	3.5	运行算例24
	3.6	后处理
	3.7	收敛阶计算24
4	圆柱组	· 烧流
	4.1	曲面边界27
	4.2	初始条件和边界条件28
	4.3	物理特性参数29
	4.4	运行算例及后处理31

License

THE WORK (AS DEFINED BELOW) IS PROVIDED UNDER THE TERMS OF THIS CREATIVE COMMONS PUBLIC LICENSE ("CCPL" OR "LICENSE"). THE WORK IS PROTECTED BY COPYRIGHT AND/OR OTHER APPLICABLE LAW. ANY USE OF THE WORK OTHER THAN AS AUTHORIZED UNDER THIS LICENSE OR COPYRIGHT LAW IS PROHIBITED.

BY EXERCISING ANY RIGHTS TO THE WORK PROVIDED HERE, YOU ACCEPT AND AGREE TO BE BOUND BY THE TERMS OF THIS LICENSE. TO THE EXTENT THIS LICENSE MAY BE CONSIDERED TO BE A CONTRACT, THE LICENSOR GRANTS YOU THE RIGHTS CONTAINED HERE IN CONSIDERATION OF YOUR ACCEPTANCE OF SUCH TERMS AND CONDITIONS.

1. Definitions

- a. "Adaptation" means a work based upon the Work, or upon the Work and other pre-existing works, such as a translation, adaptation, derivative work, arrangement of music or other alterations of a literary or artistic work, or phonogram or performance and includes cinematographic adaptations or any other form in which the Work may be recast, transformed, or adapted including in any form recognizably derived from the original, except that a work that constitutes a Collection will not be considered an Adaptation for the purpose of this License. For the avoidance of doubt, where the Work is a musical work, performance or phonogram, the synchronization of the Work in timed-relation with a moving image ("synching") will be considered an Adaptation for the purpose of this License.
- b. "Collection" means a collection of literary or artistic works, such as encyclopedias and anthologies, or performances, phonograms or broadcasts, or other works or subject matter other than works listed in Section 1(f) below, which, by reason of the selection and arrangement of their contents, constitute intellectual creations, in which the Work is included in its entirety in unmodified form along with one or more other contributions, each constituting separate and independent works in themselves, which together are assembled into a collective whole. A work that constitutes a Collection will not be considered an Adaptation (as defined above) for the purposes of this License.
- c. **"Distribute"** means to make available to the public the original and copies of the Work through sale or other transfer of ownership.
- d. "Licensor" means the individual, individuals, entity or entities that offer(s) the Work under the terms of this License.
- e. "Original Author" means, in the case of a literary or artistic work, the individual, individuals, entity or entities who created the Work or if no individual or entity can be

- identified, the publisher; and in addition (i) in the case of a performance the actors, singers, musicians, dancers, and other persons who act, sing, deliver, declaim, play in, interpret or otherwise perform literary or artistic works or expressions of folklore; (ii) in the case of a phonogram the producer being the person or legal entity who first fixes the sounds of a performance or other sounds; and, (iii) in the case of broadcasts, the organization that transmits the broadcast.
- f. "Work" means the literary and/or artistic work offered under the terms of this License including without limitation any production in the literary, scientific and artistic domain, whatever may be the mode or form of its expression including digital form, such as a book, pamphlet and other writing; a lecture, address, sermon or other work of the same nature; a dramatic or dramatico-musical work; a choreographic work or entertainment in dumb show; a musical composition with or without words; a cinematographic work to which are assimilated works expressed by a process analogous to cinematography; a work of drawing, painting, architecture, sculpture, engraving or lithography; a photographic work to which are assimilated works expressed by a process analogous to photography; a work of applied art; an illustration, map, plan, sketch or three-dimensional work relative to geography, topography, architecture or science; a performance; a broadcast; a phonogram; a compilation of data to the extent it is protected as a copyrightable work; or a work performed by a variety or circus performer to the extent it is not otherwise considered a literary or artistic work.
- g. "You" means an individual or entity exercising rights under this License who has not previously violated the terms of this License with respect to the Work, or who has received express permission from the Licensor to exercise rights under this License despite a previous violation.
- h. "Publicly Perform" means to perform public recitations of the Work and to communicate to the public those public recitations, by any means or process, including by wire or wireless means or public digital performances; to make available to the public Works in such a way that members of the public may access these Works from a place and at a place individually chosen by them; to perform the Work to the public by any means or process and the communication to the public of the performances of the Work, including by public digital performance; to broadcast and rebroadcast the Work by any means including signs, sounds or images.
- i. "Reproduce" means to make copies of the Work by any means including without limitation by sound or visual recordings and the right of fixation and reproducing fixations of the Work, including storage of a protected performance or phonogram in digital form or other electronic medium.
- **2. Fair Dealing Rights.** Nothing in this License is intended to reduce, limit, or restrict any uses free from copyright or rights arising from limitations or exceptions that are provided for in connection with the copyright protection under copyright law or other applicable laws.

- **3. License Grant.** Subject to the terms and conditions of this License, Licensor hereby grants You a worldwide, royalty-free, non-exclusive, perpetual (for the duration of the applicable copyright) license to exercise the rights in the Work as stated below:
 - a. to Reproduce the Work, to incorporate the Work into one or more Collections, and to Reproduce the Work as incorporated in the Collections; and,
 - b. to Distribute and Publicly Perform the Work including as incorporated in Collections.

The above rights may be exercised in all media and formats whether now known or hereafter devised. The above rights include the right to make such modifications as are technically necessary to exercise the rights in other media and formats, but otherwise you have no rights to make Adaptations. Subject to 8(f), all rights not expressly granted by Licensor are hereby reserved, including but not limited to the rights set forth in Section 4(d).

- **4. Restrictions.** The license granted in Section 3 above is expressly made subject to and limited by the following restrictions:
 - a. You may Distribute or Publicly Perform the Work only under the terms of this License. You must include a copy of, or the Uniform Resource Identifier (URI) for, this License with every copy of the Work You Distribute or Publicly Perform. You may not offer or impose any terms on the Work that restrict the terms of this License or the ability of the recipient of the Work to exercise the rights granted to that recipient under the terms of the License. You may not sublicense the Work. You must keep intact all notices that refer to this License and to the disclaimer of warranties with every copy of the Work You Distribute or Publicly Perform. When You Distribute or Publicly Perform the Work, You may not impose any effective technological measures on the Work that restrict the ability of a recipient of the Work from You to exercise the rights granted to that recipient under the terms of the License. This Section 4(a) applies to the Work as incorporated in a Collection, but this does not require the Collection apart from the Work itself to be made subject to the terms of this License. If You create a Collection, upon notice from any Licensor You must, to the extent practicable, remove from the Collection any credit as required by Section 4(c), as requested.
 - b. You may not exercise any of the rights granted to You in Section 3 above in any manner that is primarily intended for or directed toward commercial advantage or private monetary compensation. The exchange of the Work for other copyrighted works by means of digital file-sharing or otherwise shall not be considered to be intended for or directed toward commercial advantage or private monetary compensation, provided there is no payment of any monetary compensation in connection with the exchange of copyrighted works.
 - c. If You Distribute, or Publicly Perform the Work or Collections, You must, unless a request has been made pursuant to Section 4(a), keep intact all copyright notices for the Work and provide, reasonable to the medium or means You are utilizing: (i) the name of the Original Author (or pseudonym, if applicable) if supplied, and/or if the Original Author and/or Licensor designate another party or parties (e.g., a sponsor

institute, publishing entity, journal) for attribution ("Attribution Parties") in Licensor's copyright notice, terms of service or by other reasonable means, the name of such party or parties; (ii) the title of the Work if supplied; (iii) to the extent reasonably practicable, the URI, if any, that Licensor specifies to be associated with the Work, unless such URI does not refer to the copyright notice or licensing information for the Work. The credit required by this Section 4(c) may be implemented in any reasonable manner; provided, however, that in the case of a Collection, at a minimum such credit will appear, if a credit for all contributing authors of Collection appears, then as part of these credits and in a manner at least as prominent as the credits for the other contributing authors. For the avoidance of doubt, You may only use the credit required by this Section for the purpose of attribution in the manner set out above and, by exercising Your rights under this License, You may not implicitly or explicitly assert or imply any connection with, sponsorship or endorsement by the Original Author, Licensor and/or Attribution Parties, as appropriate, of You or Your use of the Work, without the separate, express prior written permission of the Original Author, Licensor and/or Attribution Parties.

d. For the avoidance of doubt:

- i. Non-waivable Compulsory License Schemes. In those jurisdictions in which the right to collect royalties through any statutory or compulsory licensing scheme cannot be waived, the Licensor reserves the exclusive right to collect such royalties for any exercise by You of the rights granted under this License;
- ii. Waivable Compulsory License Schemes. In those jurisdictions in which the right to collect royalties through any statutory or compulsory licensing scheme can be waived, the Licensor reserves the exclusive right to collect such royalties for any exercise by You of the rights granted under this License if Your exercise of such rights is for a purpose or use which is otherwise than noncommercial as permitted under Section 4(b) and otherwise waives the right to collect royalties through any statutory or compulsory licensing scheme; and,
- iii. **Voluntary License Schemes**. The Licensor reserves the right to collect royalties, whether individually or, in the event that the Licensor is a member of a collecting society that administers voluntary licensing schemes, via that society, from any exercise by You of the rights granted under this License that is for a purpose or use which is otherwise than noncommercial as permitted under Section 4(b).
- e. Except as otherwise agreed in writing by the Licensor or as may be otherwise permitted by applicable law, if You Reproduce, Distribute or Publicly Perform the Work either by itself or as part of any Collections, You must not distort, mutilate, modify or take other derogatory action in relation to the Work which would be prejudicial to the Original Author's honor or reputation.

5. Representations, Warranties and Disclaimer

UNLESS OTHERWISE MUTUALLY AGREED BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTIBILITY, FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

6. Limitation on Liability. EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. Termination

- a. This License and the rights granted hereunder will terminate automatically upon any breach by You of the terms of this License. Individuals or entities who have received Collections from You under this License, however, will not have their licenses terminated provided such individuals or entities remain in full compliance with those licenses. Sections 1, 2, 5, 6, 7, and 8 will survive any termination of this License.
- b. Subject to the above terms and conditions, the license granted here is perpetual (for the duration of the applicable copyright in the Work). Notwithstanding the above, Licensor reserves the right to release the Work under different license terms or to stop distributing the Work at any time; provided, however that any such election will not serve to withdraw this License (or any other license that has been, or is required to be, granted under the terms of this License), and this License will continue in full force and effect unless terminated as stated above.

8. Miscellaneous

- a. Each time You Distribute or Publicly Perform the Work or a Collection, the Licensor offers to the recipient a license to the Work on the same terms and conditions as the license granted to You under this License.
- b. If any provision of this License is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this License, and without further action by the parties to this agreement, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.
- c. No term or provision of this License shall be deemed waived and no breach consented to unless such waiver or consent shall be in writing and signed by the party to be charged with such waiver or consent.

- d. This License constitutes the entire agreement between the parties with respect to the Work licensed here. There are no understandings, agreements or representations with respect to the Work not specified here. Licensor shall not be bound by any additional provisions that may appear in any communication from You. This License may not be modified without the mutual written agreement of the Licensor and You.
- e. The rights granted under, and the subject matter referenced, in this License were drafted utilizing the terminology of the Berne Convention for the Protection of Literary and Artistic Works (as amended on September 28, 1979), the Rome Convention of 1961, the WIPO Copyright Treaty of 1996, the WIPO Performances and Phonograms Treaty of 1996 and the Universal Copyright Convention (as revised on July 24, 1971). These rights and subject matter take effect in the relevant jurisdiction in which the License terms are sought to be enforced according to the corresponding provisions of the implementation of those treaty provisions in the applicable national law. If the standard suite of rights granted under applicable copyright law includes additional rights not granted under this License, such additional rights are deemed to be included in the License; this License is not intended to restrict the license of any rights under applicable law.

关于 HopeFOAM

HopeFOAM 是一款在 OpenFOAM 基础上扩展了任意高阶有限元等数值方法的计算力学软件,由中国军事科学院国防科技创新研究院 Exercise 小组开发。该小组致力于开发针对大规模科学与工程计算的开源软件。HopeFOAM 具有以下特点:

- **高阶(High Order)**: 在保留原有 OpenFOAM 有限体积离散方法之外,HopeFOAM 致力于融合更多高阶数值离散方法形成计算力学工具箱,其中 DGM (Discontinuous Galerkin Method,间断伽辽金方法)是第一个设计实现的高阶离散方法。
- **并行(Parallel)**: 为了改进并行计算的性能及可扩展性,HopeFOAM 集成了多种并行计算工具集或软件以加速离散和计算过程。
- **可扩展(Extensible):** 在引入了高阶数值离散与高效并行计算的基础上, HopeFOAM 将为使用者的进一步应用功能开发提供一个可扩展的软件框架及便 捷接口。
- **FOAM**: 此版 HopeFOAM 是基于 2016 年 6 月 OpenFOAM-4.0 进行大幅 扩展而成。

HopeFOAM-0.1 作为 HopeFOAM 的第一个公开发布版本,是基于OpenFOAM-4.0 大幅扩展而成。广为人知的高阶数值离散方法 DGM (Discontinuous Galerkin Method,间断伽辽金方法)被设计实现于HopeFOAM-0.x 系列中,关于该方法的相关知识可参考书籍:【Hesthaven J S, Warburton T. Nodal discontinuous Galerkin methods: algorithms, analysis, and applications[M]. Springer Science & Business Media, 2007.】

HopeFOAM-0.1 提供二维 DGM 离散及相关技术支持,主要包括数据结构、DGM 离散、求解器及相关工具,同时 PETSc 被集成用于求解线性方程系统。三维应用相关功能将在未来几个月的新版本中发布。

开发HopeFOAM-0.1的一个重要原则就是尽可能复用OpenFOAM-4.0的原始数据结构,并保持用户接口的一致性。因此,OpenFOAM 用户可基于以往经验通过较为直接的途径实现或使用对应高阶 DGM 求解器。同时,原有 OpenFOAM 支持的功能可以继续使用。

本手册作为 HopeFOAM-0.1 的使用指南,将通过 4 个案例教程指导读者练习 HopeFOAM-0.1 的基本使用方法。求解器源代码和执行命令位于案例目录下,所有算例均位于 tutorials/DG/2D 目录下。

1 可压熵涡流

本节介绍如何对二维可压缩无粘流体熵涡流问题算例进行前处理、运行和后处理。计算区域几何为 $0m \le x \le 10m$, $-5m \le y \le 5m$,如图 1.1 所示。




图 1.1 可压熵涡流几何

可压缩流体熵涡流问题的精确解为:

$$\begin{split} u &= u_0 - \beta e^{(1-r^2)} \, \frac{y - y_0}{2\pi}, \\ v &= v_0 + \beta e^{(1-r^2)} \, \frac{x - x_0 - t}{2\pi}, \\ \rho &= \left(1 - \left(\frac{\gamma - 1}{16\gamma\pi^2}\right) \beta^2 e^{2(1-r^2)}\right)^{\frac{1}{\gamma - 1}}, \\ p &= \rho^{\gamma}, \end{split}$$

其中 $r = \sqrt{(x - t - x_0)^2 + (y - y_0)^2}$, $x_0 = 5$, $y_0 = 0$, $u_0 = 1$, $v_0 = 0$, $\beta = 5$, $\gamma = 1.4$, 表示涡流从计算区域中心以 1 米每秒的速度向右移动。

1.1 网格生成

切换到算例目录 isentropic Vortex:

cd \$FOAM_RUN/tutorials/DG/2D/isentropicVortex

本算例几何外形为 xy 平面的正方形,正方形边界设置为 wall。HopeFOAM 支持结构网格和非结构网格,一方面,可以使用 OpenFOAM 提供的 blockMesh 工具,通过配置 system/blockMeshDict 文件以生成结构网格命令生成网格。system/blockMeshDict 文件边界条件信息如下:

40 boundary 41 (42 Wall 43 {

```
44
            type wall;
45
            faces
46
47
                (3762)
48
                (0473)
49
                (2651)
50
                (1540)
51
52
53
       frontAndBackPlanes
54
55
            type empty;
56
            faces
57
                (0321)
58
59
                (4567)
60
            );
61
       }
```

通过上述方法生成网格,仅需要直接执行如下命令:

\$ blockMesh

同时,HopeFOAM 也支持使用诸如 Gambit、Pointwise、Fluent ICEM 等第三方工具生成网格。在本案例下,我们提供了三套不同尺度的 Fluent 网格文件 vortex0256.msh,vortex1024.msh,vortex4096.msh,分别对应的特征尺度为 h,h/2,h/4,如图 1.2 所示。




图 1.2 不同特征尺度网格

网格在算例目录下使用如下命令生成:

\$ fluentMeshToFoam vortex0256.msh

用户可以查阅 OpenFOAM UserGuide 第五章详细了解网格相关内容。

1.2 初始条件和边界条件

HopeFOAM 中,诸如固定值、零梯度的简单边界条件可以通过配置场文件的 patch 类型指定。但是,isentropicVortex 算例的边界条件是通过用于表示解析解的复杂方程描述的。这里,我们将解析解编码在位于 dgEulerFoam 求解器目录的 setNonUniformInlet.H,setBoundaryValues.H 文件中。求解该问题的 Euler 方程可写成如下向量形式:

$$\frac{\partial \mathbf{q}}{\partial t} + \frac{\partial \mathbf{F}}{\partial x} + \frac{\partial \mathbf{G}}{\partial y} = 0$$

$$\mathbf{q} = \begin{pmatrix} \rho \\ \rho u \\ \rho v \\ E \end{pmatrix}, \quad \mathbf{F} = \begin{pmatrix} \rho u \\ \rho u^2 + p \\ \rho u v \\ u(E+p) \end{pmatrix}, \quad \mathbf{G} = \begin{pmatrix} \rho v \\ \rho u v \\ \rho v^2 + p \\ v(E+p) \end{pmatrix}$$

0 文件夹下包含 Ener,rho,rhoU,U,p 五个文件,上式中, ρ 为气体密度对应 rho 文件,(u,v) 为速度矢量的分量对应 U 文件, $(\rho u, \rho v)$ 动量矢量的分量对应于 rhoU 文件,p 为气体压力对应 p 文件,E 为气体能量对应 Ener 文件。其中 Ener,rho,rhoU 为原始变量,而 U 与 p 则通过如下方程导出:

$$E = \frac{p}{\gamma - 1} + \frac{\rho}{2} (u^2 + v^2)$$

边界和内部场的解析解可以通过上述方式给出,但 patch 的类型仍需明确。 针对标量场 rho, p, Ener, 它们的 internalField 内部场和 boundaryField 边界场 类型指定如下:

```
19 internalField
                  uniform 0:
21 boundaryField
22 {
       Wall
23
24
25
                               fixedValue;
             type
26
             value
                               uniform 0;
28
29
        frontAndBackPlanes
30
31
             type
                               empty;
32
33 }
```

矢量场 rhoU 和 U 的 internalField 内部场和 boundaryField 边界场类型指定为:

```
19 internalField
                   uniform (000);
21 boundaryField
22 {
23
        Wall
24
         {
25
                                fixedValue;
             type
26
                               uniform (0 0 0);
27
28
29
        frontAndBackPlanes
31
                  type
                                    empty;
32
33 }
```

需要注意的是,上述文件的有效信息仅是指定 patch 的类型,其值并没有什么意义(值其实是通过之前头文件的形式直接写在代码中的)。

1.3 物理特性参数

isentropicVortex 算例需要指定的物理特性参数为气体类型无量纲常数γ,储存在 constant/transportProperties 字典文件,关键词为 gamma,如下所示:

1.4 离散方法和矩阵求解器设置

用户在 system 目录下的 dgScheme 文件中指定 DG 的离散格式,通量方法和限制器。与 OpenFOAM 类似, HopeFOAM 也支持 default 参数设置。这里,条目 godunovScheme 是用于对可压 NS 模拟设置通量与限制器的:

```
18 ddtSchemes
19 {
2.0
      default
                         Euler;
21 }
22
23 gradSchemes
24 {
                 default none;
default none;
25
      default
26
      grad(p)
      grad(gther_p)
27
                        default none;
28 }
29
30 godunovScheme
31 {
32
      fluxScheme
                        Roe;
33
      limiteScheme
                         Triangle;
34 }
```

dgSolution 文件指定逼近阶、残差以及其它算法控制。DG 子字典 meshDimension 网格维度设置为 2, baseOrder 逼近阶设置范围为 1-8。为测试高阶方法的高精度, solver 子字典的误差 tolerance 设置为 1e-12。

```
17 DG
18 {
19
      meshDimension
                          2;
20
      baseOrder
                          4;
21 }
23 solvers
24 {
25
      dgrho
26
27
          tolerance
                         1e-12;
28
          relTol
                         0;
```

```
29
       kspSolver
                   preonly;
30
31
32
    rhoU
33
     {
34
                   1e-12;
       tolerance
35
       relTol
       kspSolver preonly;
    }
37
38
39
    Ener
40
    {
41
       tolerance
                   1e-12;
42
       relTol
                  0;
43
       kspSolver
                   preonly;
44
45
46
    "rho(1 | 2 | 3)"
47
     {
                   1e-12;
48
       tolerance
49
       relTol
50
       kspSolver
                   preonly;
51
    "rhoU(1|2|3)"
53
54
                0;
55
       tolerance
                   1e-12;
56
       relTol
       kspSolver preonly;
57
58
59
60
     "Ener(1|2|3)"
61
                   1e-12;
62
       tolerance
63
       relTol
                  0;
       kspSolver
64
                   preonly;
65
     }
66 }
67
68 PISO
69 {
70
    nCorrectors
                2;
71
    nNonOrthogonalCorrectors 0;
72
            0;
    pRefCell
    pRefValue
73
                 0;
74 }
75
```

1.5 计算时间和控制

在 system 目录下 ControlDict 文件对时间步,输入输出时间进行控制。算例运算结束时,我们希望涡流没有穿过计算域,endtime 应小于 5s,我们设置结束时间为 2s。时间步长 deltaT 与网格大小和逼近阶有关,计算方法参考《Nodal Discontinuous Galerkin Methods Algorithms Analysis and Applications》6.4节内容。

表 1 1	不同网枚7	不同语诉除	deltaT 设置
1X 1.1	- /[Y]中[]/Y]/紹子/	17月7年7月17日	uenar ix =

baseOrder	vortex0256	vortex1024	vortex4096	
1	0.04	0.02	0.01	
2	0.02	0.01	0.005	
3	0.008	0.004	0.002	
4	0.008	0.004	0.002	
5	0.004	0.002	0.001	
6	0.002	0.001	0.0005	

1.6 运行算例

如同 OpenFOAM 程序一样,HopeFOAM-0.1 提供前置进程的方法运行求解器。

\$./dgEulerFoamVortex

由于求解器源代码文件夹和执行命令都位于算例目录,它们不能重名,同时针对 isentropic Vortex 算例修改了部分求解器代码,因此我们在标准执行命令后添加后 缀 Vortex。

1.7 后处理

我们选择 vortex1024.msh 网格, baseOrder=4 案例进行计算。在结果写入时间步文件以后,使用命令

\$ dgToVTK

生成 VTK 文件夹(HopeFOAM 支持高阶后处理),使用 ParaView 软件进行后处理。file>Open...选择生成的.vtk 文件,点击 OK。Properties 栏下点击 apply,选择Coloring 下拉选框为 rho,rhoU,Ener 查看云图。




图 1.3 isentropicVortex 算例密度云图

更多使用方法参考 OpenFOAM UserGuide 第二章相关内容。

1.8 收敛阶计算

我们通过 eulererror.H 文件计算数值解精度。算例运行结束时,输出密度和 动量数值解与精确解的误差:

rhoError: 8.807979526797244e-06

rhoUError: 1.865574862711117e-05

用户可以通过网格逐步加密实现相同逼近阶下收敛阶的计算。计算公式为:

$$\log_2(\frac{\mathcal{E}_h}{\mathcal{E}_{h/2}})$$

 \mathcal{E}_h 为特征尺度为 h 的密度或动量误差。

1.9 并行计算

针对计算量较大的问题, HopeFOAM 支持并行处理。与 OpenFOAM 提供 decomposePar 工具类似, 首先配置 decomposeParDict 字典文件。 numberOfSubdomains 指定计算区域划分的数量,通常等于处理器数量。 simpleCoeffs 子字典中的向量 n 指定计算区域在 x, y, z 方向子区域的数量。保 证 $n_x \times n_y \times n_z = \text{numberOfSubdomains}$ 。本算例几何为二维, $n_z = 1$ 。

26 numberOfSubdomains 12; 28 method simple;

30 simpleCoeffs

31 { 32 (3 4 1);

delta 33 0.001;

34 }

运行命令,将计算区域划分为 12 个子区域,算例目录生成 processor0 等 12 个文件。

\$ dqDecomposePar

通过以下命令实现并行计算。

\$ mpirun -np 12 ./dgEulerFoamVortex -parallel 计算完成之后通过以下命名将分割的场和网格合并:

\$ dgReconstructPar

2 双马赫反射

双马赫反射与可压熵涡流使用同一求解器,类似地,我们修改了文件 setNonUniformInlet.H, setBoundaryValues.H 和 eulererror.H 文件。注意:进行双马赫反射模拟时器,dgEulerFoam/dgEulerFoam.C 文件中第 91 行和 118 行的注释符"//"被删除了,从而激活限制器。针对激波类问题模拟,为了模拟的稳定性,限制器是必不可少的。

91 Godunov.limite(rho1,rhoU1,Ener1);
118 Godunov.limite(rho,rhoU,Ener);

保存文件, 重新编译求解器。

\$ wclean

\$ wmake

修改后的 dgEulerFoam 求解器文件夹保存在 doubleMach 算例目录下。

双马赫反射如图 2.1 所示,马赫数为 10 的激波向反射平面运动,激波与平面成 60 度夹角。计算区域几何为 $0 \le x \le 3.2$, $0 \le y \le 1$,如图 2.2 所示。气体类型无量纲常数 y=1.4。初始时刻,马赫数为 10 的激波由 (0.16667,0),(0.74402,1) 两点连成的虚线表示。未扰动的气体(激波右侧) $\rho=1.4$,p=1。 y=0的 inlet和 wall 边界为固定边界, $0 \le x \le 0.16667$ 的区域允许激波传播离开计算区域,wall即为反射平面。y=1的上部边界与时间有关,inlet边界和 far 边界的交点向右移动,用来描述激波传播进入计算区域。当模拟时间等于 0.2 时,激波传播到计算区域的 outlet 边界附近。




图 2.1 双马赫反射示意图




图 2.2 双马赫反射几何与边界设置

2.1 网格生成

我们在算例目录下提供 doubleMach.msh 网格文件,在算例目录使用如下命令生成网格:

\$ fluentMeshToFoam doubleMach.msh

2.2 初始条件和边界条件

与 1.2 节所介绍情况类似, doubleMach 算例把初始条件和移动边界条件通过 setNonUniformInlet.H, setBoundaryValues.H 写入求解器 dgEulerFoam。0 文件夹下标量场 rho, p, Ener 的 internalField 内部场和 boundaryField 边界场统一指定为:

```
19 internalField
                   uniform 0;
21 boundaryField
22 {
23
         wall
24
25
                                reflective;
             type
26
             value
                                uniform 0;
27
         }
28
29
        far
30
         {
31
                                fixedValue;
             type
32
                                uniform 0;
             value
33
         }
34
35
        inlet
36
                                fixedValue;
37
             type
                                uniform 0;
38
             value
39
         }
40
41
        outlet
42
                                fixedValue;
43
             type
44
                                uniform 0;
             value
```

矢量场 rhoU,U 的 internalField 内部场和 boundaryField 边界场统一指定为:

```
19 internalField
                   uniform (000);
21 boundaryField
22 {
23
        wall
24
25
                                reflective;
             type
26
             value
                                uniform (0 0 0);
27
        }
28
29
        far
30
31
                                fixedValue:
             type
32
             value
                                uniform (0\ 0\ 0);
33
        }
34
35
        inlet
36
        {
37
                                fixedValue;
             type
38
                                uniform (0 0 0);
             value
39
40
41
        outlet
42
        {
43
                                fixedValue;
             type
44
                                uniform (0 0 0);
             value
45
46
47
        frontAndBackPlanes
48
49
                                empty;
50
```

注意 wall 的边界条件设置为反射边界条件 reflective。

2.3 运行算例

本算例 transportProperties 和 dgScheme 与 isentropicVortex 算例一致。 dgSolution 的子字典 DG 的关键字逼近阶 baseOrder 设置为 1。我们设置 ControlDict 文件中结束时间 endtime 为 0.2,时间步 deltaT 为 1e-5。

由于算例网格数量较多,我们建议采用并行计算。配置 decomposeParDict 参考 1.9 节。

划分计算区域:

\$ dgDecomposePar

并行计算:


\$ mpirun -np 12 ./dgEulerFoamDouble -parallel


合并场和网格:

\$ dgReconstructPar

2.4 后处理

使用命令 dgToVTK 生成 VTK 文件夹,打开 ParaView 软件,file>Open...选择生成的.vtk 文件。Coloring 下拉选框为 rho 查看云图。点击 VCR controls 面板 play 查看不同时刻 rho 变化。





t = 0.2

图 2.3 doubleMach 算例密度云图

激波问题需要使用限制器使计算稳定,当前版本的限制器为一阶限制器,不适用于高阶计算。我们提供加密网格 doubleMachDense.msh。计算更精细的流场。

3 不可压涡流

本算例为利用不可压涡流问题讲解不可压二维 Navier-Stokes 方程层流 dgChorinFoam 求解器的前处理,运行和后处理。计算区域几何如图 3.1 所示,有 4 个流入与 4 个流出边界。 $-0.5m \le x \le 0.5m$, $-0.5m \le y \le 0.5m$ 。




图 3.1 不可压涡流几何

3.1 网格生成

切换到算例目录 pearsonVortex,整个区域分为 4 个 block, xy 平面的 Block 结构如图 3.2 所示。用户可打开算例录下 system/blockMeshDict 文件查看。

0(9)	2(12)	6 (15)	
1(10)	4(13)	7 (16)	
2(11)	5 (14)	8(17)	

图 3.2 pearsonVortex 算例 block 结构

```
17 convertToMeters 1;
18
19 vertices
20 (
21
         (-0.5\ 0.5\ 0)
22
         (-0.5\ 0\ 0)
23
         (-0.5 -0.5 0)
24
         (0.50)
25
         (0\ 0\ 0)
26
         (0 - 0.5 0)
27
         (0.5\ 0.5\ 0)
         (0.5\ 0\ 0)
29
         (0.5 - 0.5 0)
         (-0.5\ 0.5\ 0.1)
```

```
31
        (-0.5\ 0\ 0.1)
32
        (-0.5 - 0.5 0.1)
33
        (0.0.50.1)
34
        (0\ 0\ 0.1)
35
        (0 - 0.5 \ 0.1)
36
        (0.5\ 0.5\ 0.1)
37
        (0.5\ 0\ 0.1)
38
        (0.5 -0.5 0.1)
39);
40
41 blocks
42 (
43
        hex (0 1 4 3 9 10 13 12) (8 8 1) simpleGrading (1 1 1)
        hex (1 2 5 4 10 11 14 13) (8 8 1) simpleGrading (1 1 1)
44
45
        hex (3 4 7 6 12 13 16 15) (8 8 1) simpleGrading (1 1 1)
46
        hex (4 5 8 7 13 14 17 16) (8 8 1) simpleGrading (1 1 1)
47);
48
49 edges
50 (
51);
52
53 boundary
54 (
55
        inlet
56
57
             type wall;
58
             faces
59
60
                  (2 11 10 1)
61
                  (8 17 14 5)
62
                  (6 15 16 7)
63
                  (0 9 12 3)
64
             );
65
        }
        outlet
66
67
         {
68
             type wall;
69
             faces
70
71
                  (1\ 10\ 9\ 0)
72
                  (5 14 11 2)
73
                  (7 16 17 8)
74
                  (3 12 15 6)
75
             );
76
77
        frontAndBackPlanes
78
79
             type empty;
80
             faces
81
82
                  (1034)
                  (10 13 12 9)
83
84
                  (2145)
85
                  (11 14 13 10)
86
                  (5478)
87
                  (14 17 16 13)
88
                  (4367)
                  (13 16 15 12)
89
90
             );
91
         }
92);
94 mergePatchPairs
95 (
96);
```

输入如下命令生成网格: \$ blockMesh

3.2 初始条件和边界条件

与第 1.2 节类似,pearsonVortex 算例利用精确解设置速度和压力边界条件。 通 过 头 文 件 setNonUniformInlet.H , setBoundaryValues.H 写 入 求 解 器 dgChorinFoam。

$$u = -\sin(2\pi y)e^{-\nu 4\pi t},$$

$$v = \sin(2\pi x)e^{-\nu 4\pi t},$$

$$p = -\cos(2\pi x)\cos(2\pi y)e^{-\nu 8\pi t}.$$

0 文件夹下 U 内部初始场和入口速度统一设置为 (0 0 0)。速度出口为 Neumann 边界条件,设置 outlet 边界的梯度值为 (110)。

```
19 internalField
                  uniform (0 0 0);
21 boundaryField
22 {
23
        inlet
24
25
                               fixedValue;
             type
                               uniform (0 0 0);
26
27
        }
28
29
        outlet
30
31
             type
                               fixedGradient;
32
             gradient
                              uniform (1 1 0);
33
34
35
        frontAndBackPlanes
36
37
             type
                               empty;
38
39 }
```

p 文件设置入口压力的边界条件为 zeroGradient,出口压力的边界条件设置为 fixedValue 0。

3.3 物理特性参数

pearsonVortex 算例需要指定的物理参数为运动粘度,储存在字典文件 transportProperties 中,输运模型选择牛顿流体 Newtonian,运动粘度关键词为 nu,本算例设置为 0.01。

```
17 transportModel Newtonian;
18 nu nu [ 0 2 -1 0 0 0 0 ] 0.01;
```

3.4 离散方法和矩阵求解器设置

system 目录下的 dgScheme 文件中离散格式和通量方法采用默认设置。 dgSolution 文件设置与 isentropicVortex 案例类似, DG 子字典中 baseOrder 逼近阶 设置范围为 1-8。

3.5 运行算例

逼近阶 baseOrder 设置为 2,ControlDict 文件关键词 endtime 为 0.1,deltaT 为 0.001,运行算例:

\$./dgChorinFoamVortex

3.6 后处理

使用命令 dgToVTK 生成 VTK 文件以后,使用 paraView 查看矢量图。1、pearsonVortex_*文件前眼睛图标活跃,选择 filter>Alphabetical>cell centers,单击 Apply。2、cell center 文件前眼睛图标活跃,选择 filter>Alphabetical>Glyph,单击 Apply。3、进行设置: Glyph Source 选择 Arror,Vectors 选择 U,scale Mode 中选 OFF,Coloring 选择 U,单击 Apply。




图 3.3 pearsonVortex 速度矢量图

3.7 收敛阶计算

与 isentropic Vortex 算例类似,我们给出三套网格及其在不同逼近阶下 deltaT 的参考值来计算收敛阶。deltaT 与特征尺度 h 成正比关系。算例运行结束以后,可获得计算误差。

表 3.1 不同网格不同逼近阶 deltaT 设置

baseOrder	vortexh	vortex0.5h	vortex0.25h
1	0.002500000	0.001250000	0.000625000
2	0.001100000	0.000555560	0.000285710
3	0.000625000	0.000322580	0.000161290
4	0.000400000	0.000204080	0.000103090
5	0.000285710	0.000142860	0.000071429
6	0.000208330	0.000105260	0.000052632

4 圆柱绕流

瞬态圆柱绕流和不可压涡流采用同一求解器,但是为配置圆柱绕流算例,我们修改 pCorrectEquation.H、setNonUniformInlet.H、setparaT.H、pEqnCorrect.H 和 setBoundaryValues.H 文件。同时在 dgChorinFoam.C 文件中的修改如下:

- 添加文件 createTimeControls.H
- 45 #include "createTimeControls.H"
- 每一时间步中参数设置
- paraT4 = std::sin(pi*runTime.value()/8)/paraT3;
- 71 paraT3 = std::sin(pi*runTime.value()/8);
- paraT3 修改为 paraT1
- shared_ptr<dg::Equation<scalar>> result1 =

make_shared<bCorrectEquation<scalar>>(dgm::lap lacian(p), paraT1);

● 注释误差求解

116 // #include "chorinerror.H"

保存文件, 重新编译求解器。

- \$ wclean
- \$ wmake

生产的 dgChorinFoam 求解器二进制文件保存在 cylinder 算例目录下。

瞬态圆柱绕流是依赖时间的二维管道流,在管道中间有一圆柱,圆柱位置偏离管道中心线。当流入速度由 0 逐渐形成抛物型流时,逐步形成涡流。算例的计算几何区域如图 4.1 所示。圆柱圆心位于原点(0,0),半径为 0.05。




图 4.1 圆柱绕流几何与边界设置

t=0时流体速度为零,流入边界假设为抛物型流乘以时间正弦函数,模拟持续 8s。

$$u(x, y,t) = 0.41^{-2} \sin(\frac{\pi t}{8})6(y+0.2)(0.21-y),$$

$$v(x, y,t) = 0.$$

4.1 曲面边界

HopeFOAM 中引入了类 arcPolyPatch 以支持高阶曲面边界表示。曲面边界相关配置位于 constant/polyMesh/ boundary 文件中,下面以 upcylinder 为例讲解曲面边界配置: 圆柱边界类型 type 选择圆弧 arc, name 指定曲面边界名称; 重点通过 code#{ #}内的弧形三维表达式分别描述参数 u,v 与圆弧的 x,y,z 坐标的关系,u_Range 指定参数 u 的取值范围为-0.5 到 0.5, v_Range 同理。

```
19 (
20
        channel
21
22
                                wall;
             type
23
                                1(wall);
             inGroups
24
             nFaces
                                128;
25
             startFace
                               2666;
26
27
        outlet
28
29
                                patch;
             type
30
             inGroups
                                1(wall);
31
             nFaces
                                12;
32
             startFace
                              2794;
33
34
        inlet
35
36
                                patch;
             type
37
             inGroups
                                1(wall);
38
             nFaces
                                16;
39
             startFace
                               2806;
40
41
        upcylinder
42
43
                                arc;
             type
44
             inGroups
                                1(wall);
45
             nFaces
                                16;
46
             startFace
                               2822;
47
             name
                                 codeup;
48
                                 (-0.5\ 0.5);
             u_Range
49
             v_Range
                                 (0\ 0);
50
             code
51
             #{
52
                      0.05*Foam::sin(Foam::constant::mathematical::pi*u),
53
                      0.05*Foam::cos(Foam::constant::mathematical::pi*u),
54
55
             #};
56
57
        downcylinder
58
59
             type
                                arc;
60
             inGroups
                                1(wall);
61
             nFaces
                                16;
                               2838;
62
             startFace
63
             name
                                 codedown;
```

```
(-0.5\ 0.5);
64
            u_Range
65
            v_Range
                                (0\ 0);
66
            code
67
            #{
68
                      0.05*Foam::sin(Foam::constant::mathematical::pi*u),
69
                     -0.05*Foam::cos(Foam::constant::mathematical::pi*u),
70
                      v
            #};
71
72
73
74
        frontAndBackPlanes
75
76
            type
                               empty;
77
                               1(empty);
            inGroups
78
            nFaces
                               3680;
79
            startFace
                             2854;
80
81)
```

4.2 初始条件和边界条件

流入边界 inlet 速度场和压力场由相关文件设定,流出边界 outlet 速度设置为 zeroGradient。圆柱和管道固定壁面使用无滑移边界条件 fixedValue:

```
21 boundaryField
22 {
23
        inlet
24
         {
                                fixedValue;
25
             type
26
                               uniform (0 0 0);
             value
27
        }
28
29
        outlet
30
31
             type
                               zeroGradient;
32
33
34
        channel
35
36
                                fixedValue;
             type
37
                               uniform (0 0 0);
             value
38
39
40
        upcylinder
41
42
                                fixedValue;
             type
43
                               uniform (0 0 0);
             value
44
        }
45
46
        downcylinder
47
48
                                fixedValue;
             type
49
                               uniform (0 0 0);
             value
50
        }
51
52
        frontAndBackPlanes
53
54
                               empty;
             type
55
56 }
```

壁面的压力法相梯度为0,压力边界条件设置为zeroGradient,流出边界zeroGradient,流出边界zeroGradient,流出边界zeroGradient,流出边界zeroGradient

```
21 boundaryField
23
        inlet
24
25
                               zeroGradient;
             type
26
28
        outlet
29
30
             type
                               fixedValue;
31
                               uniform 0;
32
33
        channel
35
36
                               zeroGradient;
             type
37
38
39
        upcylinder
41
             type
                               zeroGradient;
42
43
44
        downcylinder
45
                               zeroGradient:
46
             type
47
48
49
        frontAndBackPlanes
50
51
             type
                               empty;
52
53 }
```

4.3 物理特性参数

使流体的雷诺数 $Re \approx 100$,在 constant/ transportProperties 文件中设置粘性系数 nu $\nu=10^{-3}$ 。

dgSolution 的子字典 DG 的关键字逼近阶 baseOrder 设置为 3。

圆柱绕流问题不存在精确解,定义圆柱的阻力与升力系数为圆柱体上总力在 水平和垂直方向的分量,由公式给出:

$$C_{d}(t) = -\oint_{Cylinder} -p\hat{n}_{x} + v(\hat{n}_{x} 2 \frac{\partial u}{\partial x} + \hat{n}_{y} (\frac{\partial v}{\partial x} + \frac{\partial u}{\partial y})) ds,$$

$$C_{l}(t) = -\oint_{Cylinder} -p\hat{n}_{y} + v(\hat{n}_{y} 2 \frac{\partial v}{\partial y} + \hat{n}_{x} (\frac{\partial u}{\partial y} + \frac{\partial v}{\partial x})) ds,$$

其中 (\hat{n}_x, \hat{n}_y) 为圆柱表面外法向量。ControlDict 文件中结束时间 endtime 为 8,时间步 deltaT 为 2e-4,添加 forceCoeffs 计算升力、阻力系数功能。

```
18 application
                   dgChorinFoam;
20 startFrom
                    startTime;
21
22 startTime
                    0;
                     endTime;
24 stopAt
25
26 endTime
                     8;
27
28 deltaT
                    2.0E-04;
30 writeControl
                   timeStep;
32 writeInterval
34 purgeWrite
                    0;
35
36 writeFormat
                    ascii;
37
38 writePrecision 6;
40 writeCompression off;
41
42 timeFormat
                     general;
43
44 timePrecision
46 runTimeModifiable false;
48 adjustTimeStep no;
49
50 maxCo
                      0.9;
51
52 maxDeltaT
                     0.01;
53
54
    functions
55
       #include "forceCoeffs"
56
57
```

forceCoeffs 文件 rhoInf 设置密度参考值,magUInf 设置速度参考值,liftDir 和 dragDir 分别设置升力和阻力方向。pitchAxis 指定力矩参考轴。outputInterval 设置计算时间步。

```
11
        type dgForceCoeffs;
        functionObjectLibs ("libdgforces.so");
12
13
        patches (upcylinder downcylinder);
        log true;
14
15
        pName p;
16
        Uname U;
        rho rhoInf;
17
        rhoInf 1;
18
        magUInf 1;
19
20
        liftDir (0 1 0);
        dragDir (1 0 0);
21
        pitchAxis (0 0 -1);
23
        CofR (0 0 0);
        Aref 0.1; //2D example default height of the grid is 1
24
25
        lRef 1;
26
        outputControl
                         timeStep;
27
        outputInterval 1;
```

4.4 运行算例及后处理

当前曲面边界不支持并行计算,在 cylinder 算例目录下串行计算: \$./dgChorinFoamCylinder

使用 Paraview 软件查看速度云图。




图 4.2 cylinder 算例速度云图

系数保存在 postProcessing/forceCoeffs/0/目录下的 .dat 文件中。

dgForce coefficients

liftDir : (0.000000e+00 1.000000e+00 0.000000e+00) # dragDir : (1.000000e+00 0.000000e+00 0.000000e+00)

pitchAxis : (0.000000e+00 0.000000e+00 -1.000000e+00)
magUInf : 1.000000e+00
IRef : 1.000000e+00
Aref : 1.000000e-01
CofR : (0.000000e+00 0.000000e+00 0.000000e+00)

# Time	Cm	Cd	Cl	Cl(f)	Cl(r)
0.0002	3.304978e-08	-1.063947e+00	9.374337e-02	4.687172e-02	4.687165e-02
0.0004	-2.644742e-06	6.580886e+01	-2.782665e-01	-1.391359e-01	-1.391306e-01
0.0006	-1.471373e-06	-9.094215e+01	1.099570e-01	5.497701e-02	5.497995e-02
0.0008	6.263473e-06	-8.928743e+00	6.684385e-02	3.342819e-02	3.341566e-02
0.001	2.419367e-06	2.894768e+01	-1.229158e-02	-6.143369e-03	-6.148207e-03
0.0012	-3.171261e-06	1.875261e+01	-4.258361e-02	-2.129498e-02	-2.128864e-02
0.0014	-3.142487e-06	-1.222173e+00	-6.661137e-03	-3.333711e-03	-3.327426e-03
0.0016	-3.236623e-07	-7.782365e+00	3.629908e-02	1.814922e-02	1.814986e-02
0.0018	1.215003e-06	-4.201885e+00	1.098737e-02	5.494901e-03	5.492471e-03

Cm 为力矩系数, Cd 为阻力系数, Cl 为升力系数。