## Quiz Microprocessor

Total points 1

				n
1	$\cap$	/1	$\cap$	
Ц	U,	/ I	U	



Solve all Questions

Email address \*
ameythakur@ternaengg.ac.in

Class: TEC B DIV

X Name of Student \*

AMEY THAKUR

X

Correct answer

**Correct Answer** 

Roll No \*

50

- ✓ 1. The \_\_\_\_\_ is a general-purpose programmable I/O device designed to 1/1 transfer the data from I/O to interrupt I/O.
- A. 8285A
- B. 8241A
- C. 8255A
- D. 8251A

2. How many ports 8255A have?	1/1
A. 2	
■ B. 3	<b>✓</b>
O C. 4	
O D. 5	
✓ 3. Which port can be split into two parts?	1/1
A. PORT A	
O B. PORT B	
C. PORT C	<b>✓</b>
O. PORT D	
4. Which of the following are Features of 8255A? *	1/1
A. It consists of 3 8-bit IO ports i.e. PA, PB, and PC.	
B. Address/data bus must be externally demux'd.	
C. It is TTL compatible.	
D. All of the above	<b>✓</b>

5. Which of the following is responsible for controlling the internal/external transfer of data/control/status word?	1/1
A. Data Bus Buffer	
B. Read/Write Control Logic	<b>✓</b>
O C. CS	
O. WR	
✓ 6. Which of the following uses N-MOS technology?	1/1
A. 8253	<b>✓</b>
B. 8254	
C. 8255	
D. 8256	
7. It is a tri-state, bi-directional, 8-bit buffer, which is used to interface the 8253/54 to the system data bus.	1/1
A. Read/Write Logic	
B. Data Bus Buffer	<b>✓</b>
C. system data bus	
D. System Buffer	

√ 8. 8253/54 can be operated in Modes?	1/1
A. 3	
O B. 4	
O C. 5	
D. 6	<b>✓</b>
9. Which mode can be used as a mono stable multi-vibrator?	1/1
A. Mode 0	
B. Mode 1	<b>✓</b>
C. Mode 2	
D. Mode 3	
✓ 10. Which mode generates a strobe in response to an externally generated signal?	1/1
A. Mode 3	
B. Mode 4	
C. Mode 5	<b>✓</b>
D. Mode 6	

This form was created inside of Terna.

Google Forms