

PART B

EXPERIMENT NUMBER 8

Aim: To design and implement the second pass of a two-pass assembler for IBM 360/370 Processor.

(PART B: TO BE COMPLETED BY STUDENTS)

(Students must submit the soft copy as per the following segments within two hours of the practical. The soft copy must be uploaded at the end of the practical)

Roll No. 50	Name: AMEY THAKUR
Class: Comps TE B	Batch: B3
Date of Experiment: 30/04/2021	Date of Submission: 30/04/2021
Grade:	

B.1 Software Code written by a student:

(Paste your code completed during the 2 hours of practice in the lab here)

- **SPCC-8.C**

```
#include<stdio.h>
#include<conio.h>
#include<string.h>
void main()
{
    char a[10], ad[10], label[10], opcode[10], operand[10], symbol[10], ch;
    int st, diff, i, address, add, len, actual_len, finaddr, prevaddr, j=0;
    char mnemonic[15][15]={"LDA","STA","LDCH","STCH"};
    char code[15][15]={"33","44","53","57"};
    FILE *fp1,*fp2,*fp3,*fp4;

    fp1=fopen("ASSMLIST.DAT","w");
    fp2=fopen("SYMTAB.DAT","r");
    fp3=fopen("INTERMED.DAT","r");
    fp4=fopen("OBJCODE.DAT","w");
    fscanf(fp3,"%s%s%s",label,opcode,operand);

    while(strcmp(opcode,"END")!=0)
    {
        prevaddr=address;
        fscanf(fp3,"%d%s%s%s",&address,label,opcode,operand);
```

```

}
finaddr=address;
fclose(fp3);
fp3=fopen("INTERMED.DAT","r");

fscanf(fp3,"%s%s%s",label,opcode,operand);
if(strcmp(opcode,"START")==0)
{
    fprintf(fp1,"\t%s\t%s\t%s\n",label,opcode,operand);
    fprintf(fp4,"H^%s^00%s^00%d\n",label,operand,finaddr);
    fscanf(fp3,"%d%s%s%s",&address,label,opcode,operand);
    st=address;
    diff=prevaddr-st;
    fprintf(fp4,"T^00%d^%d",address,diff);
}
while(strcmp(opcode,"END")!=0)
{
    if(strcmp(opcode,"BYTE")==0)
    {
        fprintf(fp1,"%d\t%s\t%s\t%s\t",address,label,opcode,operand);
        len=strlen(operand);
        actual_len=len-3;
        fprintf(fp4,"");
        for(i=2;i<(actual_len+2);i++)
        {
            itoa(operand[i],ad,16);
            fprintf(fp1,"%s",ad);
            fprintf(fp4,"%s",ad);
        }
        fprintf(fp1,"\n");
    }
    else if(strcmp(opcode,"WORD")==0)
    {
        len=strlen(operand);
        itoa(atoi(operand),a,10);
        fprintf(fp1,"%d\t%s\t%s\t%s\t00000%s\n",address,label,opcode,operand,a);
        fprintf(fp4,"^00000%s",a);
    }
    else if((strcmp(opcode,"RESB")==0)||(strcmp(opcode,"RESW")==0))
        fprintf(fp1,"%d\t%s\t%s\t%s\n",address,label,opcode,operand);
    else
    {
        while(strcmp(opcode,mnemonic[j])!=0)

```

```

        j++;
        if(strcmp(operand,"COPY")==0)

fprintf(fp1,"%d\t%s\t%s\t%s\t%s0000\n",address,label,opcode,operand,code[j]);
    else
    {
        rewind(fp2);
        fscanf(fp2,"%s%d",symbol,&add);
        while(strcmp(operand,symbol)!=0)
            fscanf(fp2,"%s%d",symbol,&add);

fprintf(fp1,"%d\t%s\t%s\t%s\t%s%d\n",address,label,opcode,operand,code[j],add
);
        fprintf(fp4,"%s%d",code[j],add);
    }
}
fscanf(fp3,"%d%s%s%s",&address,label,opcode,operand);
}
fprintf(fp1,"%d\t%s\t%s\t%s\n",address,label,opcode,operand);
fprintf(fp4,"\nE^00%d",st);
printf("\n Intermediate file is converted into object code");
fcloseall();

printf("\n\nThe contents of Intermediate file:\n\n\t");
fp3=fopen("INTERMED.DAT","r");
ch=fgetc(fp3);
while(ch!=EOF)
{
    printf("%c",ch);
    ch=fgetc(fp3);
}
printf("\n\nThe contents of Symbol Table :\n\n");
fp2=fopen("SYMTAB.DAT","r");
ch=fgetc(fp2);
while(ch!=EOF)
{
    printf("%c",ch);
    ch=fgetc(fp2);
}
printf("\n\nThe contents of Output file :\n\n");
fp1=fopen("ASSMLIST.DAT","r");
ch=fgetc(fp1);
while(ch!=EOF)

```

```

{
    printf("%c",ch);
    ch=fgetc(fp1);
}
printf("\n\nThe contents of Object code file :\n\n");
fp4=fopen("OBJCODE.DAT","r");
ch=fgetc(fp4);
while(ch!=EOF)
{
    printf("%c",ch);
    ch=fgetc(fp4);
}
fcloseall();
getch();
}

```

- **Symtab.dat**

```

ALPHA  2012
FIVE   2015
CHARZ  2018
C1     2019

```


- **Intermed.dat**

```

COPY  START  2000
2000  **  LDA  FIVE
2003  **  STA  ALPHA
2006  **  LDCH CHARZ
2009  **  STCH  C1
2012  ALPHA RESW  1
2015  FIVE  WORD  5
2018  CHARZ BYTE  C'EOF'
2019  C1   RESB  1
2020  **  END   **

```

B.2 Input and Output:



```
DOSBox 0.74, Cpu speed: max 100% cycles, Frameskip 0, Progra...

ALPHA    2012
FIVE     2015
CHARZ    2018
C1       2019

The contents of Output file :

COPY     START    2000
2000     **      LDA     FIVE     332015
2003     **      STA     ALPHA    442012
2006     **      LDCH    CHARZ    532018
2009     **      STCH    C1       572019
2012     ALPHA   RESW     1
2015     FIVE    WORD     5      000005
2018     CHARZ   BYTE     C' EOF' 454f46
2019     C1      RESB     1
2020     **      END      **

The contents of Object code file :

H^COPY^002000^002020
T^002000^19^332015^442012^532018^572019^000005^454f46
E^002000_
```

B.3 Observations and learning:

(Students are expected to comment on the output obtained with clear observations and learning for each task/ subpart assigned)

We have learnt about the two passes of the two-pass assembler.

B.4 Conclusion:

(Students must write the conclusion as per the attainment of individual outcome listed above and learning/observation noted in section B.3)

We have successfully implemented a c program for the second pass of a two-pass assembler.

B.5 Question of Curiosity

(To be answered by a student based on the practical performed and learning/ observations)

1. Give Example of Working of Two-Pass Assembler

Ans:


→ Two-pass assembler: Assemblers typically make two or more passes through a source program to resolve forward references in a program. A forward reference is defined as a type of instruction in the code segment that is referencing the label of instruction, but the assembler has not yet encountered the definition of that instruction.

Pass 1:

- Assembler reads the entire source program and constructs a symbol table of names and labels used in the program, that is, the name of data fields and programs labels and their relative location (offset) within the segment. Pass 1 determines the amount of code to be generated for each instruction.

Pass 2:

- The assembler uses the symbol table that is constructed in Pass 1. Now it knows the length and relative of each data field and instruction, it can complete the object code for each instruction. It produces OBJ (Object file), LST (list file) and cross-reference (.CRF) files.



2. Mention the Advantage of assemblers with Multiple Passes?

Ans:

- The main reason why most assemblers use a 2-pass system is to address the problem of forwarding references -- references to variables or subroutines that have not yet been encountered when parsing the source code. A strict 1-pass scanner cannot assemble source code that contains forward references. Pass 1 of the assembler scans the source, determining the size and address of all data and instructions; then pass 2 scans the source again, outputting the binary object code.
- Some assemblers have been written to use a 1.5 (one and a half) pass scheme, whereby the source is only scanned once, but any forward references are simply assumed to be of the largest size necessary to hold any native machine data type (for instance, assuming a reference to the address of an as-yet unencountered subroutine could be very far away, necessitating the use of a far branch). The unknown quantity is temporarily filled in as zero during pass 1 of the assembler, and the forward reference is added to a 'fix-up list'. After pass 1, the '.5' pass goes through the fix-up list and patches the output machine code with the values of all resolved forward references. This can result in sub-optimal opcode construction but allows for a very fast assembly phase.