Distributed Systems

Chapter 01: Introduction

Distributed versus Decentralized



Centralized Decentralized Distributed

When does a decentralized system become distributed?

- Adding 1 link between two nodes in a decentralized system?
- Adding 2 links between two other nodes?
- In general: adding $k > 0$ links....?

Alternative approach

Two views on realizing distributed systems

- Integrative view: connecting existing networked computer systems into a larger a system.
- Expansive view: an existing networked computer systems is extended with additional computers

Two definitions

- A decentralized system is a networked computer system in which processes and resources are necessarily spread across multiple computers.
- A distributed system is a networked computer system in which processes and resources are sufficiently spread across multiple computers.

Perspectives on distributed systems

Distributed systems are complex: take persepctives

- Architecture: common organizations
- Process: what kind of processes, and their relationships
- Communication: facilities for exchanging data
- Coordination: application-independent algorithms
- Naming: how do you identify resources?
- Consistency and replication: performance requires of data, which need to be the same
- Fault tolerance: keep running in the presence of partial failures
- Security: ensure authorized access to resources

What do we want to achieve?

Overall design goals

- Support sharing of resources
- Distribution transparency
- Openness
- Scalability

Sharing resources

Canonical examples

- Cloud-based shared storage and files
- Peer-to-peer assisted multimedia streaming
- Shared mail services (think of outsourced mail systems)
- Shared Web hosting (think of content distribution networks)

Observation

"The network is the computer"

quote from John Gage, then at (Sun Microsystems)

Distribution transparency



What is transparency?

The phenomenon by which a distributed system attempts to hide the fact that its processes and resources are physically distributed across multiple computers, possibly separated by large distances.

Observation

Distribution transparancy is handled through many different techniques in a layer between applications and operating systems: a middleware layer

Distribution transparency

Types

Transparency	Description
Access	Hide differences in data representation and how an object is accessed
Location	Hide where an object is located
Relocation	Hide that an object may be moved to another location while in use
Migration	Hide that an object may move to another location
Replication	Hide that an object is replicated
Concurrency	Hide that an object may be shared by several independent users
Failure	Hide the failure and recovery of an object

Degree of transparency

Aiming at full distribution transparency may be too much

- There are communication latencies that cannot be hidden
- Completely hiding failures of networks and nodes is (theoretically and practically) impossible
  - You cannot distinguish a slow computer from a failing one
  - You can never be sure that a server actually performed an operation before a crash
- Full transparency will cost performance, exposing distribution of the system
  - Keeping replicas exactly up-to-date with the master takes time
  - Immediately flushing write operations to disk for fault tolerance

Degree of transparency

Exposing distribution may be good

- Making use of location-based services (finding your nearby friends)
- When dealing with users in different time zones
- When it makes it easier for a user to understand what's going on (when e.g., a server does not respond for a long time, report it as failing).

Conclusion

Distribution transparency is a nice goal, but achieving it is a different story, and it should often not even be aimed at.

Openness of distributed systems

Open distributed system

A system that offers components that can easily be used by, or integrated into other systems. An open distributed system itself will often consist of components that originate from elsewhere.

What are we talking about?

Be able to interact with services from other open systems, irrespective of the underlying environment:

- Systems should conform to well-defined interfaces
- Systems should easily interoperate
- Systems should support portability of applications
- Systems should be easily extensible

Policies versus mechanisms

Implementing openness: policies

- What level of consistency do we require for client-cached data?
- Which operations do we allow downloaded code to perform?
- Which QoS requirements do we adjust in the face of varying bandwidth?
- What level of secrecy do we require for communication?

Implementing openness: mechanisms

- Allow (dynamic) setting of caching policies
- Support different levels of trust for mobile code
- Provide adjustable QoS parameters per data stream
- Offer different encryption algorithms

Reliability versus availability

Reliability $R(t)$ of component C

Conditional probability that C has been functioning correctly during $[0, t)$ given C was functioning correctly at the time $T = 0$.

Traditional metrics

- Mean Time To Failure ($MTTF$): The average time until a component fails.
- Mean Time To Repair ($MTTR$): The average time needed to repair a component.
- Mean Time Between Failures ($MTBF$): Simply $MTTF + MTTR$.

Terminology

Failure, error, fault

Term	Description	Example
Failure	A component is not living up to its specifications	Crashed program
Error	Part of a component that can lead to a failure	Programming bug
Fault	Cause of an error	Sloppy programmer

Terminology

Handling faults

Term	Description	Example
Fault prevention	Prevent the occurrence of a fault	Don't hire sloppy programmers
Fault tolerance	Build a component and make it mask the occurrence of a fault	Build each component by two independent programmers
Fault removal	Reduce the presence, number, or seriousness of a fault	Get rid of sloppy programmers
Fault forecasting	Estimate current presence, future incidence, and consequences of faults	Estimate how a recruiter is doing when it comes to hiring sloppy programmers

Scale in distributed systems

Observation

Many developers of modern distributed systems easily use the adjective "scalable" without making clear why their system actually scales.

At least three components

- Number of users or processes (size scalability)
- Maximum distance between nodes (geographical scalability)
- Number of administrative domains (administrative scalability)

Observation

Most systems account only, to a certain extent, for size scalability. Often a solution: multiple powerful servers operating independently in parallel. Today, the challenge still lies in geographical and administrative scalability.

Size scalability

Root causes for scalability problems with centralized solutions

- The computational capacity, limited by the CPUs
- The storage capacity, including the transfer rate between CPUs and disks
- The network between the user and the centralized service

Problems with geographical scalability

- Cannot simply go from LAN to WAN: many distributed systems assume synchronous client-server interactions: client sends request and waits for an answer. Latency may easily prohibit this scheme.
- WAN links are often inherently unreliable: simply moving streaming video from LAN to WAN is bound to fail.
- Lack of multipoint communication, so that a simple search broadcast cannot be deployed. Solution is to develop separate naming and directory services (having their own scalability problems).

Problems with administrative scalability

Essence

Conflicting policies concerning usage (and thus payment), management, and security

Examples

- Computational grids: share expensive resources between different domains.
- Shared equipment: how to control, manage, and use a shared radio telescope constructed as large-scale shared sensor network?

Exception: several peer-to-peer networks

- File-sharing systems (based, e.g., on BitTorrent)
- Peer-to-peer telephony (early versions of Skype)
- Peer-assisted audio streaming (Spotify)

Note: end users collaborate and not administrative entities.

Techniques for scaling

Hide communication latencies

- Make use of asynchronous communication
- Have separate handler for incoming response
- Problem: not every application fits this model

Techniques for scaling

Facilitate solution by moving computations to client





Techniques for scaling

Partition data and computations across multiple machines

- Move computations to clients (Java applets and scripts)
- Decentralized naming services (DNS)
- Decentralized information systems (WWW)

Techniques for scaling

Replication and caching: Make copies of data available at different machines

- Replicated file servers and databases
- Mirrored Websites
- Web caches (in browsers and proxies)
- File caching (at server and client)

Scaling: The problem with replication

Applying replication is easy, except for one thing

- Having multiple copies (cached or replicated), leads to inconsistencies: modifying one copy makes that copy different from the rest.
- Always keeping copies consistent and in a general way requires global synchronization on each modification.
- Global synchronization precludes large-scale solutions.

Observation

If we can tolerate inconsistencies, we may reduce the need for global synchronization, but tolerating inconsistencies is application dependent.