Padilla, Amiel Keith E
BSIT-1C


```
#include <stdio.h>

int main()

{

   printf("SET A\n");

   float annual;

   printf("Enter Amount for Annual Subscription: ");

   scanf("%f", & annual);

   float monthlypaymenttbp = annual / 12;

   printf("Amount per month to pay: %.2f\n",
monthlypaymenttbp);

   float monthly;

   float minuspercent = 0.95;

   printf("Enter Monthly payment:");

   scanf("%f", &monthly);


   float month7 = monthly * minuspercent;

   float month8 = monthly * minuspercent;

   float month9 = monthly * minuspercent;

   float month10 = monthly * minuspercent;

   float month11 = monthly * minuspercent;

   float month12 = monthly * minuspercent;

   printf("Month 6 = %.2f\n", monthly);

   printf("July Subscription = %.2f\n", month7);

   printf("August Subscription = %.2f\n", month8);

   printf("September Subscription = %.2f\n", month9);

   printf("October Subscription = %.2f\n", month10);

   printf("November Subscription = %.2f\n", month11);

   printf("December Subscription = %.2f\n", month12);

   printf("Amount Paid = %.2f\n", annual);

   float monthlydue = monthly;

   printf("Amount to be paid per month: %.2f\n\n",
monthlydue);

   float month1 = monthly;

   float month2 = monthly;

   float month3 = monthly;

   float month4 = monthly;

   float month5 = monthly;

   float month6 = monthly;

   float due1 = monthlydue - month1;

   float due2 = monthlydue - month2;

   float due3 = monthlydue - month3;

   float due4 = monthlydue - month4;

   float due5 = monthlydue - month5;

   float due6 = monthlydue - month6;

   float due7 = monthlydue - month7;

   float due8 = monthlydue - month8;

   float due9 = monthlydue - month9;

   float due10 = monthlydue - month10;

   float due11 = monthlydue - month11;

   float due12 = monthlydue - month12;


   printf("EXTRA BALANCED TO BE RETURNED\n");

   printf("January = %.2f\n", due1);

   printf("February = %.2f\n", due2);

   printf("March = %.2f\n", due3);

   printf("April = %.2f\n", due4);

   printf("May = %.2f\n", due5);

   printf("June = %.2f\n", due6);

   printf("July = %.2f\n", due7);

   printf("August = %.2f\n", due8);

   printf("September = %.2f\n", due9);

   printf("October = %.2f\n", due10);

   printf("November = %.2f\n", due11);

   printf("December = %.2f\n", due12);


   double refund = due6 + due7 + due8 + due9 + due10 +
due11 + due12;

   printf("Amount of Internet Subscription Refund =
%.2lf\n\n", refund);
```

```
   printf("SET B\n");
   float annuala;
   printf("Enter Amount for Annual Subscription: ");
   scanf("%f", & annuala);
   float monthlypaymenttbpa = annuala / 12;
   printf("Amount per month to pay: %.2f\n",
monthlypaymenttbpa);
   float monthlya;
   printf("Enter Monthly payment:");
   scanf("%f", &monthlya);
   float minuspercenta = 0.95;

   float month7a = monthlya * minuspercenta;
   float month8a = monthlya * minuspercenta;
   float month9a = monthlya * minuspercenta;
   float month10a = monthlya * minuspercenta;
   float month11a = monthlya * minuspercenta;
   float month12a = monthlya * minuspercenta;
   printf("Month 6 = %.2f\n", monthlya);
   printf("July Subscription = %.2f\n", month7a);
   printf("August Subscription = %.2f\n", month8a);
   printf("September Subscription = %.2f\n", month9a);
   printf("October Subscription = %.2f\n", month10a);
   printf("November Subscription = %.2f\n", month11a);
   printf("December Subscription = %.2f\n", month12a);

   printf("Amount Paid = %.2f\n", annuala);
   float monthlyduea = monthlya;
   printf("Amount to be paid per month: %.2f\n\n",
monthlyduea);

   float month1a = monthlya;
   float month2a = monthlya;
   float month3a = monthlya;
   float month4a = monthlya;
   float month5a = monthlya;
   float month6a = monthlya;
   float due11a = monthlyduea - month11a;
   float due2a = monthlyduea - month2a;
   float due3a = monthlyduea - month3a;
   float due4a = monthlyduea - month4a;
   float due5a = monthlyduea - month5a;
   float due6a = monthlyduea - month6a;
   float due7a = monthlyduea - month7a;
   float due8a = monthlyduea - month8a;
   float due9a = monthlyduea - month9a;
   float due10a = monthlyduea - month10a;
   float due11a = monthlyduea - month11a;
   float due12a = monthlyduea - month12a;

   printf("EXTRA BALANCED TO BE RETURNED\n");
   printf("January = %.2f\n", due11a);
   printf("February = %.2f\n", due2a);
   printf("March = %.2f\n", due3a);
   printf("April = %.2f\n", due4a);
   printf("May = %.2f\n", due5a);
   printf("June = %.2f\n", due6a);
   printf("July = %.2f\n", due7a);
   printf("August = %.2f\n", due8a);
   printf("September = %.2f\n", due9a);
   printf("October = %.2f\n", due10a);
   printf("November = %.2f\n", due11a);
   printf("December = %.2f\n", due12a);
   double refunda = due6a + due7a + due8a + due9a +
due10a + due11a + due12a;
   printf("Amount of Internet Subscription Refund =
%.2lf\n", refunda);

   return 0;
}
```