M1 Freeze + M2 Bounded Reproduction

CS4928 – **Group 17** – **Project 23**

Jakub Bolka, Mateusz Przywozny, Amelia Polak, Colin Walsh, Luke Scanlon.

GitHub: https://github.com/SpencerLabAQ/performance-test-coverage

Group fork (our evidence): https://github.com/Amilkamija/performance-test-coverage

Research: https://link.springer.com/article/10.1007/s10664-025-10712-3

Excel Tracker for the Project: https://ulcampus-my.sharepoint.com/personal/abdul_razzaq_ul_ie/Documents/CS4928/Student%20Tracker.xlsx?web=1

1. What the original paper investigates

Muhammad Imran, Vittorio Cortellessa, Davide Di Ruscio, Riccardo Rubei and Luca Traini published "Is code coverage of performance tests related to source code features? An empirical study on open-source Java systems" in Empirical Software Engineering (2025). The paper investigates how much Java source code performance tests exercise, how performance testing compares with JUnit functional testing, the cost of executing those tests, and whether static source-code characteristics help predict which methods performance tests cover.

Its central findings include relatively low JMH method coverage compared with functional tests and limited generalisable associations between static source-code features and performance-test coverage. Our group does NOT attempt to reproduce the complete paper; M2 reproduces a bounded subset of its coverage/overlap analysis.

2. Original Study and bounded sample

Population / Sample	Count	Interpretation
JMH systems	**28**	Final project set for performance-coverage analysis
JMH benchmarks	2,190	Performance benchmarks analysed
Extracted methods	187,319	Methods across 28 systems
JUnit comparison systems	19	Subset with usable JUnit data

Static-feature modelling methods	177,697	Different dataset used in the source-feature modelling analysis

Group sample: four randomly picked projects, selected to give contrasting coverage/overlap outcomes (see reason below) - **byte-buddy, fastjson, commons-bcel and SquidLib** - corresponding to 4/28 (14.3%) of JMH systems and 4/19 (21.1%) of systems in the JUnit comparison.

Selected project	Total methods	JMH benchmark count
byte-buddy	5,046	39
fastjson	17,524	4
commons-bcel	3,132	3
SquidLib	5,663	236
TOTAL	31,365	282

Reason for the bounded sample: these systems offer contrasting coverage/overlap outcomes, including high benchmark overlap in byte-buddy/fastjson and unusually low JMH overlap in commons-bcel

3. M1 Freeze

Group RQ1: Can the selected coverage/source-feature relationship be reproduced?

Group RQ2: Can the selected coverage/source-feature analysis be improved through additional code metrics or optimising the existing analysis scripts?

Bounded sample IDs: byte-buddy, fastjson, commons-bcel, SquidLib.

Recorded M1 method/decision rule: Run the four original overlap and coverage scripts to compare outputs with the supplied results.

Recorded M1 expected result (before execution): All four scripts should run successfully and reproduce the supplied results without changes.

Non-reproduction rule for interpreting M2: report any mismatch with the publication/reference outputs or failure to complete execution on the documented environment.

4. Reproduction environment and method

Documented environment: Windows 11, Python 3.10.5 virtual environment, original replication package and provided inputs.

Additional run (Mateusz, 22 Oct 2026): macOS, Python 3.10.11, fresh virtual environment; numpy 1.24.3, scipy 1.10.1 (Fig. 2). Scripts run unchanged from the analysis directory.

Run scripts from the analysis directory in the original prescribed order:

python 1-Overlap-JMH.py

python 2-Overlap-JUnit.py

python 3-Coverage-JMH.py

python 4-Coverage-JUnit.py

Metrics: overall method coverage = methods covered by any test / total methods, direct method coverage = methods directly exercised / total methods, overlap ratio measures the fraction of suite-covered methods covered by more than one test, ranging from 0 to 1. JMH refers to performance benchmarks and JUnit to functional tests.

5. Reproduced outputs: overlap comparison

Project	JMH reproduced	Paper JMH	Junit reproduced	Paper JUnit
byte-buddy	1.00	1.00	0.70	0.70
fastjson	0.91	0.91	0.15	0.15
commons-bcel	0.09	0.09	0.66	0.66
SquidLib	0.80	≈0.80	0.50	≈0.50

Interpretation: all four recorded JMH/JUnit overlap outcomes match or are consistent with the paper comparisons. JMH overlap exceeds JUnit overlap for three systems; commons-bcel is the exception

Evidence: both overlap scripts were re-run on macOS and reproduced all eight selected ratios (Fig. 3, Fig. 4). The regenerated Overlap_Ratios_JMH.csv is byte-identical to the supplied file; the regenerated Overlap_Ratios_Junit.csv has identical values and differs only in line endings (Fig. 7).

	Project Name	Overlap Ratio
0	arrow	0.65
1	byte-buddy	1.00
2	cantaloupe	0.90
3	client_java	0.73
4	commons-bcel	0.09
5	crate	0.78
6	eclipse-collections	0.85
7	fastjson	0.91
8	feign	0.87
9	HdrHistogram	0.77
10	imglib2	0.89
11	iri	0.33
12	jdbi	0.97
13	jetty.project	0.53
14	jgrapht	0.70
15	jooby	0.89
16	kafka	0.67
17	logbook	0.86
18	netty	0.73
19	objenesis	0.79
20	panda	0.48
21	protostuff	0.98
22	r2dbc-h2	0.98
23	rdf4j	0.97
24	RxJava	0.83
25	SquidLib	0.80
26	tinkerpop	0.82
27	vert.x	0.75

Fig. 3: 1-Overlap-JMH.py output on macOS (2.8 s; first cold run 24.6 s).

	Project Name	Overlap Ratio
0	arrow	0.77
1	byte-buddy	0.70
2	cantaloupe	0.81
3	client_java	0.70
4	commons-bcel	0.66
5	fastjson	0.15
6	feign	0.77
7	HdrHistogram	0.78
8	imglib2	0.67
9	iri	0.65
10	jdbi	0.83
11	jgrapht	0.80
12	jooby	0.55
13	logbook	0.78
14	objenesis	0.57
15	panda	0.76
16	r2dbc-h2	0.59
17	SquidLib	0.50
18	vert.x	0.74

Fig. 4: 2-Overlap-JUnit.py on macOS: completed in about 8 minutes, reproducing byte-buddy 0.70, fastjson 0.15, commons-bcel 0.66 and SquidLib 0.50.

6. Reproduced outputs: JMH method coverage

Project	Methods covered	Coverage %	Direct %
byte-buddy	107	2.12	0.46
fastjson	64	0.37	0.02
commons-bcel	396	12.64	3.38
SquidLib	441	7.79	3.43

The JMH method-coverage values were reproduced on macOS (Fig. 5); the regenerated coverageJMH.csv is byte-identical to the supplied file for all 28 projects (Fig. 7). fastjson has 4 JMH benchmarks (122 is its “Methods Benchmarked” count).

```
python 3-Coverage-JMH.py  3.56s user 0.78s system 331% cpu 1.309 total
Project Name  Total Methods  Methods Covered  Methods Directly Covered  Coverage
 Percentage  Direct Coverage Percentage  Total Benchmarks
    SquidLib           5663              441                       194
        7.79                        3.43                236
  byte-buddy           5046              107                        23
        2.12                        0.46                 39
commons-bcel           3132              396                       106
       12.64                        3.38                  3
     fastjson          17524               64                         3
        0.37                        0.02                  4
```

Fig. 5: 3-Coverage-JMH.py on macOS (1.3 s) and the selected rows of coverageJMH.csv.

JUnit method coverage - selected projects: regenerated by 4-Coverage-JUnit.py on macOS (Fig. 6); the output is byte-identical to the supplied coverageJUnit.csv for all 19 projects (Fig. 7).

Project	Junit overall coverage	Junit direct Coverage
byte-buddy	12.80%	9.63%
fastjson	34.54%	27.84%
commons-bcel	34.71%	4.25%
SquidLib	6.20%	3.05%

```
python 4-Coverage-JUnit.py  4.15s user 0.76s system 314% cpu 1.564 total
Project Name  Total Methods  Methods Covered  Methods Directly Covered  Coverage
 Percentage  Direct Coverage Percentage  Total Tests
    SquidLib           5663              351                       173
        6.20                        3.05                 73
  byte-buddy           5046              646                       486
       12.80                        9.63               6357
commons-bcel           3132             1087                       133
       34.71                        4.25                137
     fastjson          17524             6053                      4879
       34.54                       27.84                4979
```

Fig. 6: 4-Coverage-JUnit.py on macOS (1.6 s), run after 2-Overlap-JUnit.py had completed, and the selected rows of coverageJUnit.csv.




Fig. 7: diff -s of regenerated outputs against the supplied originals: three files byte-identical; Overlap_Ratios_Junit.csv identical once line endings are ignored (diff --strip-trailing-cr).

7. Execution outcome, deviations and audit

Script	Outcome	Evidence
1-Overlap-JMH.py	Completed in all environments; reproduced selected ratios. macOS: 2.8 s (first cold run 24.6 s)	Fig. 3, Fig. 7
2-Overlap-JUnit.py	Completed for Jakub and on macOS (about 8 min); interrupted (Amelia/Mateusz); exceeded 300 s (Colin/Luke). macOS output matches supplied (line endings differ)	Fig. 4, Fig. 7; team reports
3-Coverage-JMH.py	CSV generated; byte-identical to supplied. macOS: 1.3 s. One setup initially lacked SciPy	Fig. 5, Fig. 7; coverageJMH.csv
4-Coverage-JUnit.py	CSV generated; byte-identical to supplied. macOS: 1.6 s	Fig. 6, Fig. 7; coverageJUnit.csv

Dependency threats: the original pinned numpy==1.24.2 conflicts with imbalanced-learn==0.13.0 in the recorded environment; upgrading to numpy==1.24.3 resolved installation for Jakub. Amelia independently reported a missing SciPy dependency and a

prolonged/interrupted JUnit overlap analysis. These are differences across recorded setups. A fresh macOS environment (22 Oct) reproduced the same numpy conflict (Fig. 1); with numpy==1.24.3 all packages, including SciPy, installed (Fig. 2). The missing SciPy reported in other setups is therefore likely a side effect of the failed install rather than a separate dependency problem.

```
ERROR: Could not open requirements file: [Errno 2] No such file or directory: 'r
equirements.txt'
```

Fig. 1: pip install --dry-run numpy==1.24.2 imbalanced-learn==0.13.0 in the macOS environment: ResolutionImpossible, because imbalanced-learn 0.13.0 requires numpy>=1.24.3.

```
OK 1.24.3 1.10.1
```

Fig. 2: Successful install after changing the pin to numpy==1.24.3; import check prints OK 1.24.3 1.10.1.

Group execution comparison (four reports):

-**Jakub:** all four analysis scripts completed after a NumPy dependency adjustment; selected overlap outputs agreed with the paper and coverage CSVs were generated.

-Amelia and Mateusz: JMH overlap completed; JUnit overlap was interrupted after prolonged execution; SciPy was missing until installed; the two coverage scripts subsequently completed.

-**Colin and Luke:** JMH overlap ran in 11.713 s, JMH coverage in 5.449 s and JUnit coverage in 6.388 s. JUnit overlap exceeded a 300-second limit. The JUnit coverage run therefore reused the pre-existing JUnit overlap reference CSV, although the coverage counts were freshly transformed.

-**Colin and Luke:** independently recalculated all eight selected overlap ratios from test-to-method sets; each matched the supplied CSV ratio to two decimal places. Five selected figures were directly compared with values explicitly stated in the paper; the remaining chart-based values should not be presented as exact published decimals.

-**Colin and Luke:** also ran the nested plotting/table scripts: 12 of 13 completed. The table script rq1-table_II.py failed under pandas 3 because a text placeholder was inserted into float columns. This is a supplementary compatibility finding, not a failure of the bounded four-script sample.

-Mateusz (macOS re-run, 22 Oct): a fresh environment reproduced the numpy conflict and installed fully with numpy==1.24.3 (Fig. 1–2). All four scripts completed: 1-Overlap-JMH.py 2.8 s (first cold run 24.6 s), 2-Overlap-JUnit.py about 8 min (started 19:55, within the pre-set 30-minute limit), 3-Coverage-JMH.py 1.3 s and 4-Coverage-JUnit.py 1.6 s (Fig. 3–6). Overlap_Ratios_JMH.csv, coverageJMH.csv and coverageJUnit.csv are byte-

identical to the supplied files for all projects; Overlap_Ratios_Junit.csv has identical values but different line endings (CRLF in the supplied file, LF on macOS) (Fig. 7). The JUnit overlap script is therefore slow but not broken: on this machine it finished in about 8 minutes, longer than the 300 s limit used by Colin and Luke.

8. Bounded M2 conclusion

For the selected four projects, the JMH and JUnit overlap ratios matched the supplied replication data. Five explicitly stated overlap values were also confirmed against the paper; other values are consistent with its plotted comparisons. Colin independently checked all eight selected ratios, and the JMH/JUnit coverage percentages were validated against the supplied summary counts. Different group environments exposed reproducibility limits: dependency conflicts, missing SciPy, an interrupted or timed-out JUnit overlap script, and a table-script compatibility error. These results constitute a bounded reproduction of analyses using supplied data, not a fresh collection of Java call stacks or a reproduction of the machine-learning experiments.

Verdict against the M1 rule: partial reproduction. All selected values match the supplied outputs and are consistent with the paper, and the macOS re-run regenerated all four output files with values identical to the supplied ones. However, the preregistered expectation ("all four scripts should run successfully and reproduce the supplied results without changes") was not met: the numpy pin had to be changed in every recorded environment, and 2-Overlap-JUnit.py did not complete in 2 of 4 recorded runs (it completed for Mateusz on macOS, taking about 8 minutes).

Scope note: RQ1 as frozen at M1 refers to the "coverage/source-feature relationship"; M2 reproduces the coverage/overlap component only. The RQ1 wording is kept unchanged.