

338. Counting Bits

Easy

5546

275

Add to List

Share

Given an integer n , return an array `ans` of length $n + 1$ such that for each i ($0 \leq i \leq n$), `ans[i]` is the **number of 1's** in the binary representation of i .

Example 1:

Input: $n = 2$
Output: `[0,1,1]`
Explanation:
 $0 \rightarrow 0$
 $1 \rightarrow 1$
 $2 \rightarrow 10$

Example 2:

Input: $n = 5$
Output: `[0,1,1,2,1,2]`
Explanation:
 $0 \rightarrow 0$
 $1 \rightarrow 1$
 $2 \rightarrow 10$
 $3 \rightarrow 11$
 $4 \rightarrow 100$
 $5 \rightarrow 101$

Constraints:

- $0 \leq n \leq 10^5$

Follow up:

- It is very easy to come up with a solution with a runtime of $O(n \log n)$. Can you do it in linear time $O(n)$ and possibly in a single pass?
- Can you do it without using any built-in function (i.e., like `__builtin_popcount` in C++)?

Accepted 476,560

Submissions 656,905

Seen this question in a real interview before?

Yes

No

Companies

Related Topics

Similar Questions

```
1 class Solution {
2     public int[] countBits(int n) {
3         int[] bitCounts = new int[n + 1];
4
5         for(int i = 0; i <= n; i++){
6             int count = 0;
7             int j = i;
8
9             while(j != 0){
10                 count++;
11                 j = j & (j - 1);
12             }
13
14             bitCounts[i] = count;
15         }
16
17         return bitCounts;
18     }
19 }
```

⋮

Your previous code was restored from your local storage. [Reset to default](#)

