

EXPLORER

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

+ ▾ ×

GOMYCODE

> learn_git

```
(base) aminasamb@sm-j260f-2 GOMYCODE % mkdir learn_git  
(base) aminasamb@sm-j260f-2 GOMYCODE %
```

zsh

zsh

1

> OUTLINE

> TIMELINE

master* ↻ ⊞ ✘ 0 ▲ 0

EXPLORER

...

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

+ ✓ ✕

GOMYCODE

> learn_git

```
(base) aminasamb@sm-j260f-2 GOMYCODE % mkdir learn_git  
(base) aminasamb@sm-j260f-2 GOMYCODE % cd learn_git  
(base) aminasamb@sm-j260f-2 learn_git % █
```

zsh

zsh learn_git

2

> OUTLINE

> TIMELINE

A screenshot of a dark-themed terminal interface, likely from a code editor like VS Code. The interface includes a left sidebar with icons for Explorer, Search, Issues, and Timeline, and a bottom navigation bar with icons for File, Edit, View, Insert, Select, and Help.

The main area shows a terminal window titled "TERMINAL". The terminal output is as follows:

```
(base) aminasamb@sm-j260f-2 GOMYCODE % mkdir learn_git
(base) aminasamb@sm-j260f-2 GOMYCODE % cd learn_git
(base) aminasamb@sm-j260f-2 learn_git % touch third.txt
(base) aminasamb@sm-j260f-2 learn_git %
```

The status bar at the bottom indicates the current branch is "master*" and shows file statistics: 0 files, 0 changes, and 0 additions.

The screenshot shows a dark-themed terminal window in the VS Code interface. The terminal tab is active, indicated by an orange border. The command history is as follows:

```
(base) aminasamb@sm-j260f-2 GOMYCODE % mkdir learn_git
(base) aminasamb@sm-j260f-2 GOMYCODE % cd learn_git
(base) aminasamb@sm-j260f-2 learn_git % touch third.txt
(base) aminasamb@sm-j260f-2 learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@sm-j260f-2 learn_git %
```

The Explorer sidebar on the left shows a folder named 'GOMYCODE' containing a 'learn_git' folder, which contains a file named 'third.txt'. The bottom status bar indicates the current branch is 'master*' and shows other system information like battery level (0%) and signal strength (0).

The screenshot shows a dark-themed terminal window in the VS Code interface. The terminal tab is active, displaying a session in zsh. The session starts with the user navigating into a directory named 'learn_git' and creating a file named 'third.txt'. It then runs 'git init', which initializes an empty Git repository in the current directory. The terminal also provides hints about the default branch name ('master') and suggests alternatives like 'main' or 'trunk'. Finally, the user adds the 'third.txt' file to the repository with 'git add third.txt'.

```
(base) aminasamb@sm-j260f-2 GOMYCODE % mkdir learn_git
(base) aminasamb@sm-j260f-2 GOMYCODE % cd learn_git
(base) aminasamb@sm-j260f-2 learn_git % touch third.txt
(base) aminasamb@sm-j260f-2 learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@sm-j260f-2 learn_git % git add third.txt
(base) aminasamb@sm-j260f-2 learn_git %
```

VS Code interface elements include the Explorer, Problems, Output, and Debug Console tabs at the top, and the Outline and Timeline panels at the bottom. The terminal has a status bar at the bottom showing 'master*' and other terminal metadata.

The screenshot shows a dark-themed terminal window in the VS Code interface. The terminal tab is active, indicated by an orange border. The command-line history is as follows:

```
(base) aminasamb@Aminas-MacBook-Air GOMYCODE % mkdir learn_git
(base) aminasamb@Aminas-MacBook-Air GOMYCODE % cd learn_git
(base) aminasamb@Aminas-MacBook-Air learn_git % touch third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@Aminas-MacBook-Air learn_git % git add third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git % git commit -m'adding third.txt'
[master (root-commit) 9b3f8a4] adding third.txt
  1 file changed, 0 insertions(+), 0 deletions(-)
  create mode 100644 third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git %
```

The left sidebar shows a project structure with a folder named 'GOMYCODE' containing a 'learn_git' folder which has a 'third.txt' file. The bottom left corner shows navigation links for 'OUTLINE' and 'TIMELINE'. The bottom right corner displays the number '6'. The top right corner features standard window control buttons (+, -, ×).

The screenshot shows the Visual Studio Code (VS Code) interface. The left sidebar contains icons for Explorer, Search, Open, Find, and Outline/Timeline. The main area has tabs for Problems, Output, Debug Console, and Terminal, with Terminal selected. The terminal window displays a command-line session for creating a Git repository and committing a file. The file explorer on the left shows a folder named 'GOMYCODE' containing a 'learn_git' folder which includes a 'third.txt' file.

```
(base) aminasamb@Aminas-MacBook-Air GOMYCODE % mkdir learn_git
(base) aminasamb@Aminas-MacBook-Air GOMYCODE % cd learn_git
(base) aminasamb@Aminas-MacBook-Air learn_git % touch third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@Aminas-MacBook-Air learn_git % git add third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git % git commit -m'adding third.txt'
[master (root-commit) 9b3f8a4] adding third.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git % git log
commit 9b3f8a4e95478ee5e263b7e90959856b9472a3f9 (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date:   Tue Jun 28 13:49:18 2022 +0000

    adding third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git %
```

EXPLORER

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

+ - ^ X

GOMYCODE

learn_git

fourth.txt
third.txt

```
(base) aminasamb@Aminas-MacBook-Air GOMYCODE % mkdir learn_git
(base) aminasamb@Aminas-MacBook-Air GOMYCODE % cd learn_git
(base) aminasamb@Aminas-MacBook-Air learn_git % touch third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@Aminas-MacBook-Air learn_git % git add third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git % git commit -m'adding third.txt'
[master (root-commit) 9b3f8a4] adding third.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git % git log
commit 9b3f8a4e95478ee5e263b7e90959856b9472a3f9 (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date:   Tue Jun 28 13:49:18 2022 +0000

    adding third.txt
(base) aminasamb@Aminas-MacBook-Air learn_git % touch fourth.txt
(base) aminasamb@Aminas-MacBook-Air learn_git %
```

zsh

zsh learn_git

zsh learn_git

8

> OUTLINE

> TIMELINE

EXPLORER ... PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

+ - X

zsh

zsh learn_git

GOMYCODE

learn_git

fourth.txt

third.txt

```
(base) aminasamb@aminas-air GOMYCODE % mkdir learn_git
(base) aminasamb@aminas-air GOMYCODE % cd learn_git
(base) aminasamb@aminas-air learn_git % touch third.txt
(base) aminasamb@aminas-air learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@aminas-air learn_git % git add third.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding third.txt'
[master (root-commit) 8fb3997] adding third.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 third.txt
(base) aminasamb@aminas-air learn_git % git log
commit 8fb3997bcd3d88d51e396d67accab2d6963102ba (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date:   Tue Jun 28 14:34:53 2022 +0000

      adding third.txt
(base) aminasamb@aminas-air learn_git % touch fourth.txt
(base) aminasamb@aminas-air learn_git % git add fourth.txt
(base) aminasamb@aminas-air learn_git %
```

> OUTLINE

> TIMELINE

master* 0 △ 0

9

EXPLORER ... PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL + - X

COMYCODE

learn_git

fourth.txt

third.txt

(base) aminasamb@aminas-air GOMYCODE % mkdir learn_git
(base) aminasamb@aminas-air GOMYCODE % cd learn_git
(base) aminasamb@aminas-air learn_git % touch third.txt
(base) aminasamb@aminas-air learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint: git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint: git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@aminas-air learn_git % git add third.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding third.txt'
[master (root-commit) 8fb3997] adding third.txt
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 third.txt
(base) aminasamb@aminas-air learn_git % git log
commit 8fb3997bcd3d88d51e396d67accab2d6963102ba (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date: Tue Jun 28 14:34:53 2022 +0000

adding third.txt
(base) aminasamb@aminas-air learn_git % touch fourth.txt
(base) aminasamb@aminas-air learn_git % git add fourth.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding fourth.txt'
[master 403cd74] adding fourth.txt
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 fourth.txt
(base) aminasamb@aminas-air learn_git %

zsh

zsh learn_git

> OUTLINE

> TIMELINE

master* 0 0 ▲ 0 10

EXPLORER

...

PROBLEMS OUTPUT DEBUG CONSOLE

TERMINAL

+ - ×

GOMYCODE

learn_git

fourth.txt

```
(base) aminasamb@aminas-air GOMYCODE % mkdir learn_git
(base) aminasamb@aminas-air GOMYCODE % cd learn_git
(base) aminasamb@aminas-air learn_git % touch third.txt
(base) aminasamb@aminas-air learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@aminas-air learn_git % git add third.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding third.txt'
[master (root-commit) 8fb3997] adding third.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 third.txt
(base) aminasamb@aminas-air learn_git % git log
commit 8fb3997bcd3d88d51e396d67accab2d6963102ba (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date:   Tue Jun 28 14:34:53 2022 +0000

    adding third.txt
(base) aminasamb@aminas-air learn_git % touch fourth.txt
(base) aminasamb@aminas-air learn_git % git add fourth.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding fourth.txt'
[master 403cd74] adding fourth.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 fourth.txt
(base) aminasamb@aminas-air learn_git % git rm third.txt
rm 'third.txt'
(base) aminasamb@aminas-air learn_git % █
```

zsh

zsh learn_git

EXPLORER

...

PROBLEMS OUTPUT DEBUG CONSOLE

TERMINAL

+ - ×

GOMYCODE

learn_git

fourth.txt

```
(base) aminasamb@aminas-air GOMYCODE % mkdir learn_git
(base) aminasamb@aminas-air GOMYCODE % cd learn_git
(base) aminasamb@aminas-air learn_git % touch third.txt
(base) aminasamb@aminas-air learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@aminas-air learn_git % git add third.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding third.txt'
[master (root-commit) 8fb3997] adding third.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 third.txt
(base) aminasamb@aminas-air learn_git % git log
commit 8fb3997bcd3d88d51e396d67accab2d6963102ba (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date:   Tue Jun 28 14:34:53 2022 +0000

      adding third.txt
(base) aminasamb@aminas-air learn_git % touch fourth.txt
(base) aminasamb@aminas-air learn_git % git add fourth.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding fourth.txt'
[master 403cd74] adding fourth.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 fourth.txt
(base) aminasamb@aminas-air learn_git % git rm third.txt
rm 'third.txt'
(base) aminasamb@aminas-air learn_git % git add .
(base) aminasamb@aminas-air learn_git %
```

zsh

zsh learn_git



> OUTLINE

> TIMELINE

12

The screenshot shows a terminal window in Visual Studio Code (VS Code) with a dark theme. The terminal tab is selected at the top. The left sidebar contains icons for Explorer, Search, Find, and Outline/Timeline. The main area displays a command-line session:

```
(base) aminasamb@aminas-air GOMYCODE % mkdir learn_git
(base) aminasamb@aminas-air GOMYCODE % cd learn_git
(base) aminasamb@aminas-air learn_git % touch third.txt
(base) aminasamb@aminas-air learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@aminas-air learn_git % git add third.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding third.txt'
[master (root-commit) bc5f90d] adding third.txt
  1 file changed, 0 insertions(+), 0 deletions(-)
  create mode 100644 third.txt
(base) aminasamb@aminas-air learn_git % git log
commit bc5f90dcf4accf514a037ab0777ec52057ab3a47 (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date:  Tue Jun 28 14:52:02 2022 +0000

      adding third.txt
(base) aminasamb@aminas-air learn_git % touch fourth.txt
(base) aminasamb@aminas-air learn_git % git add fourth.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding fourth.txt'
[master 91a636e] adding fourth.txt
  1 file changed, 0 insertions(+), 0 deletions(-)
  create mode 100644 fourth.txt
(base) aminasamb@aminas-air learn_git % git rm third.txt
rm 'third.txt'
(base) aminasamb@aminas-air learn_git % git add .
(base) aminasamb@aminas-air learn_git % git commit -m'removing third.txt'
[master 010fdc3] removing third.txt
  1 file changed, 0 insertions(+), 0 deletions(-)
  delete mode 100644 third.txt
(base) aminasamb@aminas-air learn_git %
```

The terminal also shows two tabs on the right: "zsh" and "zsh learn_git". The status bar at the bottom indicates "master*" and "0 △ 0". The page number "13" is located in the bottom right corner.

EXPLORER PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

GOMYCODE

learn_git

fourth.txt

```
(base) aminasamb@aminas-air GOMYCODE % mkdir learn_git
(base) aminasamb@aminas-air GOMYCODE % cd learn_git
(base) aminasamb@aminas-air learn_git % touch third.txt
(base) aminasamb@aminas-air learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@aminas-air learn_git % git add third.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding third.txt'
[master (root-commit) a907e4c] adding third.txt
  1 file changed, 0 insertions(+), 0 deletions(-)
  create mode 100644 third.txt
(base) aminasamb@aminas-air learn_git % git log
commit a907e4c09a5c075d49fe29f240e7728e3b8ef84a (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date:  Tue Jun 28 15:23:33 2022 +0000

      adding third.txt
(base) aminasamb@aminas-air learn_git % touch fourth.txt
(base) aminasamb@aminas-air learn_git % git add fourth.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding fourth.txt'
[master 9ecfa4d] adding fourth.txt
  1 file changed, 0 insertions(+), 0 deletions(-)
  create mode 100644 fourth.txt
(base) aminasamb@aminas-air learn_git % git rm third.txt
rm 'third.txt'
(base) aminasamb@aminas-air learn_git % git add .
(base) aminasamb@aminas-air learn_git % git commit -m'removing third.txt'
[master dbc62f0] removing third.txt
  1 file changed, 0 insertions(+), 0 deletions(-)
  delete mode 100644 third.txt
(base) aminasamb@aminas-air learn_git % git log
commit dbc62f012c3309807fda4c5d71d045425fe64b59 (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date:  Tue Jun 28 15:26:02 2022 +0000

      removing third.txt

commit 9ecfa4d034d9fa85b622bdcacd16e9fb814a0ebb
Author: YOUR NAME <imanesamb07@gmail.com>
Date:  Tue Jun 28 15:25:08 2022 +0000

      adding fourth.txt

commit a907e4c09a5c075d49fe29f240e7728e3b8ef84a
Author: YOUR NAME <imanesamb07@gmail.com>
Date:  Tue Jun 28 15:23:33 2022 +0000

      adding third.txt
(base) aminasamb@aminas-air learn_git %
```

zsh

zsh learn_git

zsh learn_git

OUTLINE

TIMELINE

master* 0 △ 0

14

EXPLORER ... PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

+ - ×

GOMYCODE

learn_git

fourth.txt

```
(base) aminasamb@aminas-air GOMYCODE % mkdir learn_git
(base) aminasamb@aminas-air GOMYCODE % cd learn_git
(base) aminasamb@aminas-air learn_git % touch third.txt
(base) aminasamb@aminas-air learn_git % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/aminasamb/Desktop/GOMYCODE/learn_git/.git/
(base) aminasamb@aminas-air learn_git % git add third.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding third.txt'
[master (root-commit) a907e4c] adding third.txt
  1 file changed, 0 insertions(+), 0 deletions(-)
  create mode 100644 third.txt
(base) aminasamb@aminas-air learn_git % git log
commit a907e4c09a5c075d49fe29f240e7728e3b8ef84a (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date:  Tue Jun 28 15:23:33 2022 +0000

    adding third.txt
(base) aminasamb@aminas-air learn_git % touch fourth.txt
(base) aminasamb@aminas-air learn_git % git add fourth.txt
(base) aminasamb@aminas-air learn_git % git commit -m'adding fourth.txt'
[master 9ecfa4d] adding fourth.txt
  1 file changed, 0 insertions(+), 0 deletions(-)
  create mode 100644 fourth.txt
(base) aminasamb@aminas-air learn_git % git rm third.txt
rm 'third.txt'
(base) aminasamb@aminas-air learn_git % git add .
(base) aminasamb@aminas-air learn_git % git commit -m'removing third.txt'
[master dbc62f0] removing third.txt
  1 file changed, 0 insertions(+), 0 deletions(-)
  delete mode 100644 third.txt
(base) aminasamb@aminas-air learn_git % git log
commit dbc62f012c3309807fd4c5d71d045425fe64b59 (HEAD -> master)
Author: YOUR NAME <imanesamb07@gmail.com>
Date:  Tue Jun 28 15:26:02 2022 +0000

    removing third.txt

commit 9ecfa4d034d9fa85b622bcdcacd16e9fb814a0ebb
Author: YOUR NAME <imanesamb07@gmail.com>
Date:  Tue Jun 28 15:25:08 2022 +0000

    adding fourth.txt

commit a907e4c09a5c075d49fe29f240e7728e3b8ef84a
Author: YOUR NAME <imanesamb07@gmail.com>
Date:  Tue Jun 28 15:23:33 2022 +0000

    adding third.txt
(base) aminasamb@aminas-air learn_git % git config --global core.pager'cat'
(base) aminasamb@aminas-air learn_git %
```

zsh

zsh learn_git

zsh learn_git

OUTLINE

TIMELINE

master* ⊞ ⊖ 0 △ 0

15

EXPLORER ... PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

+ - X

GOMYCODE

learn_git

fourth.txt

```

commit 9ecfa4d034d9fa85b622bcdacd16e9fb814a0ebb
Author: YOUR NAME <imanesamb07@gmail.com>
Date: Tue Jun 28 15:25:08 2022 +0000

adding fourth.txt

commit a907e4c09a5c075d49fe29f240e7728e3b8ef84a
Author: YOUR NAME <imanesamb07@gmail.com>
Date: Tue Jun 28 15:23:33 2022 +0000

adding third.txt
(base) aminasamb@aminas-air learn_git % git config --global core.pager'cat'
(base) aminasamb@aminas-air learn_git % git config --global
usage: git config [<options>]

Config file location
--global          use global config file
--system          use system config file
--local           use repository config file
--worktree        use per-worktree config file
-f, --file <file> use given config file
--blob <blob-id> read config from given blob object

Action
--get             get value: name [value-pattern]
--get-all         get all values: key [value-pattern]
--get-regexp      get values for regexp: name-regex [value-pattern]
--get-urlmatch   get value specific for the URL: section[.var] URL
--replace-all    replace all matching variables: name value [value-pattern]
--add             add a new variable: name value
--unset           remove a variable: name [value-pattern]
--unset-all       remove all matches: name [value-pattern]
--rename-section rename section: old-name new-name
--remove-section remove a section: name
-l, --list        list all
--fixed-value    use string equality when comparing values to 'value-pattern'
-e, --edit        open an editor
--get-color      find the color configured: slot [default]
--get-colorbool  find the color setting: slot [stdout-is-tty]

Type
-t, --type <type> value is given this type
--bool            value is "true" or "false"
--int             value is decimal number
--bool-or-int    value is --bool or --int
--bool-or-str    value is --bool or string
--path            value is a path (file or directory name)
--expiry-date   value is an expiry date

Other
-z, --null        terminate values with NUL byte
--name-only      show variable names only
--includes        respect include directives on lookup
--show-origin     show origin of config (file, standard input, blob, command line)
--show-scope      show scope of config (worktree, local, global, system, command)
--default <value> with --get, use default value when missing entry

```

(base) aminasamb@aminas-air learn_git %

zsh
zsh learn_git
zsh learn_git

16

EXPLORER ... PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL + × ×

zsh
zsh learn_git
zsh learn_git

GOMYCODE

learn_git

fourth.txt

adding third.txt
(base) aminasamb@aminas-air learn_git % git config --global core.pager'cat'
(base) aminasamb@aminas-air learn_git % git config --global
usage: git config [<options>]

Config file location

--global	use global config file
--system	use system config file
--local	use repository config file
--worktree	use per-worktree config file
-f, --file <file>	use given config file
--blob <blob-id>	read config from given blob object

Action

--get	get value: name [value-pattern]
--get-all	get all values: key [value-pattern]
--get-regexp	get values for regexp: name-regex [value-pattern]
--get-urlmatch	get value specific for the URL: section[.var] URL
--replace-all	replace all matching variables: name value [value-pattern]
--add	add a new variable: name value
--unset	remove a variable: name [value-pattern]
--unset-all	remove all matches: name [value-pattern]
--rename-section	rename section: old-name new-name
--remove-section	remove a section: name
-l, --list	list all
--fixed-value	use string equality when comparing values to 'value-pattern'
-e, --edit	open an editor
--get-color	find the color configured: slot [default]
--get-colorbool	find the color setting: slot [stdout-is-tty]

Type

-t, --type <type>	value is given this type
--bool	value is "true" or "false"
--int	value is decimal number
--bool-or-int	value is --bool or --int
--bool-or-str	value is --bool or string
--path	value is a path (file or directory name)
--expiry-date	value is an expiry date

Other

-z, --null	terminate values with NUL byte
--name-only	show variable names only
--includes	respect include directives on lookup
--show-origin	show origin of config (file, standard input, blob, command line)
--show-scope	show scope of config (worktree, local, global, system, command)
--default <value>	with --get, use default value when missing entry

(base) aminasamb@aminas-air learn_git % git config --list

credential.helper=osxkeychain
user.name=YOUR NAME
user.email=imanesamb07@gmail.com
core.repositoryformatversion=0
core.filemode=true
core.bare=false
core.logallrefupdates=true
core.ignorecase=true
core.precomposeunicode=true

(base) aminasamb@aminas-air learn_git %

> OUTLINE
> TIMELINE

master* ↻ ⊞ ⊖ 0 △ 0

17