

Student Task Manager

Login Form

Overview

A full login/registration feature was added: a JWT-based auth backend (Express + Mongoose, matching the existing Task API's style) and a React login page designed using the installed ui-ux-pro-max skill for accessibility and form UX guidance.

Per instruction, the database was kept local and was NOT connected or run live during this work. Everything below was verified with compile-only checks (bundling and linting) rather than a live server + MongoDB session. See 'How to run' for the steps to actually try it.

Backend changes

server/models/User.ts (new)

Mongoose schema for user accounts.

- Fields: name, email (unique, lowercase, validated format), password (min 8 chars, select: false by default)

- A pre-

server/routes/auth.ts (new)

Two endpoints, mounted at /api/auth:

- POST /api/auth/register - creates a user, returns { token, user }

- POST

server/index.ts (modified)

- Mounted the new auth router: app.use('/api/auth', auth)

- Exten

409 'An

server/env.example and server/.env (modified)

Added two variables:

```
JWT_SECRET=<random 64-char hex string>
JWT_EXPIRES_IN=7d
```

server/.env already existed locally (gitignored) from earlier setup; a real random secret was generated with `openssl rand -hex 32` and appended to it. server/env.example only documents the variable with a placeholder value.

server/package.json (modified)

New dependencies:

```
bcryptjs      ^3.0.3    (password hashing)
jsonwebtoken  ^9.0.3    (JWT sign/verify)
@types/jsonwebtoken ^9.0.10    (dev)
```

Verification performed (no live DB connection)

- bun install in server/ - dependencies resolved cleanly

- bun b
catches

Frontend changes

client/src/components/AuthPage.jsx (new)

A single component handling both login and registration, toggled in place (no router in this project, so it follows the existing tab-toggle pattern already used for task filters).

- Fields: name + confirm-password only shown in register mode; email + password always shown

- Client
confirm-

client/src/api.js (modified)

- New exported `auth` object: auth.register(), auth.login(), auth.logout(), auth.isAuthenticated()

- The J

client/src/App.jsx (modified)

- App now gates on auth: if no token is stored, it renders <AuthPage /> instead of the task manager

- On su

client/src/index.css (modified)

New rules reuse the project's existing CSS custom properties (--accent, --card, --line, --danger, etc.), including the existing dark-mode block, so the login page matches the task manager's look automatically in both themes.

- .auth / .auth-card - centered card layout for the login/register form

- .field-c

Verification performed

- bun run build (vite) - built cleanly, 75 modules, no errors

- bun r
conditio
and swit

Design guidance applied (ui-ux-pro-max skill)

Specific rules pulled from the skill's UX guideline search and applied directly:

- Form Labels: inputs must have an associated label, not placeholder-only text

- Passw

How to run it

Not run live during this session per instruction. To try it yourself:

```
# 1. Start MongoDB locally (already installed via Homebrew)
brew services start mongodb-community

# 2. Backend
cd server
bun install
bun run dev          # http://localhost:5001 (see server/.env for PORT)

# 3. Frontend, in a second terminal
cd client
bun install
bun run dev          # http://localhost:5173

# 4. Open the app, click 'Sign up', create an account, then sign in.
```

Security notes

- server/.env holds the real JWT secret and is gitignored - never commit it

- Passw
(select:

Not done yet / suggested next steps

- /api/tasks is still unauthenticated - the JWT is issued and attached to requests, but nothing on the server checks it yet. To make tasks per-user: add an auth middleware that verifies the JWT and attaches req.userId, add an 'owner' field to the Task model, and filter/scope all task queries by it.

- Logge
name/en