## WHILE (Transact-SQL)

03/15/2017 • 2 minutes to read • 🤱 📵 🌑 🦜 🐑 +1

#### In this article

**Syntax** 

**Arguments** 

Remarks

Examples

Examples: Azure SQL Data Warehouse and Parallel Data Warehouse

See Also

**APPLIES TO:** SQL Server ✓ Azure SQL Database ✓ Azure SQL Data Warehouse ✓ Parallel Data Warehouse

Sets a condition for the repeated execution of an SQL statement or statement block. The statements are executed repeatedly as long as the specified condition is true. The execution of statements in the WHILE loop can be controlled from inside the loop with the BREAK and CONTINUE keywords.

Transact-SQL Syntax Conventions

## **Syntax**

```
-- Syntax for SQL Server and Azure SQL Database

WHILE Boolean_expression
{ sql_statement | statement_block | BREAK | CONTINUE }
```

```
-- Syntax for Azure SQL Data Warehouse and Parallel Data Warehouse

WHILE Boolean_expression
{ sql_statement | statement_block | BREAK }
```

## **Arguments**

#### Boolean\_expression

Is an <u>expression</u> that returns **TRUE** or **FALSE**. If the Boolean expression contains a SELECT statement, the SELECT statement must be enclosed in parentheses.

#### {sql\_statement | statement\_block}

Is any Transact-SQL statement or statement grouping as defined with a statement block. To define a statement block, use the control-of-flow keywords BEGIN and END.

#### **BREAK**

Causes an exit from the innermost WHILE loop. Any statements that appear after the END keyword, marking the end of the loop, are executed.

#### CONTINUE

Causes the WHILE loop to restart, ignoring any statements after the CONTINUE keyword.

## Remarks

If two or more WHILE loops are nested, the inner BREAK exits to the next outermost loop. All the statements after the end of the inner loop run first, and then the next outermost loop restarts.

## **Examples**

## A. Using BREAK and CONTINUE with nested IF...ELSE and WHILE

In the following example, if the average list price of a product is less than \$300, the WHILE loop doubles the prices and then selects the maximum price. If the maximum price is less than or equal to \$500, the WHILE loop restarts and doubles the prices again. This loop continues doubling the prices until the maximum price is greater than \$500, and then exits the WHILE loop and prints a message.

```
USE AdventureWorks2012;

GO

WHILE (SELECT AVG(ListPrice) FROM Production.Product) < $300

BEGIN

UPDATE Production.Product

SET ListPrice = ListPrice * 2

SELECT MAX(ListPrice) FROM Production.Product

IF (SELECT MAX(ListPrice) FROM Production.Product) > $500

BREAK

ELSE
```

```
CONTINUE
END
PRINT 'Too much for the market to bear';
```

### B. Using WHILE in a cursor

The following example uses <code>@@FETCH\_STATUS</code> to control cursor activities in a <code>while</code> loop.

```
Copy
DECLARE @EmployeeID as nvarchar(256)
DECLARE @Title as nvarchar(50)
DECLARE Employee_Cursor CURSOR FOR
SELECT LoginID, JobTitle
FROM AdventureWorks2012.HumanResources.Employee
WHERE JobTitle = 'Marketing Specialist';
OPEN Employee Cursor;
FETCH NEXT FROM Employee Cursor;
FETCH NEXT FROM Employee_Cursor INTO @EmployeeID, @Title;
WHILE @@FETCH STATUS = 0
   BEGIN
      Print ' ' + @EmployeeID + '
                                         '+ @Title
      FETCH NEXT FROM Employee Cursor;
   END;
CLOSE Employee_Cursor;
DEALLOCATE Employee_Cursor;
GO
```

# Examples: Azure SQL Data Warehouse and Parallel Data Warehouse

## C: Simple While Loop

In the following example, if the average list price of a product is less than \$300, the WHILE loop doubles the prices and then selects the maximum price. If the maximum price is less than or equal to \$500, the WHILE loop restarts and doubles the prices again. This loop continues doubling the prices until the maximum price is greater than \$500, and then exits the WHILE loop.

```
-- Uses AdventureWorks

WHILE ( SELECT AVG(ListPrice) FROM dbo.DimProduct) < $300
```

```
BEGIN
    UPDATE dbo.DimProduct
    SET ListPrice = ListPrice * 2;
    SELECT MAX ( ListPrice) FROM dbo.DimProduct
    IF ( SELECT MAX (ListPrice) FROM dbo.DimProduct) > $500
        BREAK;
END
```

## **See Also**

ALTER TRIGGER (Transact-SQL).

Control-of-Flow Language (Transact-SQL).

CREATE TRIGGER (Transact-SQL).

Cursors (Transact-SQL).

SELECT (Transact-SQL).