

```

from pathlib import Path
from typing import List, Tuple, Dict
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from sklearn.preprocessing import StandardScaler
from sklearn.metrics import (
    confusion_matrix,
    ConfusionMatrixDisplay,
    roc_curve,
    auc,
    precision_recall_curve,
    PrecisionRecallDisplay,
    RocCurveDisplay,
)
from minisom import MiniSom

# trains a SOM on the input data
def fit_som(data: np.ndarray, grid: Tuple[int, int] = (22, 22), seed:
int = 42) -> MiniSom:
    rows, cols = grid # SOM grid dimensions set to 22x22
    som = MiniSom(
        x=rows, y=cols,
        input_len=data.shape[1], # number of features
        sigma=3.0, # spread of the neighborhood
        learning_rate=0.5, # speed of learning
        neighborhood_function="gaussian", # type of neighborhood
    )
    som.random_weights_init(data)
    som.train_batch(data, num_iteration=10_000, verbose=False) #
train the SOM
    return som

# create a lookup table from each SOM node BMU to a majority label
def majority_vote_lookup(som: MiniSom, data: np.ndarray, labels:
np.ndarray) -> Dict[Tuple[int, int], int]:
    vote: Dict[Tuple[int, int], List[int]] = {}

    for vec, lbl in zip(data, labels): # go through
each data point and its label
        bmu = som.winner(vec) # find best-
matching unit (BMU) for the vector
        vote.setdefault(bmu, []).append(lbl) # collect all
labels that map to this BMU

    # assign each BMU the most common label (rounded average)
    return {bmu: int(round(np.mean(v))) for bmu, v in vote.items()}

```

```

# predict labels for new data using the trained SOM and the vote map
def predict_som(som: MiniSom, vote_map: Dict[Tuple[int, int], int],
data: np.ndarray) -> np.ndarray:
    # for each input vector, find its BMU and use the vote_map to
    assign a predicted label
    return np.array([vote_map.get(som.winner(v), 0) for v in data])

import time
import psutil
import os

# performs cross-validation using a Self-Organizing Map (SOM)
def som_cross_validate(Syn_df: pd.DataFrame, feature_columns:
List[str], grid: Tuple[int, int] = (22, 22)) -> List[float]:
    accuracies = []
    process = psutil.Process(os.getpid())
    oof_true, oof_score = [], []

    # resource monitoring starting
    overall_start_time = time.time()
    overall_start_ram = process.memory_info().rss / 1024 / 1024 # in
MB
    overall_start_cpu = psutil.cpu_percent(interval=1)

    # loop over each fold in the dataset
    for fold in sorted(Syn_df["Fold"].unique()):
        train_df = Syn_df[Syn_df["Fold"] != fold]
        validate_df = Syn_df[Syn_df["Fold"] == fold]

        scaler = StandardScaler()
        X_train = scaler.fit_transform(train_df[feature_columns])
        X_validate = scaler.transform(validate_df[feature_columns])
        y_train = train_df["Label"].values
        y_validate = validate_df["Label"].values

        som = fit_som(X_train, grid)
        vote_map = majority_vote_lookup(som, X_train, y_train)
        y_predict = predict_som(som, vote_map, X_validate)

    # plot U-Matrix for each fold
    plt.figure(figsize=(10, 8))
    u_matrix = som.distance_map()
    plt.imshow(u_matrix, cmap='bone_r')
    plt.colorbar(label='Distance')
    plt.title(f'SOM U-Matrix - Fold {fold+1}')
    plt.savefig(f"som_umatrix_fold_{fold+1}.png", dpi=300,
bbox_inches="tight")
    plt.show()
    plt.close()

```

```

# accuracy
acc = (y_predict == y_validate).mean()
accuracies.append(float(acc))
print(f"Fold {fold+1}: accuracy = {acc:.4f}")

oof_true.extend(y_validate.tolist())
oof_score.extend(y_predict.tolist())

cm = confusion_matrix(oof_true, oof_score)
ConfusionMatrixDisplay(confusion_matrix=cm).plot(cmap="Blues")
plt.title("SOM Confusion Matrix")
plt.show()

fpr, tpr, _ = roc_curve(oof_true, oof_score)
roc_auc = auc(fpr, tpr)
RocCurveDisplay(fpr=fpr, tpr=tpr, roc_auc=roc_auc).plot()
plt.title("SOM ROC Curve")
plt.show()

prec, rec, _ = precision_recall_curve(oof_true, oof_score)
PrecisionRecallDisplay(precision=prec, recall=rec).plot()
plt.title("SOM Precision-Recall Curve")
plt.show()

# end of resource monitoring
overall_end_time = time.time()
overall_end_ram = process.memory_info().rss / 1024 / 1024 # in MB
overall_end_cpu = psutil.cpu_percent(interval=1)

# results
print("\n===== SOM Validation Summary =====")
for i, a in enumerate(accuracies, 1):
    print(f"Fold {i}: {a:.4f}")
print(f"Mean Accuracy: {np.mean(accuracies):.4f}")
print(f"Standard Deviation: {np.std(accuracies):.4f}")

# resources used
print("\n Overall Training Stats ")
print(f"Total Training Time: {overall_end_time - overall_start_time:.2f} seconds")
print(f"Total RAM Usage Increase: {overall_end_ram - overall_start_ram:.2f} MB")
print(f"CPU Usage (at final check): {overall_end_cpu}%")

return accuracies

# Load the dataset
Syn_df = pd.read_csv("D:\Coding Projects\Detection-of-SYN-Flood-

```


```
Attacks-Using-Machine-Learning-and-Deep-Learning-Techniques-with-  
Feature-Base\Data\K5_Dataset.csv")
```

```
# select first 12 feature columns (exclude label and fold info)  
feature_columns = Syn_df.columns.difference(["Label",  
"Fold"]).tolist()[:12]
```


```
# run cross-validation using a Self-Organizing Map  
accs = som_cross_validate(Syn_df, feature_columns)  
print("\nFinal SOM Cross-Validation Results:")  
print(f"Fold Accuracies: {accs}")
```

```
# save the notebook as a web PDF  
os.getcwd()
```


```
!jupyter nbconvert --to webpdf "d:\\Coding Projects\\Detection-of-SYN-  
Flood-Attacks-Using-Machine-Learning-and-Deep-Learning-Techniques-  
with-Feature-Base\\Taulant Matarova\\SOM_model_finalv2.ipynb"
```




Fold 1: accuracy = 0.9979




Fold 2: accuracy = 0.9984




Fold 3: accuracy = 0.9958





Fold 4: accuracy = 0.9974



Fold 5: accuracy = 0.9964







==== SOM Validation Summary ====

Fold 1: 0.9979

Fold 2: 0.9984

Fold 3: 0.9958

Fold 4: 0.9974

Fold 5: 0.9964

Mean Accuracy: 0.9972

Standard Deviation: 0.0010

Overall Training Stats

Total Training Time: 5.65 seconds

Total RAM Usage Increase: 27.32 MB

CPU Usage (at final check): 5.8%

Final SOM Cross-Validation Results:

Fold Accuracies: [0.9979177511712649, 0.9984383133784487, 0.9958355023425299, 0.9973971889640812, 0.9963541666666667]

[NbConvertApp] Converting notebook d:\\Coding Projects\\Detection-of-SYN-Flood-Attacks-Using-Machine-Learning-and-Deep-Learning-Techniques-with-Feature-Base\\Taulant Matarova\\SOM_model_finalv2.ipynb to webpdf
[NbConvertApp] Building PDF

```
[NbConvertApp] PDF successfully created  
[NbConvertApp] Writing 99241 bytes to d:\Coding Projects\Detection-of-  
SYN-Flood-Attacks-Using-Machine-Learning-and-Deep-Learning-Techniques-  
with-Feature-Base\Taulant Matarova\SOM_model_finalv2.pdf
```