



# **Data Science Intern at Data Glacier**

## **Week 5: Cloud API Development**

**Name:** Amir Ali

**Batch Code:** LISUM08

**Date:** 04 April 2022

**Submitted to:** Data Glacier

## Table of Contents:

1. Introduction .....	3
2. Data Information .....	4
2.1.Attribute Information .....	4
3. Build Machine Learning Model .....	5
4. Turning Model into Flask Framework .....	6
4.1.App.py .....	7
4.2.Home.html .....	8
4.3.Style.css .....	9
4.4.Result.html .....	9
4.5.Running Procedure .....	10
5. Model Development using Heroku .....	12
5.1.Steps for Model Development using Heroku .....	12

# 1. Introduction

In this project, we are going to deploying machine learning model (SVM) using the Flask Framework. As a demonstration, our model help to predict the spam and ham comment of YouTube.




Figure 1.1: Application Workflow

we will focus on both: building a machine learning model for YouTube Comments SD, then create an API for the model, using Flask, the Python micro-framework for building web applications. This API allows us to utilize predictive capabilities through HTTP requests.

## 2. Data Information

The samples were extracted from the comments section of five videos that were among the 10 most viewed on YouTube during the collection period. The table below lists the datasets, the YouTube video ID, the number of samples in each class and the total number of samples per dataset.

Table 2.1: Dataset Information

Dataset	YouTube ID	Spam	Ham	Total
Psy	9bZkp7q19f0	175	175	350
KatyPerry	CevxZvSJLk8	175	175	350
LMFAO	KQ6zr6kCPj8	236	202	438
Eminem	uelHwf8o7_U	245	203	448
Shakira	pRpeEdMmmQ0	174	196	370

## 2.1 Attribute Information

The collection is composed of one CSV file per dataset, where each line has the following attributes:

Table 2.2: Attribute Information

Attributes	Example (1 instance)
COMMENT_ID	LZQPQhLyRh80UYxNuaDWhIGQYNQ96luCg-AYWqNPjpU
AUTHOR	Julius NM
DATE	2013-11-07 T 06:20:48
CONTENT	Huh, anyway check out this YouTube channel: kobyoshi02
Class	1 (Spam)

## 3. Building a Model

### 3.1 Import Required Libraries and Dataset

In this part, we import libraires and dataset which contain the information of five most commented video.

```
In [1]: # Import Libraries & Packages
import numpy as np          # Import Numpy for data statistical analysis
import pandas as pd         # Import Pandas for data manipulation using dataframes
import seaborn as sns      # Statistical data visualization
import matplotlib.pyplot as plt # Import matplotlib for data visualisation

In [2]: # Import Youtube Ham or Spam dataset taken from UCI
df1 = pd.read_csv("dataset/Youtube01-Psy.csv")      # Psy youtube channel most viewed video comments dataset
df2 = pd.read_csv("dataset/Youtube02-KatyPerry.csv") # KatyPerry youtube channel most viewed video comments dataset
df3 = pd.read_csv("dataset/Youtube03-LMFAO.csv")    # Psy LMFAO channel most viewed video comments dataset
df4 = pd.read_csv("dataset/Youtube04-Eminem.csv")   # Eminem youtube channel most viewed video comments dataset
df5 = pd.read_csv("dataset/Youtube05-Shakira.csv")  # Shakira youtube channel most viewed video comments dataset

In [3]: # Merge all the dataset into single file
frames = [df1,df2,df3,df4,df5]                    # make a list of all file
df_merged = pd.concat(frames)                      # concatenate the all the file into single
keys = ["Psy","KatyPerry","LMFAO","Eminem","Shakira"] # Merging with Keys
df_with_keys = pd.concat(frames,keys=keys)          # concatenate data with keys
dataset=df_with_keys

In [4]: # Infomation about dataset
print(dataset.size)                                # size of dataset
print(dataset.shape)                               # shape of dataset
print(dataset.keys())                              # attributes of dataset

9780
(1956, 5)
Index(['COMMENT_ID', 'AUTHOR', 'DATE', 'CONTENT', 'CLASS'], dtype='object')
```



## 4. Turning Model into Web Application

We develop a web application that consists of a simple web page with a form field that lets us enter a message. After submitting the message to the web application, it will render it on a new page which gives us a result of spam or ham(not spam).

First, we create a folder for this project called YouTube Spam Filtering, this is the directory tree inside the folder. We will explain each file.

Table 3.1: Application Folder File Directory

<b>app.py</b>
<b>templates/</b>
home.html
result.html
<b>static/</b>
style.css
<b>model/</b>
model.pkl
<b>dataset/</b>
Youtube01-Psy.csv
Youtube02-KatyPerry.csv
Youtube03-LMFAO.csv
Youtube04-Eminem.csv
Youtube05-Shakira.csv

The sub-directory templates are the directory in which Flask will look for static HTML files for rendering in the web browser, in our case, we have two HTML files: *home.html* and *result.html*.

### 4.1 App.py

The *app.py* file contains the main code that will be executed by the Python interpreter to run the Flask web application, it included the ML code for classifying SD.

```

@app.route('/')
def home():
    return render_template('home.html')

@app.route('/predict',methods=['POST'])
def predict():
    df1 = pd.read_csv("dataset/Youtube01-Psy.csv")           # Psy youtube channel most viewed video comments dataset
    df2 = pd.read_csv("dataset/Youtube02-KatyPerry.csv")    # KatyPerry youtube channel most viewed video comments dataset
    df3 = pd.read_csv("dataset/Youtube03-LMFAO.csv")        # Psy LMFAO channel most viewed video comments dataset
    df4 = pd.read_csv("dataset/Youtube04-Eminem.csv")       # Eminem youtube channel most viewed video comments dataset
    df5 = pd.read_csv("dataset/Youtube05-Shakira.csv")      # Shakira youtube channel most viewed video comments dataset

    # Merge all the dataset into single file
    frames = [df1,df2,df3,df4,df5]                        # make a list of all file
    df_merged = pd.concat(frames)                          # concatenate the all the file into single
    keys = ["Psy","KatyPerry","LMFAO","Eminem","Shakira"]  # Merging with Keys
    df_with_keys = pd.concat(frames,keys=keys)             # concatenate data with keys
    dataset=df_with_keys

    # working with text content
    dataset = dataset[["CONTENT" , "CLASS"]]               # context = comments of viewers & Class = ham or Spam

    # Predictor and Target attribute
    dataset_X = dataset['CONTENT']                         # predictor attribute
    dataset_y = dataset['CLASS']                          # target attribute

    # Extract Feature With TF-IDF model
    corpus = dataset_X                                    # declare the variable
    cv = TfidfVectorizer()                                # initialize the TF-IDF model
    X = cv.fit_transform(corpus).toarray()                # fit the corpus data into BOW model

    # import pickle file of my model
    model = open("model/model.pkl","rb")
    clf = pickle.load(model)

    if request.method == 'POST':
        comment = request.form['comment']
        data = [comment]
        vect = cv.transform(data).toarray()
        my_prediction = clf.predict(vect)
        return render_template('result.html',prediction = my_prediction)

if __name__ == '__main__':
    app.run(debug=True)

```

Figure 3.1: App.py

- We ran our application as a single module; thus we initialized a new Flask instance with the argument `__name__` to let Flask know that it can find the HTML template folder (*templates*) in the same directory where it is located.
- Next, we used the route decorator (`@app.route('/')`) to specify the URL that should trigger the execution of the home function.
- Our *home* function simply rendered the *home.html* HTML file, which is located in the *templates* folder.
- Inside the *predict* function, we access the spam data set, pre-process the text, and make predictions, then store the model. We access the new message entered by the user and use our model to make a prediction for its label.

- we used the *POST* method to transport the form data to the server in the message body. Finally, by setting the *debug=True* argument inside the *app.run* method, we further activated Flask's debugger.
- Lastly, we used the *run* function to only run the application on the server when this script is directly executed by the Python interpreter, which we ensured using the *if* statement with `__name__ == '__main__'`.

## 4.2 Home.html

The following are the contents of the *home.html* file that will render a text form where a user can enter a message.

```
<!DOCTYPE html>
<html>
<head>
  <title>Home</title>
  <!-- <link rel="stylesheet" type="text/css" href="../static/css/styles.css"> -->
  <link rel="stylesheet" type="text/css" href="{{ url_for('static', filename='css/styles.css') }}">
</head>
<body>

  <header>
    <div class="container">

      <h2>Youtube Comments Spam Detection</h2>

    </div>
  </header>

  <div class="ml-container">

    <form action="{{ url_for('predict') }}" method="POST">
      <p>Enter Your Comment Here</p>
      <!-- <input type="text" name="comment"/> -->
      <textarea name="comment" rows="4" cols="50"></textarea>
      <br/>

      <input type="submit" class="btn-info" value="predict">

    </form>

  </div>

</body>
</html>
```

Figure 3.2: Home.html



## 4.3 Style.css

In the header section of *home.html*, we loaded *styles.css* file. CSS is to determine how the look and feel of HTML documents. *styles.css* has to be saved in a sub-directory called *static*, which is the default directory where Flask looks for static files such as CSS.

## 4.4 Result.html

we create a *result.html* file that will be rendered via the `render_template('result.html', prediction=my_prediction)` line return inside the *predict* function, which we defined in the *app.py* script to display the text that a user-submitted via the text field.

From *result.html* we can see that some code using syntax not normally found in HTML files: `{% if prediction == 1%},{% elif prediction == 0%},{% endif %}` This is Jinja syntax, and it is used to access the prediction returned from our HTTP request within the HTML file.

```
<!DOCTYPE html>
<html>
<head>
  <title></title>
  <link rel="stylesheet" type="text/css" href="{ { url_for('static', filename='css/styles.css') } }">
</head>
<body>

  <header>
    <div class="container">

      <h2>YouTube Comments Spam Detection</h2>

    </div>
  </header>
  <p style="color:black;font-size:20;text-align: center;"><b>Results for Comment</b></p>
  <div class="results">

    {% if prediction == 1%}
    <h2 style="color:red;">Spam</h2>
    {% elif prediction == 0%}
    <h2 style="color:green;">Not a Spam (It is a Ham)</h2>
    {% endif %}

  </div>

</body>
</html>
```

Figure 3.3: Result.html

## 4.5 Running Procedure

Once we have done all of the above, we can start running the API by either double click `app.py`, or executing the command from the Terminal:

```
C:\Users\amira\Final Year Projects\1. Youtube Spam Filtering\3. ML Web Application>python app.py
* Serving Flask app "app" (lazy loading)
* Environment: production
  WARNING: This is a development server. Do not use it in a production deployment.
  Use a production WSGI server instead.
* Debug mode: on
* Restarting with stat
* Debugger is active!
* Debugger PIN: 156-226-423
* Running on http://127.0.0.1:5000/ (Press CTRL+C to quit)
```

Figure 3.4: Command Execution

Now we could open a web browser and navigate to <http://127.0.0.1:5000/>, we should see a simple website with the content like so




Figure 3.5: Spam Detection Website Page


Now we enter input in the comments form



The image shows a web interface for 'YouTube Comments Spam Detection' by Amir Ali. It features a red header with the title and a 'predict' button. Below the header is a text input field containing the comment: 'Huh, anyway check out this YouTube channel: kobyoshi02'. The input field is labeled 'Enter Your Comment Here'.

Figure 3.6: Input In The Comments Form

After entering the input click the predict button now, we can the result of our input.



The image shows the result of the spam detection. The header is the same as in Figure 3.6. Below the header, the text 'Results for Comment' is displayed. The result is 'Spam', shown in red text.

Figure 3.7: Result of Given Input

## 5. Model deployment using Heroku

We're ready to start our Heroku deployment now that our model has been trained, the machine learning pipeline has been set up, and the application has been tested locally. There are a few ways to upload the application source code onto Heroku. The easiest way is to link a GitHub repository to your Heroku account.


### Requirement.txt

It is a text file containing the python packages required to execute the application.

### 5.1 Steps for Model Deployment Using Heroku

Once we uploaded files to the GitHub repository, we are now ready to start deployment on Heroku. Follow the steps below:

1. After sign up on **heroku.com** then click on **Create new app**.



## 2. Enter App name and region

App name

youtube-comment-detection-api



youtube-comment-detection-api is available

Choose a region

United States

Add to pipeline...

Create app

## 3. Connect to GitHub repository where code is I uploaded.

Deployment method



Heroku Git  
Use Heroku CLI



GitHub  
Connected



Container Registry  
Use Heroku CLI

After that I choose the repository where I upload the code.

AmirAli5 / Cloud-and-API-deployment (Public)

< Code Issues Pull requests Actions Projects Wiki Security Insights Settings

main 1 branch 0 tags

Go to file Add file Code

AmirAli5 Add files via upload f7d99b9 7 days ago 2 commits		
model	Add files via upload	7 days ago
static/css	Add files via upload	7 days ago
templates	Add files via upload	7 days ago
Procfile	Add files via upload	7 days ago
README.md	Initial commit	7 days ago
app.py	Add files via upload	7 days ago
requirements.txt	Add files via upload	7 days ago

About

Deployment of ML models in Heroku using FLASK

Readme

0 stars

1 watching

0 forks

Releases

No releases published

Create a new release

## 4. Deploy branch

### Automatic deploys

Enables a chosen branch to be automatically deployed to this app.

### Enable automatic deploys from GitHub

Every push to the branch you specify here will deploy a new version of this app. **Deploys happen automatically:** be sure that this branch is always in a deployable state and any tests have passed before you push. [Learn more.](#)

#### Choose a branch to deploy

🔽 master ↕

☐ Wait for CI to pass before deploy

Only enable this option if you have a Continuous Integration service configured on your repo.

**Enable Automatic Deploys**

### Manual deploy

Deploy the current state of a branch to this app.

### Deploy a GitHub branch

This will deploy the current state of the branch you specify below. [Learn more.](#)

#### Choose a branch to deploy

🔽 master ↕

**Deploy Branch**



## 5. After waiting 5 to 15 minutes our application is Ready

### Manual deploy

Deploy the current state of a branch to this app.

### Deploy a GitHub branch

This will deploy the current state of the branch you specify below. [Learn more.](#)

#### Choose a branch to deploy

🔽 master ↕

**Deploy Branch**

Receive code from GitHub



Build **master** 3a3e6e70



Release phase



Deploy to Heroku



Your app was successfully deployed.



View

The app is published at

<https://youtube-comments-detection-api.herokuapp.com/>