


Statically-typed Class-based languages – Scala

<http://d3s.mff.cuni.cz>



FACULTY
OF MATHEMATICS
AND PHYSICS
Charles University

Tomas Bures

bures@d3s.mff.cuni.cz

Scala

- Statically-typed language
- Compiles to bytecode
- Modern concepts

- Example: E01

Syntax inference

- A line ending is treated as a semicolon unless one of the following conditions is true:
 - The line in question ends in a word that would not be legal as the end of a statement, such as a period or an infix operator.
 - The next line begins with a word that cannot start a statement.
 - The line ends while inside parentheses (...) or brackets [...], because these cannot contain multiple statements anyway.
- Blocks are based on indentation
 - Possible to use curly braces (version 2 syntax)

Static vs. dynamic typing

- Target function is determined
 - at compile time – static typing
 - at runtime – dynamic typing
- Example: E02

Classes vs. objects

- Scala does not have static method
- Instead it features a singleton object
 - Defines a class and a singleton instance
- Example: E03
- Decompiled – AppLogger, Logger

Type inference

- Types can be omitted – they are inferred automatically
 - At compile time
- Example: E04

Type Hierarchy

- Everything is an object
 - primitive data types behind the scene (boxing/unboxing)
- Compiler optimizes the use of primitive types
 - a primitive type is used if possible

Companion object

- A class and object may have the same name
 - Must be defined in the same source
- Then the class and object may access each others private fields
- Example: E05

Constructors

- One primary constructor
 - class parameters
 - can invoke superclass constructor
- Auxiliary constructors
 - must invoke the primary constructor (as the first one)
 - must not invoke superclass constructor

Operators

- Scala allows almost arbitrary method names (including operators)
- A method may be called without a dot
- Prefix operators have special names
- Example: E06

Flexibility in Identifiers and Operators

- Alphanumeric identifier
 - starts with letter or underscore
- Operator identifier
 - an operator character belongs to the Unicode set of mathematical symbols(Sm) or other symbols(So), or to the 7-bit ASCII characters that are not letters, digits
 - any sequence of them
- Mixed identifier
 - e.g. unary_- to denote a prefix operator
- Literal identifier
 - with backticks (e.g. `class`) to avoid clashes with reserved words, etc.

Operator precedences

- Operator precedence determined by the first character
 - Only if the operator ends with "=", the last character is used

(all other special characters)

* / %

+ -

:

= !

< >

&

^

|

(all letters)

(all assignment operators)

Extensions

- Similar to C#, Scala makes it possible to declare an extension of an existing type
- The extensions have to be brought to scope
 - Typically imported
- Example: E07

Context parameters (aka givens)

- Scala allows naming instances (called “givens”) that define canonical values of certain types
 - used to synthesize arguments for context parameters
- Givens have to be brought to scope to be applicable
 - Special import notation
- Example: E08

Implicit conversions

- Scala allows specifying functions that are applied automatically to make the code correct
 - conversion to the type of the argument or to the type of the receiver
 - the conversion is brought in as a “given” – same rules apply for making it visible as for other givens
- Example: E09 + H1

Rich wrappers

- Implicit conversions used to implement so called Rich wrappers
- Standard library contains rich types for the basic ones
 - E.g. RichInt – defines methods to, until, ...

Namespaces

- Scala allows groups classes to packages (similar to Java and C#)
- Similar to C#, it allows defining multiple classes and even packages in the same file
- Example: E10

First-class functions

- Functions are first-class citizens
- May be passed as parameters
- Anonymous functions, ...
- Anonymous functions are instances of classes
 - Function1, Function2, ...
- Example: E11

Tail recursion

- The compiler can do simple tail recursion
 - If the return value of a function is a recursive call to the function itself
- Example: E12

For-comprehension


- Generalized for-loops
 - generators, definitions, filters
- Translated to operations over collections
 - map, flatMap, withFilter, foreach
- Example: E13

Traits

- Scala does not have interfaces
 - It has something stronger – mixins (called traits)
- A trait is like an interface, but allows for defining methods and variables
- Example: E14

Linearization

- As opposed to multiple inheritance, traits do not suffer from the diamond problem
- This is because the semantics of super is determined only when the final type is defined
- Example: E15



Composing Traits

- Composition of traits can be used to address the same problem as Dependency injection addresses
 - “Cake pattern”
- Example: E16

Abstract types

- What about if we want methods in a subclass to specialize method parameters?
- Example: E17 + H2

Embedding and exporting

- Alternative to composing functionalities by traits
- Instead of extending a class, an object is embedded and its methods are exported on the interface
 - Invocation of those methods act on the embedded object
- This is similar to type embedding in Go
 - But since Go lacks inheritance or mixins, the embedding (with all its limits) is the only way of composing functionality
- Example E18

New control structures

- Currying – function that returns function
- By-name parameters
 - omitting empty parameter list in an anonymous function
- Example: E19

Case-classes, pattern matching

- Scala allows for simple pattern matching (similar to Prolog terms)
- Case-classes
 - factory method (no new necessary)
 - all parameters are vals
- Example: E20

Case sequences & Partial functions

- Functions may be defined as case sequences
 - It's like a function with more entry points
- Since the case sequence does not have to cover all cases, it yields a partial function
 - Partial function may be queried if a given value is in its domain
 - or it throws a runtime exception if called with an unsupported input argument
- Example: E21 + H3

Extractors

- Pattern matching relies on method unapply
 - apply – takes arguments, returns an object
 - unapply – takes an object, returns a tuple or sequence of arguments
- Allows creating custom matchers
- Example: E22, E23

String interpolation

- String interpolation implemented by rewriting code at compile time
- Standard interpolators
 - s – interpolator

```
val name = "reader"
println(s"Hello, $name!")
```
 - raw – interpolator

```
println(raw"No\\\\\\escape!") // prints: No\\\\\\escape!
```
 - f – interpolator (printf-like formatter)

```
f"${math.Pi}%.5f"
```
- Custom interpolators can be defined
- Example: E24


Regular Expressions

- Regular expressions are normal library class
- They can be used as extractors
 - Even more interesting when combined with string interpolation
- Example: E25

Type parameterization

- Each class and method may be parameterized by a type
- Lower and upper bounds
- Example: E26

Type Hierarchy



Null and Nothing types

- **null** is singleton instance of Null
 - can be assigned to any AnyRef
- Nothing is a subtype of everything
 - Can be assigned to anything, but does not have any instance

```
def doesNotReturn(): Nothing =  
    throw new Exception
```

Nothing in Use I

```
def fail(msg: String): Nothing =  
    println(msg)  
    sys.exit(1)
```

```
val y = if x != null then x else fail("$&#@!")
```

Nothing in Use II

```
abstract class Option[+A]:  
  def isEmpty  
  def get: A
```

```
case class Some[+A](x: A) extends Option[A]:  
  def isEmpty = false  
  def get = x
```

```
case object None extends Option[Nothing]:  
  def isEmpty = true  
  def get = throw NoSuchElementException()
```

Type variance

- Assuming: $A <: B$ (A subtype of B) and $X[T]$
- What is the relation of $X[A]$ and $X[B]$?
 - $X[A] <: X[B]$... X is covariant in its type parameter T
 - $X[A] >: X[B]$... X is contravariant in its type parameter T
 - No relation ... X is invariant w.r.t. to the type parameter T
- Example: E27

Instance private data

- The mutable state in a class typically prevents the covariance/contravariance
- Why?
- Example: E28

Collections

- Scala offers immutable and mutable variants of collections (immutable ones preferred)
 - List vs. ListBuffer
 - HashSet vs. mutable.HashSet
 - HashMap vs. mutable.HashMap
- To achieve performance, immutable types are internally often backed by mutable structures

Path dependent types

- Nested traits/classes are specific to the instance of the outer class
- This makes types different based on the instance they are tied with
 - Though this is a runtime property, it can be with some effort checked statically
- Example: E29

Structural subtyping

- It is possible to specify only properties of a type
- Example: E30