part1 Project Status (04/16/2024 - 18:32:30)			
Project File:	aa.xise	**Parser Errors:**	No Errors
Module Name:	part1	**Implementation State:**	Placed and Routed
Target Device:	xc7a100t-1csg324	• **Errors:**	No Errors
Product Version:	ISE 14.7	• **Warnings:**	132 Warnings (0 new)
Design Goal:	Balanced	• **Routing Results:**	All Signals Completely Routed
Design Strategy:	Xilinx Default (unlocked)	• **Timing Constraints:**	All Constraints Met
Environment:	System Settings	• **Final Timing Score:**	0 (Timing Report)

Device Utilization Summary				[-]
Slice Logic Utilization	**Used**	**Available**	**Utilization**	**Note(s)**
Number of Slice Registers	192	126,800	1%	
Number used as Flip Flops	192			
Number used as Latches	0			
Number used as Latch-thrus	0			
Number used as AND/OR logics	0			
Number of Slice LUTs	81	63,400	1%	
Number used as logic	65	63,400	1%	
Number using O6 output only	46			
Number using O5 output only	19			
Number using O5 and O6	0			
Number used as ROM	0			
Number used as Memory	0	19,000	0%	
Number used exclusively as route-thrus	16			
Number with same-slice register load	15			
Number with same-slice carry load	1			
Number with other load	0			
Number of occupied Slices	57	15,850	1%	
Number of LUT Flip Flop pairs used	208			
Number with an unused Flip Flop	31	208	14%	
Number with an unused LUT	127	208	61%	
Number of fully used LUT-FF pairs	50	208	24%	

Number of unique control sets	1			
Number of slice register sites lost to control set restrictions	0	126,800	0%	
Number of bonded IOBs	130	210	61%	
Number of RAMB36E1/FIFO36E1s	0	135	0%	
Number of RAMB18E1/FIFO18E1s	0	270	0%	
Number of BUFG/BUFGCTRLs	1	32	3%	
Number used as BUFGs	1			
Number used as BUFGCTRLs	0			
Number of IDELAYE2/IDELAYE2_FINEDELAYs	0	300	0%	
Number of ILOGICE2/ILOGICE3/ISERDESE2s	0	300	0%	
Number of ODELAYE2/ODELAYE2_FINEDELAYs	0			
Number of OLOGICE2/OLOGICE3/OSERDESE2s	0	300	0%	
Number of PHASER_IN/PHASER_IN_PHYs	0	24	0%	
Number of PHASER_OUT/PHASER_OUT_PHYs	0	24	0%	
Number of BSCANs	0	4	0%	
Number of BUFHCEs	0	96	0%	
Number of BUFRs	0	24	0%	
Number of CAPTUREs	0	1	0%	
Number of DNA_PORTs	0	1	0%	
Number of DSP48E1s	8	240	3%	
Number of EFUSE_USRs	0	1	0%	
Number of FRAME_ECCs	0	1	0%	
Number of IBUFDS_GTE2s	0	4	0%	
Number of ICAPs	0	2	0%	
Number of IDELAYCTRLs	0	6	0%	
Number of IN_FIFOs	0	24	0%	
Number of MMCME2_ADVs	0	6	0%	
Number of OUT_FIFOs	0	24	0%	
Number of PCIE_2_1s	0	1	0%	
Number of PHASER_REFs	0	6	0%	
Number of PHY_CONTROLs	0	6	0%	
Number of PLLE2_ADVs	0	6	0%	
Number of STARTUPs	0	1	0%	
Number of XADCs	0	1	0%	

Average Fanout of Non-Clock Nets	1.37			

Performance Summary			[-]
Final Timing Score:	0 (Setup: 0, Hold: 0, Component Switching Limit: 0)	**Pinout Data:**	Pinout Report
Routing Results:	All Signals Completely Routed	**Clock Data:**	Clock Report
Timing Constraints:	All Constraints Met		

Detailed Reports					[-]
Report Name	**Status**	**Generated**	**Errors**	**Warnings**	**Infos**
Synthesis Report	Current	Tue Apr 16 18:26:44 2024	0	0	0
Translation Report	Current	Tue Apr 16 18:31:00 2024	0	0	0
Map Report	Current	Tue Apr 16 18:31:48 2024	0	132 Warnings (0 new)	5 Infos (0 new)
Place and Route Report	Current	Tue Apr 16 18:32:13 2024	0	0	0
Power Report					
Post-PAR Static Timing Report	Current	Tue Apr 16 18:32:28 2024	0	0	3 Infos (0 new)
Bitgen Report					

Secondary Reports			[-]
Report Name	**Status**	**Generated**	

Date Generated: 04/16/2024 - 18:32:30