

Q4_Moore Project Status (03/19/2024 - 05:33:49)			
Project File:	qwee.xise	Parser Errors:	No Errors
Module Name:	Q4_Moore	Implementation State:	Placed and Routed
Target Device:	xc7a100t-3csg324	• Errors:	No Errors
Product Version:	ISE 14.7	• Warnings:	7 Warnings (7 new)
Design Goal:	Balanced	• Routing Results:	All Signals Completely Routed
Design Strategy:	Xilinx Default (unlocked)	• Timing Constraints:	All Constraints Met
Environment:	System Settings	• Final Timing Score:	0 (Timing Report)

Device Utilization Summary				[-]
Slice Logic Utilization	Used	Available	Utilization	Note(s)
Number of Slice Registers	9	126,800	1%	
Number used as Flip Flops	9			
Number used as Latches	0			
Number used as Latch-thrus	0			
Number used as AND/OR logics	0			
Number of Slice LUTs	2	63,400	1%	
Number used as logic	2	63,400	1%	
Number using O6 output only	2			
Number using O5 output only	0			
Number using O5 and O6	0			
Number used as ROM	0			
Number used as Memory	0	19,000	0%	
Number used exclusively as route-thrus	0			
Number of occupied Slices	2	15,850	1%	
Number of LUT Flip Flop pairs used	8			
Number with an unused Flip Flop	0	8	0%	
Number with an unused LUT	6	8	75%	
Number of fully used LUT-FF pairs	2	8	25%	
Number of unique control sets	1			
Number of slice register sites lost to control set restrictions	7	126,800	1%	
Number of bonded IOBs	5	210	2%	

Number of RAMB36E1/FIFO36E1s	0	135	0%	
Number of RAMB18E1/FIFO18E1s	0	270	0%	
Number of BUFG/BUFGCTRLs	1	32	3%	
Number used as BUFGs	1			
Number used as BUFGCTRLs	0			
Number of IDELAYE2/IDELAYE2_FINEDELAYs	0	300	0%	
Number of ILOGICE2/ILOGICE3/ISERDESE2s	0	300	0%	
Number of ODELAYE2/ODELAYE2_FINEDELAYs	0			
Number of OLOGICE2/OLOGICE3/OSERDESE2s	1	300	1%	
Number used as OLOGICE2s	1			
Number used as OLOGICE3s	0			
Number used as OSERDESE2s	0			
Number of PHASER_IN/PHASER_IN_PHYS	0	24	0%	
Number of PHASER_OUT/PHASER_OUT_PHYS	0	24	0%	
Number of BSCANs	0	4	0%	
Number of BUFHCEs	0	96	0%	
Number of BUFRs	0	24	0%	
Number of CAPTUREs	0	1	0%	
Number of DNA_PORTS	0	1	0%	
Number of DSP48E1s	0	240	0%	
Number of EFUSE_USRs	0	1	0%	
Number of FRAME_ECCs	0	1	0%	
Number of IBUFDS_GTE2s	0	4	0%	
Number of ICAPs	0	2	0%	
Number of IDELAYCTRLs	0	6	0%	
Number of IN_FIFOs	0	24	0%	
Number of MMCME2_ADVs	0	6	0%	
Number of OUT_FIFOs	0	24	0%	
Number of PCIE_2_1s	0	1	0%	
Number of PHASER_REFs	0	6	0%	
Number of PHY_CONTROLS	0	6	0%	
Number of PLLE2_ADVs	0	6	0%	
Number of STARTUPs	0	1	0%	
Number of XADCs	0	1	0%	
Average Fanout of Non-Clock Nets	2.53			

Performance Summary				[-]
Final Timing Score:	0 (Setup: 0, Hold: 0)		Pinout Data:	Pinout Report
Routing Results:	All Signals Completely Routed		Clock Data:	Clock Report
Timing Constraints:	All Constraints Met			

Detailed Reports						[-]
Report Name	Status	Generated	Errors	Warnings	Infos	
Synthesis Report	Current	Tue Mar 19 05:31:53 2024	0	0	1 Info (1 new)	
Translation Report	Current	Tue Mar 19 05:32:06 2024	0	0	0	
Map Report	Current	Tue Mar 19 05:32:46 2024	0	7 Warnings (7 new)	5 Infos (5 new)	
Place and Route Report	Current	Tue Mar 19 05:33:22 2024	0	0	3 Infos (3 new)	
Power Report						
Post-PAR Static Timing Report	Current	Tue Mar 19 05:33:48 2024	0	0	4 Infos (4 new)	
Bitgen Report						

Secondary Reports			[-]
Report Name	Status	Generated	

Date Generated: 03/19/2024 - 05:33:49