



NOZZLE DATA					
NOZZLE	QTY.	SERVICE	SIZE (DN)	RATING	REMARKS
N1	1	FLUSH CONNECTION	50	150# RF	C/W FLANGED CHECK AND BALL VALVES, DN25 FEMALE COUPLERS, (SW END), REDUCER DN50 x DN25
N2	1	OUTLET	50	150# RF	C/W FLANGED BALL VALVE, DN25 FEMALE COUPLERS (SW END), REDUCER DN50 x DN25
N3	1	VENT	80	150# RF	C/W GOOSE NECK
		LEVEL GAUGE			PAD TYPE TANK WALL-FLUSHED
N4	1	SPARE	50	150# RF	C/W BLIND
N5	1	FILL CONNECTION	50	150# RF	C/W FLANGED BALL VALVES, DN25 FEMALE COUPLERS (SW END), REDUCER DN50 x DN25
M1	1	MANWAY	500	PER API 650	C/W COVER, HANDLES & HINGE

ACCESSORIES / SUPPORT DATA	
QTY.	DESCRIPTION
4	LIFTING LUGS
1	NAMEPLATE AND BRACKET

NOTES

1. ALL DIMENSIONS ARE IN MM UNLESS OTHERWISE NOTED

EXXONMOBIL EXPLORATION & PRODUCTION (M) INC.

THE

9TK-153A/B
US CORR. INHIB. TOTE TANKS

APIS-F PLATFORM					WEST MALAYSIA	
SCALE:	NTS	DATE: APR. 08	DRN. BY: SL. SIM	CHKD. BY: AS	PROJ. LENGTH: MKT	
PROJECT NO			DRAWING NUMBER			REV.
ExxonMobil			TAF-03 65-20-002			0