



✓ **Congratulations! You passed!**

TO PASS 80% or higher

Keep Learning

GRADE

97.5%

Week 1 Quiz: Disease detection with computer vision

TOTAL POINTS 10

1. Which of the following is not one of the key challenges for AI diagnostic algorithms that is discussed in the lecture?

1 / 1 point

- ☐ Class imbalance
- ☒ Inflexible models
- ☐ Dataset size
- ☐ Multiple tasks

✓ **Correct**

This was not discussed as one of the key challenges, but more complex models can be used to fit data, to avoid underfitting.

2. You find that your training set has 70% negative examples and 30% positive. Which of the following techniques **will NOT help** for training this imbalanced dataset?

1 / 1 point

- ☒ Oversampling negative examples
- ☐ Undersampling negative examples
- ☐ Reweighting examples in training loss
- ☐ Oversampling positive examples

✓ **Correct**

Given that the model is being trained on more negative examples, sampling even more negative samples will bias the model even more towards making a negative prediction.

3. What is the total loss from the normal (non-mass) examples in this example dataset?

1 / 1 point

Please use the natural logarithm in your calculation. When you use `numpy.log`, this is using the natural logarithm. Also, to get the total loss, please add up the losses from each 'normal' example.

Example	P(positive)
P1 Normal	0.6
P3 Normal	0.3
P5 Mass	0.4

- ☐ 2.19
- ☐ 0.00
- ☐ -0.4
- ☒ 1.27

✓ **Correct**

Since these are negative examples, the losses will be $-\log(1 - P(\text{positive}))$.

For P1, $-\log(1 - 0.6) = 0.91$.

For P3 $-\log(1 - 0.3) = 0.36$.

The sum is $0.91 + 0.36 = 1.27$.

4. What is the typical size of medical image dataset?

1 / 1 point


- ☐ ~1 million or more images
- ☒ ~10 thousand to 100 thousand images
- ☐ ~1 to 1 hundred images
- ☐ ~1 hundred to 1 thousand images

✓ Correct

Most often datasets will range from 10,000 to 100,000 labeled images. Fewer than 1000 is typically too few to train, validate and test a classifier, and very few datasets will have millions of images due to the cost of labeling.

5. Which of the following data augmentations would be best to apply?

1 / 1 point



☐



☐ None of the above

☒



☐



✓ Correct

This rotation is most likely to help. This is a realistic transformation. Also, it does not risk changing the label.

6. Which of the following are valid methods for determining ground truth? Choose all that apply.

1 / 1 point

☒ Confirmation by CT scan

✓ Correct

A CT scan can provide an objective ground truth. Koo is said that these are likely false data.

A CT scan can provide an objective ground truth. Keep in mind that there are likely fewer data examples where patients have both the chest x-ray and an additional diagnostic test for the same disease.

☒ Consensus voting from a board of doctors

 **Correct**

Consensus is considered less reliable than biopsy verification. However, the limited availability of biopsy data means that consensus voting may still be the best (or only viable) option.

☒ Biopsy

 **Correct**

Biopsy is definitely a valid method. Keep in mind that there are likely fewer data examples where patients have both the chest x-ray and an additional diagnostic test for the same disease.

7. In what order should the training, validation, and test sets be sampled?

1 / 1 point

- ☐ Training, Validation, Test
- ☒ Test, Validation, Training
- ☐ Validation, Training, Test
- ☐ Validation, Test, Training

 **Correct**

First the test dataset should be sampled, then the validation set, then the training set. This is so that you can make sure you can adequately sample the test set, and then sample the validation set to match the distribution of labels in the test set.

8. Why is it bad to have the same patients in both training and test sets?

1 / 1 point

- ☐ None of the above
- ☐ Leaves too few images for the test set
- ☒ Overly optimistic test performance
- ☐ Leaves too few images for the training set

 **Correct**

Having images from the same patient is bad because it has been shown that the model may learn patient-specific features that are not generalizable to other patients.

9. Let's say you have a relatively small training set (~5 thousand images). Which training strategy makes the most sense?

1 / 1 point

- ☐ Train a model with randomly initialized weights
- ☒ Retraining the last layer of a pre-trained model

 **Correct**

By using a pre-trained model, you can make use of its ability to recognize lower level features, and then fine tune the last few layers using your dataset.

- ☐ Retraining all layers of a pre-trained model
- ☐ Retraining the first layer of a pre-trained model

10. Now let's say you have a very large dataset (~1 million images). Which training strategies will make the most sense?

0.75 / 1 point

- ☐ Retraining the first layer of a pretrained model
- ☒ Training a model with randomly initialized weights.



Correct

Given a very large dataset, you have the option of training a new model instead of using a pre-trained model.

- ☐ Retraining all layers of a pretrained model
- ☐ Retraining the last layer of a pretrained model

You didn't select all the correct answers