

# AWS DevOps Cheat Sheet

## 1. System Administration & Scripting

- Linux commands
- Shell scripting
- Python

## 2. Version Control

- Git
- GitHub – Cloud-based Git repository hosting
- GitLab – Git repository with built-in CI/CD pipelines
- Bitbucket – Git repository with Jira integration

## 3. Continuous Integration & Continuous Deployment (CI/CD)

- Jenkins (pipelines, declarative scripts)
- GitHub Actions (workflows, syntax)
- GitLab CI/CD (stages, jobs, runners)
- Tekton
- Circle CI
- ArgoCD (GitOps)
- Flux CD

## 4. Infrastructure as Code (IaC)

- Terraform
- CloudFormation (stacks, templates)

## 5.Containerization & Orchestration

- Docker (build, run, volumes, networks, compose)
- Kubernetes (K8s)

## 6.Cloud Services

- AWS
- Azure
- GCP

## 7.Configuration Management

- Ansible (playbooks, roles, inventory)
- Chef (recipes, cookbooks)
- Puppet (manifests, modules)
- SaltStack (states, grains)

## 8.Monitoring & Logging

- Prometheus & Grafana (metrics, alerts, visualization)
- ELK Stack (Elasticsearch, Logstash, Kibana)
- Datadog
- New Relic

## 9.Security & Compliance

- SonarQube (code analysis)
- Trivy (container vulnerability scanning)
- OWASP Dependency-Check

## 10. Networking, Ports & Load Balancing

- Networking Basics
- Ports
- Nginx (Reverse Proxy & Load Balancing)
- Nginx (Reverse Proxy & Load Balancing)
- HAProxy (Load Balancing)
- Kubernetes Ingress Controller (For Managing External Traffic)
- Practical Examples: Docker for Nginx, Apache, HAProxy, and Kubernetes Ingress

## 11. Databases

- SQL Databases (MySQL, PostgreSQL, MariaDB)
- NoSQL Databases
- Database Automation for DevOps

## 12. Storage

## 13. Helm

# 1.System Administration & Scripting

## Linux commands

### 1. File Management

- ls - List directory contents.
- cd - Change directory.
- pwd - Print working directory.
- cp - Copy files or directories.
- mv - Move or rename files or directories.
- rm - Remove files or directories.
- touch - Create a new empty file.
- mkdir - Create a new directory.
- rmdir - Remove an empty directory.
- cat - Concatenate and display file contents.
- head - Display the first few lines of a file.
- tail - Display the last few lines of a file.
- chmod - Change file permissions.
- chown - Change file ownership.
- find - Search for files in a directory hierarchy.
- locate - Find files by name.
- grep - Search text using patterns.
- diff - Compare two files line by line.
- tar - Archive files.
- zip/unzip - Compress and extract files.

- **scp** - Securely copy files over SSH.

- **ls**: List files and directories.

`ls -l` # Long listing with details

- **cd**: Change directory.

`cd /home/swapna` # Move to /home/swapna directory

- **pwd**: Show current directory.

`pwd`

- **cp**: Copy files.

`cp file1.txt /tmp` # Copy file1.txt to /tmp directory

- **mv**: Move or rename files.

`mv oldname.txt newname.txt` # Rename file

`mv file1.txt /tmp` # Move to /tmp directory

- **rm**: Remove files or directories.

`rm file1.txt` # Remove a file

`rm -rf /tmp/old_directory` # Remove directory and contents

- **mkdir**: Create directories.

`mkdir new_folder` # Create a directory called new\_folder

- **cat**: Display file contents.

cat file.txt

## 2. System Information and Monitoring

- top - Display running processes and system usage.
- htop - Interactive process viewer.
- ps - Display current processes.
- df - Show disk space usage.
- du - Show directory space usage.
- free - Show memory usage.
- uptime - Show system uptime.
- uname - Show system information.
- whoami - Display the current logged-in user.
- lsof - List open files and associated processes.
- vmstat - Report virtual memory statistics.
- iostat - Report I/O statistics.
- netstat - Display network connections and routing tables.
- ifconfig - Display or configure a network interface.
- ping - Check network connectivity.
- traceroute - Track the route packets take to a destination.

- **top**: View running processes.

top

- **df**: Show disk usage.

df -h # Human-readable format

- **free**: Display memory usage.

free -m # Show memory in MB

- **uptime**: Check system uptime.

uptime

### 3. Package Management (Ubuntu/Debian)

- apt-get update - Update package lists.
- apt-get upgrade - Upgrade all packages.
- apt-get install - Install packages.
- apt-get remove - Remove packages.
- dpkg - Install, remove, and manage individual Debian packages.
- **apt-get**: Install, remove, or update packages.

```
sudo apt-get update      # Update package lists
```

```
sudo apt-get install nginx # Install NGINX
```

### 4. User and Permission Management

- useradd - Add a new user.
- userdel - Delete a user.
- usermod - Modify a user.
- passwd - Change user password.
- groupadd - Create a new group.
- groupdel - Delete a group.
- groups - Show groups of a user.
- su - Switch user.
- sudo - Execute a command as another user, usually root.

- **useradd**: Add a new user.

```
sudo useradd -m newuser  # Create a new user with a home directory
```

- **chmod**: Change file permissions.

```
chmod 755 script.sh    # Set permissions for owner and others
```

- **chown**: Change file owner.

```
sudo chown newuser file.txt  # Change ownership to newuser
```

## 5. Networking

- curl - Transfer data from or to a server.
- wget - Download files from the internet.
- ssh - Secure shell to a remote server.
- telnet - Connect to a remote machine.
- nslookup - Query DNS records.
- dig - DNS lookup utility.
- iptables - Configure firewall rules.
- firewalld - Firewall management (CentOS/RHEL).
- hostname - Show or set the system hostname.
- **ping**: Check connectivity to a host.

```
ping google.com
```

- **curl**: Send HTTP requests.

```
curl https://example.com
```

- **ifconfig**: View network interfaces.

```
ifconfig
```

---

## 6. Process Management

- kill - Send a signal to a process.
- killall - Kill processes by name.
- pkill - Kill processes by pattern matching.
- bg - Move a job to the background.
- fg - Bring a job to the foreground.
- jobs - List background jobs.
- **ps**: Show running processes.

```
ps aux | grep nginx    # List processes related to nginx
```



- **kill**: Terminate a process by PID.

```
kill 1234 # Kill process with PID 1234
```

- **pkill**: Kill processes by name.

```
pkill nginx # Kill all nginx processes
```

---

## 7. Disk Management

- **fdisk** - Partition a disk.
- **mkfs** - Make a filesystem.
- **mount** - Mount a filesystem.
- **umount** - Unmount a filesystem.
- **lsblk** - List block devices.
- **blkid** - Print block device attributes.
- **fdisk**: Manage disk partitions.

```
sudo fdisk -l # List disk partitions
```

- **mount**: Mount a filesystem.

```
sudo mount /dev/sdb1 /mnt # Mount device sdb1 to /mnt
```

---

## 8. Text Processing

- **awk** - Pattern scanning and processing.
- **sed** - Stream editor for modifying text.
- **sort** - Sort lines of text files.
- **uniq** - Report or omit repeated lines.
- **cut** - Remove sections from each line of files.
- **wc** - Word, line, character count.
- **tr** - Translate or delete characters.
- **nl** - Number lines of files.
- **grep**: Search text.

```
grep "error" /var/log/syslog # Search for "error" in syslog
```

- **awk**: Process text with patterns.

```
awk '{print $1}' file.txt # Print the first column of each line
```

- **sed**: Edit text in streams.

```
sed 's/old/new/g' file.txt # Replace "old" with "new"
```

---

## 9. Logging and Auditing

- dmesg - Print or control kernel ring buffer.
- journalctl - Query the systemd journal.
- logger - Add entries to the system log.
- last - Show listing of last logged-in users.
- history - Show command history.
- tail -f - Monitor logs in real time.

- **tail**: View end of file in real time.

```
tail -f /var/log/nginx/access.log # Follow NGINX access log
```

- **journalctl**: View system logs.

```
sudo journalctl -u nginx # Logs for NGINX service
```

---

## 10. Archiving and Backup

- tar - Archive files.
- rsync - Synchronize files and directories.
- **tar**: Archive files.

```
tar -cvf archive.tar /path/to/files # Create an archive
```

```
tar -xvf archive.tar # Extract an archive
```

- **rsync**: Sync files and directories.

```
rsync -avz /source /destination # Sync with compression and archive mode
```

## 11. Shell Scripting

- echo - Display message or text.
- read - Read input from the user.
- export - Set environment variables.
- alias - Create shortcuts for commands.
- sh, - Execute shell scripts.
- **echo**: Display text.

```
echo "Hello, DevOps!" # Print message
```

- **export**: Set environment variables.

```
export PATH=$PATH:/new/path # Add to PATH variable
```

---

## 12. System Configuration and Management

- crontab - Schedule periodic tasks.
- systemctl - Control the systemd system and service manager.
- service - Start, stop, or restart services.
- timedatectl - Query and change the system clock.
- reboot - Restart the system.
- shutdown - Power off the system.

- **crontab**: Schedule tasks.

```
crontab -e # Edit the crontab file  
# Example entry: 0 2 * * * /path/to/backup.sh
```

- **systemctl**: Control services.

```
sudo systemctl restart nginx # Restart NGINX
```

---

## 13. Containerization & Virtualization

- docker - Manage Docker containers.

- **kubectl** - Manage Kubernetes clusters.
- **docker**: Manage Docker containers.

```
docker ps    # List running containers
docker run -d -p 8080:80 nginx    # Run NGINX container
```

- **kubect**: Manage Kubernetes clusters.

```
kubect get pods    # List all pods
kubect apply -f deployment.yaml    # Deploy configuration
```

---

## 14. Git Version Control

- **git status** - Show the status of changes.
- **git add** - Add files to staging.
- **git commit** - Commit changes.
- **git push** - Push changes to a remote repository.
- **git pull** - Pull changes from a remote repository.
- **git clone** - Clone a repository.

```
git commit -m "<message>" - Commit changes with a descriptive message.
git push <remote> <branch> - Push changes to a remote repository.
git pull <remote> <branch> - Pull changes from a remote repository.
git clone <repository> - Clone a repository.
git remote - Manage set of tracked repositories.
```

- **git remote -v** - Show URLs of remote repositories.
- **git remote add <name> <url>** - Add a new remote repository.
- **git remote remove <name>** - Remove a remote repository by name.
- **git remote rename <old-name> <new-name>** - Rename a remote repository.

---

## 15. Others

- **env** - Display environment variables.
- **date** - Show or set the system date and time.
- **alias** - Create command shortcuts.
- **source** - Execute commands from a file in the current shell.

- **sleep** - Pause for a specified amount of time.
- 

## 16. Network Troubleshooting and Analysis

- **traceroute**: Track packet route.

```
traceroute google.com # Show hops to google.com
```

- **netstat**: View network connections, routing tables, and more.

```
netstat -tuln # Show active listening ports with protocol info
```

- **ss**: Display socket statistics (modern alternative to netstat).

```
ss -tuln # Show active listening ports
```

- **iptables**: Manage firewall rules.

```
sudo iptables -L # List current iptables rules
```

---

## 17. Advanced File Management

- **find**: Search files by various criteria.

```
find /var -name "*.log" # Find all .log files under /var
```

```
find /home -type d -name "test" # Find directories named "test"
```

- **locate**: Quickly find files by name.

```
locate apache2.conf # Locate apache2 configuration file
```

---

## 18. File Content and Manipulation

- **split**: Split files into parts.

```
split -l 500 largefile.txt smallfile # Split file into 500-line chunks
```

- **sort**: Sort lines in files. `sort file.txt` # Sort lines alphabetically

```
sort -n numbers.txt # Sort numerically
```

- **uniq**: Remove duplicates from sorted files.

```
sort file.txt | uniq # Remove duplicate lines
```

---

## 19. Advanced Shell Operations

- **xargs**: Build and execute commands from standard input.

```
find . -name "*.txt" | xargs rm # Delete all .txt files
```

- **tee**: Read from standard input and write to standard output and files.

```
echo "new data" | tee file.txt # Write output to file and terminal
```

---

## 20. Performance Analysis

- **iostat**: Display CPU and I/O statistics.

```
iostat -d 2 # Show disk I/O stats every 2 seconds
```

- **vmstat**: Report virtual memory stats.

```
vmstat 1 5 # Display 5 samples at 1-second intervals
```

- **sar**: Collect and report system activity information.

```
sar -u 5 5 # Report CPU usage every 5 seconds
```

## 21. Disk and File System Analysis

- **lsblk**: List block devices.

`lsblk -f` # Show filesystems and partitions

- **blkid**: Display block device attributes.

`sudo blkid` # Show UUIDs for devices

- **ncdu**: Disk usage analyzer with a TUI.

`ncdu /` # Analyze root directory space usage

---

## 22. File Compression and Decompression

- **gzip**: Compress files.

`gzip largefile.txt` # Compress file with .gz extension

- **gunzip**: Decompress .gz files.

`gunzip largefile.txt.gz` # Decompress file

- **bzip2**: Compress files with higher compression than gzip.

`bzip2 largefile.txt` # Compress file with .bz2 extension

---

## 23. Environment Variables and Shell Management

- **env**: Display all environment variables.

`env`

- **set**: Set or display shell options and variables.

`set | grep PATH` # Show the PATH variable

- **unset**: Remove an environment variable.

```
unset VAR_NAME    # Remove a specific environment variable
```

---

## 24. Networking Utilities

- **arp**: Show or modify the IP-to-MAC address mappings.

```
arp -a    # Display all IP-MAC mappings
```

- **nc (netcat)**: Network tool for debugging and investigation.

```
nc -zv example.com 80 # Test if a specific port is open
```

- **nmap**: Network scanner to discover hosts and services.

```
nmap -sP 192.168.1.0/24 # Scan all hosts on a subnet
```

---

## 25. System Security and Permissions

- **umask**: Set default permissions for new files.

```
umask 022    # Set default permissions to 755 for new files
```

- **chmod**: Change file or directory permissions.

```
chmod 700 file.txt    # Owner only read, write, execute
```

- **chattr**: Change file attributes.

```
sudo chattr +i file.txt    # Make file immutable
```

- **lsattr**: List file attributes.

```
lsattr file.txt    # Show attributes for a file
```

---

## 26. Container and Kubernetes Management



- **docker-compose**: Manage multi-container Docker applications.  
`docker-compose up -d` # Start containers in detached mode
  - **minikube**: Run a local Kubernetes cluster.  
`minikube start` # Start minikube cluster
  - **helm**: Kubernetes package manager.  
`helm install myapp ./myapp-chart` # Install Helm chart for an app
- 

## 27. Advanced Git Operations

- **git stash**: Temporarily save changes.  
`git stash` # Stash current changes
- **git rebase**: Reapply commits on top of another base commit.  
`git rebase main` # Rebase current branch onto main
- **git log**: View commit history.  
`git log --oneline --graph` # Compact log with graph view

## 28. Troubleshooting and Debugging

- **strace**: Trace system calls and signals.  
`strace -p 1234` # Trace process with PID 1234
- **lsof**: List open files by processes.  
`lsof -i :8080` # List processes using port 8080
- **dmesg**: Print kernel ring buffer messages.  
`dmesg | tail -10` # View last 10 kernel messages

## 29. Data Manipulation and Processing

- **paste**: Merge lines of files.

```
paste file1.txt file2.txt # Combine lines from two files
```

- **join**: Join lines of two files on a common field.

```
join file1.txt file2.txt # Join files on matching lines
```

- **column**: Format text output into columns.

```
cat data.txt | column -t # Display data in columns
```

---

## 30. File Transfer

- **rsync**: Sync files between local and remote systems.

```
rsync -avz /local/dir user@remote:/remote/dir
```

- **scp**: Securely copy files between hosts.

```
scp file.txt user@remote:/path/to/destination # Copy to remote
```

- **ftp**: Transfer files using FTP protocol.

```
ftp example.com # Connect to FTP server example.com
```

## 31. Job Management and Scheduling

- **bg**: Send a job to the background.

```
./script.sh & # Run a script in the background
```

- **fg**: Bring a background job to the foreground.

```
fg %1 # Bring job 1 to the foreground
```

- **at:** Schedule a command to run once at a specified time.

```
echo "echo Hello, DevOps" | at now + 2 minutes    # Run in 2 minutes
```

---

## 2. Shell scripting

### 1. Automating Server Provisioning (AWS EC2 Launch)

```
#!/bin/bash
```

#### # Variables

```
INSTANCE_TYPE="t2.micro"
```

```
AMI_ID="ami-0abcdef1234567890" # Replace with the correct AMI ID
```

```
KEY_NAME="my-key-pair" # Replace with your key pair name
```

```
SECURITY_GROUP="sg-0abc1234def567890" # Replace with your security  
group ID
```

```
SUBNET_ID="subnet-0abc1234def567890" # Replace with your subnet ID
```

```
REGION="us-west-2" # Replace with your AWS region
```

#### # Launch EC2 instance

```
aws ec2 run-instances --image-id $AMI_ID --count 1 --instance-type  
$INSTANCE_TYPE \
```

```
--key-name $KEY_NAME --security-group-ids $SECURITY_GROUP --subnet-id  
$SUBNET_ID --region $REGION
```

```
echo "EC2 instance launched successfully!"
```

---

## 2. System Monitoring (CPU Usage Alert)

```
#!/bin/bash
```

```
# Threshold for CPU usage
```

```
CPU_THRESHOLD=80
```

```
# Get the current CPU usage
```

```
CPU_USAGE=$(top -bn1 | grep "Cpu(s)" | sed "s/.*, *\[0-9.\]*%* id.*\1/" | awk '{print 100 - $1}')
```

```
# Check if CPU usage exceeds threshold
```

```
if (( $(echo "$CPU_USAGE > $CPU_THRESHOLD" | bc -l) )); then
```

```
    echo "Alert: CPU usage is above $CPU_THRESHOLD%. Current usage is $CPU_USAGE%" | mail -s "CPU Usage Alert" user@example.com
```

```
fi
```

---

### 3. Backup Automation (MySQL Backup)

```
#!/bin/bash
```

#### # Variables

```
DB_USER="root"
```

```
DB_PASSWORD="password"
```

```
DB_NAME="my_database"
```

```
BACKUP_DIR="/backup"
```

```
DATE=$(date +%F)
```

#### # Create backup directory if it doesn't exist

```
mkdir -p $BACKUP_DIR
```

#### # Backup command

```
mysqldump -u $DB_USER -p$DB_PASSWORD $DB_NAME >  
$BACKUP_DIR/backup_$(date +%F).sql
```

#### # Optional: Compress the backup

```
gzip $BACKUP_DIR/backup_$(date +%F).sql
```

```
echo "Backup completed successfully!"
```

#### **4. Log Rotation and Cleanup**

```
#!/bin/bash
```

##### **# Variables**

```
LOG_DIR="/var/log/myapp"
```

```
ARCHIVE_DIR="/var/log/myapp/archive"
```

```
DAYS_TO_KEEP=30
```

##### **# Create archive directory if it doesn't exist**

```
mkdir -p $ARCHIVE_DIR
```

##### **# Find and compress logs older than 7 days**

```
find $LOG_DIR -type f -name "*.log" -mtime +7 -exec gzip {} \; -exec mv {}  
$ARCHIVE_DIR \;
```

##### **# Delete logs older than 30 days**

```
find $ARCHIVE_DIR -type f -name "*.log.gz" -mtime +$DAYS_TO_KEEP -exec  
rm {} \;
```

```
echo "Log rotation and cleanup completed!"
```

## 5. CI/CD Pipeline Automation (Trigger Jenkins Job)

```
#!/bin/bash
```

### # Jenkins details

```
JENKINS_URL="http://jenkins.example.com"
```

```
JOB_NAME="my-pipeline-job"
```

```
USER="your-username"
```

```
API_TOKEN="your-api-token"
```

### # Trigger Jenkins job

```
curl -X POST "$JENKINS_URL/job/$JOB_NAME/build" --user  
"$USER:$API_TOKEN"
```

```
echo "Jenkins job triggered successfully!"
```

---

## 6. Deployment Automation (Kubernetes Deployment)

```
#!/bin/bash
```

### # Variables

```
NAMESPACE="default"
```

```
DEPLOYMENT_NAME="my-app"
```

```
IMAGE="my-app:v1.0"
```

### **# Deploy to Kubernetes**

```
kubectrl set image deployment/$DEPLOYMENT_NAME  
$DEPLOYMENT_NAME=$IMAGE --namespace=$NAMESPACE
```

```
echo "Deployment updated to version $IMAGE!"
```

---

## **7. Infrastructure as Code (Terraform Apply)**

```
#!/bin/bash
```

### **# Variables**

```
TF_DIR="/path/to/terraform/config"
```

### **# Navigate to Terraform directory**

```
cd $TF_DIR
```

### **# Run terraform apply**

```
terraform apply -auto-approve
```



```
echo "Terraform apply completed successfully!"
```

---

## 8. Database Management (PostgreSQL Schema Migration)

```
bash
```

```
#!/bin/bash
```

```
# Variables
```

```
DB_USER="postgres"
```

```
DB_PASSWORD="password"
```

```
DB_NAME="my_database"
```

```
MIGRATION_FILE="/path/to/migration.sql"
```

```
# Run schema migration
```

```
PGPASSWORD=$DB_PASSWORD psql -U $DB_USER -d $DB_NAME -f  
$MIGRATION_FILE
```

```
echo "Database schema migration completed!"
```

---

## **9. User Management (Add User to Group)**

```
#!/bin/bash
```

### **# Variables**

```
USER_NAME="newuser"
```

```
GROUP_NAME="devops"
```

### **# Add user to group**

```
usermod -aG $GROUP_NAME $USER_NAME
```

```
echo "User $USER_NAME added to group $GROUP_NAME!"
```

---

## **10. Security Audits (Check for Open Ports)**

```
#!/bin/bash
```

### **# Check for open ports**

```
OPEN_PORTS=$(netstat -tuln)
```

### **# Check if any ports are open (excluding localhost)**

```
if [[ $OPEN_PORTS =~ "0.0.0.0" || $OPEN_PORTS =~ "127.0.0.1" ]]; then  
    echo "Security Alert: Open ports detected!"  
    echo "$OPEN_PORTS" | mail -s "Open Ports Security Alert" user@example.com  
else  
    echo "No open ports detected."  
Fi
```

---

## 11. Performance Tuning

This script clears memory caches and restarts services to free up system resources.

```
#!/bin/bash  
  
# Clear memory caches to free up resources  
  
sync; echo 3 > /proc/sys/vm/drop_caches  
  
# Restart services to free up resources  
  
systemctl restart nginx  
  
systemctl restart apache2
```

---

## 12. Automated Testing

This script runs automated tests using a testing framework like pytest for Python or JUnit for Java.

```
#!/bin/bash
```

```
# Run unit tests using pytest (Python example)
```

```
pytest tests/
```

```
# Or, run JUnit tests (Java example)
```

```
mvn test
```

---

### 13. Scaling Infrastructure

This script automatically scales EC2 instances in an Auto Scaling group based on CPU usage.

```
#!/bin/bash
```

```
# Check CPU usage and scale EC2 instances
```

```
CPU_USAGE=$(aws cloudwatch get-metric-statistics --namespace AWS/EC2  
--metric-name CPUUtilization --dimensions  
Name=InstanceId,Value=i-1234567890abcdef0 --statistics Average --period 300  
--start-time $(date -d '5 minutes ago' --utc +%FT%TZ) --end-time $(date --utc  
+%FT%TZ) --query 'Datapoints[0].Average' --output text)
```

```
if (( $(echo "$CPU_USAGE > 80" | bc -l) )); then
```

```
aws autoscaling update-auto-scaling-group --auto-scaling-group-name  
my-auto-scaling-group --desired-capacity 3
```

```
fi
```

---

## 14. Environment Setup

This script sets environment variables for different environments (development, staging, production).

```
#!/bin/bash  
  
# Set environment variables for different stages  
  
if [ "$1" == "production" ]; then  
    export DB_HOST="prod-db.example.com"  
    export API_KEY="prod-api-key"  
elif [ "$1" == "staging" ]; then  
    export DB_HOST="staging-db.example.com"  
    export API_KEY="staging-api-key"  
else  
    export DB_HOST="dev-db.example.com"  
    export API_KEY="dev-api-key"  
fi
```

## 15. Error Handling and Alerts

This script checks logs for errors and sends a Slack notification if an error is found.

```
#!/bin/bash

# Check logs for error messages and send Slack notification

if grep -i "error" /var/log/myapp.log; then

    curl -X POST -H 'Content-type: application/json' --data '{"text":"Error found in logs!"}' https://hooks.slack.com/services/your/webhook/url

fi
```

---

## 16. Automated Software Installation and Updates

This script installs Docker if it's not already installed on the system.

```
#!/bin/bash

# Install Docker

if ! command -v docker &> /dev/null; then

    curl -fsSL https://get.docker.com -o get-docker.sh

    sudo sh get-docker.sh

fi
```

## 17. Configuration Management

This script updates configuration files (like nginx.conf) across multiple servers.

```
#!/bin/bash
```

```
# Update nginx configuration across all servers
```

```
scp nginx.conf user@server:/etc/nginx/nginx.conf
```

```
ssh user@server "systemctl restart nginx"
```

---

## 18. Health Check Automation

This script checks the health of multiple web servers by making HTTP requests.

```
#!/bin/bash
```

```
# Check if web servers are running
```

```
for server in "server1" "server2" "server3"; do
```

```
    curl -s --head http://$server | head -n 1 | grep "HTTP/1.1 200 OK" > /dev/null
```

```
    if [ $? -ne 0 ]; then
```

```
        echo "$server is down"
```

```
    else
```

```
        echo "$server is up"
```

fi

done

---

## 19. Automated Cleanup of Temporary Files

This script removes files older than 30 days from the /tmp directory to free up disk space.

```
#!/bin/bash
```

```
# Remove files older than 30 days in /tmp
```

```
find /tmp -type f -mtime +30 -exec rm -f {} \;
```

---

## 20. Environment Variable Management

This script sets environment variables from a .env file.

```
#!/bin/bash
```

```
# Set environment variables from a .env file
```

```
export $(grep -v '^#' .env | xargs)
```



---

## 21. Server Reboot Automation

This script automatically reboots the server during off-hours (between 2 AM and 4 AM).

```
#!/bin/bash

# Reboot server during off-hours

if [ $(date +%H) -ge 2 ] && [ $(date +%H) -lt 4 ]; then

    sudo reboot

fi
```

---

## 22. SSL Certificate Renewal

This script renews SSL certificates using certbot and reloads the web server.

```
#!/bin/bash

# Renew SSL certificates using certbot

certbot renew

systemctl reload nginx
```

---

## 23. Automatic Scaling of Containers

This script checks the CPU usage of a Docker container and scales it based on usage.

```
#!/bin/bash
```

```
# Check CPU usage of a Docker container and scale if necessary
```

```
CPU_USAGE=$(docker stats --no-stream --format "{{.CPUPerc}}" my-container |  
sed 's/%//')
```

```
if (( $(echo "$CPU_USAGE > 80" | bc -l) )); then
```

```
    docker-compose scale my-container=3
```

```
fi
```

---

## 24. Backup Verification

This script verifies the integrity of backup files and reports any corrupted ones.

```
#!/bin/bash
```

```
# Verify backup files integrity
```

```
for backup in /backups/*.tar.gz; do
```

```
    if ! tar -tzf $backup > /dev/null 2>&1; then
```

```
        echo "Backup $backup is corrupted"
```

```
    else
```

```
    echo "Backup $backup is valid"
fi
done
```

---

## 25. Automated Server Cleanup

This script removes unused Docker images, containers, and volumes to save disk space.

```
#!/bin/bash

# Remove unused Docker images, containers, and volumes
docker system prune -af
```

---

## 26. Version Control Operations

This script pulls the latest changes from a Git repository and creates a release tag.

```
#!/bin/bash

# Pull latest changes from Git repository and create a release tag
git pull origin main

git tag -a v$(date +%Y%m%d%H%M%S) -m "Release $(date)"

git push origin --tags
```

---

## 27. Application Deployment Rollback

This script reverts to the previous Docker container image if a deployment fails.

```
#!/bin/bash
```

```
# Rollback to the previous Docker container image if deployment fails
```

```
if [ $? -ne 0 ]; then
```

```
    docker-compose down
```

```
    docker-compose pull my-app:previous
```

```
    docker-compose up -d
```

```
fi
```

---

## 28. Automated Log Collection

This script collects logs from multiple servers and uploads them to an S3 bucket.

```
#!/bin/bash
```

```
# Collect logs and upload them to an S3 bucket
```

```
tar -czf /tmp/logs.tar.gz /var/log/*
```

```
aws s3 cp /tmp/logs.tar.gz s3://my-log-bucket/logs/$(date
+%Y%m%d%H%M%S).tar.gz
```

---

## 29. Security Patch Management

This script checks for available security patches and applies them automatically.

```
#!/bin/bash

# Check and apply security patches

sudo apt-get update

sudo apt-get upgrade -y --only-upgrade
```

---

## 30. Custom Monitoring Scripts

This script checks if a database service is running and restarts it if necessary.

```
#!/bin/bash

# Check if a database service is running and restart it if necessary

if ! systemctl is-active --quiet mysql; then

    systemctl restart mysql

    echo "MySQL service was down and has been restarted"
```

```
else  
    echo "MySQL service is running"  
fi
```

---

### 31. DNS Configuration Automation (Route 53)

```
#!/bin/bash
```

#### # Variables

```
ZONE_ID="your-hosted-zone-id"
```

```
DOMAIN_NAME="your-domain.com"
```

```
NEW_IP="your-new-ip-address"
```

#### # Update Route 53 DNS record

```
aws route53 change-resource-record-sets --hosted-zone-id $ZONE_ID  
--change-batch '{
```

```
  "Changes": [
```

```
    {
```

```
      "Action": "UPSERT",
```

```
      "ResourceRecordSet": {
```

```
        "Name": "$DOMAIN_NAME",
```

```
        "Type": "A",
```

```
"TTL": 60,  
"ResourceRecords": [  
  {  
    "Value": "$NEW_IP"  
  }  
]  
}  
]  
'
```

---

## 32. Automated Code Linting and Formatting (ESLint and Prettier)

```
#!/bin/bash
```

```
# Run ESLint
```

```
npx eslint . --fix
```

```
# Run Prettier
```

```
npx prettier --write "**/*.js"
```

### **33. Automated API Testing (Using curl)**

```
#!/bin/bash
```

```
# API URL
```

```
API_URL="https://your-api-endpoint.com/endpoint"
```

```
# Make GET request and check for 200 OK response
```

```
RESPONSE=$(curl --write-out "%{http_code}" --silent --output /dev/null  
$API_URL)
```

```
if [ $RESPONSE -eq 200 ]; then
```

```
  echo "API is up and running"
```

```
else
```

```
  echo "API is down. Response code: $RESPONSE"
```

```
fi
```

---

### **34. Container Image Scanning (Using Trivy)**

```
#!/bin/bash
```

```
# Image to scan
```



```
IMAGE_NAME="your-docker-image:latest"
```

### **# Run Trivy scan**

```
trivy image --exit-code 1 --severity HIGH,CRITICAL $IMAGE_NAME
```

```
if [ $? -eq 1 ]; then
```

```
    echo "Vulnerabilities found in image: $IMAGE_NAME"
```

```
    exit 1
```

```
else
```

```
    echo "No vulnerabilities found in image: $IMAGE_NAME"
```

```
fi
```

---

## **35. Disk Usage Monitoring and Alerts (Email Notification)**

```
#!/bin/bash
```

### **# Disk usage threshold**

```
THRESHOLD=80
```

### **# Get current disk usage percentage**

```
DISK_USAGE=$(df / | grep / | awk '{ print $5 }' | sed 's/%//g')
```

### **# Check if disk usage exceeds threshold**

```
if [ $DISK_USAGE -gt $THRESHOLD ]; then  
  
    echo "Disk usage is above threshold: $DISK_USAGE%" | mail -s "Disk Usage  
Alert" your-email@example.com  
  
fi
```

---

### **36. Automated Load Testing (Using Apache Benchmark)**

```
#!/bin/bash  
  
# Target URL  
  
URL="https://your-application-url.com"  
  
  
# Run Apache Benchmark with 1000 requests and 10 concurrent requests  
  
ab -n 1000 -c 10 $URL
```

---

### **37. Automated Email Reports (Server Health Report)**

```
#!/bin/bash  
  
  
# Server Health Report  
  
REPORT=$(top -n 1 | head -n 10)
```

### **# Send report via email**

```
echo "$REPORT" | mail -s "Server Health Report" your-email@example.com
```

---

## **38. DNS Configuration Automation (Route 53)**

**Introduction:** This script automates the process of updating DNS records in AWS Route 53 when the IP address of a server changes. It ensures that DNS records are updated dynamically when new servers are provisioned.

```
#!/bin/bash
```

### **# Variables**

```
ZONE_ID="your-hosted-zone-id"
```

```
DOMAIN_NAME="your-domain.com"
```

```
NEW_IP="your-new-ip-address"
```

### **# Update Route 53 DNS record**

```
aws route53 change-resource-record-sets --hosted-zone-id $ZONE_ID  
--change-batch '{
```

```
  "Changes": [
```

```
    {
```

```
      "Action": "UPSERT",
```

```
      "ResourceRecordSet": {
```

```
"Name": "$DOMAIN_NAME",
>Type": "A",
>TTL": 60,
>ResourceRecords": [
>
>  {
>
>    "Value": "$NEW_IP"
>
>  }
>
>]
}
]
```

---

### 39. Automated Code Linting and Formatting (ESLint and Prettier)

**Introduction:** This script runs ESLint and Prettier to check and automatically format JavaScript code before deployment. It ensures code quality and consistency.

```
#!/bin/bash
```

```
# Run ESLint
```

```
npx eslint . --fix
```

## # Run Prettier

```
npx prettier --write "**/*.js"
```

---

## 40. Automated API Testing (Using curl)

**Introduction:** This script automates the process of testing an API by sending HTTP requests and verifying the response status. It helps ensure that the API is functioning correctly.

```
#!/bin/bash
```

### # API URL

```
API_URL="https://your-api-endpoint.com/endpoint"
```

```
# Make GET request and check for 200 OK response
```

```
RESPONSE=$(curl --write-out "%{http_code}" --silent --output /dev/null  
$API_URL)
```

```
if [ $RESPONSE -eq 200 ]; then
```

```
  echo "API is up and running"
```

```
else
```

```
  echo "API is down. Response code: $RESPONSE"
```

fi

---

## 41. Container Image Scanning (Using Trivy)

**Introduction:** This script scans Docker images for known vulnerabilities using Trivy. It ensures that only secure images are deployed in production.

```
#!/bin/bash
```

```
# Image to scan
```

```
IMAGE_NAME="your-docker-image:latest"
```

```
# Run Trivy scan
```

```
trivy image --exit-code 1 --severity HIGH,CRITICAL $IMAGE_NAME
```

```
if [ $? -eq 1 ]; then
```

```
    echo "Vulnerabilities found in image: $IMAGE_NAME"
```

```
    exit 1
```

```
else
```

```
    echo "No vulnerabilities found in image: $IMAGE_NAME"
```

```
fi
```

---

## 42. Disk Usage Monitoring and Alerts (Email Notification)

**Introduction:** This script monitors disk usage and sends an alert via email if the disk usage exceeds a specified threshold. It helps in proactive monitoring of disk space.

```
#!/bin/bash
```

```
# Disk usage threshold
```

```
THRESHOLD=80
```

```
# Get current disk usage percentage
```

```
DISK_USAGE=$(df / | grep / | awk '{ print $5 }' | sed 's/%//g')
```

```
# Check if disk usage exceeds threshold
```

```
if [ $DISK_USAGE -gt $THRESHOLD ]; then
```

```
    echo "Disk usage is above threshold: $DISK_USAGE%" | mail -s "Disk Usage  
Alert" your-email@example.com
```

```
fi
```

---

## 43. Automated Load Testing (Using Apache Benchmark)

**Introduction:** This script runs load tests using Apache Benchmark (ab) to simulate traffic on an application. It helps measure the performance and scalability of the application.

```
bash
```

```
#!/bin/bash
```

```
# Target URL
```

```
URL="https://your-application-url.com"
```

```
# Run Apache Benchmark with 1000 requests and 10 concurrent requests
```

```
ab -n 1000 -c 10 $URL
```

---

#### **44. Automated Email Reports (Server Health Report)**

**Introduction:** This script generates a server health report using system commands like top and sends it via email. It helps keep track of server performance and health.

```
#!/bin/bash
```

```
# Server Health Report
```

```
REPORT=$(top -n 1 | head -n 10)
```

```
# Send report via email
```

```
echo "$REPORT" | mail -s "Server Health Report" your-email@example.com
```



---

## 45. Automating Documentation Generation (Using pdoc for Python)

**Introduction:** This script generates HTML documentation from Python code using pdoc. It helps automate the process of creating up-to-date documentation from the source code.

```
#!/bin/bash
```

```
# Generate documentation using pdoc
```

```
pdoc --html your-python-module --output-dir docs/
```

```
# Optionally, you can zip the generated docs
```

```
zip -r docs.zip docs/
```

---

```
# List all cron jobs
```

```
crontab -l
```

```
# Edit cron jobs
```

```
crontab -e
```

```
# Remove all cron jobs
```

```
crontab -r
```

```
# Use a specific editor (e.g., nano)
```

```
EDITOR=nano crontab -e
```

```
# Cron Job Syntax
```

```
# * * * * * command_to_execute
```

```
# T T T T T
```

```
# | | | | |
```

```
# | | | | | _____ Day of the week (0-6, Sunday=0)
```

```
# | | | | _____ Month (1-12 or JAN-DEC)
```

```
# | | | _____ Day of the month (1-31)
```

```
# | | _____ Hour (0-23)
```

```
# | _____ Minute (0-59)
```

```
# Run a script every minute
```

```
* * * * * /path/to/script.sh
```

```
# Run a script every 5 minutes
```

```
*/5 * * * * /path/to/script.sh
```

# Run a script every 10 minutes

`*/10 * * * * /path/to/script.sh`

# Run a script at midnight

`0 0 * * * /path/to/script.sh`

# Run a script every hour

`0 * * * * /path/to/script.sh`

# Run a script every 2 hours

`0 */2 * * * /path/to/script.sh`

# Run a script every Sunday at 3 AM

`0 3 * * 0 /path/to/script.sh`

# Run a script at 9 AM on the 1st of every month

`0 9 1 * * /path/to/script.sh`

# Run a script every Monday to Friday at 6 PM

`0 18 * * 1-5 /path/to/script.sh`

# Run a script on the first Monday of every month

```
0 9 * * 1 [ "$(date +%d)" -le 7 ] && /path/to/script.sh
```

# Run a script on specific dates (e.g., 1st and 15th of the month)

```
0 12 1,15 * * /path/to/script.sh
```

# Run a script between 9 AM and 5 PM, every hour

```
0 9-17 * * * /path/to/script.sh
```

# Run a script every reboot

```
@reboot /path/to/script.sh
```

# Run a script daily at midnight

```
@daily /path/to/script.sh
```

# Run a script weekly at midnight on Sunday

```
@weekly /path/to/script.sh
```

# Run a script monthly at midnight on the 1st

```
@monthly /path/to/script.sh
```

# Run a script yearly at midnight on January 1st

@yearly /path/to/script.sh

# Redirect cron job output to a log file

0 0 \* \* \* /path/to/script.sh >> /var/log/script.log 2>&1

# Run a job only if the previous instance is not running

0 \* \* \* \* flock -n /tmp/job.lock /path/to/script.sh

# Run a script with a random delay (0-59 minutes)

RANDOM\_DELAY=\$((RANDOM % 60)) && sleep \$RANDOM\_DELAY &&  
/path/to/script.sh

# Run a script with environment variables

SHELL=/bin/bash

PATH=/usr/local/bin:/usr/bin:/bin

0 5 \* \* \* /path/to/script.sh

# Check cron logs (Ubuntu/Debian)

grep CRON /var/log/syslog

# Check cron logs (Red Hat/CentOS)

```
grep CRON /var/log/cron
```

```
# Restart cron service (Linux)
```

```
sudo systemctl restart cron
```

```
# Check if cron service is running
```

```
sudo systemctl status cron
```

---

## **Python**

### **Python Basics**

- Run a script: `python script.py`
- Start interactive mode: `python`
- Check Python version: `python --version`
- Install a package: `pip install package_name`

### **Create a virtual environment:**

```
python -m venv venv
```

```
source venv/bin/activate # On Linux/macOS
```

```
venv\Scripts\activate # On Windows
```

- Deactivate virtual environment: `deactivate`

### **1. File Operations**

- **Read a file:**

```
python
```

```
with open('file.txt', 'r') as file:  
    content = file.read()  
    print(content)
```

- **Write to a file:**

```
python
```

```
with open('output.txt', 'w') as file:  
    file.write('Hello, DevOps!')
```

## 2. Environment Variables

- **Get an environment variable:**

```
python
```

```
import os
```

```
db_user = os.getenv('DB_USER')  
print(db_user)
```

- **Set an environment variable:**

```
python
```

```
import os
```

```
os.environ['NEW_VAR'] = 'value'
```

## 3. Subprocess Management

- **Run shell commands:**

```
python
```

```
import subprocess
```

```
result = subprocess.run(['ls', '-l'], capture_output=True, text=True)
print(result.stdout)
```

#### 4. API Requests

- **Make a GET request:**

```
python

import requests

response = requests.get('https://api.example.com/data')
print(response.json())
```

#### 5. JSON Handling

- **Read JSON from a file:**

```
python

import json

with open('data.json', 'r') as file:
    data = json.load(file)
    print(data)
```

- **Write JSON to a file:**

```
python

import json

data = {'name': 'DevOps', 'type': 'Workflow'}
with open('output.json', 'w') as file:
    json.dump(data, file, indent=4)
```

#### 6. Logging



- **Basic logging setup:**

```
python

import logging

logging.basicConfig(level=logging.INFO)
logging.info('This is an informational message')
```

## 7. Working with Databases

- **Connect to a SQLite database:**

```
python

import sqlite3

conn = sqlite3.connect('example.db')
cursor = conn.cursor()
cursor.execute('CREATE TABLE IF NOT EXISTS users (id INTEGER
PRIMARY KEY, name TEXT)')
conn.commit()
conn.close()
```

## 8. Automation with Libraries

- **Using Paramiko for SSH connections:**

```
python

import paramiko

ssh = paramiko.SSHClient()
ssh.set_missing_host_key_policy(paramiko.AutoAddPolicy())
ssh.connect('hostname', username='user', password='password')

stdin, stdout, stderr = ssh.exec_command('ls')
print(stdout.read().decode())
ssh.close()
```

## 9. Error Handling

- **Try-except block:**

```
python

try:
    # code that may raise an exception
    risky_code()
except Exception as e:
    print(f'Error occurred: {e}')
```

## 10. Docker Integration

- **Using the docker package to interact with Docker:**

```
python

import docker

client = docker.from_env()
containers = client.containers.list()
for container in containers:
    print(container.name)
```

## 11. Working with YAML Files

- **Read a YAML file:**

```
python

import yaml

with open('config.yaml', 'r') as file:
    config = yaml.safe_load(file)
    print(config)
```

- **Write to a YAML file:**

```
python

import yaml

data = {'name': 'DevOps', 'version': '1.0'}
with open('output.yaml', 'w') as file:
    yaml.dump(data, file)
```

## 12. Parsing Command-Line Arguments

- **Using argparse:**

```
python

import argparse

parser = argparse.ArgumentParser(description='Process some integers.')
parser.add_argument('--num', type=int, help='an integer for the accumulator')

args = parser.parse_args()
print(args.num)
```

## 13. Monitoring System Resources

- **Using psutil to monitor system resources:**

```
python

import psutil

print(f"CPU Usage: {psutil.cpu_percent()}%")
print(f"Memory Usage: {psutil.virtual_memory().percent}%")
```

## 14. Handling HTTP Requests with Flask

- **Basic Flask API:**

```
python
```

```
from flask import Flask, jsonify

app = Flask(__name__)

@app.route('/health', methods=['GET'])
def health_check():
    return jsonify({'status': 'healthy'})

if __name__ == '__main__':
    app.run(host='0.0.0.0', port=5000)
```

## 15. Creating Docker Containers

- **Using the Docker SDK to create a container:**

```
python

import docker

client = docker.from_env()
container = client.containers.run('ubuntu', 'echo Hello World', detach=True)
print(container.logs())
```

## 16. Scheduling Tasks

- **Using schedule for task scheduling:**

```
python

import schedule
import time

def job():
    print("Running scheduled job...")

schedule.every(1).minutes.do(job)

while True:
    schedule.run_pending()
    time.sleep(1)
```

## 17. Version Control with Git

- **Using GitPython to interact with Git repositories:**

```
python

import git

repo = git.Repo('/path/to/repo')
repo.git.add('file.txt')
repo.index.commit('Added file.txt')
```

## 18. Email Notifications

- **Sending emails using smtplib:**

```
python

import smtplib
from email.mime.text import MIMEText

msg = MIMEText('This is the body of the email')
msg['Subject'] = 'Email Subject'
msg['From'] = 'you@example.com'
msg['To'] = 'recipient@example.com'

with smtplib.SMTP('smtp.example.com', 587) as server:
    server.starttls()
    server.login('your_username', 'your_password')
    server.send_message(msg)
```

## 19. Creating Virtual Environments

- **Creating and activating a virtual environment:**

```
python

import os
import subprocess
```

```
# Create virtual environment
subprocess.run(['python3', '-m', 'venv', 'myenv'])

# Activate virtual environment (Windows)
os.system('myenv\\Scripts\\activate')

# Activate virtual environment (Linux/Mac)
os.system('source myenv/bin/activate')
```

## 20. Integrating with CI/CD Tools

- **Using the requests library to trigger a Jenkins job:**

```
python

import requests

url = 'http://your-jenkins-url/job/your-job-name/build'
response = requests.post(url, auth=('user', 'token'))
print(response.status_code)
```

## 21. Database Migration

- **Using Alembic for database migrations:**

```
bash

alembic revision -m "initial migration"
alembic upgrade head
```

## 22. Testing Code

- **Using unittest for unit testing:**

```
python

import unittest
```

```
def add(a, b):  
    return a + b  
  
class TestMathFunctions(unittest.TestCase):  
    def test_add(self):  
        self.assertEqual(add(2, 3), 5)  
  
if __name__ == '__main__':  
    unittest.main()
```

## 23. Data Transformation with Pandas

- **Using pandas for data manipulation:**

```
python  
  
import pandas as pd  
  
df = pd.read_csv('data.csv')  
df['new_column'] = df['existing_column'] * 2  
df.to_csv('output.csv', index=False)
```

## 24. Using Python for Infrastructure as Code

- **Using boto3 for AWS operations:**

```
python  
  
import boto3  
  
ec2 = boto3.resource('ec2')  
instances = ec2.instances.filter(Filters=[{'Name': 'instance-state-name',  
'Values': ['running']}])  
for instance in instances:  
    print(instance.id, instance.state)
```

## 25. Web Scraping

- **Using BeautifulSoup to scrape web pages:**

```
python
```

```
import requests
from bs4 import BeautifulSoup

response = requests.get('http://example.com')
soup = BeautifulSoup(response.content, 'html.parser')
print(soup.title.string)
```

## 26. Using Fabric for Remote Execution

- **Running commands on a remote server:**

```
python
```

```
from fabric import Connection

conn = Connection(host='user@hostname', connect_kwargs={'password':
'your_password'})
conn.run('uname -s')
```

## 27. Automating AWS S3 Operations

- **Upload and download files using boto3:**

```
python
```

```
import boto3

s3 = boto3.client('s3')

# Upload a file
s3.upload_file('local_file.txt', 'bucket_name', 's3_file.txt')

# Download a file
s3.download_file('bucket_name', 's3_file.txt', 'local_file.txt')
```



## 28. Monitoring Application Logs

- **Tail logs using tail -f equivalent in Python:**

```
python

import time

def tail_f(file):
    file.seek(0, 2) # Move to the end of the file
    while True:
        line = file.readline()
        if not line:
            time.sleep(0.1) # Sleep briefly
            continue
        print(line)

with open('app.log', 'r') as log_file:
    tail_f(log_file)
```

## 29. Container Health Checks

- **Check the health of a running Docker container:**

```
python

import docker

client = docker.from_env()
container = client.containers.get('container_id')
print(container.attrs['State']['Health']['Status'])
```

## 30. Using requests for Rate-Limited APIs

- **Handle rate limiting in API requests:**

```
python

import requests
import time

url = 'https://api.example.com/data'
while True:
    response = requests.get(url)
    if response.status_code == 200:
        print(response.json())
        break
    elif response.status_code == 429: # Too Many Requests
        time.sleep(60) # Wait a minute before retrying
    else:
        print('Error:', response.status_code)
        break
```

### 31. Docker Compose Integration

- **Using docker-compose in Python:**

```
python

import os
import subprocess

# Start services defined in docker-compose.yml
subprocess.run(['docker-compose', 'up', '-d'])

# Stop services
subprocess.run(['docker-compose', 'down'])
```

### 32. Terraform Execution

- **Executing Terraform commands with subprocess:**

```
python

import subprocess

# Initialize Terraform
subprocess.run(['terraform', 'init'])

# Apply configuration
subprocess.run(['terraform', 'apply', '-auto-approve'])
```

### 33. Working with Prometheus Metrics

- **Scraping and parsing Prometheus metrics:**

```
python

import requests

response = requests.get('http://localhost:9090/metrics')
metrics = response.text.splitlines()

for metric in metrics:
    print(metric)
```

### 34. Using pytest for Testing

- **Simple test case with pytest:**

```
python

def add(a, b):
    return a + b

def test_add():
    assert add(2, 3) == 5
```

### 35. Creating Webhooks

- **Using Flask to create a simple webhook:**

```
python

from flask import Flask, request

app = Flask(__name__)

@app.route('/webhook', methods=['POST'])
def webhook():
    data = request.json
    print('Received data:', data)
    return 'OK', 200

if __name__ == '__main__':
    app.run(port=5000)
```

### 36. Using Jinja2 for Configuration Templates

- **Render configuration files with Jinja2:**

```
python

from jinja2 import Template

template = Template('Hello, {{ name }}!')
rendered = template.render(name='DevOps')
print(rendered)
```

### 37. Encrypting and Decrypting Data

- **Using cryptography to encrypt and decrypt:**

```
python
```

```
from cryptography.fernet import Fernet

# Generate a key
key = Fernet.generate_key()
cipher_suite = Fernet(key)

# Encrypt
encrypted_text = cipher_suite.encrypt(b'Secret Data')

# Decrypt
decrypted_text = cipher_suite.decrypt(encrypted_text)
print(decrypted_text.decode())
```

### 38. Error Monitoring with Sentry

- **Sending error reports to Sentry:**

```
python

import sentry_sdk

sentry_sdk.init('your_sentry_dsn')

def divide(a, b):
    return a / b

try:
    divide(1, 0)
except ZeroDivisionError as e:
    sentry_sdk.capture_exception(e)
```

### 39. Setting Up Continuous Integration with GitHub Actions

- **Sample workflow file (.github/workflows/ci.yml):**

```
yaml
```

```
name: CI

on: [push]

jobs:
  build:
    runs-on: ubuntu-latest

    steps:
      - uses: actions/checkout@v2
      - name: Set up Python
        uses: actions/setup-python@v2
        with:
          python-version: '3.8'
      - name: Install dependencies
        run: |
          pip install -r requirements.txt
      - name: Run tests
        run: |
          pytest
```

## 40. Creating a Simple API with FastAPI

- **Using FastAPI for high-performance APIs:**

```
python

from fastapi import FastAPI

app = FastAPI()

@app.get('/items/{item_id}')
async def read_item(item_id: int):
    return {'item_id': item_id}

if __name__ == '__main__':
    import uvicorn
    uvicorn.run(app, host='0.0.0.0', port=8000)
```

## 41. Log Aggregation with ELK Stack

- **Sending logs to Elasticsearch:**

```
python

from elasticsearch import Elasticsearch

es = Elasticsearch(['http://localhost:9200'])

log = {'level': 'info', 'message': 'This is a log message'}
es.index(index='logs', body=log)
```

## 42. Using pandas for ETL Processes

- **Performing ETL with pandas:**

```
python

import pandas as pd

# Extract
data = pd.read_csv('source.csv')

# Transform
data['new_column'] = data['existing_column'].apply(lambda x: x * 2)

# Load
data.to_csv('destination.csv', index=False)
```

## 43. Serverless Applications with AWS Lambda

- **Deploying a simple AWS Lambda function:**

```
python

import json

def lambda_handler(event, context):
    return {
        'statusCode': 200,
        'body': json.dumps('Hello from Lambda!')
    }
```

#### 44. Working with Redis

- **Basic operations with Redis using redis-py:**

```
python

import redis

r = redis.StrictRedis(host='localhost', port=6379, db=0)

# Set a key
r.set('foo', 'bar')

# Get a key
print(r.get('foo'))
```

#### 45. Using pyngrok for Tunneling

- **Create a tunnel to expose a local server:**

```
python

from pyngrok import ngrok
```



```
# Start the tunnel
public_url = ngrok.connect(5000)
print('Public URL:', public_url)

# Keep the tunnel open
input('Press Enter to exit...')
```

## 46. Creating a REST API with Flask-RESTful

- **Building REST APIs with Flask-RESTful:**

```
python

from flask import Flask
from flask_restful import Resource, Api

app = Flask(__name__)
api = Api(app)

class HelloWorld(Resource):
    def get(self):
        return {'hello': 'world'}

api.add_resource(HelloWorld, '/')
```

```
if __name__ == '__main__':  
    app.run(debug=True)
```

#### 47. Using asyncio for Asynchronous Tasks

- **Running asynchronous tasks in Python:**

```
python  
  
import asyncio  
  
async def main():  
    print('Hello')  
    await asyncio.sleep(1)  
    print('World')  
  
asyncio.run(main())
```

#### 48. Network Monitoring with scapy

- **Packet sniffing using scapy:**

```
python  
  
from scapy.all import sniff  
  
def packet_callback(packet):  
    print(packet.summary())  
  
sniff(prn=packet_callback, count=10)
```

#### 49. Handling Configuration Files with configparser

- **Reading and writing to INI configuration files:**

```
python

import configparser

config = configparser.ConfigParser()
config.read('config.ini')

print(config['DEFAULT']['SomeSetting'])

config['DEFAULT']['NewSetting'] = 'Value'
with open('config.ini', 'w') as configfile:
    config.write(configfile)
```

## 50. WebSocket Client Example

- **Creating a WebSocket client with websocket-client:**

```
python

import websocket

def on_message(ws, message):
    print("Received message:", message)

ws = websocket.WebSocketApp("ws://echo.websocket.org",
                            on_message=on_message)
ws.run_forever()
```

## 51. Creating a Docker Image with Python

- **Using docker library to build an image:**

```
python

import docker

client = docker.from_env()

# Dockerfile content
dockerfile_content = """
FROM python:3.9-slim
WORKDIR /app
COPY . /app
RUN pip install -r requirements.txt
CMD ["python", "app.py"]
"""

# Create a Docker image
image, build_logs =
client.images.build(fileobj=dockerfile_content.encode('utf-8'),
tag='my-python-app')

for line in build_logs:
    print(line)
```

## 52. Using psutil for System Monitoring

- **Retrieve system metrics such as CPU and memory usage:**

```
python

import psutil

print("CPU Usage:", psutil.cpu_percent(interval=1), "%")
print("Memory Usage:", psutil.virtual_memory().percent, "%")
```

### 53. Database Migration with Alembic

- **Script to initialize Alembic migrations:**

```
python

from alembic import command
from alembic import config

alembic_cfg = config.Config("alembic.ini")
command.upgrade(alembic_cfg, "head")
```

### 54. Using paramiko for SSH Connections

- **Execute commands on a remote server via SSH:**

```
python

import paramiko

client = paramiko.SSHClient()
client.set_missing_host_key_policy(paramiko.AutoAddPolicy())
client.connect('hostname', username='user', password='your_password')

stdin, stdout, stderr = client.exec_command('ls -la')
print(stdout.read().decode())
client.close()
```

## 55. CloudFormation Stack Creation with boto3

- **Creating an AWS CloudFormation stack:**

```
python

import boto3

cloudformation = boto3.client('cloudformation')

with open('template.yaml', 'r') as template_file:
    template_body = template_file.read()

response = cloudformation.create_stack(
    StackName='MyStack',
    TemplateBody=template_body,
    Parameters=[
        {
            'ParameterKey': 'InstanceType',
            'ParameterValue': 't2.micro'
        },
    ],
    TimeoutInMinutes=5,
    Capabilities=['CAPABILITY_NAMED_IAM'],
)
print(response)
```

## 56. Automating EC2 Instance Management

- **Starting and stopping EC2 instances:**

```
python
```

```
import boto3

ec2 = boto3.resource('ec2')

# Start an instance
instance = ec2.Instance('instance_id')
instance.start()

# Stop an instance
instance.stop()
```

## 57. Automated Backup with shutil

- **Backup files to a specific directory:**

```
python

import shutil
import os

source_dir = '/path/to/source'
backup_dir = '/path/to/backup'

shutil.copytree(source_dir, backup_dir)
```

## 58. Using watchdog for File System Monitoring

- **Monitor changes in a directory:**

```
python

from watchdog.observers import Observer
from watchdog.events import FileSystemEventHandler
```

```
class MyHandler(FileSystemEventHandler):
    def on_modified(self, event):
        print(f'File modified: {event.src_path}')

event_handler = MyHandler()
observer = Observer()
observer.schedule(event_handler, path='path/to/monitor', recursive=False)
observer.start()

try:
    while True:
        time.sleep(1)
except KeyboardInterrupt:
    observer.stop()
observer.join()
```

## 59. Load Testing with locust

- **Basic Locust load testing setup:**

```
python

from locust import HttpUser, task, between

class MyUser(HttpUser):
    wait_time = between(1, 3)

    @task
    def load_test(self):
        self.client.get('/')

# To run, save this as locustfile.py and run: locust
```

## 60. Integrating with GitHub API

- **Fetching repository details using GitHub API:**

```
python

import requests
```



```
url = 'https://api.github.com/repos/user/repo'
response = requests.get(url, headers={'Authorization': 'token
YOUR_GITHUB_TOKEN'})
repo_info = response.json()
print(repo_info)
```

## 61. Managing Kubernetes Resources with kubectl

- **Using subprocess to interact with Kubernetes:**

```
python

import subprocess

# Get pods
subprocess.run(['kubectl', 'get', 'pods'])

# Apply a configuration
subprocess.run(['kubectl', 'apply', '-f', 'deployment.yaml'])
```

## 62. Using pytest for CI/CD Testing

- **Integrate tests in your CI/CD pipeline:**

```
python

# test_example.py
def test_addition():
```

```
assert 1 + 1 == 2
```

```
# Run pytest in your CI/CD pipeline
subprocess.run(['pytest'])
```

### 63. Creating a Simple CLI Tool with argparse

- **Build a command-line interface:**

```
python

import argparse

parser = argparse.ArgumentParser(description='Process some integers.')
parser.add_argument('integers', metavar='N', type=int, nargs='+', help='an
integer to be processed')
parser.add_argument('--sum', dest='accumulate', action='store_const',
const=sum, default=max, help='sum the integers (default: find the max)')

args = parser.parse_args()
print(args.accumulate(args.integers))
```

### 64. Using dotenv for Environment Variables

- **Load environment variables from a .env file:**

```
python

from dotenv import load_dotenv
import os

load_dotenv()

database_url = os.getenv('DATABASE_URL')
print(database_url)
```

## 65. Implementing Web Scraping with BeautifulSoup

- **Scraping a web page for data:**

```
python

import requests
from bs4 import BeautifulSoup

response = requests.get('http://example.com')
soup = BeautifulSoup(response.text, 'html.parser')

for item in soup.find_all('h1'):
    print(item.text)
```

## 66. Using PyYAML for YAML Configuration Files

- **Load and dump YAML files:**

```
python

import yaml

# Load YAML file
with open('config.yaml', 'r') as file:
    config = yaml.safe_load(file)
    print(config)

# Dump to YAML file
with open('output.yaml', 'w') as file:
    yaml.dump(config, file)
```

## 67. Creating a Simple Message Queue with RabbitMQ

- **Send and receive messages using pika:**

```
python
```

```
import pika

# Sending messages
connection =
pika.BlockingConnection(pika.ConnectionParameters('localhost'))
channel = connection.channel()
channel.queue_declare(queue='hello')

channel.basic_publish(exchange="", routing_key='hello', body='Hello
World!')
connection.close()

# Receiving messages
def callback(ch, method, properties, body):
    print("Received:", body)

connection =
pika.BlockingConnection(pika.ConnectionParameters('localhost'))
channel = connection.channel()
channel.queue_declare(queue='hello')

channel.basic_consume(queue='hello', on_message_callback=callback,
auto_ack=True)
channel.start_consuming()
```

## 68. Using sentry\_sdk for Monitoring

- **Integrate Sentry for error tracking:**

```
python

import sentry_sdk

sentry_sdk.init("YOUR_SENTRY_DSN")

try:
    # Your code that may throw an exception
```

1 / 0

```
except Exception as e:  
    sentry_sdk.capture_exception(e)
```

## 69. Using openpyxl for Excel File Manipulation

- **Read and write Excel files:**

```
python  
  
from openpyxl import Workbook, load_workbook  
  
# Create a new workbook  
wb = Workbook()  
ws = wb.active  
ws['A1'] = 'Hello'  
wb.save('sample.xlsx')  
  
# Load an existing workbook  
wb = load_workbook('sample.xlsx')  
ws = wb.active  
print(ws['A1'].value)
```

## 70. Using sqlalchemy for Database Interaction

- **Define a model and perform CRUD operations:**

```
python  
  
from sqlalchemy import create_engine, Column, Integer, String  
from sqlalchemy.ext.declarative import declarative_base  
from sqlalchemy.orm import sessionmaker  
  
Base = declarative_base()  
  
class User(Base):  
    __tablename__ = 'users'
```

```
id = Column(Integer, primary_key=True)
name = Column(String)

engine = create_engine('sqlite:///example.db')
Base.metadata.create_all(engine)

Session = sessionmaker(bind=engine)
session = Session()

# Create
new_user = User(name='Alice')
session.add(new_user)
```

## 71. Monitoring Docker Containers with docker-py

- **Fetch and print the status of running containers:**

```
python

import docker

client = docker.from_env()
containers = client.containers.list()

for container in containers:
    print(f'Container Name: {container.name}, Status: {container.status}')
```

## 72. Using flask to Create a Simple API

- **Basic API setup with Flask:**

```
python

from flask import Flask, jsonify

app = Flask(__name__)

@app.route('/api/data', methods=['GET'])
```

```
def get_data():  
    return jsonify({"message": "Hello, World!"})  
  
if __name__ == '__main__':  
    app.run(debug=True)
```

### 73. Automating Certificate Renewal with certbot

- **Script to renew Let's Encrypt certificates:**

```
python  
  
import subprocess  
  
# Renew certificates  
subprocess.run(['certbot', 'renew'])
```

### 74. Using numpy for Data Analysis

- **Performing basic numerical operations:**

```
python  
  
import numpy as np  
  
data = np.array([1, 2, 3, 4, 5])  
mean_value = np.mean(data)  
print("Mean Value:", mean_value)
```

### 75. Creating and Sending Emails with smtplib

- **Send an email using Python:**

```
python
```

```
import smtplib
from email.mime.text import MIMEText

sender = 'you@example.com'
recipient = 'recipient@example.com'
msg = MIMEText('This is a test email.')
msg['Subject'] = 'Test Email'
msg['From'] = sender
msg['To'] = recipient

with smtplib.SMTP('smtp.example.com') as server:
    server.login('username', 'password')
    server.send_message(msg)
```

## 76. Using schedule for Task Scheduling

- **Schedule tasks at regular intervals:**

```
python

import schedule
import time

def job():
    print("Job is running...")

schedule.every(10).minutes.do(job)

while True:
    schedule.run_pending()
    time.sleep(1)
```

## 77. Using matplotlib for Data Visualization

- **Plotting a simple graph:**

```
python
```



```
import matplotlib.pyplot as plt

x = [1, 2, 3, 4, 5]
y = [2, 3, 5, 7, 11]

plt.plot(x, y)
plt.xlabel('X-axis')
plt.ylabel('Y-axis')
plt.title('Simple Plot')
plt.show()
```

## 78. Creating a Custom Python Package

- **Structure your project as a package:**

markdown

```
my_package/
├── __init__.py
├── module1.py
└── module2.py
```

- **setup.py for packaging:**

python

```
from setuptools import setup, find_packages
```

```
setup(
    name='my_package',
    version='0.1',
    packages=find_packages(),
    install_requires=[
        'requests',
        'flask'
    ],
)
```

## 79. Using pytest for Unit Testing

- **Writing a simple unit test:**

```
python

# test_sample.py
def add(a, b):
    return a + b

def test_add():
    assert add(1, 2) == 3
```

## 80. Implementing OAuth with requests-oauthlib

- **Authenticate with an API using OAuth:**

```
python

from requests_oauthlib import OAuth1Session

oauth = OAuth1Session(client_key='YOUR_CLIENT_KEY',
                      client_secret='YOUR_CLIENT_SECRET')
response = oauth.get('https://api.example.com/user')
print(response.json())
```

## 81. Using pandas for Data Manipulation

- **Load and manipulate data in a CSV file:**

```
python

import pandas as pd

df = pd.read_csv('data.csv')
print(df.head())
```

```
# Filter data
filtered_df = df[df['column_name'] > 10]
print(filtered_df)
```

## 82. Using requests for HTTP Requests

- **Making a GET and POST request:**

```
python

import requests

# GET request
response = requests.get('https://api.example.com/data')
print(response.json())

# POST request
data = {'key': 'value'}
response = requests.post('https://api.example.com/data', json=data)
print(response.json())
```

## 83. Creating a Basic Web Server with http.server

- **Simple HTTP server to serve files:**

```
python

from http.server import SimpleHTTPRequestHandler, HTTPServer

PORT = 8000
handler = SimpleHTTPRequestHandler

with HTTPServer(('', PORT), handler) as httpd:
    print(f'Serving on port {PORT}')
    httpd.serve_forever()
```

## 84. Using Flask for Webhooks

- **Handling incoming webhook requests:**

```
python

from flask import Flask, request

app = Flask(__name__)

@app.route('/webhook', methods=['POST'])
def webhook():
    data = request.json
    print(data)
    return "", 200

if __name__ == '__main__':
    app.run(port=5000)
```

## 85. Creating a Bash Script with subprocess

- **Run shell commands from Python:**

```
python

import subprocess

subprocess.run(['echo', 'Hello, World!'])
```

## 86. Using docker-compose with Python

- **Programmatically run Docker Compose commands:**

```
python

import subprocess
```

```
subprocess.run(['docker-compose', 'up', '-d'])
```

## 87. Using moto for Mocking AWS Services in Tests

- **Mocking AWS S3 for unit testing:**

```
python

import boto3
from moto import mock_s3

@mock_s3
def test_s3_upload():
    s3 = boto3.client('s3', region_name='us-east-1')
    s3.create_bucket(Bucket='my-bucket')
    s3.upload_file('file.txt', 'my-bucket', 'file.txt')
    # Test logic here
```

## 88. Using asyncio for Asynchronous Tasks

- **Run multiple tasks concurrently:**

```
python

import asyncio

async def say_hello():
    print("Hello")
    await asyncio.sleep(1)
    print("World")

async def main():
    await asyncio.gather(say_hello(), say_hello())

asyncio.run(main())
```

## 89. Using flask-cors for Cross-Origin Resource Sharing

- **Allow CORS in a Flask app:**

```
python

from flask import Flask
from flask_cors import CORS

app = Flask(__name__)
CORS(app)

@app.route('/data', methods=['GET'])
def data():
    return {"message": "Hello from CORS!"}

if __name__ == '__main__':
    app.run()
```

## 90. Using pytest Fixtures for Setup and Teardown

- **Create a fixture to manage resources:**

```
python

import pytest

@pytest.fixture
def sample_data():
    data = {"key": "value"}
    yield data # This is the test data
    # Teardown code here (if necessary)

def test_sample_data(sample_data):
    assert sample_data['key'] == 'value'
```

## 91. Using http.client for Low-Level HTTP Requests

- **Make a raw HTTP GET request:**

```
python

import http.client

conn = http.client.HTTPSConnection("www.example.com")
conn.request("GET", "/")
response = conn.getresponse()
print(response.status, response.reason)
data = response.read()
conn.close()
```

## 92. Implementing Redis Caching with redis-py

- **Basic operations with Redis:**

```
python

import redis

r = redis.StrictRedis(host='localhost', port=6379, db=0)

# Set and get value
r.set('key', 'value')
print(r.get('key').decode('utf-8'))
```

## 93. Using json for Data Serialization

- **Convert Python objects to JSON:**

```
python

import json

data = {"key": "value"}
json_data = json.dumps(data)
```

```
print(json_data)
```

#### 94. Using xml.etree.ElementTree for XML Processing

- **Parse an XML file:**

```
python

import xml.etree.ElementTree as ET

tree = ET.parse('data.xml')
root = tree.getroot()

for child in root:
    print(child.tag, child.attrib)
```

#### 95. Creating a Virtual Environment with venv

- **Programmatically create a virtual environment:**

```
python

import venv

venv.create('myenv', with_pip=True)
```

#### 96. Using psutil for System Monitoring

- **Get system memory usage:**

```
python

import psutil

memory = psutil.virtual_memory()
print(f'Total Memory: {memory.total}, Available Memory: {memory.available}')
```



## 97. Using sqlite3 for Lightweight Database Management

- **Basic SQLite operations:**

```
python
```

```
import sqlite3
```

```
conn = sqlite3.connect('example.db')
```

```
c = conn.cursor()
```

```
c.execute("CREATE TABLE IF NOT EXISTS users (id INTEGER  
PRIMARY KEY, name TEXT)")
```

```
c.execute("INSERT INTO users (name) VALUES ('Alice')")
```

```
conn.commit()
```

```
for row in c.execute('SELECT * FROM users'):  
    print(row)
```

```
conn.close()
```

## 98. Using pytest to Run Tests in Parallel

- **Run tests concurrently:**

```
bash
```

```
pytest -n 4 # Run tests in parallel with 4 workers
```

## 99. Using argparse for Command-Line Arguments

- **Parse command-line arguments:**

python

```
import argparse
```

```
parser = argparse.ArgumentParser(description='Process some integers.')
parser.add_argument('integers', metavar='N', type=int, nargs='+',
                    help='an integer for the accumulator')
parser.add_argument('--sum', dest='accumulate', action='store_const',
                    const=sum, default=max,
                    help='sum the integers (default: find the max)')
```

```
args = parser.parse_args()
print(args.accumulate(args.integers))
```

## 100. Using jsonschema for JSON Validation

- **Validate JSON against a schema:**

python

```
from jsonschema import validate
from jsonschema.exceptions import ValidationError
```

```
schema = {
    "type": "object",
    "properties": {
        "name": {"type": "string"},
        "age": {"type": "integer", "minimum": 0}
    },
    "required": ["name", "age"]
}
```

```
data = {"name": "John", "age": 30}
```

```
try:
    validate(instance=data, schema=schema)
    print("Data is valid")
except ValidationError as e:
    print(f"Data is invalid: {e.message}")
```

## 2. Version Control

- Git

### 1. Git Setup and Configuration

```
git --version          # Check Git version
git config --global user.name "Your Name" # Set global username
git config --global user.email "your.email@example.com" # Set global email
git config --global core.editor "vim" # Set default editor
git config --global init.defaultBranch main # Set default branch name
git config --list       # View Git configuration
git help <command>     # Get help for a Git command
```

---

### 2. Creating and Cloning Repositories

```
git init              # Initialize a new Git repository
git clone <repo_url>   # Clone an existing repository
git remote add origin <repo_url> # Link local repo to a remote repo
git remote -v         # List remote repositories
```

---

### 3. Staging and Committing Changes

```
git status            # Check the status of changes
git add <file>        # Add a file to the staging area
git add .             # Add all files to the staging area
git commit -m "Commit message" # Commit staged files
git commit -am "Commit message" # Add & commit changes in one step
```

`git commit --amend -m "New message"` # Modify the last commit message

---

#### 4. Viewing History and Logs

`git log` # Show commit history  
`git log --oneline` # Show history in one-line format  
`git log --graph --decorate --all` # Display commit history as a graph  
`git show <commit_id>` # Show details of a specific commit  
`git diff` # Show unstaged changes  
`git diff --staged` # Show staged but uncommitted changes  
`git blame <file>` # Show who modified each line of a file

---

#### 5. Branching and Merging

`git branch` # List all branches  
`git branch <branch_name>` # Create a new branch  
`git checkout <branch_name>` # Switch to another branch  
`git checkout -b <branch_name>` # Create and switch to a new branch  
`git merge <branch_name>` # Merge a branch into the current branch  
`git branch -d <branch_name>` # Delete a local branch  
`git branch -D <branch_name>` # Force delete a branch

---

#### 6. Working with Remote Repositories

`git fetch` # Fetch changes from remote repo  
`git pull origin <branch_name>` # Pull latest changes  
`git push origin <branch_name>` # Push changes to remote repo  
`git push -u origin <branch_name>` # Push and set upstream tracking

```
git remote show origin      # Show details of the remote repo
git remote rm origin        # Remove the remote repository
```

---

## 7. Undoing Changes

```
git restore <file>          # Unstage changes
git restore --staged <file>  # Unstage a file from the staging area
git reset HEAD~1            # Undo the last commit but keep changes
git reset --hard HEAD~1     # Undo the last commit and discard changes
git revert <commit_id>      # Create a new commit to undo changes
git stash                   # Save uncommitted changes temporarily
git stash pop               # Apply stashed changes
git stash drop              # Remove stashed changes
```

---

## 8. Tagging and Releases

```
git tag                     # List all tags
git tag <tag_name>          # Create a tag
git tag -a <tag_name> -m "Tag message" # Create an annotated tag
git push origin <tag_name>   # Push a tag to remote
git tag -d <tag_name>        # Delete a local tag
git push --delete origin <tag_name> # Delete a remote tag
```

---

## 9. Working with Submodules

```
git submodule add <repo_url> <path> # Add a submodule
git submodule update --init --recursive # Initialize and update submodules
git submodule foreach git pull origin main # Update all submodules
```

## 10. Git Aliases (Shortcuts)

```
git config --global alias.st status # Create alias for status command
git config --global alias.co checkout # Create alias for checkout command
git config --global alias.br branch # Create alias for branch command
git config --global alias.cm commit # Create alias for commit command
git config --list | grep alias      # View all configured aliases
```

---

## 11. Deleting Files and Folders

```
git rm <file>                # Remove a file and stage deletion
git rm -r <folder>            # Remove a directory
git rm --cached <file>        # Remove file from repo but keep locally
```

---

## 12. Force Push and Rollback (Use with Caution)

```
git push --force              # Force push changes
git reset --hard <commit_id> # Reset repo to a specific commit
git reflog                    # Show history of HEAD changes
git reset --hard ORIG_HEAD    # Undo the last reset
```

---

# 1. GitHub

## Authentication & Configuration

gh auth logout – Log out of GitHub CLI

gh auth status – Check authentication status

gh auth refresh – Refresh authentication token

gh config set editor <editor> – Set the default editor (e.g., nano, vim)

gh config get editor – Get the current editor setting

### **Repository Management**

gh repo list – List repositories for the authenticated user

gh repo delete <name> – Delete a repository

gh repo rename <new-name> – Rename a repository

gh repo fork --clone=false <url> – Fork a repository without cloning

### **Branch & Commit Management**

gh branch list – List branches in a repository

gh branch delete <branch> – Delete a branch

gh browse – Open the repository in a browser

gh co <branch> – Check out a branch

### **Issue & Pull Request Handling**

gh issue create – Create a new issue

gh issue close <issue-number> – Close an issue

gh issue reopen <issue-number> – Reopen a closed issue

gh issue comment <issue-number> --body "Comment" – Add a comment to an issue

gh pr list – List open pull requests

gh pr checkout <pr-number> – Check out a pull request branch

gh pr close <pr-number> – Close a pull request

### **Gists & Actions**

gh gist create <file> – Create a new gist

gh gist list – List all gists

gh workflow list – List GitHub Actions workflows

gh run list – List workflow runs

### **Webhooks:**

- Go to **Repo** → **Settings** → **Webhooks** → **Add Webhook**
- Events: push, pull\_request, issues, etc.
- Payload sent in JSON format to the specified URL

---

## **3. GitLab**

### **Commands**

#### **Project & Repository Management**

gitlab project create <name> – Create a new project

gitlab repo list – List repositories

gitlab project delete <id> – Delete a project

gitlab repo fork <repo> – Fork a repository



gitlab repo clone <url> – Clone a GitLab repository  
gitlab repo archive <repo> – Archive a repository

### **Issues & Merge Requests**

gitlab issue list – List all issues in a project  
gitlab issue create --title "<title>" --description "<desc>" – Create an issue  
gitlab issue close <issue\_id> – Close an issue  
gitlab issue reopen <issue\_id> – Reopen an issue  
gitlab merge\_request list – List merge requests  
gitlab merge\_request create --source-branch <branch> --target-branch <branch>  
--title "<title>" – Create a merge request  
gitlab merge\_request close <mr\_id> – Close a merge request

### **Pipeline & CI/CD**

gitlab pipeline trigger – Trigger a pipeline  
gitlab pipeline list – List all pipelines  
gitlab pipeline retry <pipeline\_id> – Retry a failed pipeline  
gitlab pipeline cancel <pipeline\_id> – Cancel a running pipeline  
gitlab pipeline delete <pipeline\_id> – Delete a pipeline  
gitlab runner register – Register a CI/CD runner  
gitlab runner list – List registered runners  
gitlab runner unregister <runner\_id> – Unregister a runner

### **User & Group Management**

gitlab user list – List users in GitLab  
gitlab user create --name "<name>" --email "<email>" – Create a new user  
gitlab group list – List groups in GitLab  
gitlab group create --name "<group\_name>" --path "<group\_path>" – Create a group  
gitlab group delete <group\_id> – Delete a group

### **Access & Permissions**

gitlab project member list <project\_id> – List project members

gitlab project member add <project\_id> <user\_id> <access\_level> – Add a user to a project

gitlab group member list <group\_id> – List group members

gitlab group member add <group\_id> <user\_id> <access\_level> – Add a user to a group

## **Repository Protection & Settings**

gitlab branch protect <branch> – Protect a branch

gitlab branch unprotect <branch> – Unprotect a branch

gitlab repository mirror – Set up repository mirroring

gitlab repository settings update – Update repository settings

## **Webhooks:**

- Go to **Settings** → **Webhooks**
  - Select triggers: Push events, Tag push, Merge request, etc.
  - Use GitLab CI/CD with .gitlab-ci.yml
- 

## **4. Bitbucket**

### **Commands**

### **Repository Management**

- bitbucket repo create <name> – Create a repository
- bitbucket repo list – List all repositories
- bitbucket repo delete <name> – Delete a repository
- bitbucket repo clone <repo-url> – Clone a repository
- bitbucket repo fork <repo> – Fork a repository
- bitbucket repo update <repo> – Update repository settings

### **Branch Management**

- bitbucket branch create <branch-name> – Create a new branch

- bitbucket branch list – List all branches
- bitbucket branch delete <branch-name> – Delete a branch

## Pipeline Management

- bitbucket pipeline run – Run a pipeline
- bitbucket pipeline list – List pipelines
- bitbucket pipeline stop <pipeline-id> – Stop a running pipeline
- bitbucket pipeline rerun <pipeline-id> – Rerun a pipeline

## Issue Tracking

- bitbucket issue list – List all issues
- bitbucket issue create "<title>" --kind=<bug/task/enhancement> – Create an issue
- bitbucket issue update <issue-id> --status=<open/closed/resolved> – Update issue status
- bitbucket issue delete <issue-id> – Delete an issue

## Pull Request Management

- bitbucket pullrequest create --source <branch> --destination <branch> – Create a pull request
- bitbucket pullrequest list – List pull requests
- bitbucket pullrequest merge <id> – Merge a pull request
- bitbucket pullrequest approve <id> – Approve a pull request
- bitbucket pullrequest decline <id> – Decline a pull request

## Webhooks:

- Go to **Repo** → **Repository Settings** → **Webhooks**
  - Choose event types like repo:push, pullrequest:created, etc.
-

## 2. Continuous Integration (CI) & Continuous Deployment (CD)

- **Jenkins** (pipelines, declarative scripts)

### Jenkins Installation (Ubuntu)

#### # Install Java (Jenkins requires Java)

```
sudo apt update && sudo apt install -y openjdk-17-jdk
```

#### # Add Jenkins repository & install Jenkins

```
wget -q -O - https://pkg.jenkins.io/debian-stable/jenkins.io.key | sudo tee  
/usr/share/keyrings/jenkins-keyring.asc > /dev/null  
echo "deb [signed-by=/usr/share/keyrings/jenkins-keyring.asc]  
https://pkg.jenkins.io/debian-stable binary/" | sudo tee  
/etc/apt/sources.list.d/jenkins.list > /dev/null  
sudo apt update && sudo apt install -y jenkins
```

#### # Start & Enable Jenkins

```
sudo systemctl enable --now jenkins
```

#### # Check Jenkins status

```
sudo systemctl status jenkins
```

#### # Access Jenkins UI at <http://your-server-ip:8080>

```
sudo cat /var/lib/jenkins/secrets/initialAdminPassword
```

---

### 1. Basic Jenkins Commands

```
systemctl start jenkins    # Start Jenkins service  
systemctl stop jenkins     # Stop Jenkins service  
systemctl restart jenkins  # Restart Jenkins service  
systemctl status jenkins   # Check Jenkins service status
```

```
journalctl -u jenkins -f    # View real-time logs
```

## 2. Jenkins CLI Commands

```
java -jar jenkins-cli.jar -s http://localhost:8080 list-jobs    # List all jobs
java -jar jenkins-cli.jar -s http://localhost:8080 build <job-name> # Trigger a job
java -jar jenkins-cli.jar -s http://localhost:8080 delete-job <job-name> # Delete a
job
java -jar jenkins-cli.jar -s http://localhost:8080 enable-job <job-name> # Enable a
job
java -jar jenkins-cli.jar -s http://localhost:8080 disable-job <job-name> # Disable a
job
java -jar jenkins-cli.jar -s http://localhost:8080 who-am-i # Show current user info
```

## 3. Jenkins Environment Variables

```
JENKINS_HOME    # Jenkins home directory
BUILD_NUMBER    # Current build number
JOB_NAME        # Job name
WORKSPACE       # Workspace directory
GIT_COMMIT      # Git commit hash of the build
BUILD_URL       # URL of the build
NODE_NAME       # Name of the node the build is running on
```

## 4. Jenkins Pipeline (Declarative)

```
groovy

pipeline {
    agent any
    environment {
        APP_ENV = 'production'
    }
    stages {
        stage('Checkout') {
```

```
    steps {
        git 'https://github.com/your-repo.git'
    }
}
stage('Build') {
    steps {
        sh 'mvn clean package'
    }
}
stage('Test') {
    steps {
        sh 'mvn test'
    }
}
stage('Deploy') {
    steps {
        sh 'scp target/*.jar user@server:/deploy/'
    }
}
}
```

## 5. Jenkins Pipeline (Scripted)

groovy

```
node {
    stage('Checkout') {
        git 'https://github.com/your-repo.git'
    }
    stage('Build') {
        sh 'mvn clean package'
    }
    stage('Test') {
        sh 'mvn test'
    }
}
```

```
}  
stage('Deploy') {  
    sh 'scp target/*.jar user@server:/deploy/'  
}  
}
```

## 6. Jenkins Webhook (GitHub Example)

1. **Go to GitHub Repo > Settings > Webhooks**
2. **Add URL:** `http://<jenkins-url>/github-webhook/`
3. **Select** application/json as content type
4. **Choose** Just the push event
5. **Save and trigger a push event to test**

## 7. Manage Plugins via CLI

```
java -jar jenkins-cli.jar -s http://localhost:8080 install-plugin <plugin-name> #
```

Install a plugin

```
java -jar jenkins-cli.jar -s http://localhost:8080 list-plugins # List
```

installed plugins

```
java -jar jenkins-cli.jar -s http://localhost:8080 safe-restart # Restart
```

safely after installing plugins

## 8. Manage Jenkins Jobs via CLI

```
java -jar jenkins-cli.jar -s http://localhost:8080 create-job my-job < job-config.xml
```

# Create a job

```
java -jar jenkins-cli.jar -s http://localhost:8080 get-job my-job > job-config.xml #
```

Export job config

```
java -jar jenkins-cli.jar -s http://localhost:8080 update-job my-job < job-config.xml
```

# Update job config

## 9. Backup & Restore Jenkins

```
cp -r $JENKINS_HOME /backup/jenkins_$(date +%F) # Backup Jenkins
```

```
cp -r /backup/jenkins_<date>/* $JENKINS_HOME # Restore Jenkins
```

## 10. Jenkins Security Commands

```
java -jar jenkins-cli.jar -s http://localhost:8080 reload-configuration # Reload  
config
```

```
java -jar jenkins-cli.jar -s http://localhost:8080 safe-shutdown      # Safe  
shutdown
```

```
java -jar jenkins-cli.jar -s http://localhost:8080 restart          # Restart Jenkins
```

## 11. Jenkins Credentials via CLI

```
java -jar jenkins-cli.jar -s http://localhost:8080 create-credentials-by-xml  
system::system::jenkins _ < credentials.xml
```

## 12. Jenkins Node Management

```
java -jar jenkins-cli.jar -s http://localhost:8080 list-nodes        # List all nodes
```

```
java -jar jenkins-cli.jar -s http://localhost:8080 create-node <node-name> # Create  
a new node
```

```
java -jar jenkins-cli.jar -s http://localhost:8080 delete-node <node-name> # Delete  
a node
```

## 13. Jenkins Job Trigger Examples

groovy

```
trigger {  
    cron('H 4 * * *') # Run at 4 AM every day  
}
```

```
trigger {  
    pollSCM('H/5 * * * *') # Check SCM every 5 minutes  
}
```

## 14. Jenkins File Parameter Example

groovy



```
pipeline {
  agent any
  parameters {
    file(name: 'configFile')
  }
  stages {
    stage('Read File') {
      steps {
        sh 'cat ${configFile}'
      }
    }
  }
}
```

## 15. Jenkins Docker Pipeline Example

```
groovy
pipeline {
  agent {
    docker {
      image 'maven:3.8.7'
    }
  }
  stages {
    stage('Build') {
      steps {
        sh 'mvn clean package'
      }
    }
  }
}
```

---

## Jenkins Pipeline Scripts with DevOps Tools

### 1. Basic CI/CD Pipeline

groovy

```
pipeline {
  agent any
  stages {
    stage('Clone Repository') {
      steps {
        git 'https://github.com/user/repo.git'
      }
    }
    stage('Build') {
      steps {
        sh 'mvn clean package'
      }
    }
    stage('Test') {
      steps {
        sh 'mvn test'
      }
    }
    stage('Deploy') {
      steps {
        sh 'scp target/app.jar user@server:/deploy/path'
      }
    }
  }
}
```

---

### 2. Docker Build & Push

groovy

```
pipeline {
  agent any
  environment {
    DOCKER_HUB_USER = 'your-dockerhub-username'
  }
  stages {
    stage('Build Docker Image') {
      steps {
        sh 'docker build -t my-app:latest .'
      }
    }
    stage('Push to Docker Hub') {
      steps {
        withDockerRegistry([credentialsId: 'docker-hub-credentials', url: '']) {
          sh 'docker tag my-app:latest $DOCKER_HUB_USER/my-app:latest'
          sh 'docker push $DOCKER_HUB_USER/my-app:latest'
        }
      }
    }
  }
}
```

---

### 3. Kubernetes Deployment

groovy

```
pipeline {
  agent any
  stages {
    stage('Deploy to Kubernetes') {
      steps {
        sh 'kubectl apply -f k8s/deployment.'
      }
    }
  }
}
```

```
}  
}
```

---

#### 4. Terraform Deployment

groovy

```
pipeline {  
  agent any  
  stages {  
    stage('Terraform Init') {  
      steps {  
        sh 'terraform init'  
      }  
    }  
    stage('Terraform Apply') {  
      steps {  
        sh 'terraform apply -auto-approve'  
      }  
    }  
  }  
}
```

---

#### 5. Security Scanning with Trivy

groovy

```
pipeline {  
  agent any  
  stages {  
    stage('Scan with Trivy') {  
      steps {  
        sh 'trivy image my-app:latest'  
      }  
    }  
  }  
}
```

```
    }  
  }  
}
```

---

## 6. SonarQube Code Analysis

groovy

```
pipeline {  
  agent any  
  environment {  
    SONAR_TOKEN = credentials('sonar-token')  
  }  
  stages {  
    stage('SonarQube Analysis') {  
      steps {  
        withSonarQubeEnv('SonarQube') {  
          sh 'mvn sonar:sonar -Dsonar.login=$SONAR_TOKEN'  
        }  
      }  
    }  
  }  
}
```

---

- **GitHub Actions** (workflows, syntax)

GitHub Actions allows automation for CI/CD pipelines directly within GitHub repositories.

- **Workflows** (.github/workflows/\*.yml): Defines automation steps.
- **Jobs**: Runs tasks inside a workflow.
- **Steps**: Individual commands executed in jobs.
- **Actions**: Predefined or custom reusable commands.

## **Commands**

### **# Initialize a GitHub Actions workflow**

```
mkdir -p .github/workflows && touch .github/workflows/main.yml
```

### **# Validate GitHub Actions workflow syntax**

```
act -l # List available workflows
```

```
act -j <job-name> # Run a specific job locally
```

```
act -w .github/workflows/main.yml # Run the workflow locally
```

### **# Set up GitHub Actions runner**

```
gh workflow list # List workflows in the repo
```

```
gh workflow run <workflow-name> # Manually trigger a workflow
```

```
gh workflow enable <workflow-name> # Enable a workflow
```

```
gh workflow disable <workflow-name> # Disable a workflow
```

### **# Manage workflow runs**

```
gh run list # List recent workflow runs
```

```
gh run view <run-id> # View details of a specific workflow run
```

```
gh run rerun <run-id> # Rerun a failed workflow
```

```
gh run cancel <run-id> # Cancel a running workflow
```

gh run delete <run-id> # Delete a workflow run

### **# Manage workflow artifacts**

gh run download -n <artifact-name> # Download artifacts from a workflow run

gh run view --log # View logs of the latest workflow run

### **# Manage secrets for GitHub Actions**

gh secret list # List repository secrets

gh secret set <SECRET\_NAME> --body <value> # Add or update a secret

gh secret remove <SECRET\_NAME> # Remove a secret

### **# Using GitHub Actions Cache**

actions/cache@v3 # GitHub Actions cache

actions/upload-artifact@v3 # Upload artifacts

actions/download-artifact@v3 # Download artifacts

### **# Run a workflow manually via API**

curl -X POST -H "Authorization: token <YOUR\_GITHUB\_TOKEN>" \

-H "Accept: application/vnd.github.v3+json" \

[https://api.github.com/repos/<owner>/<repo>/actions/workflows/<workflow\\_file>/dispatches](https://api.github.com/repos/<owner>/<repo>/actions/workflows/<workflow_file>/dispatches) \

```
-d '{"ref":"main"}'
```

---

## Github Actions Workflow:

### 🔗 Basic GitHub Actions Workflow

📌 **File:** .github/workflows/ci-cd.yml

```
name: CI/CD Pipeline
```

```
on:
```

```
  push:
```

```
    branches:
```

```
      - main
```

```
  pull_request:
```

```
jobs:
```

```
  build:
```

```
    runs-on: ubuntu-latest
```

```
    steps:
```

```
      - name: Checkout Code
```

```
        uses: actions/checkout@v4
```

```
      - name: Set Up Java
```

```
        uses: actions/setup-java@v3
```

```
        with:
```

```
          distribution: 'temurin'
```

```
          java-version: '17'
```

```
      - name: Build with Maven
```

```
        run: mvn clean package
```



- name: Upload Build Artifact
  - uses: actions/upload-artifact@v4
  - with:
    - name: application
    - path: target/\*.jar

---

## 🚧 Docker Build & Push to Docker Hub

✂ **File:** .github/workflows/docker.yml

name: Docker Build & Push

on:  
push:  
branches:  
- main

jobs:  
docker:  
runs-on: ubuntu-latest  
steps:  
- name: Checkout Code

- uses: actions/checkout@v4

  
- name: Login to Docker Hub

- uses: docker/login-action@v3
- with:
  - username: \${ secrets.DOCKER\_USERNAME }
  - password: \${ secrets.DOCKER\_PASSWORD }

  
- name: Build and Push Docker Image

- run: |  
docker build -t my-app:latest .

```
docker tag my-app:latest ${ secrets.DOCKER_USERNAME
} }/my-app:latest
docker push ${ secrets.DOCKER_USERNAME } }/my-app:latest
```

---

## ◆ Kubernetes Deployment

✦ **File:** .github/workflows/k8s.yml

name: Deploy to Kubernetes

on:

push:

branches:

- main

jobs:

deploy:

runs-on: ubuntu-latest

steps:

- name: Checkout Code

uses: actions/checkout@v4

- name: Set Up Kubectl

uses: azure/setup-kubectl@v3

with:

version: 'latest'

- name: Apply Kubernetes Manifest

run: kubectl apply -f k8s/deployment.

---

## ◆ Terraform Deployment

✦ **File:** .github/workflows/terraform.yml

name: Terraform Deployment

on:

push:

branches:

- main

jobs:

terraform:

runs-on: ubuntu-latest

steps:

- name: Checkout Code

uses: actions/checkout@v4

- name: Set Up Terraform

uses: hashicorp/setup-terraform@v3

- name: Terraform Init & Apply

run: |

terraform init

terraform apply -auto-approve

---

## ◆ Security Scanning with Trivy

✦ **File:** .github/workflows/trivy.yml

name: Security Scan with Trivy

on:

push:

branches:

- main

```
jobs:
  scan:
    runs-on: ubuntu-latest
    steps:
      - name: Checkout Code
        uses: actions/checkout@v4

      - name: Run Trivy Image Scan
        run: |
          docker pull ${ secrets.DOCKER_USERNAME }/my-app:latest
          trivy image ${ secrets.DOCKER_USERNAME }/my-app:latest
```

---

## ◆ SonarQube Code Analysis

✦ **File:** .github/workflows/sonarqube.yml

name: SonarQube Analysis

```
on:
  push:
    branches:
      - main
```

```
jobs:
  sonar:
    runs-on: ubuntu-latest
    steps:
      - name: Checkout Code
        uses: actions/checkout@v4

      - name: Set Up Java
        uses: actions/setup-java@v3
```

with:

distribution: 'temurin'

java-version: '17'

- name: Run SonarQube Analysis

run: mvn sonar:sonar -Dsonar.login=\${{ secrets.SONAR\_TOKEN }}

---

## 🔗 Upload & Deploy to AWS S3

📌 **File:** .github/workflows/s3-upload.yml

name: Upload to S3

on:

push:

branches:

- main

jobs:

deploy:

runs-on: ubuntu-latest

steps:

- name: Checkout Code

uses: actions/checkout@v4

- name: Upload Files to S3

run: |

aws s3 sync . s3://my-bucket-name --delete

env:

AWS\_ACCESS\_KEY\_ID: \${{ secrets.AWS\_ACCESS\_KEY }}

AWS\_SECRET\_ACCESS\_KEY: \${{ secrets.AWS\_SECRET\_KEY }}

---

- **GitLab CI/CD** (stages, jobs, runners)

## GitLab CI/CD Basics

- **.gitlab-ci.yml**: Defines the CI/CD pipeline in the repository root.
  - **Stages**: Pipeline execution order (build, test, deploy).
  - **Jobs**: Specific tasks in each stage.
  - **Runners**: Machines executing jobs (shared or self-hosted).
  - **Artifacts**: Files preserved after job execution.
- 

### ⚙️ Basic GitLab CI/CD Pipeline

📌 **File:** .gitlab-ci.yml

stages:

- build
- test
- deploy

build:

stage: build

script:

- echo "Building application..."
- mvn clean package

artifacts:

paths:

- target/\*.jar

test:

stage: test

script:

- echo "Running tests..."
- mvn test

```
deploy:
  stage: deploy
  script:
    - echo "Deploying application..."
    - scp target/*.jar user@server:/deploy/path
  only:
    - main
```

---

## 🚧 Docker Build & Push to GitLab Container Registry

📌 **File:** .gitlab-ci.yml

```
variables:
  IMAGE_NAME: registry.gitlab.com/your-namespace/your-repo
```

```
stages:
  - build
  - push
```

```
build:
  stage: build
  script:
    - docker build -t $IMAGE_NAME:latest .
  only:
    - main
```

```
push:
  stage: push
  script:
    - echo $CI_REGISTRY_PASSWORD | docker login -u $CI_REGISTRY_USER
    --password-stdin $CI_REGISTRY
    - docker push $IMAGE_NAME:latest
  only:
```

- main

---

## ◆ Kubernetes Deployment

✦ **File:** .gitlab-ci.yml

stages:

- deploy

deploy:

stage: deploy

image: bitnami/kubectl

script:

- kubectl apply -f k8s/deployment.

only:

- main

---

## ◆ Terraform Deployment

✦ **File:** .gitlab-ci.yml

image: hashicorp/terraform:latest

stages:

- terraform

terraform:

stage: terraform

script:

- terraform init

- terraform apply -auto-approve

only:



- main
- 

## ◆ Security Scanning with Trivy

✦ **File:** .gitlab-ci.yml

stages:

- security\_scan

security\_scan:

stage: security\_scan

script:

- docker pull registry.gitlab.com/your-namespace/your-repo:latest
- trivy image registry.gitlab.com/your-namespace/your-repo:latest

only:

- main
- 

## ◆ SonarQube Code Analysis

✦ **File:** .gitlab-ci.yml

image: maven:3.8.7

stages:

- analysis

sonarqube:

stage: analysis

script:

- mvn sonar:sonar -Dsonar.login=\$SONAR\_TOKEN

only:

- main

## ◆ AWS S3 Upload

✈ **File:** .gitlab-ci.yml

stages:

- deploy

deploy\_s3:

stage: deploy

script:

- aws s3 sync . s3://my-bucket-name --delete

only:

- main

environment:

name: production

---

## ◆ Notify on Slack

✈ **File:** .gitlab-ci.yml

notify:

stage: notify

script:

- curl -X POST -H 'Content-type: application/json' --data '{"text":"Deployment completed successfully!"}' \$SLACK\_WEBHOOK\_URL

only:

- main

---

## ◆ Tekton

## ◆ What is Tekton?

Tekton is a **Kubernetes-native CI/CD framework** that allows you to create and run pipelines for **automating builds, testing, security scans, and deployments**. It provides reusable components such as **Tasks, Pipelines, and PipelineRuns**, making it ideal for cloud-native DevOps workflows.

---

## ◆ Installation (On Kubernetes Cluster)

### 1 Install Tekton Pipelines

```
kubectl apply -f  
https://storage.googleapis.com/tekton-releases/pipeline/latest/release.
```

### 2 Verify Installation

```
kubectl get pods -n tekton-pipelines
```

### 3 Install Tekton CLI (tkn)

```
curl -LO https://github.com/tektoncd/cli/releases/latest/download/tkn-linux-amd64  
chmod +x tkn-linux-amd64  
sudo mv tkn-linux-amd64 /usr/local/bin/tkn
```

### 4 Check Tekton CLI Version

```
tkn version
```

---

## ◆ Tekton Basics

- **Tasks:** The smallest execution unit in Tekton.
- **Pipelines:** A sequence of tasks forming a CI/CD process.
- **PipelineRuns:** Executes a pipeline.
- **TaskRuns:** Executes a task.
- **Workspaces:** Used for sharing data between tasks.
- **Resources:** Defines input/output artifacts (e.g., Git repositories, images).

## ◆ Install Tekton on Kubernetes

kubectl apply -f

<https://storage.googleapis.com/tekton-releases/pipeline/latest/release.>

### Verify installation:

kubectl get pods -n tekton-pipelines

---

### Commands:

#### # Install Tekton CLI

kubectl apply -f

<https://storage.googleapis.com/tekton-releases/pipeline/latest/release.yaml>

#### # Check Tekton Installation

tkn version # Show Tekton CLI version

kubectl get pods -n tekton-pipelines # List Tekton pods

kubectl get crds | grep tekton # List Tekton-related CRDs

#### # Tekton Pipeline Commands

tkn pipeline list # List all pipelines

tkn pipeline describe <pipeline-name> # Describe a specific pipeline

tkn pipeline start <pipeline-name> --showlog # Start a pipeline and show logs

tkn pipeline delete <pipeline-name> # Delete a pipeline

#### # Tekton Task Commands

tkn task list # List all tasks

tkn task describe <task-name> # Describe a specific task

tkn task start <task-name> --showlog # Start a task and show logs

tkn task delete <task-name> # Delete a task

### **# Tekton PipelineRun Commands**

```
tkn pipelinerun list # List pipeline runs
tkn pipelinerun describe <pipelinerun-name> # Describe a pipeline run
tkn pipelinerun logs <pipelinerun-name> # Show logs of a pipeline run
tkn pipelinerun delete <pipelinerun-name> # Delete a pipeline run
```

### **# Tekton TaskRun Commands**

```
tkn taskrun list # List task runs
tkn taskrun describe <taskrun-name> # Describe a task run
tkn taskrun logs <taskrun-name> # Show logs of a task run
tkn taskrun delete <taskrun-name> # Delete a task run
```

### **# Tekton Resources Commands**

```
tkn resource list # List all pipeline resources
tkn resource describe <resource-name> # Describe a specific resource
tkn resource delete <resource-name> # Delete a resource
```

### **# Tekton Triggers Commands**

```
tkn triggerbinding list # List trigger bindings
tkn triggertemplate list # List trigger templates
tkn eventlistener list # List event listeners
tkn eventlistener logs <listener-name> # Show logs of an event listener
```

### **# Tekton Debugging & Monitoring**

```
kubectl logs -l app=tekton-pipelines-controller -n tekton-pipelines # View Tekton
controller logs
kubectl get pods -n tekton-pipelines # List running Tekton pods
kubectl describe pod <pod-name> -n tekton-pipelines # Get details of a specific
pod
```

### **# Delete All Tekton Resources**

```
kubectl delete pipelineruns --all -n <namespace>
kubectl delete taskruns --all -n <namespace>
kubectl delete pipelines --all -n <namespace>
kubectl delete tasks --all -n <namespace>
```

## ◆ Basic Tekton Task

✈ **File:** task.

```
apiVersion: tekton.dev/v1beta1
kind: Task
metadata:
  name: echo-task
spec:
  steps:
    - name: echo-message
      image: alpine
      script: |
        #!/bin/sh
        echo "Hello from Tekton Task!"
```

### **Apply:**

kubectl apply -f task.

### **Run the task:**

tkn task start echo-task

---

## ◆ Tekton Pipeline with Tasks

✈ **File:** pipeline.

```
apiVersion: tekton.dev/v1beta1
kind: Pipeline
metadata:
```

```
name: sample-pipeline
spec:
  tasks:
    - name: build-task
      taskRef:
        name: build-task
    - name: deploy-task
      taskRef:
        name: deploy-task
  runAfter:
    - build-task
```

### Apply:

kubectrl apply -f pipeline.

---

### ◆ Tekton PipelineRun

✦ **File:** pipelinerun.

```
apiVersion: tekton.dev/v1beta1
kind: PipelineRun
metadata:
  name: sample-pipelinerun
spec:
  pipelineRef:
    name: sample-pipeline
```

### Run the pipeline:

kubectrl apply -f pipelinerun.

## Check status:

```
tkn pipelinerun describe sample-pipelinerun
```

---

## ◆ Build & Push Docker Image

✦ **File:** task-build-push.

```
apiVersion: tekton.dev/v1beta1
kind: Task
metadata:
  name: build-push-task
spec:
  steps:
    - name: build-and-push
      image: gcr.io/kaniko-project/executor:latest
      script: |
        #!/bin/sh
        /kaniko/executor --context=/workspace/source
        --destination=docker.io/myrepo/myapp:latest
```

---

## ◆ Kubernetes Deployment with Tekton

✦ **File:** task-k8s-deploy.

```
apiVersion: tekton.dev/v1beta1
kind: Task
metadata:
  name: deploy-task
spec:
  steps:
    - name: apply-manifest
```



```
image: bitnami/kubectl
script: |
  #!/bin/sh
  kubectl apply -f k8s/deployment.
```

---

## ◆ Tekton with Terraform

✈ **File:** task-terraform.

```
apiVersion: tekton.dev/v1beta1
kind: Task
metadata:
  name: terraform-task
spec:
  steps:
  - name: terraform-apply
    image: hashicorp/terraform:latest
    script: |
      #!/bin/sh
      terraform init
      terraform apply -auto-approve
```

---

## ◆ Security Scanning with Trivy

✈ **File:** task-trivy.

```
apiVersion: tekton.dev/v1beta1
kind: Task
metadata:
  name: trivy-scan
spec:
  steps:
```

```
- name: run-trivy
  image: aquasec/trivy:latest
  script: |
    #!/bin/sh
    trivy image docker.io/myrepo/myapp:latest
```

---

## ◆ SonarQube Code Analysis

✦ **File:** task-sonarqube.

```
apiVersion: tekton.dev/v1beta1
kind: Task
metadata:
  name: sonarqube-task
spec:
  steps:
    - name: sonar-scan
      image: maven:3.8.7
      script: |
        #!/bin/sh
        mvn sonar:sonar -Dsonar.login=$SONAR_TOKEN
```

---

## ◆ Notify on Slack

✦ **File:** task-slack.

```
apiVersion: tekton.dev/v1beta1
kind: Task
metadata:
  name: slack-notify
spec:
  steps:
```

```
- name: send-slack-message
  image: curlimages/curl:latest
  script: |
    #!/bin/sh
    curl -X POST -H 'Content-type: application/json' --data '{"text":"Deployment
completed successfully!"}' $SLACK_WEBHOOK_URL
```

---

## Circle CI

### Introduction

CircleCI is a cloud-based CI/CD tool that automates software testing and deployment. It provides seamless integration with GitHub, Bitbucket, and other version control systems, enabling automated builds, tests, and deployments.

### Installation

- Sign up at [CircleCI](#)
- Connect your repository (GitHub, Bitbucket)
- Configure the .circleci/config.yml file in your project

### CircleCI Commands (Pipeline Example)

```
circleci checkout # Check out the repository to the current directory
circleci sphere list # List all the available workspaces in your account
circleci config process # Process the CircleCI config file and output the final
configuration
circleci step halt # Halt the current job execution, useful in workflows
circleci job follow <job_id> # Stream the logs of a specific job in real-time
circleci pipeline trigger <pipeline_id> # Trigger a pipeline by its ID
circleci pipeline list # List all the pipelines for your project
circleci project status <project_slug> # View the status of the project
circleci sphere create <sphere_name> # Create a new workspace
circleci sphere remove <sphere_name> # Remove a workspace
```

```
circleci sync # Sync CircleCI configuration for a given project
circleci orb publish <orb_name> <version> <path_to_orb> # Publish a new
version of an orb
```

---

## CircleCI Pipeline Script Example

### Basic CircleCI Pipeline Configuration

```
version: 2.1 # Define the CircleCI version
```

#### # Define jobs

```
jobs:
```

```
  build:
```

```
    docker:
```

```
      - image: circleci/python:3.8 # Use a Python 3.8 Docker image
```

```
    steps:
```

```
      - checkout # Check out the code
```

```
      - run:
```

```
        name: Install dependencies
```

```
        command: pip install -r requirements.txt
```

```
      - run:
```

```
        name: Run tests
```

```
        command: pytest
```

```
  deploy:
```

```
    docker:
```

```
      - image: circleci/python:3.8
```

```
    steps:
```

```
      - checkout
```

```
      - run:
```

```
        name: Deploy application
```

```
        command: ./deploy.sh # Custom deploy script
```

```
# Define workflows (Job execution order)
workflows:
  version: 2
  build_and_deploy:
    jobs:
      - build
      - deploy:
          requires:
            - build # Ensure deployment happens after build succeeds
```

---

## Advanced CircleCI Features

### 1. Running Jobs Based on Branches

```
jobs:
  deploy:
    docker:
      - image: circleci/python:3.8
    steps:
      - checkout
      - run:
          name: Deploy to Production
          command: ./deploy_production.sh
workflows:
  version: 2
  deploy_to_production:
    jobs:
      - deploy:
          filters:
            branches:
              only: main # Deploy only on the 'main' branch
```

## 2. Caching Dependencies to Speed Up Builds

```
jobs:
  build:
    docker:
      - image: circleci/python:3.8
    steps:
      - checkout
      - restore_cache:
          keys:
            - v1-dependencies-{{ checksum "requirements.txt" }}
      - run:
          name: Install dependencies
          command: pip install -r requirements.txt
      - save_cache:
          paths:
            - ~/.cache/pip # Save pip cache
          key: v1-dependencies-{{ checksum "requirements.txt" }}
```

## 3. Using Environment Variables for Sensitive Data

```
jobs:
  deploy:
    docker:
      - image: circleci/python:3.8
    steps:
      - checkout
      - run:
          name: Deploy using environment variables
          command: ./deploy.sh
```

environment:

API\_KEY: \$API\_KEY # Use stored API keys

#### 4. Running Jobs Conditionally Based on File Changes

jobs:

deploy:

docker:

- image: circleci/python:3.8

steps:

- checkout

- run:

name: Deploy Application

command: ./deploy.sh

filters:

branches:

only: main

requires:

- build

when:

changes:

- Dockerfile # Only run deploy if the Dockerfile changes

#### 5. Running Tests in Parallel

jobs:

test:

docker:

- image: circleci/python:3.8

parallelism: 4 # Run 4 test jobs in parallel

steps:

- checkout
- run:
  - name: Run tests
  - command: pytest

## 6. Using Multiple Docker Containers

jobs:

build:

docker:

- image: circleci/python:3.8
- image: circleci/postgres:13 # Additional container for PostgreSQL

environment:

POSTGRES\_USER: circleci

steps:

- checkout
- run:
  - name: Install dependencies
  - command: pip install -r requirements.txt
- run:
  - name: Run database migrations
  - command: python manage.py migrate
- run:
  - name: Run tests
  - command: pytest

## 7. Running Jobs Manually (Manual Approvals)

jobs:

manual\_deploy:

docker:

- image: circleci/python:3.8



```
steps:
  - checkout
  - run:
    name: Deploy to Production
    command: ./deploy.sh
when: manual # Only run when triggered manually
```

## 8. Sending Notifications on Job Failure

```
workflows:
  version: 2
  notify_on_failure:
    jobs:
      - build
    notification:
      email:
        - user@example.com # Send email notifications on failures
```

## 9. Running Multiple Jobs in Parallel

```
workflows:
  version: 2
  build_and_deploy:
    jobs:
      - build
      - deploy:
          requires:
            - build # Deploy after build completes
          filters:
            branches:
              only: main
```

---

**ArgoCD** (GitOps)

## Introduction

Argo CD is a declarative, GitOps continuous delivery tool for Kubernetes. It enables the deployment of applications from Git repositories to Kubernetes clusters, ensuring that the live state of the cluster matches the desired state defined in Git.

---

## Installation

### 1. Install Argo CD CLI

#### macOS:

```
brew install argocd
```

#### Linux:

```
curl -sSL -o /usr/local/bin/argocd
```

```
https://github.com/argoproj/argo-cd/releases/download/v2.5.4/argocd-linux-amd64
```

```
chmod +x /usr/local/bin/argocd
```

## Install Argo CD on Kubernetes

```
kubectl create namespace argocd
```

```
kubectl apply -n argocd -f
```

```
https://raw.githubusercontent.com/argoproj/argo-cd/stable/manifests/install.
```

---

## Accessing the Argo CD UI

### Access the Argo CD API Server (Local Port Forwarding)

```
kubectl port-forward svc/argocd-server -n argocd 8080:443
```

### 1. Login to the Argo CD UI

**Initial Password** (default is admin and the password is the name of the pod running Argo CD):

```
kubectrl get pods -n argocd
```

```
kubectrl logs <argocd-server-pod-name> -n argocd | grep "admin"
```

---

## Argo CD Commands

### Login to Argo CD via CLI

```
argocd login <ARGOCD_SERVER> --username admin --password <password>
```

### View the current applications

```
argocd app list
```

#### 1. Sync an Application

- Syncs the application with the desired state from the Git repository.

```
argocd app sync <app-name>
```

### Get Application Status

```
argocd app get <app-name>
```

#### 2. Create an Application

- Creates an app in Argo CD by specifying the Git repository, target namespace, and project.

```
argocd app create <app-name> \  
  --repo <git-repository-url> \  
  --path <path-to-k8s-manifests> \  
  --dest-server https://kubernetes.default.svc \  
  --dest-namespace <namespace>
```

## Delete an Application

```
argocd app delete <app-name>
```

### 3. Refresh Application

- Refreshes the application state from the Git repository.

```
argocd app refresh <app-name>
```

---

## Application Resources and Syncing

### Sync Status Check

```
argocd app sync <app-name> --prune
```

#### 1. Compare with Live

- Compare the live state of an application with the Git repository.

```
argocd app diff <app-name>
```

#### 2. Manual Sync

- Manually sync the application state.

```
argocd app sync <app-name> --force
```

---

## Managing Projects

### Create a Project

```
argocd proj create <project-name> \  
--description "<description>" \  
--dest-namespace <namespace> \  
--dest-server <server-url>
```

## List Projects

```
argocd proj list
```

## Add a Git Repo to a Project

```
argocd proj add-repo <project-name> --repo <git-repository-url>
```

---

## GitOps and Source Repositories

### Add a Git Repository

```
argocd repo add <git-repo-url> --username <username> --password <password>  
--type git
```

### List Repositories

```
argocd repo list
```

### Remove a Git Repository

```
argocd repo rm <git-repo-url>
```

---

## Notifications and Alerts

### 1. Enable Notifications

- Install Argo CD Notifications to integrate with Slack, email, etc.

```
kubectl apply -k github.com/argoproj-labs/argocd-notifications/manifests/install
```

### 2. Set Up Notification Settings

- Configure notification settings in the Argo CD UI.
- 

## Application Health and Troubleshooting

## Check Application Health

`argocd app health <app-name>`

### 1. Check Logs

- View logs for troubleshooting.

`kubectl logs <pod-name> -n argocd`

### 2. App Rollback

- Rollback to a previous revision of an application.

`argocd app rollback <app-name> <revision>`

---

## Argo CD in CI/CD Pipelines

- **Integrate with CI/CD**

- Add Argo CD commands in Jenkins, GitLab CI, or GitHub Actions pipelines to automatically deploy updates to Kubernetes based on changes in Git repositories.
- 

## Best Practices

- **Declarative GitOps:** Keep all manifests in Git, and let Argo CD automatically synchronize and deploy them.
  - **Namespaces and Projects:** Use projects to group applications and limit resource access across environments.
  - **RBAC:** Use Role-Based Access Control (RBAC) to secure Argo CD's access and resource usage.
-

## Flux CD

### Introduction

Flux CD is a GitOps tool for Kubernetes that automates deployment, updates, and rollback of applications using Git as the source of truth.

### Installation

#### Install Flux CLI

```
curl -s https://fluxcd.io/install.sh | sudo
```

#### Verify Installation

```
flux --version
```

#### Bootstrap Flux in a Cluster

```
flux bootstrap github \  
  --owner=<GITHUB_USER_OR_ORG> \  
  --repository=<REPO_NAME> \  
  --branch=main \  
  --path=clusters/my-cluster \  
  --personal
```

---

### Key Flux CD Commands

#### General Commands

flux check	# Check Flux installation
flux install	# Install Flux components in a cluster
flux bootstrap github ...	# Set up Flux in GitHub repository
flux version	# Show Flux CLI version

#### Managing Deployments

flux get sources git	# List Git sources
flux get kustomizations	# List kustomizations

```
flux reconcile kustomization <name> # Force sync a kustomization
flux suspend kustomization <name>  # Pause updates for a kustomization
flux resume kustomization <name>   # Resume updates for a kustomization
```

## Git Repository Management

```
flux create source git my-app \
  --url=https://github.com/my-org/my-app \
  --branch=main \
  --interval=1m
```

```
flux create kustomization my-app \
  --source=my-app \
  --path="./deploy" \
  --prune=true \
  --interval=5m
```

## Helm Chart Management

```
flux create source helm my-chart \
  --url=https://charts.bitnami.com/bitnami \
  --interval=1h
```

```
flux create helmrelease my-app \
  --source=my-chart \
  --chart=nginx \
  --values=./values. \
  --interval=5m
```

## Monitoring and Debugging

```
flux logs                # View Flux logs
flux get sources helm     # List Helm sources
flux get helmreleases     # List deployed Helm releases
flux trace kustomization <name> # Trace errors in a kustomization
```



```
flux suspend source git <name>    # Suspend Git syncing  
flux resume source git <name>    # Resume Git syncing
```

## Uninstall Flux

```
flux uninstall --silent
```

---

## 3. Infrastructure as Code (IaC)

- Terraform

### Terraform Installation on Ubuntu/Debian:

1. Terraform Installation:

- Official Link: [Terraform Installation](#)

#### Commands:

```
wget -O - https://apt.releases.hashicorp.com/gpg | sudo gpg --dearmor -o  
/usr/share/keyrings/hashicorp-archive-keyring.gpg
```

```
echo "deb [signed-by=/usr/share/keyrings/hashicorp-archive-keyring.gpg]  
https://apt.releases.hashicorp.com $(lsb_release -cs) main" | sudo tee  
/etc/apt/sources.list.d/hashicorp.list
```

```
sudo apt update && sudo apt install terraform
```

2. AWS CLI Installation on Ubuntu:

- Official Link: [AWS CLI Installation](#)

#### Commands:

```
curl "https://awscli.amazonaws.com/awscli-exe-linux-x86_64.zip" -o  
"awscliv2.zip"
```

```
unzip awscliv2.zip
```

```
sudo ./aws/install
```

### 3. Kubectl Installation on Ubuntu:

#### Commands:

```
curl -LO "https://dl.k8s.io/release/$(curl -L -s  
https://dl.k8s.io/release/stable.txt)/bin/linux/amd64/kubectl"
```

---

## Step-by-Step Configuration Guide with AWS EC2 Instance

### 1. Main Terraform Configuration: main.tf:

#### Terraform Configuration Example:

```
terraform {  
  required_providers {  
    aws = {  
      source = "hashicorp/aws"  
      version = "~> 4.16"  
    }  
  }  
  required_version = ">= 1.2.0"  
}
```

  

```
provider "aws" {  
  region = "us-west-2"  
}
```

```
resource "aws_instance" "app_server" {  
    ami      = "ami-08d70e59c07c61a3a"  
    instance_type = "t2.micro"  
  
    tags = {  
        Name = var.instance_name  
    }  
}
```

## 2. Input Variables: variables.tf:

Example:  
hcl

```
variable "instance_name" {  
    description = "Value of the Name tag for the EC2 instance"  
    type        = string  
    default     = "ExampleAppServerInstance"  
}
```

## 3. Output Values: outputs.tf:

Example:  
hcl

```
output "instance_id" {  
    description = "ID of the EC2 instance"  
    value       = aws_instance.app_server.id  
}
```

```
}

output "instance_public_ip" {
  description = "Public IP address of the EC2 instance"
  value      = aws_instance.app_server.public_ip
}
```

#### **4. Running the Configuration:**

##### **Initialize Terraform:**

terraform init

##### **Apply the Configuration:**

terraform apply

- Confirm by typing yes when prompted.

##### **Inspect Output Values:**

terraform output

##### **Destroy the Infrastructure:**

terraform destroy

---

### **Terraform Advanced Configuration Use Cases**

#### **1. Provider Configuration:**

```
provider "aws" {
  region = "us-west-2"
}
```

#### **2. Resource Creation:**

```
resource "aws_instance" "example" {  
    ami          = "ami-0c55b159cbfafa1f0"  
    instance_type = "t2.micro"  
    tags = {  
        Name = "ExampleInstance"  
    }  
}
```

### **3. Variable Management:**

```
variable "region" {  
    default = "us-west-2"  
}
```

```
provider "aws" {  
    region = var.region  
}
```

### **4. State Management:**

#### **Example for using remote state in S3:**

hcl

```
terraform {  
    backend "s3" {  
        bucket = "my-tfstate-bucket"
```

```
key      = "terraform/state"
region   = "us-west-2"
encrypt  = true
dynamodb_table = "terraform-locks"
}
}
```

## 5. Modules:

```
module "vpc" {
  source = "terraform-aws-modules/vpc/aws"
  name   = "my-vpc"
  cidr   = "10.0.0.0/16"

  azs          = ["us-west-2a", "us-west-2b"]
  public_subnets = ["10.0.1.0/24", "10.0.2.0/24"]
  private_subnets = ["10.0.3.0/24", "10.0.4.0/24"]
}
```

---

## Terraform Commands Cheat Sheet

- **terraform init:** Initializes the Terraform configuration.
- **terraform fmt:** Formats configuration files.
- **terraform validate:** Validates the configuration files.
- **terraform plan:** Previews changes to be applied.
- **terraform apply:** Applies the changes to reach the desired state.

- **terraform destroy**: Destroys the infrastructure and removes it from the state.
  - **terraform show**: Displays the current state of resources.
  - **terraform state list**: Lists resources in the current state.
  - **terraform taint <resource>**: Marks a resource for recreation.
  - **terraform import <resource> <resource\_id>**: Imports existing resources into Terraform.
  - **terraform providers**: Lists the providers used in the configuration.
- 

## Terraform Best Practices

- Use **Version Control** to manage your Terraform code.
  - Break your code into **Modules** for reusability.
  - Use **Remote State** (e.g., AWS S3, Terraform Cloud) to store state files.
  - Always run **terraform plan** before **terraform apply**.
  - Use **terraform fmt** & **terraform validate** to ensure code correctness.
  - Avoid **hardcoding secrets**; use environment variables or secret management tools.
  - Keep configurations **modular** and **well-documented**.
- 

- **CloudFormation** (stacks, templates)

### 1. CloudFormation Concepts

- **Stack** → A group of AWS resources defined in a template.
  - **Template** → /JSON file defining resources and configurations.
  - **StackSet** → Deploys stacks across multiple accounts and regions.
  - **Change Set** → Previews updates before applying changes.
  - **Rollback** → Automatic stack rollback if an error occurs.
  - **Drift Detection** → Identifies manual changes made outside CloudFormation.
- 

### 2. CloudFormation Template Example

AWSTemplateFormatVersion: "2010-09-09"

Description: "Basic AWS CloudFormation Example"

Resources:

MyBucket:

Type: "AWS::S3::Bucket"

MyEC2Instance:

Type: "AWS::EC2::Instance"

Properties:

InstanceType: "t2.micro"

ImageId: "ami-0abcdef1234567890"

Outputs:

InstanceID:

Description: "The Instance ID"

Value: !Ref MyEC2Instance

---

### 3. CloudFormation CLI Commands

#### Stack Operations

```
aws cloudformation create-stack --stack-name my-stack --template-body  
file://template.
```

```
aws cloudformation update-stack --stack-name my-stack --template-body  
file://template.
```



```
aws cloudformation delete-stack --stack-name my-stack
```

---

### **Viewing Stack Details**

```
aws cloudformation describe-stacks --stack-name my-stack
```

```
aws cloudformation list-stack-resources --stack-name my-stack
```

```
aws cloudformation describe-stack-events --stack-name my-stack
```

---

### **Change Set (Preview Changes)**

```
aws cloudformation create-change-set --stack-name my-stack --template-body  
file://template. --change-set-name my-change-set
```

```
aws cloudformation describe-change-set --stack-name my-stack --change-set-name  
my-change-set
```

```
aws cloudformation execute-change-set --stack-name my-stack --change-set-name  
my-change-set
```

### **Drift Detection**

```
aws cloudformation detect-stack-drift --stack-name my-stack
```

```
aws cloudformation describe-stack-drift-detection-status --stack-name my-stack
```

---

## **4. CloudFormation Best Practices**

### ✓ Use Parameters for Flexibility

**Define parameters to make templates reusable:**

Parameters:

InstanceType:

Type: String

Default: "t2.micro"

AllowedValues: ["t2.micro", "t2.small", "t2.medium"]

### ✓ Use Mappings for Region-Specific Configurations

Mappings:

RegionMap:

us-east-1:

AMI: "ami-12345678"

us-west-1:

AMI: "ami-87654321"

### ✓ Use Conditions for Conditional Resource Creation

Conditions:

IsProd: !Equals [!Ref "Environment", "prod"]

Resources:

MyDatabase:

Type: "AWS::RDS::DBInstance"

Condition: IsProd

### ✓ Use Outputs to Export Values

Outputs:

S3BucketName:

Description: "Name of the created S3 bucket"

Value: !Ref MyBucket

Export:

Name: MyBucketExport

### ✓ Use Nested Stacks for Large Templates

Break large stacks into smaller, reusable nested stacks.

---

## 5. CloudFormation Troubleshooting

- **Stack creation fails:** Check describe-stack-events for error details.
- **Parameter validation error:** Ensure correct parameter types and values.
- **Rollback triggered:** Check logs and describe-stack-events to debug.
- **Resources stuck in DELETE\_FAILED:** Manually delete dependencies before retrying.
- **Template validation error:** Use aws cloudformation validate-template --template-body file://template to validate the template.

## 4. Containerization & Orchestration

- **Docker** (build, run, volumes, networks, compose)

### Basic Commands

- `docker ps` – List running containers
- `docker ps -a` – List all containers
- `docker info` – Get Docker configuration
- `docker version` – Get Docker version

### Image Commands

- `docker build -t <image>:<tag> .` – Build an image from a Dockerfile
- `docker login <repository>` – Authenticate with a remote repository
- `docker push <image>:<tag>` – Push an image to a repository
- `docker pull <image>:<tag>` – Pull an image from a repository
- `docker images` – List locally available images
- `docker create <image>:<tag>` – Create a container from an image
- `docker rmi <image>` – Delete an image
- `docker save <image>` – Save an image as a tarball
- `docker search <image>` – Search for an image in a repository

### Container Commands

- `docker inspect <container>` – View container details
- `docker stats <container>` – Display live resource usage
- `docker logs <container>` – View container logs
- `docker run <container>` – Run a container
- `docker kill <container>` – Force stop a running container
- `docker start <container>` – Start a stopped container
- `docker stop <container>` – Gracefully stop a running container
- `docker restart <container>` – Restart a container
- `docker rm <container>` – Remove a container
- `docker port <container>` – Show port mappings
- `docker pause <container>` – Suspend container processes
- `docker unpause <container>` – Resume container processes

## Network Commands

- `docker network ls` – List networks
- `docker network inspect <network>` – View network details
- `docker network create <network>` – Create a network
- `docker network rm <network>` – Delete a network
- `docker network connect <network> <container>` – Connect a container to a network
- `docker network disconnect <network> <container>` – Disconnect a container from a network

## Volume Commands

- `docker volume ls` – List volumes
- `docker volume inspect <volume>` – View volume details
- `docker volume create <volume>` – Create a volume
- `docker volume rm <volume>` – Delete a volume

## Copy & Execution Commands

- `docker cp <container>:<source_path> <dest_path>` – Copy from container to host
- `docker cp <source_path> <container>:<dest_path>` – Copy from host to container
- `docker exec -ti <container> <command>` – Run a command inside a running container

## Dockerfile Commands

- `FROM <image>:<tag>` – Base image for the container
- `COPY <source> <destination>` – Copy files/directories
- `ADD <source> <destination>` – Copy files & extract archives
- `CMD ["command", "arg1"]` – Default command executed in container
- `ENTRYPOINT ["command", "arg1"]` – Container's main command
- `LABEL key=value` – Add metadata
- `ENV key=value` – Set environment variables
- `EXPOSE <port>` – Declare exposed ports
- `RUN <command>` – Run command during image build
- `WORKDIR <path>` – Set working directory

## System & Diagnostics

- docker system df – Show Docker disk usage
  - docker system info – Display system details
  - docker diff <container> – Show modified files in a container
  - docker top <container> – Show running processes inside a container
- 

### General Best Practices for Dockerfiles:

1. **Minimize Layers:** Combine RUN, COPY, and ADD commands to reduce layers and image size.
  2. **Use Specific Versions:** Always specify versions for base images (e.g., FROM python:3.9-slim).
  3. **.dockerignore:** Use .dockerignore to exclude unnecessary files (e.g., .git, node\_modules).
  4. **Multi-Stage Builds:** Separate the build process and runtime environment to optimize image size.
  5. **Non-root User:** Always create and use a non-root user for security.
  6. **Leverage Docker Cache:** Copy dependencies first, so Docker can cache them for faster builds.
- 

### Dockerfile Examples with different Programming language

#### 1. Python (Flask/Django)

##### **dockerfile**

FROM python:3.9-slim AS base

WORKDIR /app

##### **# Install dependencies**

COPY requirements.txt .

RUN pip install --no-cache-dir -r requirements.txt

##### **# Copy the app files**

COPY . .

EXPOSE 5000

**# Run as a non-root user**

RUN useradd -m appuser

USER appuser

CMD ["python", "app.py"]

### **Best Practices:**

- --no-cache-dir to prevent caching Python packages.
  - Copy requirements.txt first to leverage Docker cache.
  - Use a non-root user (appuser).
- 

## **2. Node.js**

### **dockerfile**

FROM node:16-alpine AS build

WORKDIR /app

**# Install dependencies**

COPY package.json package-lock.json ./

RUN npm install --production

**# Copy the app code**

COPY . .

EXPOSE 3000

**# Run as a non-root user**

RUN addgroup --system app && adduser --system --ingroup app app

USER app

CMD ["node", "app.js"]

### **Best Practices:**

- Use --production to avoid installing devDependencies.
  - Multi-stage builds for optimized images.
  - Use a non-root user (app).
- 

## **3. Java (Spring Boot)**

### **dockerfile**

FROM openjdk:17-jdk-slim AS build

WORKDIR /app

### **# Copy the jar file**

COPY target/myapp.jar myapp.jar

EXPOSE 8080

### **# Run as a non-root user**

RUN addgroup --system app && adduser --system --ingroup app app

USER app

CMD ["java", "-jar", "myapp.jar"]

### **Best Practices:**

- Multi-stage builds for separating build and runtime.
  - Use -jdk-slim for smaller images.
  - Non-root user (app).
- 

## **4. Ruby on Rails**



## **dockerfile**

FROM ruby:3.0-alpine

### **# Install dependencies**

RUN apk add --no-cache build-base

WORKDIR /app

### **# Install Ruby gems**

COPY Gemfile Gemfile.lock ./

RUN bundle install --without development test

### **# Copy the app code**

COPY . .

EXPOSE 3000

### **# Run as a non-root user**

RUN addgroup --system app && adduser --system --ingroup app app

USER app

CMD ["rails", "server", "-b", "0.0.0.0"]

## **Best Practices:**

- Install dependencies in one RUN statement.
  - Avoid devDependencies in production.
  - Use non-root user (app).
- 

## **5. Go**

### **dockerfile**

FROM golang:1.16-alpine AS build

WORKDIR /app

**# Copy and install dependencies**

COPY go.mod go.sum ./

RUN go mod tidy

**# Copy the app code and build**

COPY . .

RUN go build -o myapp .

**# Use a minimal base image for running**

FROM alpine:latest

WORKDIR /app

**# Copy the binary**

COPY --from=build /app/myapp .

EXPOSE 8080

**# Run as a non-root user**

RUN addgroup --system app && adduser --system --ingroup app app

USER app

CMD ["/myapp"]

### **Best Practices:**

- Multi-stage build to separate build and runtime.
- alpine for smaller runtime images.
- Non-root user (app).

---

## **6. Angular (Frontend)**

## **dockerfile**

### **# Build stage**

FROM node:16 AS build

WORKDIR /app

COPY . .

RUN npm install

RUN npm run build --prod

### **# Production stage using nginx**

FROM nginx:alpine

### **# Copy build artifacts from the build stage**

COPY --from=build /app/dist/ /usr/share/nginx/html

EXPOSE 80

CMD ["nginx", "-g", "daemon off;"]

## **Best Practices:**

- Multi-stage build: separate build and serving phases.
- Use nginx:alpine for a minimal serving environment.
- Copy only production build files.

---

## **7. PHP (Laravel)**

## **dockerfile**

FROM php:8.0-fpm

### **# Install dependencies**

RUN apt-get update && apt-get install -y libzip-dev && docker-php-ext-install zip

WORKDIR /var/www/html

### # Install Composer

COPY --from=composer:latest /usr/bin/composer /usr/bin/composer

### # Install PHP dependencies

COPY composer.json composer.lock ./

RUN composer install --no-dev --no-scripts

### # Copy application files

COPY . .

EXPOSE 9000

### # Run as a non-root user

RUN useradd -ms /bin/ appuser

USER appuser

CMD ["php-fpm"]

### Best Practices:

- Use Composer for PHP dependency management.
- Avoid dev dependencies in production (--no-dev).
- Run PHP-FPM as a non-root user.

---

## 8. Best Practices for Security and Optimization:

- **Minimize Image Size:** Use smaller base images like alpine or slim, and multi-stage builds to reduce the final image size.
- **Use a Non-root User:** Always run applications as a non-root user to enhance security.

- **Pin Versions:** Avoid using the latest tag for images. Use specific versions to ensure predictable builds.
  - **Leverage Caching:** Place frequently changing files (e.g., source code) after dependencies to take advantage of Docker's build cache.
  - **Avoid ADD Unless Necessary:** Use COPY instead of ADD unless you need to fetch files from a URL or extract archives.
- 

## Docker Compose Commands

- **docker-compose up:** Start all services in the background
  - **docker-compose up -d:** Start services in detached mode
  - **docker-compose up --build:** Rebuild images before starting services
  - **docker-compose down:** Stop and remove containers, networks, volumes
  - **docker-compose down -v:** Remove volumes along with containers
  - **docker-compose stop:** Stop running containers without removing them
  - **docker-compose start:** Restart stopped containers
  - **docker-compose restart:** Restart all containers
  - **docker-compose ps:** List running containers
  - **docker-compose logs:** Show logs from containers
  - **docker-compose logs -f:** Follow container logs
  - **docker-compose exec <service> <cmd>:** Execute a command inside a running container
  - **docker-compose run <service> <cmd>:** Run a one-time command inside a service
  - **docker-compose config:** Validate and view merged configuration
  - **docker-compose version:** Show Docker Compose version
- 

## Docker Compose (docker-compose.yml) Example

version: '3.8'

services:

app:

image: my-app:latest

container\_name: my\_app

ports:

- "8080:80"

environment:

- NODE\_ENV=production

volumes:

- ./app:/usr/src/app

depends\_on:

- db

db:

image: postgres:latest

container\_name: my\_db

restart: always

environment:

POSTGRES\_USER: user

POSTGRES\_PASSWORD: password

POSTGRES\_DB: mydatabase

ports:

- "5432:5432"

volumes:

- pgdata:/var/lib/postgresql/data

volumes:

pgdata:

---

## Key Directives

- **version:** Defines the Compose file format version
  - **services:** Defines all application services
  - **image:** Specifies the container image
  - **container\_name:** Names the container explicitly
  - **build:** Specifies build context for Dockerfile
  - **ports:** Maps container ports to host
  - **volumes:** Mounts persistent storage
  - **environment:** Passes environment variables
  - **depends\_on:** Specifies dependencies between services
  - **restart:** Defines restart policy (always, unless-stopped, on-failure)
- 

## General Docker Compose Structure

version: '3'

services:

service\_name:

image: <image-name>      # The image to use

build: .                      # Path to the Dockerfile if you need to build the image

container\_name: <name>    # Container name (optional)

ports:

- "<host-port>:<container-port>" # Exposing ports

environment:

- VAR\_NAME=value          # Set environment variables

volumes:

- <host-path>:<container-path> # Mount volumes for persistent data

depends\_on:

- other\_service # Define service dependencies

networks:

- <network-name> # Assign the service to a network

---

## Docker Compose Example Configurations

### 1. Python (Flask) + Redis Example:

version: '3'

services:

web:

build: ./app

ports:

- "5000:5000"

environment:

- FLASK\_APP=app.py

- FLASK\_ENV=development

volumes:

- ./app:/app

networks:

- app\_network

redis:



image: "redis:alpine"

networks:

- app\_network

networks:

app\_network:

driver: bridge

## 2. Node.js (Express) + MongoDB Example:

version: '3'

services:

app:

build: ./node-app

ports:

- "3000:3000"

environment:

- MONGO\_URI=mongodb://mongo:27017/mydb

depends\_on:

- mongo

networks:

- backend

mongo:

image: mongo:latest

volumes:

- mongo\_data:/data/db

networks:

- backend

networks:

backend:

driver: bridge

volumes:

mongo\_data:

### 3. Nginx + PHP (Laravel) Example:

version: '3'

services:

nginx:

image: nginx:alpine

volumes:

- ./nginx.conf:/etc/nginx/nginx.conf
- ./html:/usr/share/nginx/html

ports:

- "8080:80"

depends\_on:

- php

networks:

- frontend

php:

image: php:8.0-fpm

volumes:

- ./html:/var/www/html

networks:

- frontend

networks:

frontend:

driver: bridge

---

## Best Practices

- **Use Versioning:** Always specify a version for Docker Compose files (e.g., version: '3')
- **Define Volumes:** Use named volumes for persistent data (e.g., database storage)
- **Environment Variables:** Use environment variables for configuration (e.g., database connection strings)
- **Use depends\_on:** Ensure proper start order for dependent services
- **Custom Networks:** Use custom networks for better service communication management
- **Avoid latest Tag:** Always use specific version tags for predictable builds

## Advanced Options

- **Build Arguments:** Pass information during the image build process

build:

context: .

args:

NODE\_ENV: production

- **Health Checks:** Add health checks to monitor service status

services:

web:

image: my-web-app

healthcheck:

test: ["CMD", "curl", "-f", "http://localhost/health"]

interval: 30s

retries: 3

- **Scaling Services:** Scale services using the command

docker-compose up --scale web=3

- 
- **Kubernetes (K8s)**

### 1. Kubernetes Basics

kubectl cluster-info – Display cluster information  
kubectl get nodes – List all nodes in the cluster  
kubectl get pods – List all pods in the current namespace  
kubectl get services – List all services  
kubectl get deployments – List all deployments

## **2. Managing Pods**

kubectl run my-pod --image=nginx – Create a pod with Nginx  
kubectl delete pod my-pod – Delete a pod  
kubectl logs my-pod – View pod logs  
kubectl exec -it my-pod -- /bin/sh – Access a pod's shell

## **3. Managing Deployments**

kubectl create deployment my-deploy --image=nginx – Create a deployment  
kubectl scale deployment my-deploy --replicas=3 – Scale deployment to 3 replicas  
kubectl rollout status deployment my-deploy – Check rollout status  
kubectl rollout undo deployment my-deploy – Rollback to the previous version

## **4. Managing Services**

kubectl expose deployment my-deploy --type=NodePort --port=80 – Expose deployment as a service  
kubectl get svc – List services  
kubectl describe svc my-service – Get service details

## **5. Namespaces**

kubectl get ns – List all namespaces

kubectl create namespace dev – Create a new namespace

kubectl delete namespace dev – Delete a namespace

## **6. ConfigMaps & Secrets**

kubectl create configmap my-config --from-literal=key=value – Create a ConfigMap

kubectl get configmap – List ConfigMaps

kubectl create secret generic my-secret --from-literal=password=12345 – Create a secret

kubectl get secrets – List secrets

## **7. Troubleshooting**

kubectl get events – View cluster events

kubectl describe pod my-pod – Get detailed pod information

kubectl logs my-pod – View logs of a specific pod

kubectl top pod – Show resource usage of pods

## **8. Helm (Package Manager for Kubernetes)**

helm repo add stable https://charts.helm.sh/stable – Add a Helm repo

helm install my-release stable/nginx – Install a Helm chart

helm list – List installed releases

helm delete my-release – Uninstall a release

## **Persistent Volumes & Storage**

kubectl get pvc – List persistent volume claims

kubectl get pv – List persistent volumes

kubectl describe pvc <pvc> – Describe a persistent volume claim

kubectl delete pvc <pvc> – Delete a persistent volume claim

## **Autoscaling**

kubectl autoscale deployment <deployment> --cpu-percent=50 --min=1 --max=10

– Enable autoscaling

kubectl get hpa – View horizontal pod autoscaler

## **Kubernetes Debugging**

kubectl get events --sort-by=.metadata.creationTimestamp – Show events

kubectl describe pod <pod> – Show pod details

kubectl logs <pod> – Check logs

kubectl exec -it <pod> -- /bin/sh – Access pod shell

---

## **Kubernetes YAML Configurations**

### **1. Pod**

yaml

apiVersion: v1

kind: Pod

metadata:

name: my-pod

spec:

containers:

- name: nginx

image: nginx:latest

ports:

- containerPort: 80

## 2. Deployment

yaml

apiVersion: apps/v1

kind: Deployment

metadata:

name: my-deployment

spec:

replicas: 3

selector:

matchLabels:

app: my-app

template:

metadata:

labels:

app: my-app



spec:

containers:

- name: nginx

- image: nginx:latest

- ports:

- containerPort: 80

### 3. ReplicaSet

yaml

apiVersion: apps/v1

kind: ReplicaSet

metadata:

- name: my-replicaset

spec:

- replicas: 3

- selector:

- matchLabels:

- app: my-app

- template:

- metadata:

- labels:

```
  app: my-app

spec:

  containers:

    - name: nginx

      image: nginx:latest
```

#### **4. Service (ClusterIP, NodePort, LoadBalancer)**

##### **ClusterIP (default)**

```
yaml

apiVersion: v1

kind: Service

metadata:

  name: my-service

spec:

  selector:

    app: my-app

  ports:

    - protocol: TCP

      port: 80

      targetPort: 80
```

## **NodePort**

yaml

apiVersion: v1

kind: Service

metadata:

name: my-service

spec:

selector:

app: my-app

type: NodePort

ports:

- protocol: TCP

port: 80

targetPort: 80

nodePort: 30080

## **LoadBalancer**

yaml

apiVersion: v1

kind: Service

metadata:

name: my-service

spec:

selector:

app: my-app

type: LoadBalancer

ports:

- protocol: TCP

port: 80

targetPort: 80

## 5. ConfigMap

yaml

apiVersion: v1

kind: ConfigMap

metadata:

name: my-config

data:

key1: value1

key2: value2

## 6. Secret

yaml

apiVersion: v1

kind: Secret

metadata:

name: my-secret

type: Opaque

data:

password: cGFzc3dvcmQ= # Base64 encoded value

## 7. Persistent Volume (PV)

yaml

apiVersion: v1

kind: PersistentVolume

metadata:

name: my-pv

spec:

capacity:

storage: 1Gi

accessModes:

- ReadWriteOnce

hostPath:

path: /mnt/data

## 8. Persistent Volume Claim (PVC)

yaml

apiVersion: v1

kind: PersistentVolumeClaim

metadata:

name: my-pvc

spec:

accessModes:

- ReadWriteOnce

resources:

requests:

storage: 500Mi

## 9. Ingress

yaml

apiVersion: networking.k8s.io/v1

kind: Ingress

metadata:

name: my-ingress

spec:

rules:

- host: example.com

http:

paths:

- path: /

pathType: Prefix

backend:

service:

name: my-service

port:

number: 80

## 10. Horizontal Pod Autoscaler (HPA)

yaml

apiVersion: autoscaling/v2

kind: HorizontalPodAutoscaler

metadata:

name: my-hpa

spec:

scaleTargetRef:

```
  apiVersion: apps/v1
  kind: Deployment
  name: my-deployment
  minReplicas: 2
  maxReplicas: 5
  metrics:
  - type: Resource
    resource:
      name: cpu
      target:
        type: Utilization
        averageUtilization: 50
```

## 11. CronJob

```
yaml
apiVersion: batch/v1
kind: CronJob
metadata:
  name: my-cronjob
spec:
  schedule: "*/5 * * * *"
```



jobTemplate:

spec:

template:

spec:

containers:

- name: my-cron

image: busybox

command: ["echo", "Hello from CronJob"]

restartPolicy: OnFailure

---

## 5. Cloud Services

- **AWS**

### **EC2 (Elastic Compute Cloud)**

- `aws ec2 describe-instances` – List all instances
- `aws ec2 start-instances --instance-ids <id>` – Start an instance
- `aws ec2 stop-instances --instance-ids <id>` – Stop an instance
- `aws ec2 terminate-instances --instance-ids <id>` – Terminate an instance
- `aws ec2 create-key-pair --key-name <name>` – Create a key pair
- `aws ec2 describe-security-groups` – List security groups

---

### **S3 (Simple Storage Service)**

- `aws s3 ls` – List buckets

- `aws s3 mb s3://<bucket>` – Create a bucket
  - `aws s3 cp <file> s3://<bucket>/` – Upload a file
  - `aws s3 rm s3://<bucket>/<file>` – Delete a file
  - `aws s3 rb s3://<bucket> --force` – Delete a bucket
  - `aws s3 sync <local-dir> s3://<bucket>/` – Sync local and S3
- 

## **IAM (Identity and Access Management)**

- `aws iam list-users` – List IAM users
  - `aws iam create-user --user-name <name>` – Create a user
  - `aws iam attach-user-policy --user-name <name> --policy-arn <policy>` – Attach a policy
  - `aws iam list-roles` – List IAM roles
  - `aws iam create-role --role-name <name> --assume-role-policy-document file://policy.json` – Create a role
  - `aws iam list-policies` – List policies
- 

## **VPC (Virtual Private Cloud)**

- `aws ec2 describe-vpcs` – List VPCs
  - `aws ec2 create-vpc --cidr-block <CIDR>` – Create a VPC
  - `aws ec2 delete-vpc --vpc-id <id>` – Delete a VPC
  - `aws ec2 create-subnet --vpc-id <id> --cidr-block <CIDR>` – Create a subnet
  - `aws ec2 describe-security-groups` – List security groups
  - `aws ec2 describe-internet-gateways` – List internet gateways
- 

## **Lambda (Serverless Computing)**

- `aws lambda list-functions` – List all Lambda functions
- `aws lambda create-function --function-name <name> --runtime <runtime> --role <role> --handler <handler>` – Create a function

- `aws lambda update-function-code --function-name <name> --zip-file fileb://<file>.zip` – Update function code
  - `aws lambda delete-function --function-name <name>` – Delete a function
  - `aws lambda invoke --function-name <name> output.json` – Invoke a function
- 

### **Amazon EKS (Elastic Kubernetes Service)**

- `aws eks list-clusters` – List EKS clusters
  - `aws eks describe-cluster --name my-cluster` – Describe an EKS cluster
  - `aws eks create-cluster --name my-cluster --role-arn arn:aws:iam::account-id:role/EKSRole --resources-vpc-config subnetIds=subnet-xxxxxxx,securityGroupIds=sg-xxxxxxx` – Create an EKS cluster
  - `aws eks update-kubeconfig --name my-cluster` – Configure kubectl to use the EKS cluster
  - `kubectl get nodes` – Check worker nodes
  - `kubectl get pods -A` – List running pods
- 

### **Amazon ECS (Elastic Container Service)**

- `aws ecs list-clusters` – List ECS clusters
  - `aws ecs list-services --cluster my-cluster` – List ECS services
  - `aws ecs describe-services --cluster my-cluster --services my-service` – Describe an ECS service
- 

### **AWS CloudFormation**

- `aws cloudformation list-stacks` – List all stacks
- `aws cloudformation create-stack --stack-name my-stack --template-body file://template.yml` – Create a stack

## **CI/CD (CodePipeline, CodeBuild, CodeDeploy)**

### **AWS CodePipeline**

- `aws codepipeline list-pipelines` – List all pipelines
- `aws codepipeline start-pipeline-execution --name my-pipeline` – Start a pipeline execution

### **AWS CodeBuild**

- `aws codebuild list-projects` – List all CodeBuild projects
- `aws codebuild start-build --project-name my-project` – Start a build

### **AWS CodeDeploy**

- `aws deploy list-applications` – List all CodeDeploy applications
  - `aws deploy create-deployment --application-name MyApp --deployment-group-name MyDeploymentGroup --s3-location bucket=my-bucket,key=app.zip,bundleType=zip` – Deploy an application
- 

## **Security & Compliance**

- `aws cloudtrail describe-trails` – List CloudTrail logs
  - `aws secretsmanager list-secrets` – List all secrets
  - `aws secretsmanager get-secret-value --secret-id my-secret` – Retrieve a secret
- 

## **Monitoring & Logging (CloudWatch)**

- `aws cloudwatch list-metrics` – List available metrics
- `aws cloudwatch put-metric-alarm --alarm-name cpu-high --metric-name CPUUtilization --namespace AWS/EC2 --statistic Average --period 300 --threshold 80 --comparison-operator GreaterThanThreshold --dimensions`

Name=InstanceId,Value=i-xxxxxxxxxx --evaluation-periods 2  
--alarm-actions arn:aws:sns:region:account-id:my-topic – Create a  
CloudWatch alarm

- aws logs describe-log-groups – List all log groups
  - aws logs get-log-events --log-group-name my-log-group --log-stream-name my-log-stream – Retrieve log events
- 

## **Networking (VPC, ELB, Route 53)**

### **Amazon VPC**

- aws ec2 describe-vpcs – List all VPCs
- aws ec2 describe-subnets – List all subnets

### **Elastic Load Balancer (ELB)**

- aws elbv2 describe-load-balancers – List all load balancers

### **Amazon Route 53**

- aws route53 list-hosted-zones – List hosted zones
- 

### **Amazon ECR (Elastic Container Registry)**

- aws ecr get-login-password | docker login --username AWS --password-stdin <aws\_account\_id>.dkr.ecr.<region>.amazonaws.com – Authenticate Docker with ECR
  - aws ecr list-repositories – List all ECR repositories
- 

### **AWS Systems Manager (SSM)**

- aws ssm describe-instances – List managed instances

- `aws ssm send-command --document-name "AWS-RunShellScript" --targets "Key=instanceIds,Values=i-xxxxxxxxxx" --parameters commands="sudo apt update"` – Run a command on an EC2 instance
- 

## **AWS Auto Scaling**

- `aws autoscaling describe-auto-scaling-groups` – List Auto Scaling groups
  - `aws autoscaling update-auto-scaling-group --auto-scaling-group-name my-asg --desired-capacity 3` – Update the desired capacity
  - `aws autoscaling set-desired-capacity --auto-scaling-group-name my-asg --desired-capacity 2` – Manually scale an Auto Scaling group
- 

## **AWS Elastic Beanstalk**

- `aws elasticbeanstalk describe-environments` – List all environments
  - `aws elasticbeanstalk create-application --application-name my-app` – Create an application
  - `aws elasticbeanstalk update-environment --environment-name my-env --version-label new-version` – Deploy a new version
- 

## **AWS Step Functions**

- `aws stepfunctions list-state-machines` – List all state machines
  - `aws stepfunctions start-execution --state-machine-arn arn:aws:states:region:account-id:stateMachine:MyStateMachine` – Start a state machine execution
  - `aws stepfunctions describe-execution --execution-arn arn:aws:states:region:account-id:execution:MyStateMachine:MyExecution` – Get execution details
-

## **AWS Glue (ETL Service)**

- `aws glue get-databases` – List all Glue databases
  - `aws glue get-tables --database-name my-database` – List all tables in a database
  - `aws glue start-job-run --job-name my-glue-job` – Start a Glue job
- 

## **AWS SNS (Simple Notification Service)**

- `aws sns list-topics` – List all SNS topics
- `aws sns publish --topic-arn arn:aws:sns:region:account-id:MyTopic --message "Test Message"` – Publish a message to an SNS topic

## **AWS SQS (Simple Queue Service)**

- `aws sqs list-queues` – List all SQS queues
  - `aws sqs send-message --queue-url https://sqs.region.amazonaws.com/account-id/my-queue --message-body "Hello World"` – Send a message
- 

## **AWS Outposts(Managed on-prem cloud/On-premises AWS)**

### **# List and Describe Outposts**

`aws outposts list-outposts` # List all AWS Outposts

`aws outposts get-outpost --outpost-id <outpost-id>` # Get details of a specific Outpost

`aws outposts get-outpost-instance-types --outpost-id <outpost-id>` # List instance types in an Outpost

### **# Manage Outpost Resources**

aws outposts list-sites # List all Outpost sites

aws outposts list-orders # List Outpost orders

aws outposts list-outpost-instances --outpost-id <outpost-id> # List EC2 instances in an Outpost

### **# Deploy and Configure Outposts**

aws outposts create-order --line-items "[{\"catalogItemId\": \"item-id\", \"quantity\": 1}]" --outpost-id <outpost-id> # Order an Outpost

aws outposts update-outpost --outpost-id <outpost-id> --name <new-name> # Update Outpost configuration

### **# Networking and Storage on Outposts**

aws outposts list-outpost-network-devices --outpost-id <outpost-id> # List network devices in an Outpost

aws s3 ls --outpost-id <outpost-id> # List S3 buckets on an Outpost

aws s3 mb s3://<bucket-name> --outpost-id <outpost-id> # Create an S3 bucket in Outpost

### **# Deploy EC2 Instances in Outposts**

aws ec2 run-instances --image-id <ami-id> --instance-type <type> --subnet-id <outpost-subnet-id> # Launch an EC2 instance in Outpost

### **# Automate Outpost Deployments with CloudFormation**



```
aws cloudformation deploy --template-file outpost-config.yml --stack-name  
my-outpost-stack # Deploy Outpost resources using CloudFormation
```

### **# Monitor Outposts with CloudWatch**

```
aws cloudwatch list-metrics --namespace AWS/Outposts # List Outpost-related  
CloudWatch metrics
```

```
aws cloudwatch get-metric-data --metric-name CPUUtilization --namespace  
AWS/Outposts # Monitor CPU usage of Outpost instances
```

### **# Integrate Outposts with CI/CD**

```
aws codepipeline list-pipelines # List all CI/CD pipelines
```

```
aws codepipeline start-pipeline-execution --name <pipeline-name> # Start a  
deployment pipeline for Outposts
```

```
aws codebuild start-build --project-name <build-project> # Start a build process  
for Outposts workloads
```

```
aws deploy create-deployment --application-name <app-name>  
--deployment-group-name <group-name> --s3-location  
bucket=<bucket-name>,key=<app.zip>,bundleType=zip # Deploy an application  
to an Outpost
```

### **# Security and Compliance for Outposts**

```
aws iam create-role --role-name <role-name> --assume-role-policy-document  
file://policy.json # Create an IAM role for Outpost management
```

```
aws secretsmanager list-secrets # List stored secrets for Outposts
```

aws secretsmanager get-secret-value --secret-id <secret-name> # Retrieve a stored secret

aws cloudtrail describe-trails # List AWS CloudTrail logs for security auditing

aws guardduty list-findings # Detect security threats related to Outposts

## # Delete or Deactivate an Outpost

aws outposts delete-outpost --outpost-id <outpost-id> # Delete an Outpost (must be empty)

aws outposts cancel-order --order-id <order-id> # Cancel an Outpost order before delivery

---

- **Azure**

## Azure Cheat Sheet

### 1. Azure Virtual Machines (VMs)

- az vm create --resource-group <rg> --name <vm-name> --image <image>  
→ Create a VM
- az vm list -o table  
→ List all VMs
- az vm stop --name <vm-name> --resource-group <rg>  
→ Stop a VM
- az vm start --name <vm-name> --resource-group <rg>  
→ Start a VM
- az vm delete --name <vm-name> --resource-group <rg>  
→ Delete a VM
- az vm resize --name <vm-name> --resource-group <rg> --size <vm-size>  
→ Resize a VM

- `az vm show --name <vm-name> --resource-group <rg>`  
→ Show VM details
  - `az vm open-port --port <port-number> --name <vm-name> --resource-group <rg>`  
→ Open a port on a VM
- 

## 2. Azure Storage

- `az storage account create --name <storage-name> --resource-group <rg> --location <region>`  
→ Create a storage account
  - `az storage container create --name <container-name> --account-name <storage-name>`  
→ Create a blob container
  - `az storage blob upload --file <file-path> --container-name <container-name> --account-name <storage-name>`  
→ Upload a file to Blob Storage
  - `az storage blob list --container-name <container-name> --account-name <storage-name>`  
→ List blobs in a container
  - `az storage account delete --name <storage-name> --resource-group <rg>`  
→ Delete a storage account
- 

## 3. Azure Kubernetes Service (AKS)

- `az aks create --resource-group <rg> --name <aks-name> --node-count <num> --generate-ssh-keys`  
→ Create an AKS cluster
- `az aks get-credentials --resource-group <rg> --name <aks-name>`  
→ Get kubeconfig for AKS cluster
- `kubectl get nodes`  
→ List AKS cluster nodes

- `kubectl get pods -A`  
→ List all pods in AKS
  - `kubectl apply -f <file.>`  
→ Deploy an application in AKS
  - `kubectl delete -f <file.>`  
→ Remove an application from AKS
  - `az aks delete --name <aks-name> --resource-group <rg>`  
→ Delete an AKS cluster
- 

#### 4. Azure Functions

- `az functionapp create --resource-group <rg> --name <app-name> --consumption-plan-location <region> --runtime <runtime>`  
→ Create an Azure Function App
- `az functionapp list -o table`  
→ List all Function Apps
- `az functionapp delete --name <app-name> --resource-group <rg>`  
→ Delete a Function App
- `func init <app-name>`  
→ Initialize a local Azure Functions project
- `func new`  
→ Create a new function
- `func start`  
→ Run functions locally
- `func azure functionapp publish <app-name>`  
→ Deploy function to Azure

#### 6. Azure Networking

##### Virtual Network (VNet)

- `az network vnet list --output table` – List VNets
- `az network vnet create --name myVNet --resource-group myResourceGroup --subnet-name mySubnet` – Create a VNet

## Network Security Group (NSG)

- `az network nsg list --output table` – List NSGs
- `az network nsg create --resource-group myResourceGroup --name myNSG` – Create an NSG

## Load Balancer

- `az network lb list --output table` – List load balancers
  - `az network lb create --resource-group myResourceGroup --name myLB --sku Standard --frontend-ip-name myFrontend --backend-pool-name myBackendPool` – Create a Load Balancer
- 

## Azure DevOps (CI/CD)

### Azure DevOps Projects

- `az devops project list --output table` – List all DevOps projects
- `az devops project create --name myDevOpsProject` – Create a DevOps project
- `az devops project delete --id PROJECT_ID --yes` – Delete a DevOps project

### Azure Repos (Git)

- `az repos list --output table` – List all repositories
- `az repos create --name myRepo` – Create a new repo
- `az repos delete --name myRepo --yes` – Delete a repo

### Azure Pipelines

- `az pipelines list --output table` – List all pipelines
  - `az pipelines create --name myPipeline --repository myRepo --branch main --repository-type gitHub` – Create a pipeline
  - `az pipelines run --name myPipeline` – Run a pipeline
-

## Azure Monitor & Logging

### Azure Monitor

- az monitor metrics list --resource myResourceID – List metrics for a resource
- az monitor metrics alert list --resource-group myResourceGroup – List metric alerts

### Azure Log Analytics

- az monitor log-analytics workspace list --output table – List log analytics workspaces
  - az monitor log-analytics workspace create --resource-group myResourceGroup --workspace-name myWorkspace – Create a Log Analytics workspace
- 

## Security & Compliance

### Azure Security Center

- az security assessment list --output table – List security assessments
- az security setting update --name AutoProvisioning --value On – Enable auto-provisioning for Security Center

### Azure Key Vault

- az keyvault list --output table – List Key Vaults
  - az keyvault create --name myKeyVault --resource-group myResourceGroup --location eastus – Create a Key Vault
  - az keyvault secret set --vault-name myKeyVault --name mySecret --value "MySecretValue" – Store a secret in Key Vault
  - az keyvault secret show --vault-name myKeyVault --name mySecret – Retrieve a secret
-

## Azure Policies & Governance

- az policy assignment list --output table – List all policy assignments
  - az policy assignment create --name myPolicyAssignment --policy myPolicyDefinition – Assign a policy
  - az policy assignment delete --name myPolicyAssignment – Delete a policy assignment
- 

## Azure Active Directory (AAD)

- az ad user list --output table – List all users
  - az ad group list --output table – List all groups
  - az ad app list --output table – List all applications
  - az ad sp list --output table – List all service principals
- 

## Azure Backup & Recovery

- az backup vault list --output table – List all backup vaults
  - az backup vault create --resource-group myResourceGroup --name myBackupVault – Create a backup vault
  - az backup item list --resource-group myResourceGroup --vault-name myBackupVault --output table – List backup items
- 

- GCP

### 1. Compute Engine (VMs)

- gcloud compute instances create <vm-name> --zone=<zone> --machine-type=<type> --image=<image>  
→ Create a VM instance

- gcloud compute instances list  
→ List all VM instances
  - gcloud compute instances start <vm-name> --zone=<zone>  
→ Start a VM instance
  - gcloud compute instances stop <vm-name> --zone=<zone>  
→ Stop a VM instance
  - gcloud compute instances delete <vm-name> --zone=<zone>  
→ Delete a VM instance
  - gcloud compute ssh <vm-name> --zone=<zone>  
→ SSH into a VM instance
  - gcloud compute firewall-rules create <rule-name> --allow tcp:<port>  
→ Open a specific port
- 

## 2. Google Kubernetes Engine (GKE)

- gcloud container clusters create <cluster-name> --num-nodes=<num>  
--zone=<zone>  
→ Create a GKE cluster
  - gcloud container clusters get-credentials <cluster-name> --zone=<zone>  
→ Get credentials for the GKE cluster
  - kubectl get nodes  
→ List cluster nodes
  - kubectl get pods -A  
→ List all running pods
  - kubectl apply -f <file.>  
→ Deploy an application to GKE
  - kubectl delete -f <file.>  
→ Remove an application from GKE
  - gcloud container clusters delete <cluster-name> --zone=<zone>  
→ Delete a GKE cluster
- 

## 3. Cloud Run (Serverless Containers)



- `gcloud run deploy <service-name> --image=<gcr.io/project/image> --platform=managed --region=<region> --allow-unauthenticated`  
→ Deploy an application to Cloud Run
- `gcloud run services list`  
→ List all deployed Cloud Run services
- `gcloud run services update-traffic <service-name> --to-latest`  
→ Update Cloud Run service to the latest image
- `gcloud run services delete <service-name>`  
→ Delete a Cloud Run service
- `gcloud run services update <service-name> --set-env-vars VAR_NAME=value`  
→ Set environment variables in a Cloud Run service

#### 4. Google Cloud Storage (GCS)

- `gcloud storage buckets list` – List all storage buckets
  - `gcloud storage buckets create my-bucket --location US` – Create a storage bucket
  - `gcloud storage cp file.txt gs://my-bucket/` – Upload a file
  - `gcloud storage rm gs://my-bucket/file.txt` – Delete a file
  - `gcloud storage buckets delete my-bucket` – Delete a storage bucket
- 

#### 5. Google Cloud IAM (Identity & Access Management)

- `gcloud iam roles list` – List all IAM roles
  - `gcloud iam service-accounts list` – List all service accounts
  - `gcloud projects add-iam-policy-binding PROJECT_ID --member=user:EMAIL --role=roles/editor` – Assign a role to a user
  - `gcloud projects remove-iam-policy-binding PROJECT_ID --member=user:EMAIL --role=roles/editor` – Remove a role from a user
- 

#### Google Cloud SQL (Managed Database Service)

- `gcloud sql instances list` – List all Cloud SQL instances
  - `gcloud sql instances create my-db --tier=db-f1-micro --region=us-central1` – Create a Cloud SQL instance
  - `gcloud sql instances start my-db` – Start a Cloud SQL instance
  - `gcloud sql instances stop my-db` – Stop a Cloud SQL instance
  - `gcloud sql instances delete my-db` – Delete a Cloud SQL instance
- 

## **Google Cloud Build (CI/CD)**

- `gcloud builds list` – List all Cloud Build runs
  - `gcloud builds submit --tag gcr.io/PROJECT_ID/my-app` – Build and push an image
  - `gcloud builds triggers list` – List Cloud Build triggers
- 

## **Google Cloud Deploy (CI/CD)**

- `gcloud deploy releases list --delivery-pipeline=my-pipeline` – List deployment releases
  - `gcloud deploy rollouts list --release=my-release --delivery-pipeline=my-pipeline` – List rollouts
- 

## **Google Cloud Logging & Monitoring**

### **Cloud Logging**

- `gcloud logging logs list` – List available logs
- `gcloud logging read "resource.type=gce_instance" --limit 10` – Read VM logs

### **Cloud Monitoring**

- `gcloud monitoring metrics list` – List available monitoring metrics
- `gcloud monitoring dashboards list` – List all dashboards

## **Google Cloud Networking**

### **VPC (Virtual Private Cloud)**

- gcloud compute networks list – List VPC networks
- gcloud compute networks create my-vpc --subnet-mode=custom – Create a VPC network

### **Firewall Rules**

- gcloud compute firewall-rules list – List firewall rules
- gcloud compute firewall-rules create allow-ssh --network=my-vpc --allow=tcp:22 – Allow SSH access

### **Load Balancers**

- gcloud compute forwarding-rules list – List all load balancers
- 

## **Google Cloud Security**

### **Cloud Identity-Aware Proxy (IAP)**

- gcloud iap web list – List IAP-secured applications
- gcloud iap settings get --resource-type=app-engine – Get IAP settings

### **Cloud Key Management Service (KMS)**

- gcloud kms keyrings list --location global – List key rings
  - gcloud kms keys list --keyring my-keyring --location global – List encryption keys
- 

## **Google Artifact Registry**

- gcloud artifacts repositories list – List all Artifact Repositories
  - gcloud artifacts repositories create my-repo --repository-format=docker --location=us-central1 – Create a Docker registry
- 

### **Google Cloud Pub/Sub (Messaging)**

- gcloud pubsub topics list – List all Pub/Sub topics
  - gcloud pubsub topics create my-topic – Create a topic
  - gcloud pubsub subscriptions list – List all subscriptions
  - gcloud pubsub subscriptions create my-sub --topic=my-topic – Create a subscription
- 

### **Google Cloud Backup & Disaster Recovery**

- gcloud backup vaults list – List all backup vaults
  - gcloud backup policies list – List backup policies
- 

### **Google Cloud Policies & Governance**

- gcloud policy-tags list --location=us – List policy tags
  - gcloud resource-manager org-policies list – List all organizational policies
- 

### **Google Cloud Scheduler (Cron Jobs)**

- gcloud scheduler jobs list – List all scheduled jobs
  - gcloud scheduler jobs create http my-job --schedule="0 \* \* \* \*" --uri=https://example.com/cron – Create a scheduled HTTP job
-

## 6. Configuration Management

**Ansible** (playbooks, roles, inventory)

### 1. Ansible Basics

**Check version:**

```
ansible --version
```

**Check inventory:**

```
ansible-inventory --list -y
```

**Ping all hosts:**

```
ansible all -m ping
```

**Run command on all hosts:**

```
ansible all -a "uptime"
```

---

### 2. Inventory & Configuration

- Default inventory: /etc/ansible/hosts

**Custom inventory:**

```
ansible -i inventory.ini all -m ping
```

**Define hosts in inventory.ini:**

```
ini
```

```
[web]
```

```
web1 ansible_host=192.168.1.10 ansible_user=ubuntu
```

```
[db]
```

```
db1 ansible_host=192.168.1.20 ansible_user=root
```

---

### 3. Ad-Hoc Commands

**Run as a specific user:**

```
ansible all -m ping -u ubuntu --become
```

**Copy file to remote host:**

```
ansible all -m copy -a "src=/etc/hosts dest=/tmp/hosts"
```

**Install a package (example: nginx):**

```
ansible all -m apt -a "name=nginx state=present" --become
```

## 4. Playbook Structure

```
- name: Install Nginx
```

```
  hosts: web
```

```
  become: yes
```

```
  tasks:
```

```
    - name: Install Nginx
```

```
      apt:
```

```
        name: nginx
```

```
        state: present
```

**Run the playbook:**

```
ansible-playbook install_nginx.yml
```

## 5. Variables & Facts

**Define variables in vars.yml:**

```
nginx_version: latest
```

**Use variables in playbook:**

- name: Install Nginx

apt:

name: nginx={{ nginx\_version }}

state: present

**Display all facts:**

ansible all -m setup

**6. Handlers & Notifications**

- name: Restart Nginx

hosts: web

become: yes

tasks:

- name: Install Nginx

apt:

name: nginx

state: present

notify: Restart Nginx

handlers:

- name: Restart Nginx

service:

name: nginx

state: restarted

## 7. Loops & Conditionals

### Loop over items:

- name: Install multiple packages

apt:

name: "{{ item }}"

state: present

loop:

- nginx

- curl

- git

### Conditional execution:

- name: Restart service only if Nginx is installed

service:

name: nginx

state: restarted

when: ansible\_facts['pkg\_mgr'] == 'apt'

## 8. Roles & Reusability

### Create a role:

Ansible-galaxy init my\_role



**Run a role in a playbook:**

- hosts: web

roles:

- my\_role

## 9. Debugging & Testing

**Debug a variable:**

- debug:

msg: "The value of nginx\_version is {{ nginx\_version }}"

**Check playbook syntax:**

ansible-playbook myplaybook.yml --syntax-check

**Run in dry mode:**

ansible-playbook myplaybook.yml --check

---

## Ansible Playbook

### 1. Playbook Structure

- name: Example Playbook

hosts: all

become: yes

tasks:

- name: Print a message

debug:

msg: "Hello, Ansible!"

**Run the playbook:**

ansible-playbook playbook.yml

---

**2. Defining Hosts & Privilege Escalation**

- name: Install Nginx

hosts: web

become: yes

**Run as a specific user:**

- name: Install package

apt:

name: nginx

state: present

become\_user: root

---

**3. Tasks & Modules**

- name: Ensure Nginx is installed

hosts: web

become: yes

tasks:

- name: Install Nginx

apt:

name: nginx

state: present

- **Common Modules**

- command: Run shell commands
- copy: Copy files
- service: Manage services
- user: Manage users
- file: Set file permissions

---

## 4. Using Variables

**Define variables inside the playbook:**

vars:

package\_name: nginx

**Use them in tasks:**

- name: Install {{ package\_name }}

apt:

name: "{{ package\_name }}"

state: present

**Load external variables from vars.yml:**

- name: Load Variables

include\_vars: vars.yml

---

## 5. Conditionals

- name: Restart Nginx only if installed

service:

name: nginx

state: restarted

when: ansible\_facts['pkg\_mgr'] == 'apt'

---

## 6. Loops

- name: Install multiple packages

apt:

name: "{{ item }}"

state: present

loop:

- nginx

- git

- curl

---

## 7. Handlers

- name: Install Nginx

apt:

name: nginx

state: present

notify: Restart Nginx

handlers:

- name: Restart Nginx

```
service:  
  
  name: nginx  
  
  state: restarted
```

---

## 8. Debugging & Testing

- name: Debug Variable

```
debug:  
  
  msg: "The server is running { { ansible_distribution } }"
```

### Check syntax:

```
ansible-playbook playbook.yml --syntax-check
```

### Dry run:

```
ansible-playbook playbook.yml --check
```

---

## 9. Roles (Best Practice)

### Create a role:

```
ansible-galaxy init my_role
```

### Use the role in a playbook:

```
- hosts: web
```

```
roles:
```

```
- my_role
```

---

- **Chef** (recipes, cookbooks)

## Basic Concepts

- **Recipe:** Defines a set of resources to configure a system.
- **Cookbook:** A collection of recipes, templates, and attributes.

- **Resource:** Represents system objects (e.g., package, service, file).
- **Node:** A machine managed by Chef.
- **Run List:** Specifies the order in which recipes are applied.
- **Attributes:** Variables used to customize recipes.

## Commands

```
chef-client          # Run Chef on a node

knife cookbook create my_cookbook  # Create a new cookbook

knife node list      # List all nodes

knife role list      # List all roles

chef-solo -c solo.rb -j run_list.json # Run Chef in solo mode
```

## Example Recipe

```
package 'nginx' do

  action :install

end


service 'nginx' do

  action [:enable, :start]

end


file '/var/www/html/index.html' do

  content '<h1>Welcome to Chef</h1>'
```

end

- 
- **Puppet** (manifests, modules)

## Basic Concepts

- **Manifest:** A file defining resources and configurations (.pp).
- **Module:** A collection of manifests, templates, and files.
- **Class:** A reusable block of Puppet code.
- **Node:** A system managed by Puppet.
- **Fact:** System information collected by Facter.
- **Resource:** The basic unit of configuration (e.g., package, service).

## Commands

```
puppet apply my_manifest.pp      # Apply a local manifest
puppet module install my_module  # Install a module
puppet agent --test              # Run Puppet on an agent node
puppet resource service nginx    # Check a resource state
```

## Example Manifest

```
puppet
class nginx {
  package { 'nginx':
    ensure => installed,
```

```
}

service { 'nginx':

  ensure => running,

  enable => true,

}

file { '/var/www/html/index.html':

  content => '<h1>Welcome to Puppet</h1>',

  mode    => '0644',

}

}
```

include nginx

- 
- **SaltStack** (states, grains)

## Basic Concepts

- **State:** Defines configurations and how they should be enforced.
- **Grain:** System metadata like OS, CPU, and memory.
- **Pillar:** Secure data storage for variables.
- **Minion:** A node managed by the Salt master.
- **Master:** The central server controlling minions.



## Commands

```
salt '*' test.ping          # Check connectivity with minions
salt '*' pkg.install nginx  # Install a package on all minions
salt '*' service.start nginx # Start a service
salt '*' grains.items        # Show all grains for a minion
salt '*' state.apply webserver # Apply a state to minions
```

## Example State (nginx.sls)

nginx:

pkg.installed: []

service.running:

- enable: true

/var/www/html/index.html:

file.managed:

- source: salt://webserver/index.html

- mode: 644

---

## 7. Monitoring & Logging

### Prometheus & Grafana

## Prometheus CLI Commands

```
prometheus --version          # Check Prometheus version

prometheus --config.file=prometheus.yml # Start Prometheus

curl -X POST http://localhost:9090/-/reload # Reload Prometheus configuration

curl http://localhost:9090/api/v1/targets # List active targets

curl "http://localhost:9090/api/v1/query?query=up" # Query Prometheus API

curl http://localhost:9090/metrics      # View Prometheus metrics

curl http://localhost:9090/api/v1/alerts # List running alerts
```

---

## Prometheus Configuration (prometheus.yml)

```
yaml

scrape_configs:

  - job_name: 'node'

    static_configs:

      - targets: ['localhost:9100']

  - job_name: 'kubernetes'

    static_configs:

      - targets: ['kube-state-metrics:8080']
```

---

## Prometheus Alert Manager Configuration (alertmanager.yml)

yaml

route:

receiver: 'slack'

receivers:

- name: 'slack'

slack\_configs:

- channel: '#alerts'

send\_resolved: true

api\_url: 'https://hooks.slack.com/services/your\_webhook\_url'

## Useful PromQL Queries

up # Check target availability

100 - (avg by(instance) (rate(node\_cpu\_seconds\_total{mode="idle"}[5m])) \* 100)  
# CPU usage

(1 - (node\_memory\_MemAvailable\_bytes / node\_memory\_MemTotal\_bytes)) \*  
100 # Memory usage

sum(rate(http\_requests\_total[5m])) # HTTP request count

node\_filesystem\_free\_bytes / node\_filesystem\_size\_bytes \* 100 # Disk space  
usage

count(kube\_pod\_status\_phase{phase="Running"}) # Active Kubernetes pods

---

## Grafana CLI Commands

```
grafana-server -v          # Check Grafana version

systemctl start grafana-server    # Start Grafana

systemctl stop grafana-server     # Stop Grafana

systemctl restart grafana-server  # Restart Grafana

systemctl enable grafana-server    # Enable Grafana on boot
```

---

## Grafana API Commands

```
curl -X GET http://localhost:3000/api/search?query=\&type=dash-db -H
"Authorization: Bearer <API_TOKEN>" # List dashboards

curl -X POST http://localhost:3000/api/dashboards/db -H "Content-Type:
application/json" -H "Authorization: Bearer <API_TOKEN>" --data
'@dashboard.json' # Create dashboard

curl -X POST http://localhost:3000/api/datasources -H "Content-Type:
application/json" -H "Authorization: Bearer <API_TOKEN>" --data '{ "name":
"Prometheus", "type": "prometheus", "url": "http://localhost:9090", "access":
"proxy" }' # Add Prometheus data source

curl -X GET http://localhost:3000/api/users -H "Authorization: Bearer
<API_TOKEN>" # List all users
```

---

## Integrating Prometheus with Grafana

1. **Add Prometheus Data Source in Grafana**
  - **Grafana → Configuration → Data Sources → Add Prometheus**
  - Set **URL** to `http://localhost:9090`
  - Click **Save & Test**
2. **Import a Prebuilt Dashboard**
  - **Grafana → Dashboards → Import**

- Enter **Dashboard ID** from Grafana Repository
- Select **Prometheus** as data source → **Import**
- 3. **Create a New Dashboard**
  - **Grafana** → **Dashboards** → **New Dashboard**
  - Add **PromQL** queries for visualization
  - Choose **Panel Type** (Graph, Gauge, Table, etc.)
  - Click **Save Dashboard**

## **Grafana Alerting Setup**

### **# Create Alert in Grafana**

1. Open **\*\*Dashboard → Edit Panel\*\***
2. Click **\*\*Alert → Create Alert\*\***
3. Set **\*\*Condition\*\*** (e.g., CPU usage > 80%)
4. Define **\*\*Evaluation Interval\*\*** (e.g., Every 1 min)
5. Configure **\*\*Notification Channels\*\*** (Slack, Email, PagerDuty, etc.)
6. Click **\*\*Save Alert\*\***

### **# Configure Slack Alerts in Grafana**

1. **\*\*Grafana → Alerting → Notification Channels\*\***
2. Click **\*\*Add New Channel\*\***
3. Select **\*\*Slack\*\***, enter **\*\*Webhook URL\*\***
4. Click **\*\*Save & Test\*\***

---

## **ELK Stack (Elasticsearch, Logstash, Kibana)**

## 1. Elasticsearch Commands

### Elasticsearch CLI Commands

```
elasticsearch --version          # Check Elasticsearch version

systemctl start elasticsearch    # Start Elasticsearch

systemctl stop elasticsearch     # Stop Elasticsearch

systemctl restart elasticsearch  # Restart Elasticsearch

systemctl enable elasticsearch   # Enable Elasticsearch on boot

curl -X GET "http://localhost:9200"    # Check Elasticsearch status

curl -X GET "http://localhost:9200/_cluster/health?pretty" # Cluster health

curl -X GET "http://localhost:9200/_cat/nodes?v" # List cluster nodes

curl -X GET "http://localhost:9200/_cat/indices?v" # List all indices

curl -X DELETE "http://localhost:9200/index_name" # Delete an index
```

### Index Management

```
curl -X PUT "http://localhost:9200/index_name" # Create an index

curl -X GET "http://localhost:9200/index_name/_search?pretty" # Search index

curl -X PUT "http://localhost:9200/index_name/_doc/1" -H "Content-Type:
application/json" -d '{"name": "DevOps"}' # Insert a document

curl -X GET "http://localhost:9200/index_name/_doc/1?pretty" # Retrieve a
document

curl -X DELETE "http://localhost:9200/index_name/_doc/1" # Delete a document
```

## Elasticsearch Query Examples

```
curl -X GET "http://localhost:9200/index_name/_search?q=name:DevOps&pretty"  
# Search for "DevOps"
```

```
curl -X GET "http://localhost:9200/index_name/_search" -H "Content-Type:  
application/json" -d '{ "query": { "match": { "name": "DevOps" } } }' # Query  
using JSON
```

```
curl -X GET "http://localhost:9200/index_name/_search?pretty" -H "Content-Type:  
application/json" -d '{ "size": 10, "query": { "match_all": { } } }' # Get all  
documents
```

---

## 2. Logstash Commands

### Logstash CLI Commands

```
logstash --version          # Check Logstash version
```

```
logstash -f /etc/logstash/logstash.conf # Start Logstash with a config file
```

```
systemctl start logstash    # Start Logstash
```

```
systemctl stop logstash     # Stop Logstash
```

```
systemctl restart logstash  # Restart Logstash
```

```
systemctl enable logstash   # Enable Logstash on boot
```

### Sample Logstash Configuration (logstash.conf)

```
yaml
```

```
input {
```

```
file {
```

```
path => "/var/log/syslog"

start_position => "beginning"

}

}

filter {

  grok {

    match => { "message" => "%{SYSLOGTIMESTAMP:timestamp}
%{HOSTNAME:host} %{DATA:process}: %{GREEDYDATA:log_message}" }

  }

}

output {

  elasticsearch {

    hosts => ["http://localhost:9200"]

    index => "logstash-logs"

  }

  stdout { codec => rubydebug }

}
```

---

### 3. Kibana Commands



## Kibana CLI Commands

kibana --version	# Check Kibana version
systemctl start kibana	# Start Kibana
systemctl stop kibana	# Stop Kibana
systemctl restart kibana	# Restart Kibana
systemctl enable kibana	# Enable Kibana on boot

## Kibana API Commands

curl -X GET "http://localhost:5601/api/status" -H "kbn-xsrf: true" # Check Kibana status

curl -X GET "http://localhost:5601/api/spaces/space" -H "kbn-xsrf: true" # List all Kibana spaces

## Kibana Dashboard Import Example

curl -X POST "http://localhost:5601/api/saved\_objects/\_import" -H "kbn-xsrf: true" --form file=@dashboard.ndjson

---

## 4. Integrating ELK Stack

### 1. Configure Elasticsearch in Kibana

- Go to **Kibana** → **Management** → **Stack Management** → **Data Views**
- Click **Create Data View**
- Set Index Pattern as **logstash-\***
- Click **Save**

## 2. Configuring Logstash to Send Logs to Elasticsearch

- Open /etc/logstash/logstash.conf
- Ensure the output points to Elasticsearch:

yaml

```
output {  
  
  elasticsearch {  
  
    hosts => ["http://localhost:9200"]  
  
    index => "logstash-logs"  
  
  }  
  
}
```

- **Restart Logstash:**

```
systemctl restart logstash
```

## 3. Visualizing Logs in Kibana

- Go to **Kibana** → **Discover**
- Select logstash-\* Data View
- Apply Filters & View Logs

---

## 5. ELK Stack Monitoring

### Monitor Elasticsearch Cluster Health

```
curl -X GET "http://localhost:9200/_cluster/health?pretty"
```

```
curl -X GET "http://localhost:9200/_cat/nodes?v"
```

```
curl -X GET "http://localhost:9200/_cat/indices?v"
```

### **Monitor Logstash Logs**

```
tail -f /var/log/logstash/logstash-plain.log
```

```
journalctl -u logstash -f
```

### **Monitor Kibana Logs**

```
tail -f /var/log/kibana/kibana.log
```

```
journalctl -u kibana -f
```

---

## **Datadog**

### **# Datadog Agent Installation (Linux)**

```
DD_API_KEY=your_api_key bash -c "$(curl -L  
https://s3.amazonaws.com/dd-agent/scripts/install_script.sh)"
```

### **# Enable Log Monitoring**

```
sudo nano /etc/datadog-agent/datadog.yaml
```

```
logs_enabled: true
```

```
systemctl restart datadog-agent
```

## # Datadog Agent CLI Commands

<code>datadog-agent version</code>	<code># Check Datadog agent version</code>
<code>datadog-agent status</code>	<code># Check Datadog agent status</code>
<code>datadog-agent check &lt;integration&gt;</code> <code>`datadog-agent check cpu`)</code>	<code># Run a specific check (e.g.,</code>
<code>datadog-agent flare</code> <code>troubleshooting</code>	<code># Gather logs and configuration for</code>
<code>systemctl start datadog-agent</code>	<code># Start Datadog agent</code>
<code>systemctl stop datadog-agent</code>	<code># Stop Datadog agent</code>
<code>systemctl restart datadog-agent</code>	<code># Restart Datadog agent</code>
<code>systemctl enable datadog-agent</code>	<code># Enable Datadog agent on boot</code>

## # Metric Queries

<code>avg:system.cpu.user{*}</code>	<code># CPU usage</code>
<code>top(avg:system.disk.used{*}, 5, 'mean') # Top 5 disk users</code>	

## # Datadog API Commands

```
curl -X GET "https://api.datadoghq.com/api/v1/metrics" -H "DD-API-KEY:
<API_KEY>" # List all metrics

curl -X POST "https://api.datadoghq.com/api/v1/series" \
```

```
-H "DD-API-KEY: <API_KEY>" \  
-H "Content-Type: application/json" \  
--data '{ "series": [{ "metric": "custom.metric", "points": [[1633000000, 10]],  
"type": "gauge", "tags": ["env:prod"] }] }' # Submit a custom metric
```

### **# Datadog Configuration (/etc/datadog-agent/datadog.yaml)**

```
api_key: "<YOUR_API_KEY>"
```

```
site: "datadoghq.com"
```

```
logs_enabled: true
```

```
apm_config:
```

```
  enabled: true
```

### **# Datadog Log Collection Setup**

```
sudo nano /etc/datadog-agent/datadog.yaml
```

```
logs_enabled: true
```

```
systemctl restart datadog-agent
```

### **# Monitor Logs in Datadog UI**

```
# 1. Go to Datadog → Logs → Live Tail
```

```
# 2. Filter logs by service, environment, or host
```

## # Datadog Monitoring Commands

```
datadog-agent configcheck          # Check configuration validity
datadog-agent hostname            # Get the hostname recognized by Datadog
datadog-agent health              # Check agent health
```

## # Datadog Kubernetes Agent Installation

```
kubectrl create secret generic datadog-secret
--from-literal=api-key=<YOUR_API_KEY>

kubectrl apply -f
https://raw.githubusercontent.com/DataDog/datadog-agent/main/Dockerfiles/manifests/agent.yaml
```

## # Datadog Kubernetes Monitoring

```
kubectrl get pods -n datadog      # List Datadog agent pods
kubectrl logs -n datadog <pod-name> # Check logs of a Datadog agent pod
kubectrl describe pod <pod-name> -n datadog # Describe Datadog agent pod
```

## # Datadog Integrations for DevOps

```
datadog-agent integration install -t docker    # Install Docker integration
datadog-agent integration install -t kubernetes # Install Kubernetes integration
datadog-agent integration install -t aws       # Install AWS integration
datadog-agent integration install -t prometheus # Install Prometheus integration
```

`datadog-agent integration install -t jenkins`      `# Install Jenkins integration`

`datadog-agent integration install -t gitlab`      `# Install GitLab integration`

### **# Datadog Log Collection for Docker**

```
docker run -d --name datadog-agent \  
-e DD_API_KEY=<YOUR_API_KEY> \  
-e DD_LOGS_ENABLED=true \  
-e DD_CONTAINER_EXCLUDE="name:datadog-agent" \  
-v /var/run/docker.sock:/var/run/docker.sock:ro \  
-v /proc:/host/proc:ro \  
-v /sys/fs/cgroup:/host/sys/fs/cgroup:ro \  
datadog/agent
```

### **# Datadog APM (Application Performance Monitoring)**

`datadog-agent trace-agent status`      `# Check trace agent status`

`datadog-agent trace-agent config`      `# Show trace agent configuration`

`datadog-agent trace-agent restart`      `# Restart the trace agent`

### **# Datadog CI/CD Monitoring**

```
curl -X POST "https://api.datadoghq.com/api/v1/series" \  
-H "DD-API-KEY: <API_KEY>" \  

```

```
-H "Content-Type: application/json" \  
  
--data '{ "series": [{ "metric": "ci.pipeline.duration", "points": [[1633000000,  
30]], "type": "gauge", "tags": ["pipeline:deploy"] }] }' # Track CI/CD pipeline  
duration
```

## # Datadog Synthetic Monitoring (API Tests)

```
curl -X POST "https://api.datadoghq.com/api/v1/synthetics/tests" \  
  
-H "DD-API-KEY: <API_KEY>" \  
  
-H "Content-Type: application/json" \  
  
--data '{  
  
  "config": { "request": { "method": "GET", "url": "https://example.com" },  
"assertions": [{ "operator": "is", "type": "statusCode", "target": 200 }] },  
  
  "locations": ["aws:us-east-1"],  
  
  "message": "Website should be reachable",  
  
  "name": "Website Availability Test",  
  
  "options": { "monitor_options": { "renotify_interval": 0 } },  
  
  "tags": ["env:prod"],  
  
  "type": "api"  
  
}'
```

## # Datadog Dashboard & Alerts

# Create a new dashboard



```
curl -X POST "https://api.datadoghq.com/api/v1/dashboard" \  
  -H "Content-Type: application/json" \  
  -H "DD-API-KEY: <API_KEY>" \  
  --data '{  
    "title": "DevOps Dashboard",  
    "widgets": [  
      {  
        "definition": {  
          "type": "timeseries",  
          "requests": [  
            { "q": "avg:system.cpu.user{*}" }  
          ]  
        }  
      }  
    ]  
  }'
```

### **# Create an alert**

```
curl -X POST "https://api.datadoghq.com/api/v1/monitor" \  
  -H "Content-Type: application/json" \  
  -H "DD-API-KEY: <API_KEY>" \
```

```
--data '{
  "name": "High CPU Usage",
  "type": "query alert",
  "query": "avg(last_5m):avg:system.cpu.user{*} > 80",
  "message": "CPU usage is too high!",
  "tags": ["env:prod"]
}'
```

## # Datadog Incident Management

```
curl -X POST "https://api.datadoghq.com/api/v1/incidents" \
  -H "Content-Type: application/json" \
  -H "DD-API-KEY: <API_KEY>" \
  --data '{
    "data": {
      "type": "incidents",
      "attributes": {
        "title": "Production Outage",
        "customer_impact_scope": "global",
        "customer_impact_duration": 30,
        "severity": "critical",
        "state": "active",
```

```
"commander": "DevOps Team"
}
}
}'
```

---

## **New Relic**

### **Install New Relic Agent**

#### **For Linux Servers**

```
curl -Ls https://download.newrelic.com/install/newrelic-cli/scripts/install.sh |
```

```
newrelic install
```

- **Query Logs & Metrics**

### **NRQL Queries (New Relic Query Language)**

```
SELECT average(cpuPercent) FROM SystemSample SINCE 30 minutes ago
```

```
SELECT count(*) FROM Transaction WHERE appName = 'my-app'
```

### **New Relic Agent CLI Commands**

<code>newrelic-daemon -v</code>	<code># Check New Relic agent version</code>
<code>systemctl start newrelic-infra</code>	<code># Start New Relic infrastructure agent</code>
<code>systemctl stop newrelic-infra</code>	<code># Stop New Relic infrastructure agent</code>
<code>systemctl restart newrelic-infra</code>	<code># Restart New Relic infrastructure agent</code>
<code>systemctl enable newrelic-infra</code>	<code># Enable agent on boot</code>

journalctl -u newrelic-infra -f                      # View New Relic agent logs

## **New Relic API Commands**

```
curl -X GET "https://api.newrelic.com/v2/applications.json" -H  
"X-Api-Key:<API_KEY>" -H "Content-Type: application/json" # List all  
applications
```

```
curl -X GET "https://api.newrelic.com/v2/servers.json" -H  
"X-Api-Key:<API_KEY>" # List monitored servers
```

```
curl -X POST  
"https://api.newrelic.com/v2/applications/<APP_ID>/deployments.json" -H  
"X-Api-Key:<API_KEY>" -H "Content-Type: application/json" -d '{  
"deployment": { "revision": "1.0.1", "description": "New deployment", "user":  
"DevOps Team" } }' # Record a deployment
```

## **New Relic Configuration (/etc/newrelic-infra.yml)**

```
license_key: "<YOUR_LICENSE_KEY>"
```

```
log_file: /var/log/newrelic-infra.log
```

```
custom_attributes:
```

```
  environment: production
```

## **New Relic Log Monitoring Setup**

### **1. Enable Log Forwarding**

**Edit /etc/newrelic-infra.yml:**

```
logs:
```

enabled: true

include:

- /var/log/syslog
- /var/log/nginx/access.log

### **Restart the agent:**

systemctl restart newrelic-infra

## **2. View Logs in New Relic UI**

- Go to **New Relic** → **Logs**
- Filter logs by application, environment, or tags

### **New Relic Monitoring Commands**

newrelic-infra --status                      # Check agent status

newrelic-infra --test                        # Run a diagnostic test

---

## **8. Security & Compliance**

### **1. SonarQube (Code Analysis)**

#### **# 1. Install SonarQube**

# Download SonarQube from the official website:

<https://www.sonarqube.org/downloads/>

#### **# Extract the downloaded file:**

tar -xvzf sonarqube-<version>.zip # For Linux/macOS

unzip sonarqube-<version>.zip      # For Windows

## **# 2. Start SonarQube server**

`./bin/linux-x86-64/sonar.sh start` # For Linux/macOS

`bin\windows-x86-64\StartSonar.bat` # For Windows

## **# 3. Access SonarQube dashboard**

# Open your browser and go to: <http://localhost:9000> (default credentials: admin/admin)

---

## **# 4. Install SonarScanner (if not already installed)**

`curl -sS https://get.sonarsource.com/sonar-scanner.sh | bash` # For Linux/macOS

# For Windows, download and install from:

<https://docs.sonarqube.org/latest/analysis/scan/sonarscanner/>

---

## **# 5. Configure SonarScanner**

# Set the SonarQube server URL in the `sonar-scanner.properties` file

# Example: `sonar.host.url=http://localhost:9000`

---

## **# 6. Run analysis with SonarScanner**

`sonar-scanner -Dsonar.projectKey=<project_key>`

`-Dsonar.sources=<source_directory> -Dsonar.host.url=http://localhost:9000`

---

## **# 7. Maven: Run analysis with SonarQube**

# Add SonarQube plugin to your Maven `pom.xml`

```
<build>

<plugins>

<plugin>

  <groupId>org.sonarsource.scanner.maven</groupId>

  <artifactId>sonar-maven-plugin</artifactId>

  <version>3.9.0.1100</version>

</plugin>

</plugins>

</build>
```

## # Run SonarQube analysis with Maven

```
mvn clean verify sonar:sonar -Dsonar.host.url=http://localhost:9000
```

---

## # 8. Set up SonarQube in Jenkins

# Install SonarQube Scanner Plugin in Jenkins (Manage Jenkins > Manage Plugins > Available > SonarQube Scanner for Jenkins)

# Configure SonarQube in Jenkins (Manage Jenkins > Configure System > SonarQube Servers)

---

## # 9. Jenkins Pipeline for SonarQube analysis

```
pipeline {
    agent any
```

```
environment {  
    SONAR_SCANNER_HOME = tool 'SonarQubeScanner'  
}  
  
stages {  
    stage('Checkout') {  
        steps {  
            git 'https://github.com/your-repo.git'  
        }  
    }  
  
    stage('SonarQube Analysis') {  
        steps {  
            script {  
                withSonarQubeEnv('SonarQubeServer') {  
                    sh 'mvn sonar:sonar'  
                }  
            }  
        }  
    }  
}  
}
```

---



## # 10. GitLab CI/CD Integration for SonarQube

stages:

- code\_analysis

sonarqube\_scan:

stage: code\_analysis

image: maven:3.8.7-openjdk-17

script:

- mvn sonar:sonar -Dsonar.host.url=\$SONAR\_HOST\_URL
- Dsonar.login=\$SONAR\_TOKEN

variables:

SONAR\_HOST\_URL: "http://sonarqube-server:9000"

SONAR\_TOKEN: "your-sonarqube-token"

---

## # 11. GitHub Actions Integration for SonarQube

name: SonarQube Analysis

on:

push:

branches:

- main

jobs:

sonar\_scan:

runs-on: ubuntu-latest

steps:

- name: Checkout Code

uses: actions/checkout@v4

- name: Set up JDK

uses: actions/setup-java@v3

with:

distribution: 'temurin'

java-version: '17'

- name: Run SonarQube Scan

run: mvn sonar:sonar -Dsonar.host.url=\$SONAR\_HOST\_URL  
-Dsonar.login=\$SONAR\_TOKEN

env:

SONAR\_HOST\_URL: "http://sonarqube-server:9000"

SONAR\_TOKEN: \${ secrets.SONAR\_TOKEN }

---

## # 12. ArgoCD Integration (PreSync Hook)

apiVersion: batch/v1

kind: Job

metadata:

name: sonarqube-analysis

annotations:

argocd.argoproj.io/hook: PreSync

spec:

template:

spec:

containers:

- name: sonar-scanner

image: maven:3.8.7-openjdk-17

command: ["mvn", "sonar:sonar"]

env:

- name: SONAR\_HOST\_URL

value: "http://sonarqube-server:9000"

- name: SONAR\_TOKEN

valueFrom:

secretKeyRef:

name: sonar-secret

key: sonar-token

restartPolicy: Never

## 2. Trivy (Container Vulnerability Scanning)

### Basic Commands

#### Scan a Docker image

```
trivy image <image-name>
```

#### Scan a Kubernetes cluster

```
trivy k8s cluster
```

#### Generate a JSON report

```
trivy image --format json -o report.json <image-name>
```

### Jenkins Integration

```
groovy
```

```
pipeline {
```

```
    agent any
```

```
    stages {
```

```
        stage('Checkout') {
```

```
            steps {
```

```
                git 'https://github.com/your-repo.git'
```

```
            }
```

```
        }
```

```
        stage('Trivy Scan') {
```

```
            steps {
```

```
                sh 'trivy image your-docker-image:latest'
```

```
    }  
  }  
}  
}
```

---

## GitLab CI/CD Integration

yaml

stages:

- security\_scan

trivy\_scan:

stage: security\_scan

image: aquasec/trivy

script:

- trivy image your-docker-image:latest --format json -o trivy\_report.json

artifacts:

paths:

- trivy\_report.json

---

## GitHub Actions Integration

yaml

name: Trivy Scan

on:

push:

branches:

- main

jobs:

trivy\_scan:

runs-on: ubuntu-latest

steps:

- name: Checkout Code

uses: actions/checkout@v4

- name: Run Trivy Scan

run: |

docker pull your-docker-image:latest

trivy image your-docker-image:latest --format json --output trivy\_report.json

- name: Upload Trivy Report

uses: actions/upload-artifact@v4

with:

name: trivy-report

path: trivy\_report.json

---

## ArgoCD Integration (PreSync Hook)

yaml

apiVersion: batch/v1

kind: Job

metadata:

name: trivy-scan

annotations:

argocd.argoproj.io/hook: PreSync

spec:

template:

spec:

containers:

- name: trivy-scanner

image: aquasec/trivy

command: ["trivy", "image", "your-docker-image:latest"]

restartPolicy: Never

## Kubernetes Integration (Admission Controller)

yaml

apiVersion: admissionregistration.k8s.io/v1

kind: ValidatingWebhookConfiguration

metadata:

name: trivy-webhook

webhooks:

- name: trivy-scan.k8s

rules:

- apiGroups: [""]

apiVersions: ["v1"]

operations: ["CREATE"]

resources: ["pods"]

clientConfig:

service:

name: trivy-webhook-service

namespace: security

path: /validate

admissionReviewVersions: ["v1"]



sideEffects: None

---

## **OWASP Dependency-Check (Software Dependency Analysis)**

### **Basic Commands**

#### **Run a scan on a project**

```
./dependency-check/bin/dependency-check.sh --scan /path/to/project
```

#### **Run a scan using Maven plugin**

```
mvn org.owasp:dependency-check-maven:check
```

---

### **Jenkins Integration**

```
groovy
```

```
pipeline {
```

```
    agent any
```

```
    stages {
```

```
        stage('Checkout') {
```

```
            steps {
```

```
                git 'https://github.com/your-repo.git'
```

```
            }
```

```
        }
```

```
        stage('OWASP Dependency Check') {
```

```
            steps {
```

```
    sh 'mvn org.owasp:dependency-check-maven:check'
  }
}
}
```

---

## GitLab CI/CD Integration

yaml

stages:

- security\_scan

owasp\_dependency\_check:

stage: security\_scan

image: maven:3.8.7-openjdk-17

script:

- mvn org.owasp:dependency-check-maven:check

artifacts:

paths:

- target/dependency-check-report.html

---

## GitHub Actions Integration

yaml

name: OWASP Dependency Check

on:

push:

branches:

- main

jobs:

owasp\_dependency\_check:

runs-on: ubuntu-latest

steps:

- name: Checkout Code

uses: actions/checkout@v4

- name: Run OWASP Dependency-Check

run: mvn org.owasp:dependency-check-maven:check

- name: Upload OWASP Report

uses: actions/upload-artifact@v4

with:

name: owasp-report

path: target/dependency-check-report.html

---

## ArgoCD Integration (PreSync Hook)

yaml

apiVersion: batch/v1

kind: Job

metadata:

name: owasp-dependency-check

annotations:

argocd.argoproj.io/hook: PreSync

spec:

template:

spec:

containers:

- name: owasp-check

image: maven:3.8.7-openjdk-17

command: ["mvn", "org.owasp:dependency-check-maven:check"]

restartPolicy: Never

## 9. Networking, Ports & Load Balancing

### Networking Basics

- **IP Addressing**
    - Private IPs: 10.0.0.0/8, 172.16.0.0/12, 192.168.0.0/16
    - Public IPs: Assigned by ISPs
    - CIDR Notation: 192.168.1.0/24 (Subnet Mask: 255.255.255.0)
  - **Ports**
    - HTTP: 80
    - HTTPS: 443
    - SSH: 22
    - DNS: 53
    - FTP: 21
    - MySQL: 3306
    - PostgreSQL: 5432
  - **Protocols**
    - TCP (Reliable, connection-based)
    - UDP (Fast, connectionless)
    - ICMP (Used for ping)
    - HTTP(S), FTP, SSH, DNS
- 

## 2. Network Commands

### Linux Networking

#### Show network interfaces

`ip a` # Show IP addresses

`ifconfig` # Older command

#### Check connectivity

`ping google.com`

### **Trace route**

tracert google.com

### **DNS lookup**

nslookup google.com

dig google.com

### **Test ports**

telnet google.com 80

nc -zv google.com 443

### **Firewall Rules (iptables)**

#### **List firewall rules**

sudo iptables -L -v

#### **Allow SSH**

sudo iptables -A INPUT -p tcp --dport 22 -j ACCEPT

#### **Block an IP**

sudo iptables -A INPUT -s 192.168.1.100 -j DROP

### **Netcat (nc)**

#### **Start a simple TCP listener**

nc -lvp 8080

#### **Send data to a listening server**

echo "Hello" | nc 192.168.1.100 8080

---

## **3. Kubernetes Networking**

### **List services and their endpoints**

kubectl get svc -o wide

### **Get pods and their IPs**

kubectl get pods -o wide

### **Port forward a service**

kubectl port-forward svc/my-service 8080:80

### **Expose a pod**

```
kubectl expose pod mypod --type=NodePort --port=80
```

---

## **4. Docker Networking**

### **List networks**

```
docker network ls
```

### **Inspect a network**

```
docker network inspect bridge
```

### **Create a custom network**

```
docker network create mynetwork
```

### **Run a container in a custom network**

```
docker run -d --network=mynetwork nginx
```

---

## **5. Cloud Networking (AWS, Azure, GCP)**

### **AWS**

#### **List VPCs**

```
aws ec2 describe-vpcs
```

#### **List subnets**

```
aws ec2 describe-subnets
```

#### **Open security group port**

```
aws ec2 authorize-security-group-ingress --group-id sg-12345 --protocol tcp --port 22 --cidr 0.0.0.0/0
```

---

### **Azure**

### List VNets

```
az network vnet list -o table
```

### List NSGs

```
az network nsg list -o table
```

### Open a port in NSG

```
az network nsg rule create --resource-group MyGroup --nsg-name MyNSG --name AllowSSH --protocol Tcp --direction Inbound --priority 100 --source-address-prefixes '*' --source-port-ranges '*' --destination-port-ranges 22 --access Allow
```

---

## AWS VPC Basics

- **Definition:** A logically isolated section of the AWS Cloud where you can launch AWS resources in a virtual network.
- **CIDR Block:** Define the IP range (e.g., 10.0.0.0/16).
- **Components:**
  - **Subnets:** Divide your VPC into public (with internet access) and private (without direct internet access) segments.
  - **Route Tables:** Control the traffic routing for subnets.
  - **Internet Gateway (IGW):** Allows communication between instances in your VPC and the internet.
  - **NAT Gateway/Instance:** Enables outbound internet access for instances in private subnets.
  - **VPC Peering:** Connects multiple VPCs.
  - **VPN Connections & Direct Connect:** Securely link your on-premises network with your VPC.
  - **VPC Endpoints:** Privately connect your VPC to supported AWS services.

---

## Security Groups Essentials

- **Definition:** Virtual firewalls that control inbound and outbound traffic for your EC2 instances.



- **Key Characteristics:**
    - **Stateful:** Return traffic is automatically allowed regardless of inbound/outbound rules.
    - **Default Behavior:** All outbound traffic is allowed; inbound is denied until explicitly allowed.
  - **Rule Components:**
    - **Protocol:** (TCP, UDP, ICMP, etc.)
    - **Port Range:** Specific ports or a range (e.g., port 80 for HTTP).
    - **Source/Destination:** IP addresses or CIDR blocks (e.g., 0.0.0.0/0 for all).
  - **Usage:**
    - Assign one or more security groups to an instance.
    - Modify rules anytime without stopping or restarting the instance.
- 

## Common AWS CLI Commands

### VPC Operations

#### Create a VPC:

```
aws ec2 create-vpc --cidr-block 10.0.0.0/16
```

#### Create a Subnet:

```
aws ec2 create-subnet --vpc-id <vpc-id> --cidr-block 10.0.1.0/24
```

#### Create & Attach an Internet Gateway:

```
aws ec2 create-internet-gateway
```

```
aws ec2 attach-internet-gateway --vpc-id <vpc-id> --internet-gateway-id <igw-id>
```

#### Associate a Route Table:

```
aws ec2 associate-route-table --subnet-id <subnet-id> --route-table-id <rtb-id>
```

---

### Security Group Operations

#### Create a Security Group:

```
aws ec2 create-security-group --group-name MySecurityGroup --description "My security group" --vpc-id <vpc-id>
```

### **Authorize Inbound Traffic:**

```
aws ec2 authorize-security-group-ingress --group-id <sg-id> --protocol tcp --port 80 --cidr 0.0.0.0/0
```

### **Authorize Outbound Traffic (if restricting defaults):**

```
aws ec2 authorize-security-group-egress --group-id <sg-id> --protocol tcp --port 443 --cidr 0.0.0.0/0
```

### **List Security Groups:**

```
aws ec2 describe-security-groups
```

---

## **Ports**

### **DevOps Essential Port 🔥**

#### **🔑 Networking & Security**

- **SSH** - 22 (Secure remote access)
  - **FTP** - 21 (File Transfer Protocol)
  - **SFTP** - 22 (Secure File Transfer Protocol)
  - **Telnet** - 23 (Unsecured remote access)
  - **SMTP** - 25, 587 (Email sending)
  - **DNS** - 53 (Domain Name System)
  - **DHCP** - 67/68 (Dynamic IP assignment)
  - **HTTP** - 80 (Default web traffic)
  - **HTTPS** - 443 (Secure web traffic)
  - **SMB** - 445 (Windows file sharing)
  - **LDAP** - 389 (Directory services)
  - **LDAPS** - 636 (Secure LDAP)
  - **RDP** - 3389 (Remote Desktop Protocol)
- 

#### **🔑 CI/CD & DevOps Tools**

- **Jenkins** - 8080 (CI/CD automation server)
- **Git** - 9418 (Git repository access)

- **SonarQube** - 9000 (Code quality analysis)
  - **Nexus Repository** - 8081 (Artifact repository)
  - **Harbor** - 443 (Container registry)
  - **GitLab CI/CD** - 443, 80, 22 (GitLab services & SSH)
  - **Bitbucket** - 7990 (Bitbucket web UI)
  - **TeamCity** - 8111 (CI/CD server)
- 

## ◆ Containerization & Orchestration

- **Docker Registry** - 5000 (Private Docker Registry)
  - **Kubernetes API Server** - 6443 (Cluster API)
  - **Kubelet** - 10250 (Node agent)
  - **ETCD (Kubernetes Storage)** - 2379-2380 (Key-value store)
  - **Flannel (Kubernetes Networking)** - 8285/8286 (Overlay network)
  - **Calico (Kubernetes Networking)** - 179 (BGP Protocol)
  - **Istio Ingress Gateway** - 15021, 15090 (Service mesh ingress)
- 

## ◆ Monitoring & Logging

- **Prometheus** - 9090 (Metrics monitoring)
  - **Grafana** - 3000 (Visualization dashboard)
  - **Elasticsearch** - 9200 (Search & analytics engine)
  - **Logstash** - 5044 (Log ingestion)
  - **Fluentd** - 24224 (Log collector)
  - **Kibana** - 5601 (Log visualization)
  - **Loki** - 3100 (Log aggregation)
  - **Jaeger** - 16686 (Tracing UI)
- 

## ◆ Databases

- **PostgreSQL** - 5432 (Relational database)
- **MySQL/MariaDB** - 3306 (Relational database)

- **MongoDB** - 27017 (NoSQL database)
  - **Redis** - 6379 (In-memory database)
  - **Cassandra** - 9042 (NoSQL distributed database)
  - **CockroachDB** - 26257 (Distributed SQL database)
  - **Neo4j** - 7474 (Graph database UI), 7687 (Bolt protocol)
  - **InfluxDB** - 8086 (Time-series database)
  - **Couchbase** - 8091 (Web UI), 11210 (Data access)
- 

### ◆ Message Brokers & Caching

- **Kafka** - 9092 (Event streaming)
  - **RabbitMQ** - 5672 (Message broker)
  - **ActiveMQ** - 61616 (JMS messaging)
  - **NATS** - 4222 (High-performance messaging)
  - **Memcached** - 11211 (In-memory caching)
- 

### ◆ Web Servers & Reverse Proxies

- **Nginx** - 80, 443 (Web server & reverse proxy)
  - **Apache HTTP** - 80, 443 (Web server)
  - **HAProxy** - 443, 80 (Load balancer)
  - **Caddy** - 2019 (API endpoint)
- 

### ◆ Cloud Services & Storage

- **AWS S3** - 443 (Object storage API)
- **AWS RDS** - 3306, 5432, 1433 (Managed databases)
- **Azure Blob Storage** - 443 (Storage API)
- **Google Cloud Storage** - 443 (Object storage API)
- **MinIO** - 9000 (S3-compatible storage)

# Nginx (Reverse Proxy & Load Balancing)

---

## What is a Reverse Proxy?

A **Reverse Proxy** is a server that forwards client requests to backend servers. It helps:

- ✓ **Improve security** by hiding backend servers.
  - ✓ **Handle traffic** and **reduce load** on backend servers.
  - ✓ **Improve performance** with caching and compression.
- 

## What is Load Balancing?

**Load Balancing** distributes traffic across multiple servers to:

- ✓ **Prevent overloading** of a single server.
  - ✓ **Ensure high availability** (if one server fails, others handle traffic).
  - ✓ **Improve speed** and **performance**.
- 

## 1 Nginx Reverse Proxy & Load Balancing

### ⚙️ Reverse Proxy (Forward Requests to Backend)

✎ When a user visits **example.com**, Nginx forwards the request to the backend server.

### 📄 Configuration File (nginx.conf)

```
server {  
    listen 80; # Listen for requests on port 80  
    server_name example.com; # Your domain name
```

```
location / {  
    proxy_pass http://backend_servers; # Forward requests to backend  
    proxy_set_header Host $host; # Keep the original host  
    proxy_set_header X-Real-IP $remote_addr; # Send real client IP  
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;  
}  
}
```

### ✓ What This Does:

- Nginx **forwards requests** from example.com to **backend servers**.
  - proxy\_pass tells Nginx where to send traffic.
  - **Keeps client IP** and **host name** intact for logs.
- 

### 🔗 Load Balancing (Distribute Traffic Across Multiple Servers)

✈ Instead of sending all traffic to **one server**, Nginx distributes it across **multiple servers**.

### 📁 Configuration File (nginx.conf)

nginx

```
upstream backend_servers {  
    server server1.example.com; # Backend Server 1  
    server server2.example.com; # Backend Server 2  
}
```

```
server {  
    listen 80;  
    server_name example.com;
```

```
    location / {
```

```
    proxy_pass http://backend_servers; # Send traffic to multiple backend servers
}
}
```

### ✓ What This Does:

- upstream defines **multiple backend servers**.
  - **Traffic is balanced** between server1 and server2.
  - Default method: **Round-robin** (each request goes to the next server).
- 

## 2 Apache (reverse proxy, load balancing)

### ⚙ Enable Required Modules

✦ Before using Apache as a Reverse Proxy, enable these modules:

```
a2enmod proxy
a2enmod proxy_http
a2enmod proxy_balancer
a2enmod lbmethod_byrequests
systemctl restart apache2 # Restart Apache for changes
```

### ✓ What This Does:

- These modules allow **Apache to forward requests** and **balance traffic**.
- 

### ⚙ Reverse Proxy (Forward Requests to Backend Servers)

🔧 Configuration File (apache.conf)

```
<VirtualHost *:80>
    ServerName example.com # Domain handled by Apache

    ProxyPass "/" "http://backend_servers/"
    ProxyPassReverse "/" "http://backend_servers/"
</VirtualHost>
```

### ✓ What This Does:

- Apache listens on **example.com** and forwards requests to **backend servers**.
  - ProxyPassReverse ensures **responses return correctly** to the client.
- 

## ⚡ Load Balancing (Send Traffic to Multiple Backend Servers)

### 📁 Configuration File (apache.conf)

```
<Proxy "balancer://mycluster">
    BalancerMember "http://server1.example.com"
    BalancerMember "http://server2.example.com"
</Proxy>
```

```
<VirtualHost *:80>
    ServerName example.com

    ProxyPass "/" "balancer://mycluster/"
    ProxyPassReverse "/" "balancer://mycluster/"
</VirtualHost>
```

### ✓ What This Does:

- BalancerMember defines **multiple backend servers**.
- Apache **automatically distributes** traffic using **round-robin**.



### 3 HAProxy (Load Balancing)

✦ HAProxy is a **lightweight and high-performance** Load Balancer for web applications.

#### ◆ Install HAProxy

apt install haproxy # Ubuntu/Debian

yum install haproxy # RHEL/CentOS

---

#### ◆ Load Balancing with HAProxy

#### 🔧 Configuration File (haproxy.cfg)

```
frontend http_front
```

```
    bind *:80 # Accept traffic on port 80
```

```
    default_backend backend_servers # Forward traffic to backend servers
```

```
backend backend_servers
```

```
    balance roundrobin # Distribute traffic evenly
```

```
    server server1 server1.example.com:80 check # First server
```

```
    server server2 server2.example.com:80 check # Second server
```

#### ✓ What This Does:

- frontend handles **incoming requests**.
  - backend defines multiple **backend servers**.
  - **Round-robin** ensures traffic is **evenly distributed**.
  - check makes sure **only healthy servers** receive traffic.
- 

#### ◆ Restart HAProxy

```
systemctl restart haproxy  
systemctl enable haproxy # Enable on startup
```

---

## 4 Kubernetes Ingress Controller

### ◆ Install Nginx Ingress Controller

```
kubectl apply -f  
https://raw.githubusercontent.com/kubernetes/ingress-nginx/main/deploy/static/provider/cloud/deploy.yaml
```

### ✓ What This Does:

- Installs **Nginx Ingress Controller** for managing external traffic in Kubernetes.
- 

### ◆ Define an Ingress Resource

#### 📄 Configuration File (ingress.yaml)

```
apiVersion: networking.k8s.io/v1  
kind: Ingress  
metadata:  
  name: my-ingress  
  annotations:  
    nginx.ingress.kubernetes.io/rewrite-target: / # Optional URL rewrite  
spec:  
  rules:  
    - host: example.com # Define the domain  
      http:  
        paths:  
          - path: /  
            pathType: Prefix
```

```
backend:  
  service:  
    name: my-service # Forward traffic to this Kubernetes service  
  port:  
    number: 80
```

### ✓ What This Does:

- Routes traffic from **example.com** to **my-service** inside Kubernetes.
  - **Annotations modify behavior** (like URL rewriting).
- 

### ⚡ Verify Ingress is Working

```
kubectl get ingress  
kubectl describe ingress my-ingress
```

### ✓ What This Does:

- `kubectl get ingress` → Checks if Ingress exists.
  - `kubectl describe ingress` → Shows detailed configuration.
- 

### ⚡ Which One Should You Use?

- ✓ For a simple website/API → Use **Nginx Reverse Proxy**.
  - ✓ For balancing multiple servers → Use **Nginx, Apache, or HAProxy**.
  - ✓ For Kubernetes applications → Use **Ingress Controller**.
- 

**Practical Examples: Docker for Nginx, Apache, HAProxy, and Kubernetes Ingress**

Step-by-step practical examples using Docker for Nginx, Apache, HAProxy, and Kubernetes Ingress.

## **1. Nginx Reverse Proxy & Load Balancer (With Docker)**

**Scenario:** We have two backend servers running a Python Flask application, and we want Nginx to act as a Reverse Proxy and Load Balancer.

### **Step 1 Create Two Backend Servers (Flask)**

**Create a directory for the project**

```
mkdir nginx-loadbalancer && cd nginx-loadbalancer
```

#### **server1.py (Backend Server 1)**

```
from flask import Flask
```

```
app = Flask(__name__)
```

```
@app.route('/')
```

```
def home():
```

```
    return "Hello from Server 1"
```

```
if __name__ == '__main__':
```

```
    app.run(host='0.0.0.0', port=5000)
```

#### **server2.py (Backend Server 2)**

```
from flask import Flask
```

```
app = Flask(__name__)
```

```
@app.route('/')  
  
def home():  
  
    return "Hello from Server 2"  
  
if __name__ == '__main__':  
  
    app.run(host='0.0.0.0', port=5000)
```

## **Step 2 Create a Dockerfile for Backend Servers**

### **Dockerfile**

```
FROM python:3.9  
  
WORKDIR /app  
  
COPY server1.py /app/  
  
RUN pip install flask  
  
CMD ["python", "server1.py"]
```

**For server2.py, create another Dockerfile and replace server1.py with server2.py**

## **Step 3 Create an Nginx Configuration File**

### **nginx.conf**

```
nginx  
  
events { }
```

```
http {  
    upstream backend_servers {  
        server server1:5000;  
        server server2:5000;  
    }  
    server {  
        listen 80;  
        server_name localhost;  
  
        location / {  
            proxy_pass http://backend_servers;  
            proxy_set_header Host $host;  
            proxy_set_header X-Real-IP $remote_addr;  
            proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;  
        }  
    }  
}
```

#### **Step 4 Create a Docker Compose File**

docker-compose.yml

version: '3'

services:

server1:

build: .

container\_name: server1

ports:

- "5001:5000"

**server2:**

build: .

container\_name: server2

ports:

- "5002:5000"

**nginx:**

image: nginx:latest

container\_name: nginx\_proxy

ports:

- "80:80"

volumes:

- ./nginx.conf:/etc/nginx/nginx.conf

depends\_on:

- server1

- server2

## **Step 5 Run the Containers**

```
docker-compose up --build
```

## **Step 6 Test Load Balancing** **Run the following command**

```
curl http://localhost
```

### **Expected Output (requests will alternate)**

Hello from Server 1

Hello from Server 2

Hello from Server 1

Hello from Server 2

## **2 Apache Reverse Proxy & Load Balancer (With Docker)**

### **Step 1 Create Apache Configuration File** **apache.conf**

```
<VirtualHost *:80>
```

```
    ServerName localhost
```

```
<Proxy "balancer://mycluster">
```

```
    BalancerMember "http://server1:5000"
```



BalancerMember "http://server2:5000"

</Proxy>

ProxyPass "/" "balancer://mycluster/"

ProxyPassReverse "/" "balancer://mycluster/"

</VirtualHost>

## Step 2 Create docker-compose.yml for Apache

version: '3'

services:

### **server1:**

build: .

container\_name: server1

ports:

- "5001:5000"

### **server2:**

build: .

container\_name: server2

ports:

- "5002:5000"

**apache:**

image: httpd:latest

container\_name: apache\_proxy

ports:

- "80:80"

volumes:

- ./apache.conf:/usr/local/apache2/conf/httpd.conf

depends\_on:

- server1

- server2

### **Step 3 Run Apache Proxy**

docker-compose up --build

## **3 HAProxy Load Balancer (With Docker)**

### **Step 1 Create HAProxy Configuration File**

#### **haproxy.cfg**

frontend http\_front

bind \*:80

default\_backend backend\_servers

```
backend backend_servers
```

```
    balance roundrobin
```

```
    server server1 server1:5000 check
```

```
    server server2 server2:5000 check
```

## Step 2 Create docker-compose.yml for HAProxy

```
version: '3'
```

```
services:
```

```
  server1:
```

```
    build: .
```

```
    container_name: server1
```

```
    ports:
```

```
      - "5001:5000"
```

```
  server2:
```

```
    build: .
```

```
    container_name: server2
```

```
    ports:
```

```
      - "5002:5000"
```

```
  haproxy:
```

image: haproxy:latest

container\_name: haproxy\_loadbalancer

ports:

- "80:80"

volumes:

- ./haproxy.cfg:/usr/local/etc/haproxy/haproxy.cfg

depends\_on:

- server1

- server2

### **Step 3 Run HAProxy**

docker-compose up --build

---

## **4. Kubernetes Ingress Controller**

### **Step 1 Deploy Nginx Ingress Controller**

kubectl apply -f

<https://raw.githubusercontent.com/kubernetes/ingress-nginx/main/deploy/static/provider/cloud/deploy>.

### **Step 2 Create Ingress Resource**

ingress.

apiVersion: networking.k8s.io/v1

kind: Ingress

metadata:

name: my-ingress

spec:

rules:

- host: example.com

http:

paths:

- path: /

pathType: Prefix

backend:

service:

name: my-service

port:

number: 80

### Step 3 Apply Ingress

kubectl apply -f ingress.

---

### Comparison Table

**Nginx:** Reverse Proxy (forwards requests to backend servers), Load Balancing (distributes traffic across servers)

**Apache:** Reverse Proxy (similar to Nginx), Load Balancing (balances traffic using a balancer)

**HAProxy:** Load Balancing (efficient traffic handling)

**Kubernetes Ingress:** Traffic Routing (manages external traffic in Kubernetes)

---

## 10. Database Cheat Sheet

Databases are essential for CI/CD pipelines, monitoring, logging, and cloud automation. DevOps engineers interact with databases to store configurations, manage infrastructure state, and automate deployments. This guide covers SQL, NoSQL, and cloud databases with relevant DevOps commands and use cases.

---

## Database Automation for DevOps

### Why Automate Databases in DevOps?

- ✓ Eliminate manual work in database provisioning, backup, and monitoring
  - ✓ Ensure consistency across environments (dev, staging, production)
  - ✓ Reduce downtime with automated backups and performance monitoring
  - ✓ Enable CI/CD pipelines to manage database migrations
- 

### 1. SQL Databases (MySQL, PostgreSQL, MariaDB)

### 1. SQL Databases (MySQL, PostgreSQL, MariaDB)

#### Database Management

SHOW DATABASES; → List databases

CREATE DATABASE db\_name; → Create a database

DROP DATABASE db\_name; → Delete a database

USE db\_name; → Select a database

### **User Management**

CREATE USER 'devops'@'localhost' IDENTIFIED BY 'password';

GRANT ALL PRIVILEGES ON db\_name.\* TO 'devops'@'localhost';

### **Table & Data Operations**

SHOW TABLES; → List tables

INSERT INTO users (name, email) VALUES ('Alice', 'alice@example.com');

SELECT \* FROM users;

### **Backup & Restore**

mysqldump -u root -p db\_name > backup.sql

mysql -u root -p db\_name < backup.sql

## **2. NoSQL Databases**

### **MongoDB**

show dbs; → List databases

use mydb; → Select a database

db.createCollection("users"); → Create a collection

db.users.insertOne({ name: "Alice" }); → Insert data

mongodump --out /backup/ → Backup

### **Redis**

SET key "value"; → Store a key

GET key; → Retrieve value

DEL key; → Delete key

### **Cassandra (CQL)**

CREATE KEYSPACE mykeyspace WITH replication = {'class': 'SimpleStrategy',  
'replication\_factor': 1};

CREATE TABLE users (id UUID PRIMARY KEY, name TEXT);

### **3. Database Automation**

#### **Terraform for AWS RDS**

```
resource "aws_db_instance" "default" {  
  
    identifier = "devops-db"  
  
    engine = "mysql"  
  
    instance_class = "db.t3.micro"  
  
    allocated_storage = 20  
  
}
```

#### **Docker Database Containers**

```
docker run -d --name mysql -e MYSQL_ROOT_PASSWORD=root -p 3306:3306  
mysql
```

```
docker run -d --name postgres -e POSTGRES_PASSWORD=root -p 5432:5432  
postgres
```

#### **Automating MySQL with Ansible**

yaml

- name: Install MySQL

hosts: db\_servers

become: yes

tasks:

- name: Install MySQL



```
apt: name=mysql-server state=present
```

```
- name: Create Database
```

```
mysql_db: name=devops_db state=present
```

## **Jenkins Pipeline for Database Backup**

```
groovy
```

```
pipeline {
```

```
    agent any
```

```
    stages {
```

```
        stage('Backup') {
```

```
            steps { sh 'mysqldump -u root -p$MYSQL_ROOT_PASSWORD db >
/backup/db.sql' }
```

```
        }
```

```
        stage('Restore') {
```

```
            steps { sh 'mysql -u root -p$MYSQL_ROOT_PASSWORD db <
/backup/db.sql' }
```

```
        }
```

```
    }
```

```
}
```

## **Database Monitoring (MySQL + Prometheus & Grafana)**

```
wget
https://github.com/prometheus/mysqld_exporter/releases/download/v0.14.0/mysqld_exporter.tar.gz

tar xvf mysqld_exporter.tar.gz && mv mysqld_exporter /usr/local/bin/

mysqld_exporter --config.my-cnf=/etc/.my.cnf &
```

#### 4. Deploying MongoDB with Docker Compose

```
yaml

version: '3.8'

services:

  mongo:

    image: mongo

    container_name: mongodb

    environment:

      MONGO_INITDB_ROOT_USERNAME: admin

      MONGO_INITDB_ROOT_PASSWORD: DevOps@123

    ports:

      - "27017:27017"
```

---

## 11. Storage Cheat Sheet

## 1. Storage Types in DevOps

✓ **Block Storage** – Used for databases, VMs, containers (e.g., EBS, Cinder)

✓ **File Storage** – Used for shared access & persistence (e.g., NFS, EFS)

✓ **Object Storage** – Used for backups, logs, and media (e.g., S3, MinIO)

---

### # Disk Management (Linux)

lsblk # List disks and partitions

fdisk -l # List disk partitions

df -h # Show disk usage

du -sh /path/to/directory # Check disk space usage

mount /dev/sdb1 /mnt # Mount a disk

umount /mnt # Unmount a disk

mkfs.ext4 /dev/sdb1 # Format a disk

df -Th # Check filesystem usage

smartctl -a /dev/sdb # Check disk health

### # AWS S3

aws s3 ls # List all S3 buckets

aws s3 cp file.txt s3://mybucket/ # Upload a file to S3

aws s3 cp s3://mybucket/file.txt . # Download a file from S3

aws s3 sync /local/path s3://mybucket/ # Sync local directory to S3

## **# Azure Blob Storage**

az storage account list # List all storage accounts

az storage blob upload --container-name mycontainer --file file.txt --name file.txt

## **# Upload a file to Azure Blob**

az storage blob download --container-name mycontainer --name file.txt --file file.txt # Download a file from Azure Blob

## **# Google Cloud Storage (GCS)**

gsutil ls # List GCS buckets

gsutil cp file.txt gs://mybucket/ # Upload a file to GCS

gsutil cp gs://mybucket/file.txt . # Download a file from GCS

## **# Linux Storage Monitoring**

iotop # Monitor disk usage in real-time

iostat -x 1 # Check disk performance

## **# Linux Backup**

rsync -av --delete /source/ /backup/ # Backup using rsync

## **# AWS Backup**

aws s3 sync /data s3://backup-bucket/ # Backup data to AWS S3

## # Azure Backup

```
az storage blob upload-batch --destination mycontainer --source /data # Backup  
data to Azure Blob
```

---

## YAML Configurations:

### Persistent Volume (PV)

yaml

apiVersion: v1

kind: PersistentVolume

metadata:

name: my-pv

spec:

capacity:

storage: 10Gi

accessModes:

- ReadWriteOnce

persistentVolumeReclaimPolicy: Retain

hostPath:

path: "/mnt/data"

## **Persistent Volume Claim (PVC)**

yaml

apiVersion: v1

kind: PersistentVolumeClaim

metadata:

name: my-pvc

spec:

accessModes:

- ReadWriteOnce

resources:

requests:

storage: 5Gi

## **Pod with Persistent Volume**

yaml

apiVersion: v1

kind: Pod

metadata:

name: storage-pod

spec:

containers:

```
- name: app

image: nginx

volumeMounts:

  - mountPath: "/usr/share/nginx/html"

    name: storage-volume

volumes:

  - name: storage-volume

    persistentVolumeClaim:

      claimName: my-pvc
```

### **Terraform Configurations:**

AWS S3 Bucket

```
provider "aws" {

region = "us-east-1"

}

resource "aws_s3_bucket" "devops_bucket" {

  bucket = "devops-backup-bucket"

  acl    = "private"

}

output "bucket_name" {

  value = aws_s3_bucket.devops_bucket.id
```

```
}
```

Azure Storage Account

```
provider "azurerm" {  
  
  features {}  
  
}  
  
resource "azurerm_storage_account" "example" {  
  
  name                = "devopsstorageacc"  
  
  resource_group_name = "devops-rg"  
  
  location            = "East US"  
  
  account_tier        = "Standard"  
  
  account_replication_type = "LRS"  
  
}
```

---

## 12. Helm Chart

### 1. What is Helm?

- **Helm** helps deploy applications in Kubernetes using pre-configured templates called **Helm Charts**.
- A **Chart** is a collection of files that describe a Kubernetes application.

---

### # Helm Basics

helm version      # Check which version of Helm is installed



helm help           # Get help with Helm commands

helm repo list       # Show all added Helm repositories

### **# Adding and Updating Repositories**

helm repo add <repo-name> <repo-url> # Add a repository

helm repo update     # Get the latest list of available charts

helm search repo <chart-name> # Search for a chart

### **# Installing Applications using Helm**

helm install <release-name> <chart> # Install an application

kubectl get pods     # See running applications in Kubernetes

### **# Listing Installed Applications**

helm list            # Show all installed applications

### **# Checking Application Details**

helm status <release-name>   # Check the status of your installed application

helm get values <release-name> # See configuration values used

### **# Updating an Installed Application**

helm upgrade <release-name> <chart> --set <parameter> # Update an installed application

### **# Uninstalling an Application**

helm uninstall <release-name> # Remove an application

### **# Debugging Helm Charts**

helm lint <chart>     # Check for issues in a Helm chart

helm install --debug --dry-run <release-name> <chart> # Simulate installation

## **# Creating Your Own Helm Chart**

helm create <chart-name> # Create a new Helm chart