PIZZA SALES SQL QUERIES

A. KPI's

1. Total Revenue:

```
SELECT SUM(total_price) AS Total_Revenue FROM pizza_sales;
```

	total_revenue numeric
1	817860.05

2. Average Order Value

```
SELECT CAST(CAST(SUM(total_price) AS DECIMAL(10,2)) /
CAST(COUNT(DISTINCT order_id) AS DECIMAL(10,2))
AS DECIMAL(10,2)) AS Avg_Pizzas_per_order FROM pizza_sales;
```

	avg_order_value numeric (10,2)
1	38.31

3. Total Pizzas Sold

```
SELECT SUM(quantity) AS Total_pizza_sold FROM pizza_sales;
```

	total_pizza_sold bigint
1	49574

4. Total Orders

```
SELECT COUNT(DISTINCT order_id) AS Total_Orders FROM pizza_sales;
```

	total_orders bigint
1	21350

5. Average Pizzas Per Order

```
SELECT CAST(CAST(SUM(quantity) AS DECIMAL(10,2)) /
CAST(COUNT(DISTINCT order_id) AS DECIMAL(10,2)) AS DECIMAL(10,2))
AS Avg_Pizzas_per_order FROM pizza_sales;
```

	avg_pizzas_per_order numeric (10,2)
1	2.32

B. Visuals

1. Daily Trend for Total Orders

```
SELECT TO_CHAR( Order_date, 'DAY') AS order_day, COUNT(DISTINCT order_id) AS
total_orders FROM pizza_sales GROUP BY TO_CHAR( Order_date, 'DAY');
```

Output:

	order_day text	total_orders bigint
1	FRIDAY	3538
2	MONDAY	2794
3	SATURDAY	3158
4	SUNDAY	2624
5	THURSDAY	3239
6	TUESDAY	2973
7	WEDNESD...	3024

2. Monthly Trend for Orders

```
SELECT TO_CHAR( Order_date, 'MONTH') AS order_day,
COUNT(DISTINCT order_id) AS total_orders
FROM pizza_sales GROUP BY TO_CHAR( Order_date, 'MONTH');
```

Output

	order_day text	total_orders bigint
1	APRIL	1799
2	AUGUST	1841
3	DECEMBER	1680
4	FEBRUARY	1685
5	JANUARY	1845
6	JULY	1935
7	JUNE	1773
8	MARCH	1840
9	MAY	1853
10	NOVEMBER	1792
11	OCTOBER	1646
12	SEPTEMB...	1661

3. % of Sales by Pizza Category

```
SELECT pizza_category,
CAST(SUM(total_price) AS DECIMAL(10,2)) as total_revenue,
CAST(SUM(total_price) * 100 / (SELECT SUM(total_price) from pizza_sales) AS
DECIMAL(10,2)) AS PCT FROM pizza_sales GROUP BY pizza_category;
```

Output

	pizza_category character varying (50)	total_revenue numeric (10,2)	pct numeric (10,2)
1	Supreme	208197.00	25.46
2	Chicken	195919.50	23.96
3	Veggie	193690.45	23.68
4	Classic	220053.10	26.91

4. % of Sales by Pizza Size

```
SELECT pizza_size,
CAST(SUM(total_price) AS DECIMAL(10,2)) as total_revenue,
CAST(SUM(total_price) * 100 / (SELECT SUM(total_price) from pizza_sales) AS
DECIMAL(10,2)) AS PCT FROM pizza_sales
GROUP BY pizza_size ORDER BY pizza_size;
```

Output

	pizza_size character varying (10)	total_revenue numeric (10,2)	pct numeric (10,2)
1	L	375318.70	45.89
2	M	249382.25	30.49
3	S	178076.50	21.77
4	XL	14076.00	1.72
5	XXL	1006.60	0.12

5. Total Pizzas Sold by Pizza Category

```
SELECT pizza_category, SUM(quantity) as Total_Quantity_Sold
FROM pizza_sales WHERE EXTRACT(MONTH FROM order_date) = 1
GROUP BY pizza_category ORDER BY Total_Quantity_Sold DESC;
```

Output

	pizza_category character varying (50)	total_quantity_sold bigint
1	Classic	14888
2	Supreme	11987
3	Veggie	11649
4	Chicken	11050

6. Top 5 Pizzas by Revenue

```
SELECT pizza_name, SUM(total_price) AS Total_Revenue
FROM pizza_sales GROUP BY pizza_name
ORDER BY Total_Revenue DESC LIMIT 5;
```

	pizza_name text	total_revenue numeric
1	The Thai Chicken Pizza	43434.25
2	The Barbecue Chicken Piz...	42768.00
3	The California Chicken Piz...	41409.50
4	The Classic Deluxe Pizza	38180.50
5	The Spicy Italian Pizza	34831.25

7. Bottom 5 Pizzas by Revenue

```
SELECT pizza_name, SUM(total_price) AS Total_Revenue
FROM pizza_sales GROUP BY pizza_name
ORDER BY Total_Revenue ASC LIMIT 5;
```

	pizza_name text	total_revenue numeric
1	The Brie Carre Pizza	11588.50
2	The Green Garden Pizza	13955.75
3	The Spinach Supreme Piz...	15277.75
4	The Mediterranean Pizza	15360.50
5	The Spinach Pesto Pizza	15596.00

8. Top 5 Pizzas by Quantity

```
SELECT pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales GROUP BY pizza_name
ORDER BY Total_Pizza_Sold DESC LIMIT 5;
```

Output

	pizza_name text	total_pizza_sold bigint
1	The Classic Deluxe Pizza	2453
2	The Barbecue Chicken Piz...	2432
3	The Hawaiian Pizza	2422
4	The Pepperoni Pizza	2418
5	The Thai Chicken Pizza	2371

9. Bottom 5 Pizzas by Quantity

```
SELECT pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales GROUP BY pizza_name
ORDER BY Total_Pizza_Sold ASC LIMIT 5;
```

Output

	pizza_name text	total_pizza_sold bigint
1	The Brie Carre Pizza	490
2	The Mediterranean Pizza	934
3	The Calabrese Pizza	937
4	The Spinach Supreme Piz...	950
5	The Soppressata Pizza	961

10. Top 5 Pizzas by Total Orders

```
SELECT pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales GROUP BY pizza_name
ORDER BY Total_Orders DESC LIMIT 5;
```

Output

	pizza_name text	total_orders bigint
1	The Classic Deluxe Pizza	2329
2	The Hawaiian Pizza	2280
3	The Pepperoni Pizza	2278
4	The Barbecue Chicken Piz...	2273
5	The Thai Chicken Pizza	2225

11. Bottom 5 Pizzas by Total Orders

```
SELECT pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales GROUP BY pizza_name
ORDER BY Total_Orders ASC Limit 5;
```

	pizza_name text	total_orders bigint
1	The Brie Carre Pizza	480
2	The Mediterranean Pizza	912
3	The Calabrese Pizza	918
4	The Spinach Supreme Piz...	918
5	The Chicken Pesto Pizza	938

NOTE

If you want to apply the pizza_category or pizza_size filters to the above queries you can use WHERE clause. Follow some of below examples

```
SELECT pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales WHERE pizza_category = 'Classic'
GROUP BY pizza_name ORDER BY Total_Orders ASC LIMIT 5;
```
