

UUU (Universal Update Utility)

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME
c20dc76	Wed May 27 12:33:30 2020 -0500	Updated FAQ (asciidoc)	nxpfrankli
a391fbf	Thu Jul 16 08:34:14 2020 -0500	Updated Home (asciidoc)	nxpfrankli
2579055	Wed Sep 16 11:47:32 2020 -0500	Updated UUU default support protocol list (asciidoc)	nxpfrankli
5bda312	Tue Oct 27 09:18:34 2020 -0500	Updated Release Notes (asciidoc)	nxpfrankli
124d5a5	Fri Jan 15 10:41:40 2021 -0600	Updated Release Notes (asciidoc)	nxpfrankli
6f1d4c7	Thu Mar 11 11:38:19 2021 -0600	Updated Example (asciidoc)	nxpfrankli
9c919f2	Thu Mar 11 11:41:19 2021 -0600	Updated Example (asciidoc)	nxpfrankli
52359bb	Thu May 27 10:14:14 2021 -0500	Updated Release Notes (asciidoc)	nxpfrankli
0ed9304	Thu Jun 3 08:38:30 2021 -0500	Updated Release Notes (asciidoc)	nxpfrankli
b8ecd46	Fri Sep 24 11:27:13 2021 -0500	Updated Home (asciidoc)	nxpfrankli
3917b99	Fri Sep 24 11:27:44 2021 -0500	Updated Home (asciidoc)	nxpfrankli
5a35dd1	Fri Oct 22 13:43:28 2021 -0500	Updated Release Notes (asciidoc)	nxpfrankli
5fddf1f	Tue Feb 1 13:07:55 2022 -0600	Updated Example (asciidoc)	nxpfrankli
1a66a0c	Thu Feb 10 16:13:03 2022 -0600	Updated UUU default support protocol list (asciidoc)	allenxh
df6ea0b	Tue Mar 29 13:32:14 2022 -0500	Updated Release Notes (asciidoc)	nxpfrankli
698fdd0	Thu Jun 9 14:14:15 2022 -0500	Updated UUU default support protocol list (asciidoc)	nxpfrankli
d42cb9c	Thu Jun 9 14:18:35 2022 -0500	Updated UUU default support protocol list (asciidoc)	nxpfrankli

NUMBER	DATE	DESCRIPTION	NAME
c20dc76	Wed May 27 12:33:30 2020 -0500	Updated FAQ (asciidoc)	nxpfrankli
a391fbf	Thu Jul 16 08:34:14 2020 -0500	Updated Home (asciidoc)	nxpfrankli
2579055	Wed Sep 16 11:47:32 2020 -0500	Updated UUU default support protocol list (asciidoc)	nxpfrankli
5bda312	Tue Oct 27 09:18:34 2020 -0500	Updated Release Notes (asciidoc)	nxpfrankli
124d5a5	Fri Jan 15 10:41:40 2021 -0600	Updated Release Notes (asciidoc)	nxpfrankli
6f1d4c7	Thu Mar 11 11:38:19 2021 -0600	Updated Example (asciidoc)	nxpfrankli
9c919f2	Thu Mar 11 11:41:19 2021 -0600	Updated Example (asciidoc)	nxpfrankli
52359bb	Thu May 27 10:14:14 2021 -0500	Updated Release Notes (asciidoc)	nxpfrankli
0ed9304	Thu Jun 3 08:38:30 2021 -0500	Updated Release Notes (asciidoc)	nxpfrankli
b8ecd46	Fri Sep 24 11:27:13 2021 -0500	Updated Home (asciidoc)	nxpfrankli
3917b99	Fri Sep 24 11:27:44 2021 -0500	Updated Home (asciidoc)	nxpfrankli
5a35dd1	Fri Oct 22 13:43:28 2021 -0500	Updated Release Notes (asciidoc)	nxpfrankli
5fddf1f	Tue Feb 1 13:07:55 2022 -0600	Updated Example (asciidoc)	nxpfrankli
1a66a0c	Thu Feb 10 16:13:03 2022 -0600	Updated UUU default support protocol list (asciidoc)	allenxh
df6ea0b	Tue Mar 29 13:32:14 2022 -0500	Updated Release Notes (asciidoc)	nxpfrankli
698fdd0	Thu Jun 9 14:14:15 2022 -0500	Updated UUU default support protocol list (asciidoc)	nxpfrankli
d42cb9c	Thu Jun 9 14:18:35 2022 -0500	Updated UUU default support protocol list (asciidoc)	nxpfrankli

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME
6bfb126	Fri Jun 10 11:40:11 2022 -0500	Updated UUU default support protocol list (asciidoc)	ChrisWu86459
22268e9	Fri Jun 10 11:54:49 2022 -0500	Updated UUU default support protocol list (asciidoc)	ChrisWu86459
86c4f28	Tue Jun 21 10:24:46 2022 -0500	Updated UUU default support protocol list (asciidoc)	nxpfrankli
38065c0	Mon Jul 11 14:55:29 2022 -0500	Updated UUU default support protocol list (asciidoc)	nxpfrankli
a890d5a	Mon Jul 11 14:56:00 2022 -0500	Updated UUU default support protocol list (asciidoc)	nxpfrankli
1be5ece	Thu Sep 15 10:07:15 2022 -0500	Updated Release Notes (asciidoc)	nxpfrankli
40133f4	Thu Sep 15 10:07:30 2022 -0500	Updated Release Notes (asciidoc)	nxpfrankli
f9162c6	Mon Mar 6 10:10:21 2023 -0600	Updated Release Notes (asciidoc)	nxpfrankli

Contents

1	Introduction	1
1.1	Running environment	1
1.2	Typical Usage	1
1.3	Typical Script	2
1.4	License	2
1.5	What Firmware Need	3
1.6	Setup auto parameter complete	3
1.6.1	windows	3
1.6.2	linux	3
1.7	L4.9.123_2.3.0_8MM GA	3
2	Syntactic	3
3	Usage Example	5
3.1	Basic	5
3.1.1	Download boot loader for imx6\imx7	5
3.1.2	Download boot loader for imx8qxp	5
3.1.3	Download SPL and uboot, such as imx8mq	5
3.1.4	Burn Android Image to eMMC	5
3.1.5	Burn yocto Image to eMMC	5
3.2	Built-in script	5
3.3	multi boards support	6
3.3.1	For the same boards	6
3.3.2	For the difference boards	6
3.4	Talk with fastboot	6
3.4.1	boot linux kernel	6
3.4.2	write image to emmc	6
3.5	Talk with linux kernel, transfer file between board and pc	6
4	Sample scripts	6
5	Supported protocol	6
5.1	SDP: i.MX6/7 ROM download protocol	7
5.1.1	Supported command:	7
5.2	HABv4 closed chip support	8
5.3	SDPU\SDPV: uboot implement simplified ROM SDP protocol	9
5.4	SDPS: i.MX8QXP and i.MX8QM ROM download protocol	9
5.5	FB: Android fastboot protocol	9
5.5.1	Support command:	9
5.6	FBK: Android fastboot protocol, implement at initramfs. See project imx-uuc	10
5.6.1	Support command:	10
5.7	Common command for all protocol	10

6 Migration from mfgtool ucl2.xml	11
7 Win 7 User Guide	13
7.1 Back Ground	13
7.2 Install updated winusb inf file	13
7.3 Use zadig to install winusb driver	14
8 FAQ	15
9 Build Steps	18
9.1 windows	18
9.2 linux	19
10 Uboot config requirement	19
11 kernel config requirement	20
12 Release Notes	20
12.1 1.5.21	20
12.1.1 New features	20
12.1.2 Bug fixes	21
12.2 1.4.243	21
12.2.1 New features	21
12.2.2 Bug fixes	21
12.3 1.4.193	21
12.3.1 New features	21
12.3.2 Bug fixes	21
12.4 1.4.165	21
12.4.1 New features	21
12.4.2 Bug fixes	22
12.5 1.4.139	22
12.5.1 New features	22
12.5.2 Bug fixes	22
12.6 1.4.72	22
12.6.1 New features	22
12.6.2 Bug fixes	22
12.7 1.4.43	22
12.7.1 New features	22
12.7.2 Bug fixes	23
12.8 1.3.191	23
12.8.1 New features	23

12.8.2 Bug fixes	23
12.9 1.3.154	23
12.9.1 New features	23
12.9.2 Bug fixes	23
12.10 1.3.134	23
12.10.1 Bug fixes	23
12.11 1.3.130	23
12.11.1 New features	23
12.11.2 Bug fixes	24
12.12 1.3.102	24
12.12.1 New features	24
12.12.2 Bug fixes	24
12.13 1.3.82	24
12.13.1 New features	24
12.13.2 Bug fixes	25
12.14 1.2.135	25
12.14.1 New features	25
12.14.2 Bug fixes	25
12.15 1.2.91	25
12.15.1 New features	25
12.15.2 Bug fixes	26
12.16 1.2.0	26
12.16.1 New features	26
12.16.2 Bug fixes	26
12.17 1.1.81	26
12.17.1 New features	26
12.17.2 Bug fixes	26
12.18 1.1.41	27
12.18.1 New features	27
12.18.2 Bug fixes	27

13 Known issue

27

1 Introduction

Welcome to the UUU (Universal Update Utility). This is an evolution of MFGTools (aka MFGTools v3).

UUU is Freescale/NXP I.MX Chip image deploy tools.

With the time, the need for an update utility portable to Linux and Windows increased. UUU have the same usage on both Windows and Linux. It means the same script works on both OS.

UUU is **command line tools**. look like

```
uuu (universal update utility) for nxp imx chips -- libuuu-1.0.1-gffd9837

Succues:0           Failure:3           Wait for Known USB Device Appear...

1:11      5/5 [           ] SDP: jump -f u-boot-dtb.imx - <-
    iwtinitramf....                         ] SDP: boot -f u-boot-imx7dsabresd_sd. <-
2:1       1/5 [==>           ] imx ....
```

UUU design as common library and UI. So user can easily integrate into their tools with uuu library. UUU also easy run in any scripts.

[PDF](#) of wiki content also is available at release page.

1.1 Running environment

- Windows 10, 64bit, early version(below 1.2.0) need install [vs2017 redistribute package](#)
- Ubuntu 16.14 or above, 64bit

Windows 7 user please read [WIN7-User-Guide](#)

1.2 Typical Usage

Set board boot pin to serial download mode. Generally iMX ROM will fail back to usb serial download mode if boot failure.

Download uboot

```
uuu bootloader
```

Burn uboot into emmc

```
uuu -b emmc bootloader
```

Burn bootimage into QSPI flash

```
uuu -b qspi qspi_bootloader
```

Burn rootfs image into emmc

```
uuu -b emmc_all bootloader rootfs.sdcards
```

Decompress rootfs image and burn into emmc (since 1.1.87)

```
uuu -b emmc_all bootloader rootfs.sdcards.bz2
```

Decompress rootfs image and burn into emmc without bootloader (since 1.4.146 and after 2021 Q4 yocto image)

```
uuu -b emmc_all rootfs.wic.bz2
```

Notes: bootloader means bootable image, which included ROM required header. for imx6/7, it should be uboot.imx generally. for imx8qxp\imx8qm\imx8mm\im8mq, it is flash.bin.

Burn release image into emmc

```
uuu L4.9.123_2.3.0_8mm-ga.zip
```

Note: some release combine multi board into one zip package, you need use uuu release.zip/uuu.auto-<boardname>

More usage please refer [Example](#)

1.3 Typical Script

uuu's script is plain text file

**first line must be

```
uuu_version 1.0.1
```

version number represent the minimum uuu version that uuu can parse this script.

Then flow uuu commands.

UUU command format as

PROTOCOL: CMD

The below is example to boot uboot for imx6 and imx7.

```
uuu_version 1.0.1
SDP: dcd -f u-boot.imx
SDP: write -f u-boot.imx -ivt 0
SDP: jump -f u-boot.imx -ivt 0
```

more sample scripts see [Sample-script](#)

The below table environment may be used when write uuu script

Table 1: Table Fastboot environment

Variable	Description
fastboot_dev	fastboot flash device, support mmc and sata
fastboot_buffer	fastboot download buffer address
fastboot_bytes	fastboot download file size
emmc_dev	eMMC device number
sd_dev	sd slot device number

1.4 License

uuu is licensed under the BSD license. See LICENSE. The BSD licensed prebuilt Windows binary version of uuu is statically linked with the LGPL libusb library, which remains LGPL.

- bzip2 (BSD license) is from <https://github.com/enthought/bzip2-1.0.6>
- zlib (zlib license) is from <https://github.com/madler/zlib.git>

- libusb (LGPL-2.1) is from <https://github.com/libusb/libusb.git>

1.5 What Firmware Need

What you want	Firmware Need
Download bootloader	N/A
Burn Image to eMMC/SD	uboot with fastboot enable
Burn Image to qspi\spi\nor	uboot with fastboot enable
Burn Image into Nand flash	uboot(1), linux kernel\initramfs\uboot\dtb
Need linux shell cmd such as fdisk	uboot(1), linux kernel\initramfs\uboot\dtb
Boot linux kernel with rootfs already in eMMC	uboot with fastboot enable
Boot Linux kernel with nfs over USB	uboot with fastboot enable, initramfs

(1) prefer enable fastboot. If ROM HID support write additional image to DDR place, you can write kernel\dtb\initramfs to ddr before jump to uboot. Enable fastboot give more flexibility to change kernel command line.

1.6 Setup auto parameter complete

1.6.1 windows

Just power shell support customized auto complete

Powershell: Enjoy auto [tab] command complete by run below command or put into Documents\WindowsPowerShell\Microsoft.PowerShell_profile.ps1

```
Register-ArgumentCompleter -CommandName uuu -ScriptBlock {param($commandName, $parameterName, $wordToComplete, $commandAst, $fakeBoundParameter); C:\Users\xna23210\uuu\uuu\x64\Release\lib\uuu.exe -autocomplete $parameterName }
```

1.6.2 linux

Enjoy auto [tab] command complete by put below script into /etc/bash_completion.d/uuu

```
_uuu_autocomplete()
{
    COMPREPLY=($(~/home/lizhi/source/mfgtools/uuu/uuu \$1 \$2 \$3))
}
complete -o nospace -F _uuu_autocomplete uuu
```

1.7 L4.9.123_2.3.0_8MM GA

It is first official BSP release to support uuu For L4.9.123_2.3.0_8MM GA with i.MX8M Mini, see [?]

2 Syntactic

```
uuu (Universal Update Utility) for nxp imx chips -- libuuu_1.3.191-1-g7010e4e
uuu [-d -m -v -V] <bootloader|cmdlists|cmd>

bootloader download bootloader to board by usb
cmdlist run all commands in cmdlist file
```

```

If it is path, search uuu.auto in dir
If it is zip, search uuu.auto in zip
cmd      Run one command, use -H see detail
example: SDPS: boot -f flash.bin
-d       Daemon mode, wait for forever.
-v -V    verbose mode, -V enable libusb error\warning info
-dry     Dry run mode, check if script or cmd correct
-m       USBPATH Only monitor these paths.
           -m 1:2 -m 1:3

-t       Timeout second for wait known usb device appeared
-pp      usb polling period in milliseconds
uuu -s   Enter shell mode. uuu.inputlog record all input commands
           you can use "uuu uuu.inputlog" next time to run all commands

uuu -udev  linux: show udev rule to avoid sudo each time
uuu -lsusb  List connected know devices
uuu -h -H   show help, -H means detail helps

uuu [-d -m -v] -b[run] <emmc|emmc_all|fat_write|nand|qspi|sd|sd_all|spl> arg...
     Run Built-in scripts
     emmc   burn boot loader to eMMC boot partition
            arg0: _flash.bin bootloader
            arg1: _image[Optional] image burn to emmc, default is the same as ←
                  bootloader
     emmc_all   burn whole image to eMMC
            arg0: _flash.bin
            arg1: _rootfs.sdcard
     fat_write   update one file in fat partition, require uboot fastboot ←
                  running in board
            arg0: _image image, which cp to fat partition
            arg1: _device storage device, mmc\sata
            arg2: _filename[Optional] file name in target fat partition, only ←
                  support rootdir now
            arg3: _partition
     nand    burn boot loader to NAND flash
            arg0: _flash.bin bootloader
            arg1: _image[Optional] image burn to nand, default is the same as ←
                  bootloader
     qspi    burn boot loader to qspi nor flash
            arg0: _flexspi.bin bootloader
            arg1: _image[Optional] image burn to flexspi, default is the same ←
                  as bootloader
     sd      burn boot loader to sd card
            arg0: _flash.bin bootloader
            arg1: _image[Optional] image burn to emmc, default is the same as ←
                  bootloader
     sd_all  burn whole image to sd card
            arg0: _flash.bin
            arg1: _rootfs.sdcard
     spl     boot spl and uboot
            arg0: _flash.bin

uuu -bshow <emmc|emmc_all|fat_write|nand|qspi|sd|sd_all|spl>
Show built-in script

```

Notes: Some board supports super speed (USB3.0). USB 3.0 port path is difference USB 2.0. If use -m to filter port, you need

add USB 3.0 port number otherwise fastboot will not be detected.

3 Usage Example

3.1 Basic

3.1.1 Download boot loader for imx6\imx7

```
uuu uboot.imx
```

3.1.2 Download boot loader for imx8qxp

```
uuu flash.bin
```

3.1.3 Download SPL and uboot, such as imx8mq.

```
uuu sdp: boot -f flash.bin
uuu sdpu: delay 1000
uuu sdpu: write -f flash.bin -offset 0x57c00
uuu sdpu: jump
```

3.1.4 Burn Android Image to eMMC

```
uuu android.zip (not implement default yet)
```

3.1.5 Burn yocto Image to eMMC

```
uuu L4.9.123_2.3.0_8mm-ga.zip
```

3.2 Built-in script

```
uuu -b emmc bootloader
uuu -b emmc_all bootloader rootfs.sdcard
uuu -b emmc_all bootloader rootfs.sdcard.bz2/*
    rootfs to emmc
uuu -b sd bootloader
uuu -b sd_all bootloader rootfs.sdcard
uuu -b sd_all bootloader rootfs.sdcard.bz2/*
    rootfs to sd card
uuu -b qspi qspi_bootloader
uuu -b qspi qspi_bootloader m4image
uuu -b spl bootloader
```

```
Write bootloader to emmc
Write rootfs to emmc
Decompress rootfs and write ←
Write bootloader to sd card
Write rootfs to sd card
Decompress rootfs and write ←
write bootloader to qspi
write m4image to qpsi
Download SPL and uboot
```

Notes:

Some boards have many sd slot. built-in script only work uboot environment \${ ←
sd_dev} point to slot

Some boards have not emmc chip, emmc build in script does not work for such boards

3.3 multi boards support

3.3.1 For the same boards

```
uuu -d uuu.auto          The same boards connected
```

3.3.2 For the difference boards

```
uuu -d -m 1:1 -m 2:1 boardA_uuu.auto      monitor port 1:1 and 2:1 for ↵
boardsA.                                     monitor port 1:3 and 4:1 for ↵
uuu -d -m 1:3 -m 4:1 boardB_uuu.auto      boardsB.
```

Note: please avoid monitor the same port by difference uuu instance, which cause unexpected result.

3.4 Talk with fastboot

3.4.1 boot linux kernel

```
uuu FB: ucmd setenv fastboot_buffer ${loadaddr}
uuu FB: download -f Image
uuu FB: ucmd setenv fastboot_buffer ${fdt_addr}
uuu FB: download -f imx8qxp_mek.dtb
uuu FB: acmd booti ${loadaddr} - ${fdt_addr}
```

Notes: Linux/Mac user need add \ before \$ to avoid shell replace environment variable.

Extended environment for fastboot

```
fastboot_buffer      Image download address
fastboot_bytes       reflect previous download image byte size
```

3.4.2 write image to emmc

```
uuu FB: flash -raw2sparse all <image file>
```

3.5 Talk with linux kenrel, transfer file between board and pc

```
on board, run \linuxrc&
on pc,     uuu fbk:ucp file t:\file
```

4 Sample scripts

5 Supported protocol

UUU is scripted base multi protocol system.

Built in config:

Pctl	Chip	Vid	Pid	BcdVersion
<hr/>				
SDPS:	MX8QXP	0x1fc9	0x012f	[0x0002..0xffff]
SDPS:	MX8QM	0x1fc9	0x0129	[0x0002..0xffff]
SDPS:	MX8DXL	0x1fc9	0x0147	
SDPS:	MX28	0x15a2	0x004f	
SDPS:	MX815	0x1fc9	0x013e	
SDPS:	MX865	0x1fc9	0x0146	
SDPS:	MX8ULP	0x1fc9	0x014a	
SDPS:	MX8ULP	0x1fc9	0x014b	
SDPS:	MX93	0x1fc9	0x014e	
SDP:	MX7D	0x15a2	0x0076	
SDP:	MX6Q	0x15a2	0x0054	
SDP:	MX6D	0x15a2	0x0061	
SDP:	MX6SL	0x15a2	0x0063	
SDP:	MX6SX	0x15a2	0x0071	
SDP:	MX6UL	0x15a2	0x007d	
SDP:	MX6ULL	0x15a2	0x0080	
SDP:	MX6SLL	0x1fc9	0x0128	
SDP:	MX7ULP	0x1fc9	0x0126	
SDP:	MXRT106X	0x1fc9	0x0135	
SDP:	MX8MM	0x1fc9	0x0134	
SDP:	MX8MQ	0x1fc9	0x012b	
SDPU:	SPL	0x0525	0xb4a4	[0x0000..0x04ff]
SDPV:	SPL1	0x0525	0xb4a4	[0x0500..0x9998]
SDPV:	SPL1	0x1fc9	0x0151	[0x0500..0x9998]
SDPU:	SPL	0x0525	0xb4a4	[0x9999..0x9999]
SDPU:	SPL	0x3016	0x1001	[0x0000..0x04ff]
SDPV:	SPL1	0x3016	0x1001	[0x0500..0x9998]
FBK:		0x066f	0x9afe	
FBK:		0x066f	0x9bff	
FBK:		0x1fc9	0x0153	
FB:		0x0525	0xa4a5	
FB:		0x18d1	0x0d02	
FB:		0x3016	0x0001	
FB:		0x1fc9	0x0152	

Table 2: Table UUU Protocol to USB lower level Map

UUU Protocol	USB Low level transfer
SDP	HID i.MX6/7, i.MX8 MM, i.MX8M
SDPU\SDPV	HID uboot implement of SDP, SPL download uboot
SDPS	HID i.MX8QXP i.MX8QM
FB	winusb (windows), raw transfer by libusb
FBK	winusb (windows), raw transfer by libusb

5.1 SDP: i.MX6/7 ROM download protocol

5.1.1 Supported command:

Run DCD from image with ivt header

```
dcd -f <filename>

write image to address.

write -f <filename> [-addr 0x000000] [-ivt 0]

ivt 0 means write to the address, which ivt pointer
jump to image with ivt header

jump -f <filename> [-ivt 0]

boot image, include (dcd, write and jump three commands)

boot -f <filename> [-nojump]
```

5.2 HABv4 closed chip support

For boot images not including a DCD table the same image used for SDCard/eMMC boot can be used with UUU tool.

For boot images including a DCD table, the DCD is loaded in OCRAM and must be properly signed.

Since U-Boot v2017.01 a build log containing the U-Boot and DCD addresses and lengths is available just after building U-Boot:

```
$ cat u-boot-dtb.imx.log
Image Type: Freescale IMX Boot Image
Image Ver: 2 (i.MX53/6/7 compatible)
Mode: DCD
Data Size: 602112 Bytes = 588.00 KiB = 0.57 MiB
Load Address: 877ff420
Entry Point: 87800000
HAB Blocks: 877ff400 00000000 0008ec00
DCD Blocks: 00910000 0000002c 000001c4
```

Users can copy the information above to create their CSF Authenticate Data command:

```
Block = 0x877ff400 0x00000000 0x0006DC00 "u-boot-dtb.imx", \
      0x00910000 0x0000002c 0x000001c4 "u-boot-dtb.imx"
```

Alternatively users can also extract the DCD length from the DCD table header:

```
$ od -x -j 0x2c -N 4 --Endian=big u-boot-dtb.imx
0000054 d201 c440
0000060
DCD Header: 0xd2, DCD Length: 0x01c4, DCD Version: 0x40
```

For the i.MX devices not supporting the skip DCD command (i.MX6Dual/Quad and i.MX6SoloLite) the pointer to the DCD table is cleared in the IVT in order to prevent the HAB library from processing the DCD table again during the authentication process. There is no need to re-initialize memory when it already contains valid data.

Since the IVT is modified when downloading to the target the binary must be signed with a cleared DCD pointer. However, the binary must be provided with a valid DCD pointer to allow the UUU tool to locate the DCD table.

The following script can be used to handle the DCD pointer:

```
#!/bin/bash
# DCD address must be cleared for signature, as UUU will clear it.
if [ "$1" == "clear_dcd_addr" ]; then
    # store the DCD address
```

```

dd if=$2 of=dcd_addr.bin bs=1 count=4 skip=12
# generate a NULL address for the DCD
dd if=/dev/zero of=zero.bin bs=1 count=4
# replace the DCD address with the NULL address
dd if=zero.bin of=$2 seek=12 bs=1 conv=notrunc
fi
# DCD address must be set for mfgtool to localize the DCD table.
if [ "$1" == "set_dcd_addr" ]; then
    # restore the DCD address with the original address dd
    if=dcd_addr.bin of=$2 seek=12 bs=1 conv=notrunc
    rm zero.bin
fi

```

The steps below can be used as an example:

```

$ ./mod_4_mfgtool.sh clear_dcd_addr u-boot-dtb.imx
$ ./cst --i u-boot-csf.txt --o u-boot-csf.bin
$ ./mod_4_mfgtool.sh set_dcd_addr u-boot-dtb.imx

```

For the i.MX devices supporting the skip DCD command (i.MX7D, i.MX6UL/ULL, i.MX8MQ and i.MX7ULP), there is no need to do any modification, UUU tool can download the binary directly.

NOTICE: For i.MX7D only, due to an erratum, the UUU download DCD address (0x00911000) is not aligned with the DCD address in u-boot (0x00910000), there are two options:

- use the command to specify the DCD address, `uuu boot -f u-boot-signed.imx -dcdaddr 0x00911000`
- change the csf DCD address when signing the u-boot: `Blocks = 0x00911000 0x0000002c 0x000001c4 "u-boot-dtb.imx"`

5.3 SDPU\SDPV: uboot implement simplified ROM SDP protocol

Uboot implemented i.MX 6/7 ROM SDP protocol. The support command the same as SDP.

SDPV is upgrade version of SDPU, which support `-skipspl` option for write command

See below for uboot requirement [uboot-config-requirement](#)

5.4 SDPS: i.MX8QXP and i.MX8QM ROM download protocol

send image by sdp command.

```
boot -f <filename> [-offset 0x0000]
```

5.5 FB: Android fastboot protocol

refer [fast boot protocol](#)

See below for [uboot requirement](#)

5.5.1 Support command:

```

getvar
ucmd <any uboot command>
acmd <any never returned uboot command, like booti, reboot>

# partition "all" means whole device.

```

```

flash [-raw2sparse] <partition> <filename>
download -f <filename>
crc -f <filename> [-format "mmc read $loadaddr"]
    [-blkSz 512] [ -crcblock 0x4000000]
    [-seek 0] [-skip 0] [-nostop]
        seek      skip block number from storage
        skip      skips byte from -f
        nostop   continue check even if found mismatch

```

**Some Uboot command need long time to finish. Default FB timeout is 2s. You can use below method to change timeout value

```

# time out set to 10000ms
FB[-t 10000]: ucmd <any uboot command>

```

Table 3: Table Fastboot environment

Variable	Description
fastboot_dev	fastboot flash device, support mmc and sata
fastboot_buffer	fastboot download buffer address
fastboot_bytes\filesize	fastboot download file size, new uboot provide filesize environment
emmc_dev	eMMC device number
sd_dev	sd slot device number

5.6 FBK: Android fastboot protocol, implement at initramfs. See project [imx-uuc](#)

5.6.1 Support command:

```

ucmd <any kernel command> and wait for command finish
acmd <any kernel command> don't wait for command finish
sync          wait for acmlid processs finish.
ucp <soure> <destinate> copy file from/to target
T:<filename> means target board file.
T:- means copy data to target's stdio pipe.
copy image T:/root/image ;download image to path /root/ ←
image
copy T:/root/image image ;upload /root/image to file ←
image.....

```

Example for transfer big file

```

acmd tar -           ; run tar background and get data from stdio
ucp rootfs.tar.gz T:- ; send to target stdio pipe
sync                 ; wait for tar process exit.

```

Linux environment:

Each command in separate process so environment can not be affect next command. Use below method to workaround this problem.

```
FBK: ucmand source /tmp/mtd.sh; flash_erase /dev/mtd${nandrootfs} 0 0
```

5.7 Common command for all protocol

Table 4: Table Common command for all protocol

Command	Description
Done	last command for finish whole flow.
Delay	Busy wait for millisecond
SH/SHELL	run external command
<	stdout as command, such as "< echo ucmd print", which generally used for burn serial number
@	using environment variable, such as "FBK:@ ucmd echo @MSG@" MSG will be replace by OS's environment variable.
error	show error message and exit
if	basic logic check, such as SDPS: if @chip@ == mx8qm then boot -f flash.bin. Only support == and !=. only support one logic check

6 Migration from mfgtool ucl2.xml

**Most case user can use uboot fastboot protocol to finish image program work.

In case you have to load kernel to burn whole image.

The below simple map ucl2.xml to uuu script.

ucl2.xml	uuu
<CMD state="Bootstrap" type="boot" body="Bootstrap" file="firmware/flash.bin" ifdev="MX8QXPB0">Loading boot image</CMD>	SDPS: boot -f flash.bin
<CMD state="Bootstrap" type="boot" body="Bootstrap" file="firmware/flash.bin" ifdev="MX8QXPB0">Loading boot image</CMD>	SDPS: boot -f flash.bin
<CMD state="Bootstrap" type="boot" body="Bootstrap" file="firmware/flash.bin" ifdev="MX8MM">Loading U-boot</CMD>	SDP: boot -f flash.bin SDP: boot -f flash.bin SDPU: write -f flash.bin -offset 0x57c00 SDPU: jump
<CMD state="Bootstrap" type="load" file="firmware/Image" address="0x80280000" loadSection="OTH" setSection="OTH" HasFlashHeader="FALSE" ifdev="MX8QXP MX8QM">Loading Kernel.</CMD>	FB: ucmd download -f Image
<CMD state="Bootstrap" type="load" file="firmware/initramfs.cpio.gz.uboot" address="0x83800000" loadSection="OTH" setSection="OTH" HasFlashHeader="FALSE" ifdev="MX8QM MX8QXP">Loading Initramfs.</CMD>	FB: ucmd download -f initramfs.cpio.gz.uboot
<CMD state="Bootstrap" type="load" file="firmware/fsl-imx8qxp.dtb" address="0x83000000" loadSection="OTH" setSection="OTH" HasFlashHeader="FALSE" ifdev="MX8QXP">Loading device tree.</CMD>	FB: ucmd download -f fsl-imx8qxp.dtb
<CMD state="Bootstrap" type="jump" > Jumping to OS image. </CMD>	
<!-- create partition --><CMD state="Updater" type="push" body="send" file="mksdcard.sh.tar">Sending partition shell</CMD>	FBK: ucp mksdcard.sh.tar t:/tmp

<CMD state="Updater" type="push" body="\$ tar xf \$FILE"> Partitioning...</CMD>	FBK: ucmd tar xf /tmp/mksdcard.sh.tar -d /tmp
<CMD state="Updater" type="push" body="\$ sh mksdcard.sh /dev/mmcblk%mmc%"> Partitioning...</CMD>	FBK: ucmd mksdcard.sh /dev/mmcblk0mmc
<!-- burn uboot --> <CMD state="Updater" type="push" body="send" file="files/imx-boot-imx8qxp-sd.bin" ifdev="MX8QXPB0">Sending u-boot.bin</CMD>	FBK: ucp imx-boot-imx8qxp-sd.bin t:/tmp
<CMD state="Updater" type="push" body="\$ dd if=/dev/zero of=/dev/mmcblk0 bs=1k seek=4096 conv=fsync count=8">clear u-boot arg</CMD>	FBK: ucmd dd if=/dev/zero of=/dev/mmcblk0 bs=1k seek=4096 conv=fsync count=8
<CMD state="Updater" type="push" body="\$ dd if=\$FILE of=/dev/mmcblk0 bs=1k seek=33 conv=fsync" ifdev="MX8QM MX8QXP MX8MQ">write u-boot.bin to sd card</CMD>	FBK: ucmd dd if=/tmp/imx-boot-imx8qxp-sd.bin of=/dev/mmcblk0 bs=1k seek=33 conv=fsync
<CMD state="Updater" type="push" body="\$ while [! -e /dev/mmcblk0p1]; do sleep 1; echo waiting...; done ">Waiting for the partition ready</CMD>	FBK: ucmd while [! -e /dev/mmcblk%mmc%p1]; do sleep 1; echo waiting...; done
<CMD state="Updater" type="push" body="\$ mkfs.vfat /dev/mmcblk0p1">Formatting rootfs partition</CMD>	FBK: ucmd mkfs.vfat /dev/mmcblk0p1
<CMD state="Updater" type="push" body="\$ mkdir -p /mnt/mmcblk0p1"/>	FBK: ucmd mkdir -p /mnt/mmcblk0p1
<CMD state="Updater" type="push" body="\$ mount -t vfat /dev/mmcblk0p1 /mnt/mmcblk0p1"/>	FBK: ucmd vfat /dev/mmcblk0p1 /mnt/mmcblk0p1
<!-- burn zImage --> <CMD state="Updater" type="push" body="send" file="files/Image">Sending kernel</CMD>	FBK: ucp Image t:/tmp
<CMD state="Updater" type="push" body="\$ cp \$FILE /mnt/mmcblk0p1/Image">write kernel image to sd card</CMD>	FBK: ucmd /tmp/Image /mnt/mmcblk0p1/Image
<!-- burn dtb --> <CMD state="Updater" type="push" body="send" file="files/fsl-imx8qxp.dtb" ifdev="MX8QXP MX8QXPB0">Sending Device Tree file</CMD>	FBK: ucp fsl-imx8qxp.dtb /tmp
<CMD state="Updater" type="push" body="\$ cp \$FILE /mnt/mmcblk0p1/fsl-imx8qm.dtb" ifdev="MX8QM">write device tree to sd card</CMD>	FBK: ucmd cp /tmp/fsl-imx8qxp.dtb /mnt/mmcblk0p1/
<CMD state="Updater" type="push" body="\$ umount /mnt/mmcblk0p1">Unmounting vfat partition</CMD>	FBK: ucmd umount /mnt/mmcblk0p1
<!-- burn rootfs --> <CMD state="Updater" type="push" body="\$ mkfs.ext3 -F -j /dev/mmcblk0p2">Formatting rootfs partition</CMD>	FBK: ucmd mkfs.ext3 -F -j /dev/mmcblk0p2
<!-- burn rootfs --> <CMD state="Updater" type="push" body="\$ mkfs.ext3 -F -j /dev/mmcblk0p2">Formatting rootfs partition</CMD>	FBK: ucmd mkfs.ext3 -F -j /dev/mmcblk0p2
<CMD state="Updater" type="push" body="\$ mkdir -p /mnt/mmcblk0p2"/>	FBK: ucmd mkdir -p /mnt/mmcblk0p2
<CMD state="Updater" type="push" body="\$ mount -t ext3 /dev/mmcblk0p2 /mnt/mmcblk0p2"/>	FBK: ucmd mount -t ext3 /dev/mmcblk0p2 /mnt/mmcblk0p2
<CMD state="Updater" type="push" body="pipe tar -jxv -C /mnt/mmcblk0p2" file="files/rootfs.tar.bz2">Sending and writting rootfs</CMD>	FBK: acmd tar -jxv -C /mnt/mmcblk0p2 FBK: ucp rootfs.tar.bz2 t:-
<CMD state="Updater" type="push" body="frf">Finishing rootfs write</CMD>	FBK: sync
<CMD state="Updater" type="push" body="\$ umount /mnt/mmcblk0p2">Unmounting rootfs partition</CMD>	FBK: ucmd umount /mnt/mmcblk0p2

```
<CMD state="Updater" type="push" body="$ echo Update | done  
Complete!">Done</CMD>
```

7 Win 7 User Guide

Win7 user may face some additional one time setup work because original win7 missed a updated .inf file


7.1 Back Ground

Win7 ships with correct *winusb.sys* file. but is missing an updated *.inf* that associates with "usb\ms_comp_winusb" devices. Normally if the USB device supports Microsoft OS descriptors, then it will allow Windows to automatically install the WinUSB driver. This mechanism is supported "in-box" for Win8 and newer. For Win7 the mechanism is supported through Windows update. Depending on the update policy for the Win7 machine, the appropriate driver may or may not be already available on the machine. If it is not already on the machine, user can use the following manual procedure to install the driver if necessary. (copy from https://www.silabs.com/community/interface/knowledge-base.entry.html/2017/02/06/manually_installwin-A2Jj)

Some windows update also included updated *.inf* file. You can try run uuu to see what happen. If windows report "can't install driver", that means your system missed such update file.

7.2 Install updated winusb inf file

- Download package
- unzip
- run install.bat as administrator permission.



- The below screen show install success

```
C:\Windows\system32>echo off
Administrative permission confirmed
===
Microsoft PnP Utility

Processing inf :          winusbcompat.inf
Driver package added successfully.
Published name :          oem8.inf

Total attempted:          1
Number successfully imported: 1

"SUCCESS: WINUSB WCID install"
Hit enter to close_
```


Notes:

4.9.123 8MM GA and 4.14 beta release missed a patch. Please apply below **patch** in uboot

7.3 Use zadig to install winusb driver

Please make sure you success download uboot and uboot auto launch fastboot command. windows find **Usb download device**, NOT **SE Blank**

If still fail install winusb driver you can try below method. you can try download zadig from <https://zadig.akeo.ie/> Choose **USB download device** and click install.



If you already apply patch and still see WCID is red "x", please submit issue.

Notes:

"SE Blank xx" is ROM HID device. PLEASE DON'T CHOOSE IT TO WINUSB. libusb can work well with HID device. Only "Usb download device" need check

8 FAQ

- **Win7 can't found driver**

- Need install winusb driver, you can use <https://zadig.akeo.ie/> to install winusb driver
- see page [WIN7-User-Guide](#)

- **Linux: Open device failure**

```
sudo uuu xxx
```

- **Some iMX8mm(845) chip failure write at linux system**

Need apply ROM patch, contact FAE to get it.

- **How to use absolute path in scripts**

Default all paths in script is related uuu scripts. if you want to use absolute path in scripts

Add ">" in path like

```
>/home/xxx
```

- **uuu exit silence or report missed dll**

Please upgrade to 1.2.x

- **How to avoid sudo in linux**

Put below context into /etc/udev/rules.d/99-uuu.rules (need sudo)

```
SUBSYSTEM=="usb", ATTRS{idVendor}=="1fc9", ATTRS{idProduct}=="012f", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="1fc9", ATTRS{idProduct}=="0129", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="15a2", ATTRS{idProduct}=="0076", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="15a2", ATTRS{idProduct}=="0054", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="15a2", ATTRS{idProduct}=="0061", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="15a2", ATTRS{idProduct}=="0063", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="15a2", ATTRS{idProduct}=="0071", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="15a2", ATTRS{idProduct}=="007d", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="15a2", ATTRS{idProduct}=="0080", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="1fc9", ATTRS{idProduct}=="0128", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="1fc9", ATTRS{idProduct}=="0126", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="1fc9", ATTRS{idProduct}=="0135", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="1fc9", ATTRS{idProduct}=="0134", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="1fc9", ATTRS{idProduct}=="012b", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="0525", ATTRS{idProduct}=="b4a4", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="0525", ATTRS{idProduct}=="a4a5", MODE="0666"
SUBSYSTEM=="usb", ATTRS{idVendor}=="066F", ATTRS{idProduct}=="9BFF", MODE="0666"
```

run sudo udevadm control --reload-rules

uuu -udev can show above help.

- **How to get file in zip without decompress**

Assume there are file name uuu.auto in A.zip file.

A.zip/uuu.auto

for example:

uuu A.zip/uuu.auto

- **How to send out uncompress bz2**

Added /* after bz2 file

for example

uuu -b emmc_all <bootloader> sdcard.bz2/*

- **Boot fail after burn > 4G Image**

uboot need below patch

```
diff --git a/common/image-sparse.c b/common/image-sparse.c
index ddf5772..86ff5a0 100644
--- a/common/image-sparse.c
+++ b/common/image-sparse.c
@@ -59,7 +59,7 @@ void write_sparse_image(
        uint32_t bytes_written = 0;
        unsigned int chunk;
        unsigned int offset;
-       unsigned int chunk_data_sz;
+       uint64_t chunk_data_sz;
        uint32_t *fill_buf = NULL;
        uint32_t fill_val;
        sparse_header_t *sparse_header;
@@ -130,7 +130,7 @@ void write_sparse_image(
                                sizeof(chunk_header_t));
    }

-       chunk_data_sz = sparse_header->blk_sz * chunk_header->chunk_sz;
+       chunk_data_sz = (uint64_t)sparse_header->blk_sz * (uint64_t)chunk_header->chunk_sz;
        blkcnt = chunk_data_sz / info->blk_sz;
        switch (chunk_header->chunk_type) {
            case CHUNK_TYPE_RAW:
```

- **WCID failure load**

Apply below uboot patch

```

diff --git a/drivers/usb/gadget/f_fastboot.c b/drivers/usb/gadget/f_fastboot.c
index ae8fe80..cd46ca4 100644
--- a/drivers/usb/gadget/f_fastboot.c
+++ b/drivers/usb/gadget/f_fastboot.c
@@ -2543,10 +2543,10 @@ static int fastboot_bind(struct usb_configuration *c, ←
    struct usb_function *f)
{
    f->os_desc_table->if_id = id;
    INIT_LIST_HEAD(&fb_os_desc.ext_prop);
    fb_ext_prop.name_len = strlen(fb_ext_prop.name) * 2 + 2;
-
    fb_os_desc.ext_prop_len = 14 + fb_ext_prop.name_len;
+
    fb_os_desc.ext_prop_len = 10 + fb_ext_prop.name_len;
    fb_os_desc.ext_prop_count = 1;
-
    fb_ext_prop.data_len = strlen(fb_ext_prop.data);
-
    fb_os_desc.ext_prop_len += fb_ext_prop.data_len;
+
    fb_ext_prop.data_len = strlen(fb_ext_prop.data) * 2 + 2;
+
    fb_os_desc.ext_prop_len += fb_ext_prop.data_len + 4;
    list_add_tail(&fb_ext_prop.entry, &fb_os_desc.ext_prop);

    id = usb_string_id(c->cdev);
}

```

- **out of memory at 64bit system**

If use bz2 or zip file, it is possible out of memory. Please increase swap partition size in linux. increase virtual memory size in windows.

- **How to use uuu in docker**

libusb need udev event to get new devices appeared.


Added option

docker run --net=host -v /run/udev/control:/run/udev/control


<https://stackoverflow.com/questions/49687378/how-to-get-hosts-udev-events-from-a-docker-container>

- **How to use uuu in virtual machine**

- Map HID device into virtual machine



- Map fastboot device into virtual machine after uboot boot



- You can use uuu burn image in virtual machine

9 Build Steps

9.1 windows

- download visual studio 2017 community version (free)
- git clone <https://github.com/NXPmicro/mfgtools.git>
- cd mfgtools
- git submodule init
- git submodule update
- open msvs/uuu.sln by vs2017
- click build

9.2 linux

- git clone <https://github.com/NXPmicro/mfgtools.git>
- cd mfgtools
- sudo apt-get install libusb-1.0.0-dev libzip-dev libbz2-dev
- cmake .
- make

10 Uboot config requirement

To talk with uuu, uboot need enable fastboot. fastboot need auto run when detect boot from USB.

```
CONFIG_CMD_FASTBOOT=y
CONFIG_USB_FUNCTION_FASTBOOT=y
CONFIG_USB_GADGET=y
CONFIG_USB_GADGET_DOWNLOAD=y
CONFIG_USB_GADGET_MANUFACTURER="FSL"
CONFIG_USB_GADGET_VENDOR_NUM=0x0525
CONFIG_USB_GADGET_PRODUCT_NUM=0xa4a5
CONFIG_CI_UDC=y                                # UDC need change according system, ←
                                                some system use CONFIG_USB DWC3, some use CONFIG_USB_CDNS3
CONFIG_FSL_FASTBOOT=y
CONFIG_FASTBOOT=y
CONFIG_FASTBOOT_BUF_ADDR=0x83800000      # Address need change according ←
                                                system, generally it can be the same as ${LOADADDR}
CONFIG_FASTBOOT_BUF_SIZE=0x40000000
CONFIG_FASTBOOT_FLASH=y
CONFIG_FASTBOOT_FLASH_MMC_DEV=1
CONFIG_EFI_PARTITION=y
CONFIG_ANDROID_BOOT_IMAGE=y
```

If use SPL, SDP need be enabled.

```
CONFIG_SPL_USB_HOST_SUPPORT=y
CONFIG_SPL_USB_GADGET_SUPPORT=y
CONFIG_SPL_USB_SDH_SUPPORT=y
CONFIG_SDH_LOADADDR=0x40400000      # Address need change according ←
                                                system, choose free memory
```

uuu related patches.

https://source.codeaurora.org/external/imx/uboot-imx/log/?h=imx_v2017.03_4.9.123_imx8mm_ga

About Fastboot enable:

```
719651a MLK-18257-1 Enable fastboot support in qxp mek board
d5226a3 MLK-18257-2: fix fastboot build warning
219c989 MLK-18257-3 run fastboot if initramfs is in validate
09b1876 MLK-18257-4 use another method check if need run bootcmd_mfg
3b1fa9d MLK-18257-5 enhance fastboot uboot cmd
ca96e0b MLK-18406 fastboot support all partition
```

About uboot SDP enable:

```
192a26d MLK-18707-1: SDP: use CONFIG_SDP_LOADADDR as default load address
9764fb2 MLK-18707-2 iMX8M enable fastboot as default
db9a634 MLK-18862 imx8mm uuu can write emmc by fastboot
```

Additional environment need be define

Table 5: Table uuu environment

Variable	Usage	Description
emmc_dev	emmc burn	eMMC device number
sd_dev	burn sd	sd slot device number
kboot	boot kernel\burn nand	kernel boot command, it is booti for arm64, bootz for arm32
weim_uboot	burn weim nor	uboot burn to position of weim nor
weim_base	burn weim nor	weim base address
mtdparts	burn nand	NAND flash partition configuration, such as "mtdparts=8000000.nor:1m(boot),-(rootfs)\;gpmi-nand:64m(nandboot),16m(nandkernel),16m(nandrootfs)"
spi_bus	burn spi (not qspi\fspi)	spi nor flash bus number
spi_uboot	burn spi (not qspi\fspi)	spi nor flash uboot offset

11 kernel config requirement

Some kernel config required

- USB CONFIG FS need be built-in
- One of UDC driver and PHY need be built-in
- Function FS need be enabled

```
Device Drivers
USB support
    USB gadget support (very last entry)
        USB Gadget Drivers (...)

        USB functions configurable through configfs
            Mass storage
            Function filesystem (functionFS)
```

12 Release Notes

12.1 1.5.21

12.1.1 New features

- Reduce memory usage when burn single board with compressed Image.
- Http(s) prompt request username and passwords when require authorization.

12.1.2 Bug fixes

- fixed android super.img loop download 52byte after some block.
- fix memory leak cause by getaddrinfo.
- fix support of empty environment variables in Windows OS.
- fix crash when environment variable is last word in script

12.2 1.4.243

12.2.1 New features

- Add zstd support
- Add iMX93 support

12.2.2 Bug fixes

- Fixed random crash when download bz2 from http
- Fix crash when download speed slower than decompress speed and need resize buffer

12.3 1.4.193

12.3.1 New features

- Add NXP FB/FBK/SDPV device PID

12.3.2 Bug fixes

- Fixed 314 Corrupt image with larger transfer sizes at sdp(s)
- Fixed missed true at else branch at built-in fat_write script and nand_burn_loader
- Fixed invalid progress percentage in verbose mode
- Fixed QSPI flashing script
- Fix #297 print error when run quit cmd in shell mode
- Fix #180 support check getval return value

12.4 1.4.165

12.4.1 New features

- Burn wic file(after 2021 Q4 yocto image) directly. uuu -b emmc_all wic
- Add *upload* fastboot command support
- Support uboot that use plugin initialize ddr
- Support simple logical check in uuu script

12.4.2 Bug fixes

- fix buildin script bz2 have not replaced with bz2* if path included space
- fixed #284: deadlock when using built-in script with filename include _
- Fix a potential crash if open usb device 400ms after detect attached
- fix uuu return success even ucp failure

12.5 1.4.139

12.5.1 New features

- Add help option -IgSerNum to set windows registry to ignore serial number above too much entry in register when burn many boards.
- Add snap support
- Add 8ulp support
- Deploy mac image

12.5.2 Bug fixes

- Fixed missed last chunk when meet specific android sparse file
- return out of memory when allocate failure
- -bshow don't show uuu version information and recover cursor ESC

12.6 1.4.72

12.6.1 New features

- http\https add port support at url
- improve progress show when burn android sparse image

12.6.2 Bug fixes

- Fix the dead loop when flash specific android super.img. There are bug when split big super.img into small sparse file running time. The bug trigger if split point at whole sparse chuck.

12.7 1.4.43

12.7.1 New features

- add environment variable support command
- Added support for *FB:reboot* and *FASTBOOT:reboot*
- allow to pass sparse limit from command line
- Update version number support build number > 255
- Mac OS (Catalina) support

12.7.2 Bug fixes

- fix #193 fb:< echo ucmd print failure
- fix fat_write partition parser error

12.8 1.3.191

12.8.1 New features

- Added Boundary Devices fastboot IDs

12.8.2 Bug fixes

- Workaround problem: some data pattern cause timeout at dell docker hub.
- update 7D free memory address, errata e11166 https://www.nxp.com/docs/en/errata/IMX7DS_3N09P.pdf
- Fix can't build from source tarball.

12.9 1.3.154

12.9.1 New features

- ffu image basic support
- add boundary device VID/PID
- Added basic fastboot logical partition support

12.9.2 Bug fixes

- fastboot: fix oem command separator
- Fix crash when download bz2 file

12.10 1.3.134

12.10.1 Bug fixes

- fix qm\qxp download failure if use spl image

12.11 1.3.130

12.11.1 New features

- Add android fastboot continue command
- Add i.MX8DXL support
- Add i.MX865 support
- build in script sd, support burn difference uboot
- Add option -pp to set pool time
- sdp: bootcmd: add support for --dcdaddr
- change the default nandbcb command from update to init

12.11.2 Bug fixes

- fix one line miss when exit uuu
- fix show 99% when use bz2 file
- fix miss ucmd at nand built-in script
- fix show time wrong, use system time instead of tick as timesample

12.12 1.3.102

12.12.1 New features

- Support simple https. (experimental).
- -b option support script file
- support >=4G zip file

12.12.2 Bug fixes

- fixed #136 fix decompress failure if use uncompressed method in zip file.
- fixed something wait forever when download bz2 from http
- fix http request failure at some host (use \r\n at http request)

12.13 1.3.82

12.13.1 New features

- add dry-run option to check if all files exist at script
- Start download before scan whole Bz2 file. Progress only show how many data burned instead of percentage before finish scan.
- Add NAND built in script to burn boot loader into nand flash, which need uboot support nandbcb command
- Add --skipfhdr option to skip flexspi header
- Can use SD card uboot for flexspi, which need uboot support qspihdr command
- Add timestamp info for each command. (-v show how many time is consumed for each command).
- Add tar.bz2 support.(experimental).
- Add tar.gz support. (experimental).
- Add http download. (experimental).
- Auto append /* for bz2 file when use built-in script.
- Add -lsusb option to list all connected known devices to help find usb path when do multi boards support

12.13.2 Bug fixes

- Fix SPL download uboot failure if uboot size > 2M
- Upgrade libusb to 1.0.23-rc3 to resolve some windows compatibility problem. such as exit if not usb port under virtual root hub.
- Fix bz2 decompress problem if bz2 created by bzip2 instead of pbzip2.
- Fix missed last chunk data for android sparse image
- fixed #123: implement timeout for wait known usb device appear

12.14 1.2.135

12.14.1 New features

- Support i.MX28
- Add Read\write a memory address for i.MX6/i.MX7
- built-in script emmc support burn difference files
- Support i.MX815

12.14.2 Bug fixes

- fix crash when console width between 47 to 54
- fix crash when use ssh <host> uuu
- fix wrong data by decompress sdcard.bz2/* if enable -O2 build option

12.15 1.2.91

12.15.1 New features

- Auto parameter complete support
- Add option -udev to help create udev rule to avoid use sudo
- Remove VT color at win7
- Fail back to verbose mode at win7
- Enable uboot shell mode
- Just print help when run uuu and doesn't scan auto.uuu in current directory.
- Added blog command to fetch message from uboot boot log
- Support file path include space. need add "" at file path
- Windows version built-in libusb
- New SDPV support to support -skipsql for uboot, which support auto scan uboot position.

12.15.2 Bug fixes

- Fixed uuu "fb[-t 1000]:" ucmd wait forever problem
- Fixed missed sdpu: done at spl built in script
- Fixed show nothing when wait for usb connection
- Fixed random claim interface failure at windows platform
- Fixed random crash when multi-device download at windows platform
- Fixed memory leak.
- Fixed #79 file all zero when ucp from target to host
- Fixed crash when done is not last cmd

12.16 1.2.0

12.16.1 New features

- Support decompress bz2 file, sdcard.bz2/* means decompress it.
- Support enter shell after run script

12.16.2 Bug fixes

- Fix mx6 boot failure when enable security
- Fix windows version dependent on vs redistribute package

12.17 1.1.81

12.17.1 New features

- Support shell command
- Support shell command generate dynamic uuu command to burn sequence id, like MAC address
- Reduce cpu usage rate at windows platform by increase each bulk transfer size
- Added q(quit) to exit shell at -s mode

12.17.2 Bug fixes

- fixed some typo
- fixed build script qspi burn failure if file size > 1M
- fixed file locked by uuu to prevent user update it.
- fixed crash at special uboot size

12.18 1.1.41

12.18.1 New features

- Support SDP protocol (i.MX6x, i.MX7, i.MX8M, i.MX8MM)
- Support SDPS protocol (i.MX8QXP B0, i.MX8QM B0)
- Support SDPU protocol (uboot\SPL implemented SDP protocol)
- Support FB protocol (fastboot with uboot)
- Support FBK protocol (fastboot in kernel, daemon implement at imx-uuc)
- Support multi-device download
- Support built-in script

12.18.2 Bug fixes

- Fix sometime open usb device failure at windows platform.
- Fix protocol case sensitive problem in script
- Fix open zip file failure

13 Known issue

- Some old i.MX8MM board HID can't work in linux system. Need apply ROM patch to fix. Please contact FAE.
- QXP/QM NAND image can't download by UUU because alignment requirement is difference
- Bz2 file only support one that is generated by pbbz2. there are problem if use bzip2 generate bz2.
- i.MX815 only support 3 boards at the same time.
- Some typeC dell dock USB hub cause transfer timeout if meet some magic data pattern, see branch magic_pattern. Try use differerce hub or direct connect to PC usb port if this happen.