

Weather Data API Documentation

API Overview

- **Domain:** wsapi.iotblitz.com
- **Port:** Default HTTPS port (443)
- **Endpoint:** https://wsapi.iotblitz.com/api/device/weather_data_api
- **Method:** POST

Description

This API is used to send weather data from devices to the server. The payload includes various weather parameters such as temperature, humidity, atmospheric pressure, and more.

Request Details

Endpoint

https://wsapi.iotblitz.com/api/device/weather_data_api

Method

POST

Headers

- Content-Type: application/json

Payload Body

The payload should be a JSON object with the following structure:

```
{  
  "api_key": "string",  
  "CL_ID": 0,  
  "UID": "string",  
  "DT": "string",  
  "TM": "string",  
  "TW": 0,  
  "TEMP": 0.00,  
  "RAIN": 0.00,
```

```
"RAIN_CUM": 0.00,  
"ATM_PRESS": 0.00,  
"SOLAR_RAD": 0.00,  
"HUMID": 0.00,  
"WIND_SPD": 0.00,  
"WIND_DIR": 0.00,  
"RUNHR": 0.00  
}
```

Example Payload

```
{  
  "api_key": "ncgXkolUnBmVr1Ewk3VMq4mYy8DzihfiDY+YiCuiHg4=",  
  "CL_ID": 1,  
  "UID": "ABCDE01001",  
  "DT": "040125",  
  "TM": "132502",  
  "TW": 0,  
  "TEMP": 40.05,  
  "RAIN": 5.64,  
  "RAIN_CUM": 5.64,  
  "ATM_PRESS": 10.08,  
  "SOLAR_RAD": 20.62,  
  "HUMID": 5.94,  
  "WIND_SPD": 50.05,  
  "WIND_DIR": 20.26,  
  "RUNHR": 10.26  
}
```

Field Descriptions

Field	Type	Description
api_key	String	Your API key for authentication. Example: "ncgXkolUnBmVr1Ewk3VMq4mYy8DzihfiDY+YiCuiHg4="
CL_ID	Integer	Client ID (default: 1).
UID	String	Unique device ID (max length: 10).
DT	String	Date in the format %d%m%y (e.g., 040125 for 4th January 2025).
TM	String	Time in the format %H%M%S (e.g., 152230 for 15:22:30, 24-hour format).
TW	Integer	Net signal strength (range: 0 to 30).
TEMP	Float	Temperature value.
RAIN	Float	Rainfall value.
RAIN_CUM	Float	Cumulative rainfall value.
ATM_PRESS	Float	Atmospheric pressure value.
SOLAR_RAD	Float	Solar radiation value.
HUMID	Float	Humidity value.
WIND_SPD	Float	Wind speed value.
WIND_DIR	Float	Wind direction value.
RUNHR	Float	Device runtime in hours.

Response Details

Success Response

- **Status Code:** 200 OK
- **Body:**

```
{
  "status": "success",
  "message": "data stored successfully",
  "data": {
```

```
"weather_data_id": 1146,  
"device_id": 1,  
"device": "ABCDE01001"  
}  
}
```

Error Responses

- **Status Code:** 400 / 422 Bad Request

- **Body:**

```
{  
  "detail": [  
    {  
      "type": "string_type",  
      "loc": [  
        "body",  
        "DT"  
      ],  
      "msg": "Input should be a valid string",  
      "input": 1  
    }  
  ]  
}
```

- **Status Code:** 500 Internal Server Error

- **Body:**

```
{  
  "detail": "Internal server error"  
}
```

Notes

- Ensure that all required fields are included in the payload.
- Use appropriate data formats for each field.
- Validate the payload before sending it to the server.
- Contact the API support team for authentication or integration issues.