

Weather Data API Documentation

API Overview

- **Domain:** wsapi.iotblitz.com
- **Port:** Default HTTPS port (443)
- **Endpoint:** https://wsapi.iotblitz.com/api/device/weather_data_api
- **Method:** POST

Description

This API is used to send weather data from devices to the server. The payload includes various weather parameters such as temperature, humidity, atmospheric pressure, and more.

Request Details

Endpoint

https://wsapi.iotblitz.com/api/device/weather_data_api

Method

POST

Headers

- **Content-Type:** application/json

Payload Body

The payload should be a JSON object with the following structure:

```
{  
  "api_key": "string", // Required  
  "CL_ID": 0,          // Required  
  "UID": "string",    // Required  
  "TW": 0,            // Required  
  "C1": 0.00,         // Optional (Temperature)  
  "C2": 0.00,         // Optional (Rainfall)  
  "C3": 0.00,         // Optional (Cumulative Rainfall)  
  "C4": 0.00,         // Optional (Atmospheric Pressure)  
  "C5": 0.00,         // Optional (Solar Radiation)
```

```
"C6": 0.00,    // Optional (Humidity)
"C7": 0.00,    // Optional (Wind Speed)
"C8": 0.00,    // Optional (Wind Direction)
"RUNHR": 0.00  // Optional (Device Runtime)
}
```

Example Payload

```
{
  "api_key": "ncgXkolUnBmVr1Ewk3VMq4mYy8DzihfiDY+YiCuiHg4=",
  "CL_ID": 1,
  "UID": "ABCDE01001",
  "TW": 25,
  "C1": 40.05,
  "C2": 5.64,
  "C3": 5.64,
  "C4": 10.08,
  "C5": 20.62,
  "C6": 5.94,
  "C7": 50.05,
  "C8": 20.26,
  "RUNHR": 10.26
}
```

Field Descriptions

Field	Type	Description	Required
api_key	String	Your API key for authentication. Example: "ncgXkolUnBmVr1Ewk3VMq4mYy8DzihfiDY+YiCuiHg4="	Yes
CL_ID	Integer	Client ID.	Yes
UID	String	Unique device ID (length: 10).	Yes

Field	Type	Description	Required
TW	Integer	Net signal strength (range: 0 to 30).	Yes
C1	Float	Temperature value.	No
C2	Float	Rainfall value.	No
C3	Float	Cumulative rainfall value.	No
C4	Float	Atmospheric pressure value.	No
C5	Float	Solar radiation value.	No
C6	Float	Humidity value.	No
C7	Float	Wind speed value.	No
C8	Float	Wind direction value.	No
RUNHR	Float	Device runtime in hours.	No

Response Details

Success Response

- **Status Code:** 200 OK
- **Body:**

```
{
  "status": "success",
  "message": "data stored successfully",
  "data": {
    "weather_data_id": 1146,
    "device_id": 1,
    "device": "ABCDE01001"
  }
}
```

Error Responses

- **Status Code:** 400 / 422 Bad Request

- **Body:**

```
{  
  "detail": [  
    {  
      "type": "string_type",  
      "loc": ["body", "UID"],  
      "msg": "Input should be a valid string",  
      "input": 1  
    }  
  ]  
}
```

- **Status Code:** 500 Internal Server Error

- **Body:**

```
{  
  "detail": "Internal server error"  
}
```

Notes

- Ensure that all required fields are included in the payload.
- Use appropriate data formats for each field.
- Validate the payload before sending it to the server.
- Contact the API support team for authentication or integration issues.