- Create a Docker volume named studentdata.
- Run an Ubuntu container and mount studentdata at /student.
- Create a file inside the container and verify it persists after container deletion.
- Attach the same volume to another container and verify the file exists.
- Demonstrate data sharing between two containers using a shared volume.
- Show that deleting a container does NOT delete the volume data.

```
Copyright (C) Microsoft Corporation. All rights reserved.

Install the latest PowerShell for new features and improvements! https://aka.ms/PSWindows

PS C:\WINDOWS\system32> docker -v
Docker version 29.2.0, build 0b9d198
PS C:\WINDOWS\system32> pwd

Path
----
C:\WINDOWS\system32


PS C:\WINDOWS\system32> docker volume create studentdata
studentdata
PS C:\WINDOWS\system32> docker volume ls
DRIVER    VOLUME NAME
local     899da049f600d1b8a245b271adf2c4a8f63e9414872d3913997d41eca80ef8dc
local     85263da2a7b80d0bcda71fd728bdc20428977319e0dd37779429da9e25c6ac12
local     studentdata
PS C:\WINDOWS\system32> docker run -it --name container1 -v studentdata:/student ubuntu /bin/bash
docker: Error response from daemon: Conflict. The container name "/container1" is already in use by container "94de36e3ee3e55d8196129191abb9d21d25a89c50eb4df8
at container to be able to reuse that name.

Run 'docker run --help' for more information
PS C:\WINDOWS\system32> docker run -it --name container3 -v studentdata:/student ubuntu /bin/bash
root@595bf4eae0eb:/# cd /student
root@595bf4eae0eb:/student# touch data.txt
root@595bf4eae0eb:/student# echo "Hello from container3" > data.txt
root@595bf4eae0eb:/student# exit
exit
PS C:\WINDOWS\system32> docker rm container1
container1
PS C:\WINDOWS\system32> docker run -it --name container4 -v studentdata:/student ubuntu /bin/bash
root@b0676d8777a6:/# cd /student
root@b0676d8777a6:/student# ls
data.txt
root@b0676d8777a6:/student# cat data.txt
Hello from container3
root@b0676d8777a6:/student# echo "shared text" > shared.txt
root@b0676d8777a6:/student# ls
data.txt  shared.txt
root@b0676d8777a6:/student# exit
exit
```

```
PS C:\WINDOWS\system32> docker run -it --name container5 -v studentdata:/student ubuntu /bin/bash
root@105e6f473328:/# cd /student
root@105e6f473328:/student# ls
data.txt  shared.txt
root@105e6f473328:/student# exit
exit
PS C:\WINDOWS\system32> docker rm container4
container4
PS C:\WINDOWS\system32> docker rm container5
container5
PS C:\WINDOWS\system32> docker volume
Usage:  docker volume COMMAND

Manage volumes

Commands:
  create      Create a volume
  inspect     Display detailed information on one or more volumes
  ls          List volumes
  prune       Remove unused local volumes
  rm          Remove one or more volumes

Run 'docker volume COMMAND --help' for more information on a command.
PS C:\WINDOWS\system32> docker volume ls
DRIVER    VOLUME NAME
local     899da049f600d1b8a245b271adf2c4a8f63e9414872d3913997d41eca80ef8dc
local     85263da2a7b80d0bcda71fd728bdc20428977319e0dd37779429da9e25c6ac12
local     studentdata
PS C:\WINDOWS\system32> docker volume inspect studentdata
[
    {
        "CreatedAt": "2026-03-10T06:48:49Z",
        "Driver": "local",
        "Labels": null,
        "Mountpoint": "/var/lib/docker/volumes/studentdata/_data",
        "Name": "studentdata",
        "Options": null,
        "Scope": "local"
    }
]
PS C:\WINDOWS\system32>
```